



Product Service

---

Choose certainty.  
Add value.

# Report On

RF Exposure Assessment of the  
EDTracker Ltd  
EDTDGL001 EDTracker Wireless Dongle

FCC ID: 2AKV8-000002

Document 75938172 Report 08 Issue 1

April 2017



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuv-sud.co.uk](http://www.tuv-sud.co.uk)

**REPORT ON**

RF Exposure Assessment of the  
EDTracker Ltd  
EDTDGL001 EDTracker Wireless Dongle

Document 75938172 Report 08 Issue 1

April 2017

**PREPARED FOR**

EDTracker Ltd  
16 Woodhurst Lane  
Wokingham  
Berkshire  
RG41 1JQ  
UK

**PREPARED BY**

A handwritten signature in black ink, appearing to read "David Guyett-Smith".

**David Guyett-Smith**  
Chief Engineer - Technical Solutions

**APPROVED BY**

A handwritten signature in blue ink, appearing to read "Matthew Russell".

**Matthew Russell**  
Authorised Signatory

**DATED**

11 April 2017



Product Service

## CONTENTS

Section	Page No
<b>1 REPORT SUMMARY .....</b>	<b>3</b>
1.1 Introduction .....	4
1.2 Regional Requirements .....	5
1.3 Product Information .....	5
1.3.1 Technical Description .....	5
1.3.2 Supported Features .....	5
1.3.3 Antennas.....	5
1.4 Brief Summary of Results .....	5
<b>2 TEST DETAILS .....</b>	<b>7</b>
2.1 Rationale for Assessment of the RF Exposure .....	8
2.2 Test Result Details.....	9
<b>3 DISCLAIMERS AND COPYRIGHT.....</b>	<b>10</b>
3.1 Disclaimers and Copyright.....	11

S



Product Service

## **SECTION 1**

### **REPORT SUMMARY**

RF Exposure Assessment of the  
EDTracker Ltd  
EDTDGL001 EDTracker Wireless Dongle



Product Service

## 1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the EDTracker Ltd EDTDGL001 EDTracker Wireless Dongle to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	EDTracker Ltd
Manufacturer	EDTracker Ltd
Manufacturing Description	EDTracker Wireless Dongle
Model Number(s)	EDTDGL001
Test Specification/Issue/Date	EN 62311:2008 CFR 47 Pt1.1310



Product Service

## 1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
EU	EN 62311:2008
FCC	CFR 47 Pt1.1310

## 1.3 PRODUCT INFORMATION

### 1.3.1 Technical Description

The Equipment under test was an EDTracker Ltd EDTDGL001 EDTracker Wireless Dongle. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the EDTDGL001 EDTracker Wireless Dongle to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

### 1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	2.4 GHz SRD
Frequency Band	2403-2481

### 1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain (dBi)
1	2.4 GHz	5

## 1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.2	0.2

**Table 1 – Compliance Boundary Results**



Product Service

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m <sup>2</sup> )		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
EU	0.3146	50.0000	10.8904	137.0000	0.0289	0.3600
FCC*	0.0315	5.0000	N/A	N/A	N/A	N/A

\* Requirement and Result in mW/cm<sup>2</sup>

**Table 2 – Occupational Results**

The calculations show that the EUT complies with the occupational exposure levels described in the EN 62311:2008 and CFR 47 Pt1.1310 at the point of investigation, 0.2 m.

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (W/m <sup>2</sup> )		E Field (V/m)		H Field (A/m)	
	Result	Limit	Result	Limit	Result	Limit
EU	0.3146	10.0000	10.8904	61.0000	0.0289	0.1600
FCC*	0.0315	1.0000	N/A	N/A	N/A	N/A

\* Requirement and Result in mW/cm<sup>2</sup>

**Table 3 – General Population Results**

The calculations show that the EUT complies with the occupational exposure levels described in the EN 62311:2008 and CFR 47 Pt1.1310 at the point of investigation, 0.2 m.



Product Service

## **SECTION 2**

### **TEST DETAILS**



Product Service

## 2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The EDTDGL001 EDTracker Wireless Dongle operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_o}$$

Where:

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

$\eta_o = 377$



Product Service

## 2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (W/m <sup>2</sup> )	E Field (V/m)	H Field (A/m)
1	1	1	2.4 GHz SRD	0.158	20	5	2403.2	0.3146	10.8904	0.0289

**Table 4 – Occupational Transmitter Summary**

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (W/m <sup>2</sup> )	E Field (V/m)	H Field (A/m)
1	1	1	2.4 GHz SRD	0.158	20	5	2403.2	0.3146	10.8904	0.0289

**Table 5 – General Population Transmitter Summary**



Product Service

## **SECTION 3**

### **DISCLAIMERS AND COPYRIGHT**



Product Service

### 3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of  
TÜV SÜD Product Service

© 2017 TÜV SÜD Product Service



Product Service

## **ANNEX A**

### **REGIONAL REQUIREMENTS**



Product Service

Frequency Range (MHz)	Power Density (W/m <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.065 - 1	-	610	1.6/f
1 - 10	-	610/f	1.6/f
10 - 400	10	61	0.162
400 - 2000	f/40	3*f^0.5	0.008*f^0.5
2000 - 300000	50	137	0.36

**Table A.1 – EN 62311:2008 Occupational Limits**

Frequency Range (MHz)	Power Density (W/m <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0.003 - 0.15	-	87	5
0.15 - 1	-	87	0.73/f
1 - 10	-	87/f^0.5	0.73/f
10 - 400	2	28	0.073
400 - 2000	f/200	1.375*f^0.5	0.0037*f^0.5
2000 - 300000	10	61	0.16

**Table A.2 – EN 62311:2008 General Population Limits**

Frequency Range (MHz)	S Field (mW/cm <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	900/f^2	1842/f	4.89/f
30 - 300	1	61.4	0.163
300 - 1500	f/300	-	-
1500 - 100000	5	-	-

**Table A.3 – CFR 47 Pt1.1310 Occupational Limits**

Frequency Range (MHz)	S Field (mW/cm <sup>2</sup> )	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	180/f^2	824/f	2.19/f
30 - 300	0.2	27.5	0.073
300 - 1500	f/1500	-	-
1500 - 100000	1	-	-

**Table A.4 – CFR 47 Pt1.1310 General Population Limits**