FCC RF EXPOSURE REPORT

Music Wave Limited

CAR AUDIO

Model Number: NA851

Additional Model:MW095DCKBT

FCC ID: 2AKVT-MW-DCKBT

Prepared By: Music Wave Limited

Room 07, 14/F.,Blk. B,Wing Cheung Ind. Bldg.,58-70 Kwai Cheong

Road, Kwai Chung, Hong Kong, China

Prepared By: EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City, GuangDong,

China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1701021

Date of Test : December 21,2016~ January 13,2017

Date of Report: January 16,2017



Maximum Permissible Exposure

1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging	
Range (MHz)	Strength E)	Field Strength	Density (S)	Times E	
	(V/m)	(H) (A/m)	(mW/cm2)	2 , H 2 or	
				S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842/f	4.89/f	(900/f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-10000			5	6	

(b) Limits for General Population / Uncontrolled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging	
Range (MHz)	Strength E)	Field Strength	Density (S)	Times E	
	(V/m)	(H) (A/m)	(mW/cm2)	2, H 2 or	
				S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-10000			1.0	30	

Note: f=frequency in MHz; *Plane-wave equivalent power density

2. MPE Calculation Method

E (V/m) = (30*P*G) 0.5/d Power Density: Pd (W/m2) = E2/377

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30*P*G) / (377*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



3. Calculated Result and Limit

Mode 1	Frequency (MHz)	Frequency Output output (MHz) power power (dBm) (mW)		Antenna gain			Limited		
						Power	of		
				Target			Density	Power	Test
			power	(dBi)	(Linear)	(S)	Density	Result	
	,		1	(dBm)	(421)	(2)	(mW	(S)	
							/cm2)	(mW	
								/cm2)	
GFSK	2402	2.549	1.798	2 ± 1	0	1	0.00040	1	Complies
	2441	3.049	2.018	3 ± 1	0	1	0.00050	1	Complies
	2480	3.722	2.356	3 ± 1	0	1	0.00050	1	Complies
8-DPSK	2402	2.488	1.773	2 ± 1	0	1	0.00040	1	Complies
	2441	3.940	2.477	3 ± 1	0	1	0.00050	1	Complies
	2480	3.660	2.323	3 ± 1	0	1	0.00063	1	Complies