

TEST REPORT

Report No.: 17020518HKG-002

Winlite Limited

Application
For
Certification
(Original Grant)
(FCC ID: 2AKW6D99)

Transceiver

Prepared and Checked by: Approved by:

Signed On File Xu Lap Ho, Leo Assistant Engineer

Wong Kwok Yeung, Kenneth Senior Lead Engineer Date: April 05, 2017

- Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.

material, product, or service is or has ever been under an Intertek certification program.

© 2016 Intertek

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the

GENERAL INFORMATION

Grantee:	Winlite Limited
Grantee Address:	Room 1401, Tower A, Tian An Cyber Times,
	Shennan Avenue, Futian District, Shenzhen,
	China.
Contact Person:	Yamma Zhang
Tel:	86-755-83474236
Fax:	86-755-83475111
e-mail:	winnie@winlite.net
Manufacturer:	ZHONGSHAN BSD ELECTRON TECHNOLOGY
	CO., LTD.
Manufacturer Address:	F 1~4, District G3,No.6, Muhejing StreetII, Gangkou
	Town,ZHONGSHAN Guangdong CHINA
Brand Name:	MEDION /
	WINLITE
Model:	MD 43510 /
	WIP-D99
Type of EUT:	Transceiver
Description of EUT:	Wireless Light Bulb Speaker
Serial Number:	N/A
FCC ID:	2AKW6D99
Date of Sample Submitted:	February 17, 2017
Date of Test:	February 17, 2017 to March 31, 2017
Report No.:	17020518HKG-002
Report Date:	April 05, 2017
Environmental Conditions:	Temperature: +10 to 40°C
	Humidity: 10 to 90%

Report No.: 17020518HKG-002

SUMMARY OF TEST RESULT

TEST SPECIFICATION	REFERENCE	RESULTS
Radiated Emission Radiated Emission on the Bandedge	15.249, 15.209	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards: FCC Part 15, October 1, 2015 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

Report No.: 17020518HKG-002 ii

^{2.} Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Table of Contents

1.0	General Description	
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	
2.0	System Test Configuration	
2.1	Justification	
2.2	EUT Exercising Software	
2.3	Special Accessories	
2.4	Measurement Uncertainty	
2.5	Support Equipment List and Description	2
3.0	Emission Results	3
3.1	Field Strength Calculation	
3.2	Radiated Emission Configuration Photograph	
3.3	Radiated Emission Data	
5.5	Natiated Littlesion Data	
4.0	Equipment Photographs	13
5.0	Product Labelling	12
5.0	1 Toddet Labelling	10
6.0	Technical Specifications	13
7.0	Instruction Manual	12
1.0	instruction Manual	13
8.0	Miscellaneous Information	14
8.1	Radiated Emission on the Bandedge	
8.2	Discussion of Pulse Desensitization	
	DISCUSSION OF THE USE DESCRIBING AND THE PROPERTY OF THE PROPE	
8.3		
8.3 8.4	Calculation of Average Factor Emissions Test Procedures	15
8.4	Calculation of Average Factor Emissions Test Procedures	15 17
	Calculation of Average Factor	15 17
8.4	Calculation of Average Factor Emissions Test Procedures	15 17

Report No.: 17020518HKG-002

1.0 **General Description**

1.1 Product Description

The Equipment Under Test (EUT) is a Bluetooth light bulb with speaker. The light bulb powered by 85~265V 50/60Hz AC power source can be controlled to change color and play sound by the app after being paired with the smart phone. The EUT supports both Bluetooth 2.1 and BLE.

The Model: WIP-D99 is the same as the Model: MD 43510 in hardware aspect. The difference in model number and brand name serves as marketing strategy.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

1.4 Test Facility

The 3m Chamber facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

Report No.: 17020518HKG-002 1 of 20

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 110VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

2.5 Support Equipment List and Description

N/A.

Report No.: 17020518HKG-002 2 of 20

3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where $FS = Field Strength in dB\mu V/m$

RR = RA - AG - AV in $dB\mu V$

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 52.0 dB\mu V/m$

AF = 7.4 dB $RR = 18.0 \text{ dB}\mu\text{V}$ CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dB AV = 5.0 dB FS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(27 dB μ V/m)/20] = 22.4 μ V/m

Report No.: 17020518HKG-002 3 of 20

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 31.818 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 0.5 dB

Report No.: 17020518HKG-002 4 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 2.1)

Table 1 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polari- zation	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Н	2402.000	92.5	33	29.4	88.9	24	64.9	94.0	-29.1
Н	4804.000	56.6	33	34.9	58.5	24	34.5	54.0	-19.5
V	7206.000	39.7	33	37.9	44.6	24	20.6	54.0	-33.4
V	9608.000	39.3	33	40.4	46.7	24	22.7	54.0	-31.3
Н	12010.000	42.7	33	40.5	50.2	24	26.2	54.0	-27.8
Н	14412.000	44.2	33	40.0	51.2	24	27.2	54.0	-26.8

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2402.000	92.5	33	29.4	88.9	114.0	-25.1
Н	4804.000	56.6	33	34.9	58.5	74.0	-15.5
V	7206.000	39.7	33	37.9	44.6	74.0	-29.4
V	9608.000	39.3	33	40.4	46.7	74.0	-27.3
Н	12010.000	42.7	33	40.5	50.2	74.0	-23.8
Н	14412.000	44.2	33	40.0	51.2	74.0	-22.8

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 5 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 2.1)

Table 2 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polari- zation	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Н	2440.000	90.5	33	29.4	86.9	24	62.9	94.0	-31.1
Н	4880.000	53.7	33	34.9	55.6	24	31.6	54.0	-22.4
V	7320.000	39.4	33	37.9	44.3	24	20.3	54.0	-33.7
V	9760.000	39.4	33	40.4	46.8	24	22.8	54.0	-31.2
Н	12200.000	42.7	33	40.5	50.2	24	26.2	54.0	-27.8
Н	14640.000	45.9	33	38.4	51.3	24	27.3	54.0	-26.7

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2440.000	90.5	33	29.4	86.9	114.0	-27.1
Н	4880.000	53.7	33	34.9	55.6	74.0	-18.4
V	7320.000	39.4	33	37.9	44.3	74.0	-29.7
V	9760.000	39.4	33	40.4	46.8	74.0	-27.2
Н	12200.000	42.7	33	40.5	50.2	74.0	-23.8
Н	14640.000	45.9	33	38.4	51.3	74.0	-22.7

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 6 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 2.1)

Table 3 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polari- zation	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Н	2480.000	88.5	33	29.4	84.9	24	60.9	94.0	-33.1
Н	4960.000	51.9	33	34.9	53.8	24	29.8	54.0	-24.2
V	7440.000	39.3	33	37.9	44.2	24	20.2	54.0	-33.8
V	9920.000	39.6	33	40.4	47.0	24	23.0	54.0	-31.0
Н	12400.000	42.8	33	40.5	50.3	24	26.3	54.0	-27.7
Н	14880.000	45.7	33	38.4	51.1	24	27.1	54.0	-26.9

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2480.000	88.5	33	29.4	84.9	114.0	-29.1
Н	4960.000	51.9	33	34.9	53.8	74.0	-20.2
V	7440.000	39.3	33	37.9	44.2	74.0	-29.8
V	9920.000	39.6	33	40.4	47.0	74.0	-27.0
Н	12400.000	42.8	33	40.5	50.3	74.0	-23.7
Н	14880.000	45.7	33	38.4	51.1	74.0	-22.9

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 7 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

Table 4 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polari- zation	Frequency (MHz)	Reading (dB _u V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Н	2402.000	95.3	33	29.4	91.7	50	41.7	94.0	-52.3
Н	4804.000	64.8	33	34.9	66.7	50	16.7	54.0	-37.3
V	7206.000	48.1	33	37.9	53.0	50	3.0	54.0	-51.0
V	9608.000	39.8	33	40.4	47.2	50	-2.8	54.0	-56.8
Н	12010.000	42.7	33	40.5	50.2	50	0.2	54.0	-53.8
V	14412.000	44.1	33	40.0	51.1	50	1.1	54.0	-52.9

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2402.000	95.3	33	29.4	91.7	114.0	-22.3
Н	4804.000	64.8	33	34.9	66.7	74.0	-7.3
V	7206.000	48.1	33	37.9	53.0	74.0	-21.0
V	9608.000	39.8	33	40.4	47.2	74.0	-26.8
Н	12010.000	42.7	33	40.5	50.2	74.0	-23.8
V	14412.000	44.1	33	40.0	51.1	74.0	-22.9

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 8 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

Table 5 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polari- zation	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Н	2440.000	92.9	33	29.4	89.3	50	39.3	94.0	-54.7
Н	4880.000	58.5	33	34.9	60.4	50	10.4	54.0	-43.6
V	7320.000	40.2	33	37.9	45.1	50	-4.9	54.0	-58.9
V	9760.000	39.7	33	40.4	47.1	50	-2.9	54.0	-56.9
Н	12200.000	42.9	33	40.5	50.4	50	0.4	54.0	-53.6
V	14640.000	45.8	33	38.4	51.2	50	1.2	54.0	-52.8

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2440.000	92.9	33	29.4	89.3	114.0	-24.7
Н	4880.000	58.5	33	34.9	60.4	74.0	-13.6
V	7320.000	40.2	33	37.9	45.1	74.0	-28.9
V	9760.000	39.7	33	40.4	47.1	74.0	-26.9
Н	12200.000	42.9	33	40.5	50.4	74.0	-23.6
V	14640.000	45.8	33	38.4	51.2	74.0	-22.8

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 9 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting (Bluetooth 4.0 BLE)

Table 6 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

zation (MHz) (dBμV) (dB) (dB) (dBμV/m) (dB) (dBμV/m) (dBμV/m)										
H 4960.000 57.8 33 34.9 59.7 50 9.7 54.0 -44 V 7440.000 39.9 33 37.9 44.8 50 -5.2 54.0 -55 V 9920.000 39.5 33 40.4 46.9 50 -3.1 54.0 -57		' '	J	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin (dB)
V 7440.000 39.9 33 37.9 44.8 50 -5.2 54.0 -55 V 9920.000 39.5 33 40.4 46.9 50 -3.1 54.0 -57	Н	2480.000	91.7	33	29.4	88.1	50	38.1	94.0	-55.9
V 9920.000 39.5 33 40.4 46.9 50 -3.1 54.0 -57	Н	4960.000	57.8	33	34.9	59.7	50	9.7	54.0	-44.3
	V	7440.000	39.9	33	37.9	44.8	50	-5.2	54.0	-59.2
H 12400,000 43.0 33 40.5 50.5 50 0.5 54.0 -53	V	9920.000	39.5	33	40.4	46.9	50	-3.1	54.0	-57.1
	Н	12400.000	43.0	33	40.5	50.5	50	0.5	54.0	-53.5
V 14880.000 45.9 33 38.4 51.3 50 1.3 54.0 -52	V	14880.000	45.9	33	38.4	51.3	50	1.3	54.0	-52.7

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
Н	2480.000	91.7	33	29.4	88.1	114.0	-25.9
Н	4960.000	57.8	33	34.9	59.7	74.0	-14.3
V	7440.000	39.9	33	37.9	44.8	74.0	-29.2
V	9920.000	39.5	33	40.4	46.9	74.0	-27.1
Н	12400.000	43.0	33	40.5	50.5	74.0	-23.5
V	14880.000	45.9	33	38.4	51.3	74.0	-22.7

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 10 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting

Table 7 Radiated Emissions Pursuant to FCC Part 15 Section 15.209 Requirement

			Pre-	Antenna	Net	Limit	
	Frequency	Reading	amp	Factor	at 3m	at 3m	Margin
Polarization	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	31.818	44.3	16	10.0	38.3	40.0	-1.7
V	38.123	37.8	16	10.0	31.8	40.0	-8.2
V	48.187	37.8	16	11.0	32.8	40.0	-7.2
Н	71.225	44.0	16	7.0	35.0	40.0	-5.0
Н	113.905	39.8	16	14.0	37.8	43.5	-5.7
Н	152.705	39.3	16	15.0	38.3	43.5	-5.2
V	194.172	29.5	16	16.0	29.5	43.5	-14.0
Н	222.908	27.4	16	18.0	29.4	46.0	-16.6

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 11 of 20

Applicant: Winlite Limited Date of Test: March 31, 2017

Model: MD 43510

Worst-Case Operating Mode: Transmitting - Sound Playing

Table 8 Radiated Emissions Pursuant to FCC Part 15 Section 15.209 Requirement

			Pre-	Antenna	Net	Limit	
	Frequency	Reading	amp	Factor	at 3m	at 3m	Margin
Polarization	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	31.818	45.5	16	10.0	39.5	40.0	-0.5
V	39.336	37.2	16	10.0	31.2	40.0	-8.8
V	48.793	38.2	16	11.0	33.2	40.0	-6.8
V	72.073	43.6	16	7.0	34.6	40.0	-5.4
Н	112.692	39.4	16	14.0	37.4	43.5	-6.1
Н	153.675	39.6	16	15.0	38.6	43.5	-4.9
V	198.416	30.1	16	16.0	30.1	43.5	-13.4
Н	222.787	27.9	16	18.0	29.9	46.0	-16.1

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 17020518HKG-002 12 of 20

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Report No.: 17020518HKG-002 13 of 20

8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Peak Measurement

The test data of bandedge emissions were shown on the above radiated emissions table 1 & table 3 respectively.

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) but exceeded 54 dB μ V/m (Average Limit).

Report No.: 17020518HKG-002 14 of 20

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 0.295ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

8.3 Calculation of Average Factor

(Bluetooth 2.1)

Based on the Bluetooth Specification Version 2.1 + EDR, the transmitter ON time for each timeslot of Bluetooth is $625\mu s$. DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take (5+1) x $625\mu s$ = 3.75ms. For one period for a pseudo-random hopping through at least 20 RF channels in adaptive mode (worse case), it take: $20 \times 3.75ms = 75ms$.

The dwell time for DH5 is $5 \times 625 \mu s = 3.125 ms$.

For the worst case calculation, there are two transmissions might occur in 100ms. Therefore,

Duty Cycle (DC) = Maximum On time in 100ms/100ms = 3.125ms x 2/100ms = 0.0625

Average Factor (AF) of Bluetooth in dB = $20 \log_{10} (0.0625)$ = -24 dB

(Bluetooth 4.0 BLE)

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100ms


Effective period of the cycle = 0.295ms

DC = 0.295 / 100 = 0.00295 ms

Therefore, the averaging factor is found by $20\log 0.00295 = -50.6$ dB.

Report No.: 17020518HKG-002 15 of 20

Average Factor- (BLE)



Report No.: 17020518HKG-002

16 of 20

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Report No.: 17020518HKG-002 17 of 20

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


Report No.: 17020518HKG-002 18 of 20

8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz

Report No.: 17020518HKG-002 19 of 20

9.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

10.0 **Equipment List**

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	Double Ridged
			Guide Antenna
Registration No.	EW-3095	EW-2253	EW-1133
Manufacturer	R&S	R&S	EMCO
Model No.	ESCI	FSP40	3115
Calibration Date	Oct. 25, 2016	Jun. 15, 2016	Nov. 05, 2015
Calibration Due Date	Oct. 25, 2017	Jun. 15, 2017	May 05, 2017

Equipment	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-0571	EW-0447
Manufacturer	EMCO	EMCO
Model No.	3104C	3146
Calibration Date	May 18, 2016	May 18, 2016
Calibration Due Date	Nov. 18, 2017	Nov. 18, 2017

2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2329
Manufacturer	R&S
Model No.	FSP3
Calibration Date	Aug. 26, 2016
Calibration Due Date	Aug. 26, 2017

END OF TEST REPORT

Report No.: 17020518HKG-002 20 of 20