



# FCC Part 15C Test Report

## FCC ID: 2AKWRTP-1N

Product Name:	Wireless Water Time
Trademark:	N/A
Model Name :	TP-1N, TP-1B, TP-2N, TP-2B
Prepared For :	LinkTap Pty Ltd
Address :	10/16 Morell Close, Belconnen, ACT 2617, Australia
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	Dec. 12 – Dec. 30, 2016
Date of Report :	Jan. 04, 2016
Report No.:	BCTC-FY161206401E



## TEST RESULT CERTIFICATION

**Applicant's name**.....: LinkTap Pty Ltd

Address.....: 10/16 Morell Close, Belconnen, ACT 2617, Australia

**Manufacture's Name**.....: LinkTap Pty Ltd

Address.....: 10/16 Morell Close, Belconnen, ACT 2617, Australia

### Product description

Product name.....: Wireless Water Time

Model and/or type reference : TP-1N, TP-1B, TP-2N, TP-2B

**Standards**.....: FCC Part15.247

ANSI C63.10:2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Testing Engineer : 

Eric Yang

Reviewer  
(Supervisor) : 

Simon Wang

Approved &  
Authorized  
Signer(Manager) : 



## Table of Contents

	Page
<b>. SUMMARY OF TEST RESULTS.....</b>	<b>5</b>
TEST FACILITY.....	6
MEASUREMENT UNCERTAINTY.....	6
<b>. GENERAL INFORMATION.....</b>	<b>7</b>
GENERAL DESCRIPTION OF EUT.....	7
DESCRIPTION OF TEST MODES.....	8
BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	8
DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....	9
EQUIPMENTS LIST FOR ALL TEST ITEMS.....	10
<b>. EMC EMISSION TEST.....</b>	<b>11</b>
CONDUCTED EMISSION MEASUREMENT.....	11
POWER LINE CONDUCTED EMISSION LIMITS.....	11
TEST PROCEDURE.....	11
DEVIATION FROM TEST STANDARD.....	11
TEST SETUP.....	12
EUT OPERATING CONDITIONS.....	12
RADIATED EMISSION MEASUREMENT.....	13
RADIATED EMISSION LIMITS.....	13
TEST PROCEDURE.....	14
DEVIATION FROM TEST STANDARD.....	14
TEST SETUP.....	15
EUT OPERATING CONDITIONS.....	16
TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) .....	17
TEST RESULTS (BETWEEN 30MHZ – 1GHZ) .....	18
TEST RESULTS (1GHZ~25GHZ).....	20
<b>3.3 RADIATED BAND EMISSION MEASUREMENT.....</b>	<b>21</b>
<b>3.3.1 TEST REQUIREMENT:.....</b>	<b>21</b>
<b>3.3.2 TEST PROCEDURE.....</b>	<b>21</b>
DEVIATION FROM TEST STANDARD.....	22
TEST SETUP.....	22
EUT OPERATING CONDITIONS.....	22
<b>. POWER SPECTRAL DENSITY TEST.....</b>	<b>24</b>

**Table of Contents**

	<b>Page</b>
<b>APPLIED PROCEDURES / LIMIT.....</b>	<b>24</b>
<b>TEST PROCEDURE.....</b>	<b>24</b>
<b>DEVIATION FROM STANDARD.....</b>	<b>24</b>
<b>TEST SETUP.....</b>	<b>24</b>
<b>EUT OPERATION CONDITIONS.....</b>	<b>24</b>
<b>TEST RESULTS.....</b>	<b>25</b>
<b>. BANDWIDTH TEST.....</b>	<b>26</b>
<b>APPLIED PROCEDURES / LIMIT.....</b>	<b>26</b>
<b>TEST PROCEDURE.....</b>	<b>26</b>
<b>DEVIATION FROM STANDARD.....</b>	<b>26</b>
<b>TEST SETUP.....</b>	<b>26</b>
<b>EUT OPERATION CONDITIONS.....</b>	<b>26</b>
<b>TEST RESULTS.....</b>	<b>27</b>
<b>. PEAK OUTPUT POWER TEST.....</b>	<b>29</b>
<b>APPLIED PROCEDURES / LIMIT.....</b>	<b>29</b>
<b>TEST PROCEDURE.....</b>	<b>29</b>
<b>DEVIATION FROM STANDARD.....</b>	<b>29</b>
<b>TEST SETUP.....</b>	<b>29</b>
<b>EUT OPERATION CONDITIONS.....</b>	<b>29</b>
<b>TEST RESULTS.....</b>	<b>30</b>
<b>. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>31</b>
<b>APPLICABLE STANDARD.....</b>	<b>31</b>
<b>TEST PROCEDURE.....</b>	<b>31</b>
<b>DEVIATION FROM STANDARD.....</b>	<b>31</b>
<b>TEST SETUP.....</b>	<b>31</b>
<b>EUT OPERATION CONDITIONS.....</b>	<b>32</b>
<b>TEST RESULTS.....</b>	<b>32</b>
<b>. ANTENNA REQUIREMENT.....</b>	<b>34</b>
<b>STANDARD REQUIREMENT.....</b>	<b>34</b>
<b>EUT ANTENNA.....</b>	<b>34</b>
<b>. EUT TEST PHOTO.....</b>	<b>35</b>
<b>. EUT PHOTO.....</b>	<b>36</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	



## . SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	The EUT is powered by batteries.
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

**TEST FACILITY**

Shenzhen BCTC Technology Co., Ltd.

Add. : No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registered No.: 187086

**MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



## . GENERAL INFORMATION

### GENERAL DESCRIPTION OF EUT

Equipment	Wireless Water Time	
Trade Name	N/A	
Model Name	TP-1N	
Serial Model	TP-1B, TP-2N, TP-2B	
Model Difference	The product is different for model number and outlook color.	
Product Description	The EUT is a Wireless Water Time	
	Operation Frequency:	Zigbee:2405~2480MHz
	Modulation Type:	Zigbee: O-QPSK
	Number Of Channel	16
	Antenna Designation:	Please see Note 3.
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.	
Power	DC 6V battery	
hardware version	--	
Software version	--	
Serial number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

#### Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List for Zigbee							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2405	05	2425	09	2445	13	2465
02	2410	06	2430	10	2450	14	2470
03	2415	07	2435	11	2455	15	2475
04	2420	08	2440	12	2460	16	2480



3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Internal antenna	N/A	2.58	

**DESCRIPTION OF TEST MODES**

Pretest Mode	Description
Mode 1	CH1
Mode 2	CH8
Mode 3	CH16
Mode 4	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	CH1
Mode 2	CH8
Mode 3	CH16
Mode 4	Link Mode

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

**BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**

Conducted Emission/ Radiated Spurious Emission Test



**DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Wireless Water Time	N/A	TP-1N	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	MY45109572	2016.08.25	2017.08.24
2	Test Receiver	R&S	ESPI	101396	2016.08.25	2017.08.24
3	Bilog Antenna	SCHWARZB ECK	VULB9160-3369	VULB9160-3369	2016.08.25	2017.08.24
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.07.06	2017.07.05
5	Spectrum Analyzer	Agilent	N9020A	MY5051041	2016.07.06	2017.07.05
6	Horn Antenna	SCHWARZB ECK	9120D	9120D-1275	2016.08.25	2017.08.24
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05
8	Amplifier	SCHWARZB ECK	BBV9718	9718-270	2016.08.25	2017.08.24
9	Amplifier	SCHWARZB ECK	BBV9743	9743-119	2016.08.25	2017.08.24
10	Loop Antenna	ARA	PLGW-0130 /B	1029	2016.07.06	2017.07.05
11	Power Meter	R&S	NRVS	100696	2016.07.06	2017.07.05
12	Power Sensor	R&S	NRV-Z55	161905	2016.07.06	2017.07.05
13	RF cables	R&S	N/A	N/A	2016.07.06	2017.07.05

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K 03-101165-ha	2016.06.06	2017.06.05
2	LISN	R&S	NSLK81 26	812646 6	2016.08.24	2017.08.23
3	LISN	R&S	NSLK81 26	812648 7	2016.08.24	2017.08.23
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06
5	RF cables	R&S	R204	R20X	2016.07.06	2017.07.05



## . EMC EMISSION TEST

### CONDUCTED EMISSION MEASUREMENT

#### POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### DEVIATION FROM TEST STANDARD

No deviation

**TEST SETUP**

**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

**EUT OPERATING CONDITIONS**

No Application

The EUT is powered by batteries.



## RADIATED EMISSION MEASUREMENT

### RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



## TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

## DEVIATION FROM TEST STANDARD


No deviation

## TEST SETUP


### (A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz

**EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 6V battery
Test Mode :	Mode 4	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P/F
--	--	--	--	PASS
--	--	--	--	PASS

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);  
Limit line = specific limits(dBuV) + distance extrapolation factor.

**TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 6V battery		
Test Mode :	Mode 4		


**Remark:**

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree	Comment
1	41.7129	23.95	-15.19	8.76	40.00	-31.24	QP		
2	49.8813	23.71	-14.75	8.96	40.00	-31.04	QP		
3	108.2667	24.71	-16.36	8.35	43.50	-35.15	QP		
4	199.9856	25.18	-15.63	9.55	43.50	-33.95	QP		
5	480.5276	27.63	-7.68	19.95	46.00	-26.05	QP		
6 *	714.1734	33.85	-2.70	31.15	46.00	-14.85	QP		



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 6V battery		
Test Mode :	Mode 4		

**Remark:**

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height cm	Table Degree
		dBuV	dB	dBuV/m	dB/m	dB		
1	44.1200	24.35	-14.88	9.47	40.00	-30.53	QP	
2	50.0566	24.32	-14.77	9.55	40.00	-30.45	QP	
3	114.9168	25.01	-17.22	7.79	43.50	-35.71	QP	
4	416.1791	26.24	-8.94	17.30	46.00	-28.70	QP	
5	576.6443	26.87	-5.31	21.56	46.00	-24.44	QP	
6 *	689.5643	32.76	-3.17	29.59	46.00	-16.41	QP	

**TEST RESULTS (1GHZ~25GHZ)**

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>operation frequency:2405</b>									
V	4810.00	66.16	39.55	7.85	25.66	60.12	74	-13.88	PK
V	4810.00	49.62	39.55	7.85	25.66	43.58	54	-10.42	AV
V	7215.00	66.40	38.33	7.52	24.55	60.14	74	-13.86	PK
V	7215.00	47.70	38.33	7.52	24.55	41.44	54	-12.56	AV
V	15450.00	50.98	35.23	6.75	26.59	49.09	74	-24.91	PK
H	4810.00	63.20	39.55	7.85	25.66	57.16	74	-16.84	PK
H	4810.00	49.43	39.55	7.85	25.66	43.39	54	-10.61	AV
H	7215.00	69.16	38.33	7.52	23.55	61.9	74	-12.10	PK
H	7215.00	50.96	38.33	7.52	23.22	43.37	54	-10.63	AV
H	15450.00	45.84	35.45	6.75	27.88	45.02	74	-28.98	PK
<b>operation frequency:2440</b>									
V	4880.00	65.71	38.89	7.57	25.45	59.84	74	-14.16	PK
V	4880.00	48.80	38.89	7.57	25.45	42.93	54	-11.07	AV
V	7320.00	66.83	38.78	7.35	24.78	60.18	74	-13.82	PK
V	7320.00	48.40	38.78	7.35	24.78	41.75	54	-12.25	AV
V	15450.00	52.51	35.89	6.42	26.47	49.51	74	-24.49	PK
H	4880.00	65.04	38.89	7.57	25.45	59.17	74	-14.83	PK
H	4880.00	49.70	38.89	7.57	25.45	43.83	54	-10.17	AV
H	7320.00	70.50	38.78	7.35	24.78	63.85	74	-10.15	PK
H	7320.00	48.96	38.78	7.35	24.78	42.31	54	-11.69	AV
H	15450.00	48.84	36.68	6.45	26.65	45.26	74	-28.74	PK
<b>operation frequency:2480</b>									
V	4960.00	67.71	38.75	7.46	25.45	61.87	74	-12.13	PK
V	4960.00	48.80	38.75	7.46	25.45	42.96	54	-11.04	AV
V	7440.00	68.83	38.65	7.22	24.78	62.18	74	-11.82	PK
V	7400.00	49.40	38.65	7.22	24.78	42.75	54	-11.25	AV
V	15450.00	53.51	35.58	6.35	26.47	50.75	74	-23.25	PK
H	4924.00	67.04	38.75	7.46	25.45	61.20	74	-12.80	PK
H	4924.00	50.74	38.75	7.46	25.45	44.90	54	-9.10	AV
H	7386.00	69.50	38.65	7.22	24.78	62.85	74	-11.15	PK
H	7386.00	48.71	38.65	7.22	24.78	42.06	54	-11.94	AV
H	15450.00	49.84	36.42	6.32	26.65	46.39	74	-27.61	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



### 3.3 RADIATED BAND EMISSION MEASUREMENT

#### 3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

#### 3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

## DEVIATION FROM TEST STANDARD

No deviation

## TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



## EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**TEST RESULT**

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>operation frequency:2405</b>							
V	2390.00	37.58	13.83	51.41	74.00	-22.59	PK
V	2390.00	26.11	13.83	39.94	54.00	-14.06	AV
V	2400.00	37.79	13.85	51.64	74.00	-22.36	PK
V	2400.00	25.69	13.85	39.54	54.00	-14.46	AV
H	2390.00	37.88	13.83	51.71	74.00	-22.29	PK
H	2390.00	26.13	13.83	39.96	54.00	-14.04	AV
H	2400.00	37.74	13.85	51.59	74.00	-22.41	PK
H	2400.00	26.08	13.85	39.93	54.00	-14.07	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
<b>operation frequency:2480</b>							
V	2483.50	37.79	14.02	51.81	74.00	-22.19	PK
V	2483.50	26.35	14.02	40.37	54.00	-13.63	AV
V	2500.00	37.73	14.06	51.79	74.00	-22.21	PK
V	2500.00	25.79	14.06	39.85	54.00	-14.15	AV
H	2483.50	37.92	14.02	51.94	74.00	-22.06	PK
H	2483.50	26.39	14.02	40.41	54.00	-13.59	AV
H	2500.00	37.53	14.06	51.59	74.00	-22.41	PK
H	2500.00	26.64	14.06	40.70	54.00	-13.30	AV

**Remark:**

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



## POWER SPECTRAL DENSITY TEST APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

### TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### DEVIATION FROM STANDARD

No deviation.

### TEST SETUP



### EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



## TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 6V battery
Test Mode :	CH1/ CH8/ CH16		

Frequency	Read Level (dBm)	Limit (dBm)	Result
2405 MHz	-14.54	8	PASS
2440 MHz	-14.03	8	PASS
2480 MHz	-14.77	8	PASS



## . BANDWIDTH TEST

### APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

### TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### DEVIATION FROM STANDARD

No deviation.

### TEST SETUP



### EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.






## TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 6V battery
Test Mode :	CH1/ CH8/ CH16		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2405	1.548	500	Pass
Middle	2440	1.524	500	Pass
High	2480	1.575	500	Pass

### 2405MHz







## PEAK OUTPUT POWER TEST

### APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

### TEST PROCEDURE

- The EUT was directly connected to the Power meter

### DEVIATION FROM STANDARD

No deviation.

### TEST SETUP



### EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**TEST RESULTS**

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 6V battery

Modulation Standard	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
O-QPSK	2405	15.48	30
	2440	15.35	30
	2480	15.42	30



## **. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


## **TEST PROCEDURE**

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

## **DEVIATION FROM STANDARD**

No deviation.

## **TEST SETUP**






## **EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## **TEST RESULTS**

## 2405MHz: Band Edge



## 2480MHz: Band Edge





## **. ANTENNA REQUIREMENT**

### **STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **EUT ANTENNA**

The EUT antenna is Internal antenna, and used permanent connection antenna, It complies with the standard requirement.


## . EUT TEST PHOTO

### Radiated Measurement Photos



### Radiated Measurement Photos



**. EUT PHOTO**

\*\*\*\*\* END OF REPORT \*\*\*\*\*