



WML-MOD-0000X

Label Content and Position

Label Material: Polyester, with permanent acrylic adhesive

Temperature Range: -70 to +100°

(Short term maximum of 80s at 300°C, suitable for reflow process)

Label size 12.7mm x 12.7mm

[e.g. Brady p/n THT-211-727-10 for printing on BP-PR600Plus-UK]

Label position: approximately central to screening can

Font: Arial Narrow or equivalent

Font size: Minimum 3pt

Text in **Green** subject to vary, see table below

| Part Code | USA | CANADA |
|---------------|-----------|-----------|
| | FCC ID | ISED ID |
| WML-MOD-00003 | 2AKX6-M03 | 22384-M03 |
| WML-MOD-00004 | 2AKX6-M04 | 22384-M04 |

2D Barcode is Data Matrix ECC 200 format

It contains manufacturer specific information (subject to vary)

The information should contain a field identifying the manufacturer along with other information agreed with that manufacturer

| Date | Rev | Changes | Drawn | Checked | Originator | Checked by | Sheet | Scale | Date |
|------------|-----|-------------------|----------|----------|------------|------------|--------|-------|------------|
| 2017-01-06 | 1 | New drawing | J Wilson | J Wilson | J Wilson | J Wilson | 1 of 1 | NTS | 2017-03-01 |
| 2017-02-21 | 2 | Correct IDs added | J Wilson | J Wilson | | | | | |
| 2017-03-01 | 3 | Corrected IDs | J Wilson | J Wilson | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |



WIRELESS
measurement

Title: STAMP Radio Module Label Specification

Drawing No. DWG-00312

Revision 3