

FCC Test Report

Report No.: AGC02762230802FR06

FCC ID : 2AL26-KS4-US

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : Body Worn Camera

BRAND NAME : Reveal Media

MODEL NAME : KS4

APPLICANT : Reveal Media Limited

DATE OF ISSUE : Dec. 20, 2023

STANDARD(S) : FCC Part 22 Subpart H
FCC Part 24 Subpart E
FCC Part 27 Subpart L

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 20, 2023	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Related Submittal(S) / Grant (S)	8
2.3 Test Methodology	8
2.4 Device Capabilities	8
2.5 Special Accessories	8
2.6 Equipment Modifications	8
2.7 Emission Designator	9
3. Test Environment	10
3.1 Address of The Test Laboratory	10
3.2 Test Facility	10
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	11
3.5 List of Test Equipment	12
4. System Test Configuration	14
4.1 EUT Configuration	14
4.2 EUT Exercise	14
4.3 Configuration of EUT System	14
4.4 Equipment Used in Tested System	14
5. Summary of Test Results	15
5.1 Test Condition: Conducted Test	15
5.2 Test Condition: Radiated Test	15
6. Description of Test Modes	16
7. Conducted Output Power	18
7.1 Provisions Applicable	18
7.2 Measurement Procedure	18
7.3 Measurement Setup	18
7.4 Measurement Result	19
8. Radiated Output Power	21
8.1 Provisions Applicable	21
8.2 Measurement Procedure	21
8.3 Measurement Setup	22
8.4 Measurement Result	24
9. Peak-to-Average Ratio	25
9.1 Provisions Applicable	25

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.2 Measurement Procedure.....	25
9.3 Measurement Setup	26
9.4 Measurement Result	27
10. 99% Occupied Bandwidth and 26dB Emission Bandwidth	28
10.1 Provisions Applicable	28
10.2 Measurement Procedure.....	28
10.3 Measurement Setup	28
10.4 Measurement Result	29
11. Band Edge Emissions at Antenna Terminal.....	32
11.1 Provisions Applicable.....	32
11.2 Measurement Procedure	32
11.3 Measurement Setup	32
11.4 Measurement Result	33
12. Spurious Emissions at Antenna Terminal	35
12.1 Provisions Applicable	35
12.2 Measurement Procedure.....	35
12.3 Measurement Setup	35
12.4 Measurement Result	36
13. Radiated Spurious Emission	41
13.1. Provisions Applicable	41
13.2. Measurement Procedure.....	41
13.3. Measurement Setup	43
13.4 Measurement Result	44
14. Frequency Stability / Variation of Ambient Temperature	50
14.1 Provisions Applicable	50
14.2 Measurement Procedure.....	50
14.3 Measurement Setup	51
14.4 Measurement Result	52
Appendix I: Photographs of Test Setup	57
Appendix II: Photographs of EUT.....	57

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

1. General Information

Applicant	Reveal Media Limited
Address	Riverview House, 20 Old Bridge Street, Hampton Wick, KT1 4BU, United Kingdom
Manufacturer	Reveal Media Hong Kong Ltd.
Address	6/F., Luk Kwok Centre, 72 Gloucester Road, Wan Chai, HongKong
Factory	Reveal Media Hong Kong Ltd.
Address	6/F., Luk Kwok Centre, 72 Gloucester Road, Wan Chai, HongKong
Product Designation	Body Worn Camera
Brand Name	Reveal Media
Test Model	KS4
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Aug. 03, 2023
Date of Test	Aug. 03, 2023~ Dec. 20, 2023
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-GSM&WCDMA-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By



Bibo Zhang
(Project Engineer)

Dec. 20, 2023

Reviewed By



Calvin Liu
(Reviewer)

Dec. 20, 2023

Approved By



Max Zhang
Authorized Officer

Dec. 20, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2. Product Information

2.1 Product Technical Description

Support Networks	WCDMA, HSDPA, HSUPA		
Hardware Version	EP-VRM05RFB-02		
Software Version	V1.0		
Support Frequency Band	☒ UMTS FDD Band II	☒ UMTS FDD Band IV	☒ UMTS FDD Band V
	(Non-U.S. Bands)		
Frequency Range	1852.4MHz-1907.6MHz (WCDMA Band II)		
	1712.4MHz-1752.6MHz (WCDMA Band IV)		
	826.4MHz-846.6 MHz (WCDMA Band V)		
Type of Modulation	BPSK/QPSK Modulation For WCDMA/HSDPA/HSUPA		
Emission Designator	WCDMA Band II:	4M15F9W	
	WCDMA Band IV:	4M19F9W	
	WCDMA Band V:	4M15F9W	
Antenna Designation	PIFA Antenna		
Antenna Gain	WCDMA850:-3.85dBi	WCDMA1700:-0.13dBi	WCDMA1900:0.05dBi
Power Supply	DC 3.8V by Built-in Li-ion Battery		
Dual Card	WCDMA Card Slot		
Extreme Vol. Limits	DC3.23V to 4.35V (Normal: DC 3.8V)		
Extreme Temp. Tolerance	-30 °C to +50 °C		
Temperature Range	-20°C to +50°C		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA SLOT 1:

	Maximum ERP/EIRP (dBm)	Max. Average Burst Power (dBm)
UMTS BAND V	20.74	23.65
UMTS BAND II	20.78	23.28
UMTS BAND IV	20.00	23.67

WCDMA SLOT 2:

	Maximum ERP/EIRP (dBm)	Max. Average Burst Power (dBm)
UMTS BAND V	20.55	21.75
UMTS BAND II	21.01	22.01
UMTS BAND IV	20.39	21.58

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.2 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AL26-KS4-US**, filing to comply with Part 2, Part 22/24/27 of the Federal Communication Commission rules.

2.3 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR FCC Part 2	Frequency allocations and radio treaty matters, general rules and regulations.
2	47 CFR FCC Part 22	Public Mobile Services.
3	47 CFR FCC Part 24	Personal Communications Services.
4	47 CFR FCC Part 27	Miscellaneous Wireless Communications Services.
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
6	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
7	KDB 971168	D01 v03r01 Measurement Guidance For Certification Of Licensed Digital Transmitters.

2.4 Device Capabilities

850/1700/1900 WCDMA/HSPA, Multi-Band LTE, 802.11 a/n/ac for UNII, Bluetooth (LE),NFC.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape),and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

This device supports dual-SIM communication, and only the data corresponding to the worst card slot (SIM Card 1) is reflected in the report.

2.5 Special Accessories

The battery was supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2.7 Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions
Temperature range	15~35℃	-20℃~50℃
Humidity range	20 % to 75 %.	20 % to 75 %.
Pressure range	86-106kPa	86-106kPa
Power supply	DC 3.8V	DC3.23V or 4.35V
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.		

3.4 Measurement Uncertainty

Test	Measurement Uncertainty
Transmitter power conducted	±0.57 dB
Transmitter power Radiated	±2.20 dB
Conducted spurious emission 9kHz-40 GHz	±2.20 dB
Occupied Bandwidth	±0.01ppm
Radiated Emission 30~1000MHz	±4.10dB
Radiated Emission Above 1GHz	±4.32dB
Conducted Disturbance:0.15~30MHz	±3.20dB
Radio Frequency	± 6.5 x 10 ⁻⁸
RF Power, Conducted	± 0.9 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

3.5 List of Test Equipment

● Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023-02-18	2024-02-17
☒	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
☒	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMW500	120909	2023-07-05	2024-07-04
☐	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2022-03-12	2024-03-11
☒	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
☒	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023-01-05	2024-01-04
☒	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22
☒	AGC-EM-E102	Broadband Ridged Horn Antenna	ETS	3117	00154520	2023-06-03	2024-06-02
☐	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2021-10-31	2023-10-30
☒	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
☐	AGC-EM-E021	Pre-amplifier	MITEQ	AM-4A-000115	1465421	2022-06-08	2024-06-07
☒	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2023-06-01	2024-05-31
☒	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08
☒	AGC-EM-A113	Band Stop Filter (825-850MHz)	MICRO-TRONICS	BRC50717	N/A	2023-06-01	2024-05-31
☒	AGC-EM-A114	Band Stop Filter (880-890MHz)	MICRO-TRONICS	BRC50718	N/A	2023-06-01	2024-05-31
☒	AGC-EM-A115	Band Stop Filter (1710-1785MHz)	MICRO-TRONICS	BRC50719	N/A	2023-06-01	2024-05-31
☒	AGC-EM-A116	Band Stop Filter (1850-1950MHz)	MICRO-TRONICS	BRC50720	N/A	2023-06-01	2024-05-31
☒	AGC-EM-A117	Band Stop Filter (1920-1980MHz)	MICRO-TRONICS	BRC50721	N/A	2023-06-01	2024-05-31

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

● Radiated Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☐	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023-02-18	2024-02-17
☒	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02
☒	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
☒	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
☒	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
☒	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22
☒	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03

● RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-ER-E087	Spectrum Analyzer	KEYSIGHT	N9020B	MY56101792	2023-06-01	2024-05-31
☒	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMW500	120909	2023-07-05	2024-07-04
☒	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMU200	113939	2023-06-01	2024-05-31
☒	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2022-08-03	2024-08-02
☒	--	Universal Switch Control Unit	Tonscend	JS	N/A	N/A	N/A
☐	AGC-ER-E033	RF Test Plat (DECT)	RTX	RTX-2012-HS-RF	N/A	2022-08-04	2024-08-03
☒	--	RF Connection Cable	N/A	1#	N/A	Each time	N/A
☒	--	RF Connection Cable	N/A	2#	N/A	Each time	N/A

● Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
☒	AGC-ER-S006	GSM Test System	Tonscend	JS1120-4	2.1.6.0
☒	AGC-ER-S007	WCDMA Test System	Tonscend	JS1120-3	2.1.5.10
☒	AGC-EM-S011	RSE Test System	Tonscend	TS ⁺ Ver2.1(JS36-RSE)	4.0.0.0

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4. System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of EUT System




Table 2-1 Equipment Used in EUT System

4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☒ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Huawei adapter	HW-200325CP0	huawei	Input: AC 100-240V 50/60Hz, 1.8A Output: DC 5V 2A	1.0m unshielded

☒ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	ICR011GB	ICON ENERGY SYSTEM (SHENZHEN) CO.,LTD	DC 3.8V 1000mAh	--

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5. Summary of Test Results

5.1 Test Condition: Conducted Test

Item	Test Description	FCC Rules	Result
1	Occupied Bandwidth	§2.1049	Pass
2	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal	§2.1051, §22.917(a), §24.238(a) §27.53(h)	Pass
3	Conducted Output Power	§2.1046	Pass
4	Frequency stability / variation of ambient temperature	§2.1055, § 22.355, §24.235, §27.54	Pass
5	Peak- to- Average Ratio	§24.232(d), §27.50(d)(5),	Pass

5.2 Test Condition: Radiated Test

Item	Test Description	FCC Rules	Result
1	Effective Radiated Power	§22.913(a)(5)	Pass
2	Equivalent Isotropic Radiated Power	§24.232(c), §27.50(d)(4)	Pass
3	Radiated Spurious and Harmonic Emissions	§2.1053, §22.917(a), §24.238(a), §27.53(h)	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6. Description of Test Modes

Bands	Tx/Rx Frequency	RF Channel		
		Low(L)	Middle(M)	High(H)
WCDMA band V	TX (824 MHz ~ 849 MHz)	Channel 4132	Channel 4182	Channel 4233
		826.4 MHz	836.4 MHz	846.6 MHz

Bands	Tx/Rx Frequency	RF Channel		
		Low(L)	Middle(M)	High(H)
WCDMA Band II	TX (1850 MHz-1910 MHz)	Channel 9262	Channel 9400	Channel 9538
		1852.4 MHz	1880.0 MHz	1907.6 MHz

Bands	Tx/Rx Frequency	RF Channel		
		Low(L)	Middle(M)	High(H)
WCDMA Band IV	TX (1710 MHz-1755 MHz)	Channel 1312	Channel 1412	Channel 1513
		1712.4 MHz	1732.4 MHz	1752.6 MHz

Pre-scan all bandwidth and RB, find worse case mode are chosen to the report, the worse mode applicability and tested channel detail as below:

Band	Radiated	Conducted
WCDMA Band II/IV/V	RMC 12.2kbps Link	RMC 12.2kbps Link

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	MAX(CM-1,0)
Note: CM=1 for $\beta_d/\beta_d=12/15, \beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensate for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

7. Conducted Output Power

7.1 Provisions Applicable

The conduction test is carried out in a shielded room. According to the test, connect the device under test to the antenna port on the non-conductive platform directly to the test device for evaluation and measurement (ANSI-C63.26-2015 Clause 5.4)


7.2 Measurement Procedure

- The transmitter output port was connected to base station.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
- The path loss was compensated to the results for each measurement.

Measure the maximum burst average power and average power for other modulation signal.

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all mode (WCDMA/HSPA band II, WCDMA/HSPA band IV ,WCDMA/HSPA band V)at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

7.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7.4 Measurement Result

WCDMA Band II Maximum Average Power (dBm)			
Channel	9262	9400	9538
Frequency (MHz)	1852.4 MHz	1880.0 MHz	1907.6 MHz
RMC 12.2kbps	22.52	22.72	23.28
HSDPA Subtest-1	22.23	22.73	22.41
HSDPA Subtest-2	21.55	22.13	21.89
HSDPA Subtest-3	21.58	22.14	21.83
HSDPA Subtest-4	21.70	22.11	21.78
HSUPA Subtest-1	21.80	21.05	22.19
HSUPA Subtest-2	22.28	22.71	22.76
HSUPA Subtest-3	22.04	22.32	22.44
HSUPA Subtest-4	22.90	22.08	22.15
HSUPA Subtest-5	21.00	21.23	20.33

WCDMA Band IV Maximum Average Power (dBm)			
Channel	1312	1412	1513
Frequency (MHz)	1712.4 MHz	1732.4 MHz	1752.6 MHz
RMC 12.2kbps	21.82	22.05	21.10
HSDPA Subtest-1	22.80	22.28	22.26
HSDPA Subtest-2	21.23	21.76	23.65
HSDPA Subtest-3	20.28	21.78	23.67
HSDPA Subtest-4	21.30	21.78	22.66
HSUPA Subtest-1	22.81	23.17	22.47
HSUPA Subtest-2	23.33	21.66	21.97
HSUPA Subtest-3	22.06	21.39	21.73
HSUPA Subtest-4	21.81	21.15	21.49
HSUPA Subtest-5	21.88	23.18	22.56

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA Band V Maximum Average Power (dBm)			
Channel	4132	4182	4233
Frequency(MHz)	826.4 MHz	836.4 MHz	846.6 MHz
RMC 12.2kbps	22.20	22.09	21.82
HSDPA Subtest-1	22.21	21.93	22.64
HSDPA Subtest-2	23.65	22.45	21.19
HSDPA Subtest-3	23.64	22.42	20.18
HSDPA Subtest-4	21.70	23.53	20.16
HSUPA Subtest-1	22.05	21.85	20.65
HSUPA Subtest-2	21.69	23.54	20.27
HSUPA Subtest-3	21.44	22.28	21.92
HSUPA Subtest-4	22.16	21.97	21.72
HSUPA Subtest-5	22.28	21.08	20.75

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. Radiated Output Power

8.1 Provisions Applicable

The radiation test is carried out in a semi-anechoic chamber.

According to the test, put the device under test on a non-conductive platform 3 meters away from the receiving antenna (ANSI/TIA-603-E-2016 Article 2.2.17).

The following rules are for the maximum radiated power limit requirements of the product:

Mode	Nominal Peak Power
WCDMA Band II	< 2 Watts max. EIRP (33dBm)
WCDMA Band IV	< 1 Watts max. EIRP (30dBm)
WCDMA Band V	< 7 Watts max. ERP (38.45dBm)

8.2 Measurement Procedure

1. Radiated power measurements are performed using the signal analyzer's "channel power"
2. measurement capability for signals with continuous operation.
3. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
4. VBW $\geq 3 \times$ RBW
5. Span = 1.5 times the OBW
6. No. of sweep points $> 2 \times$ span / RBW
7. Detector = RMS
8. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
9. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
10. Trace mode = trace averaging (RMS) over 100 sweeps
11. The trace was allowed to stabilize.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

● **Radiation Construction Method:**


1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
3. The power is calculated by the following formula:

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dB)}$$


4. Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.
5. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
6. The EUT was tested in three orthogonal planes (X, Y, Z) and in all possible test configurations and positioning.
7. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

8.3 Measurement Setup



Radiated Power 30MHz to 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Radiated Power Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.4 Measurement Result

Mode	Ch./ Freq.		Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	Limit	ERP	
	channel	Freq. (MHz)					W	W	dBm
WCDMA850	4132	826.4	15.87	5.90	1.21	H	< 7.00	0.114	20.56
	4183	836.6	16.09	5.90	1.25	H		0.119	20.74
	4233	846.6	15.89	5.90	1.24	H		0.114	20.55
HSPA	4132	826.4	14.26	5.90	1.21	H		0.079	18.95
	4183	836.6	13.83	5.90	1.25	H		0.070	18.48
	4233	846.6	14.03	5.90	1.24	H		0.074	18.69

Mode	Ch./ Freq.		Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	Limit	EIRP	
	channel	Freq. (MHz)					W	W	dBm
WCDMA 1900	9262	1852.4	14.29	8.6	2.11	H	< 2.00	0.120	20.78
	9400	1880.0	13.70	8.6	2.15	H		0.104	20.15
	9538	1907.6	13.89	8.6	2.15	H		0.108	20.34
HSPA	9262	1852.4	12.03	8.6	2.11	H		0.071	18.52
	9400	1880.0	11.61	8.6	2.15	H		0.064	18.06
	9538	1907.6	11.72	8.6	2.15	H		0.066	18.17
WCDMA 1700	1312	1712.4	13.64	8.3	2.05	H	< 1.00	0.097	19.89
	1412	1732.4	13.75	8.3	2.05	H		0.100	20.00
	1513	1752.6	13.70	8.3	2.06	H		0.099	19.94
HSPA	1312	1712.4	11.66	8.3	2.05	H		0.062	17.91
	1412	1732.4	11.61	8.3	2.05	H		0.061	17.86
	1513	1752.6	11.79	8.3	2.06	H		0.064	18.03

Note:

1. EIRP/ERP = Substitute Level (dBm) + Ant. Gain – C.L (Cable Loss)
2. All polarizations and modes have been tested, only the worst mode is recorded in the report

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9. Peak-to-Average Ratio

9.1 Provisions Applicable

This is the test for the Peak-to-Average Ratio from the EUT.

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

9.2 Measurement Procedure

CCDF Procedure for PAPR:

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time
4. that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

Alternate Procedure for PAPR:

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{PK} . Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R.(dB) = P_{PK} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Allow trace to fully stabilize.

Use the peak marker function to determine the peak amplitude level.

■ Test Settings (Peak Power):

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})$


Any report having not been signed by authorized approval, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

■ Test Settings (Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time: Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (Automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25%.

9.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.4 Measurement Result

Bands	Modulation	Peak-to-average ratio (dB)			Limit	Result
		Lowest	Middle	Highest	(dB)	
WCDMA Band II	RMC 12.2kbps	2.97	2.92	2.93	13	Pass
WCDMA Band II	HSUPA	3.07	2.99	3.06	13	Pass
WCDMA Band II	HSDPA	4.26	4.68	4.31	13	Pass
WCDMA Band IV	RMC 12.2kbps	8.42	8.44	8.42	13	Pass
WCDMA Band IV	HSUPA	3.30	3.46	3.24	13	Pass
WCDMA Band IV	HSDPA	4.20	4.53	4.26	13	Pass
WCDMA Band V	RMC 12.2kbps	3.07	2.97	3.24	13	Pass
WCDMA Band V	HSUPA	3.24	3.18	3.21	13	Pass
WCDMA Band V	HSDPA	4.44	4.44	4.43	13	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10. 99% Occupied Bandwidth and 26dB Emission Bandwidth

10.1 Provisions Applicable

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

10.2 Measurement Procedure

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99%
2. Occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by
3. any intermediate power nulls in the fundamental emission.
4. $RBW = 1 - 5\%$ of the expected OBW
5. $VBW \geq 3 \times RBW$
6. Detector = Peak
7. Trace mode = max hold
8. Sweep = auto couple
9. The trace was allowed to stabilize
10. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within
11. $1 - 5\%$ of the 99% occupied bandwidth observed in Step 7

10.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10.4 Measurement Result


Test Band	Test Mode	Test Channel	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Verdict
WCDMA 1900	UMTS	LCH	4.1533	4.740	Pass
		MCH	4.1469	4.740	Pass
		HCH	4.1554	4.728	Pass

Test Band	Test Mode	Test Channel	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Verdict
WCDMA 1700	UMTS	LCH	4.1888	4.710	Pass
		MCH	4.1905	4.698	Pass
		HCH	4.1857	4.703	Pass


Test Band	Test Mode	Test Channel	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Verdict
WCDMA 850	UMTS	LCH	4.1499	4.730	Pass
		MCH	4.1446	4.732	Pass
		HCH	4.1451	4.727	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


WCDMA 850_LCH




WCDMA 1900_LCH




WCDMA 850_MCH




WCDMA 1900_MCH



WCDMA 850_HCH



WCDMA 1900_HCH



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

11. Band Edge Emissions at Antenna Terminal

11.1 Provisions Applicable

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


11.2 Measurement Procedure

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Note


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. All measurements were done at 2 channels (low and high operational frequency range.) The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

11.3 Measurement Setup




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

11.4 Measurement Result



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

12. Spurious Emissions at Antenna Terminal

12.1 Provisions Applicable

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

12.2 Measurement Procedure


■ Test Settings (GSM)

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

■ Test Settings (WCDMA)


1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

12.3 Measurement Setup




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.4 Measurement Result




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: aac@aaccert.com Web: <http://www.aaccert.com/>



Note:

- Below 30MHz no Spurious found and above is the worst mode data.
- As no emission found in standby or receive mode, no recording in this report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

13. Radiated Spurious Emission

13.1. Provisions Applicable

(A) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm.

At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

(B) For specific criteria, please refer to the description in section 9.2 of the report for corresponding evaluation.

13.2. Measurement Procedure

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.
11. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT.
12. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
13. The spurious emissions is calculated by the following formula;
 - ✧ $\text{Result(dBm)} = \text{Pg(dBm)} + \text{Factor(dB)}$
 - ✧ $\text{Factor(dB)} = \text{Ant Gain(dB)} - \text{Cable Loss(dB)} + \text{Power Splitter(dB)}$ (Above 1GHz)
 - ✧ $\text{Factor(dB)} = \text{Ant Gain(dB)} - \text{Cable Loss(dB)}$ (Below 1GHz)
14. Where: P_{gis} the generator output power into the substitution antenna.
15. If the Fundamental frequency is below 1GHz, RF output power has been converted to EIRP.
 - ✧ $\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15$


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

13.3. Measurement Setup

Radiated Emissions 30MHz to 1GHz Test setup



Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

13.4 Measurement Result

The measurement Below 1GHz data as follows:

WCDMA Band II							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	159.115	-66.37	15.52	-50.85	-13.00	-37.85	Horizontal
2	241.582	-63.28	16.75	-46.53	-13.00	-33.53	Horizontal
3	754.425	-58.98	19.35	-39.63	-13.00	-26.63	Horizontal
4	46.691	-65.04	10.44	-54.60	-13.00	-41.60	Vertical
5	433.220	-61.03	17.75	-43.28	-13.00	-30.28	Vertical
6	502.580	-59.63	18.66	-40.97	-13.00	-27.97	Vertical
RMC 12.2kbps_ Middle Channel							
1	29.785	-62.99	9.78	-53.21	-13.00	-40.21	Horizontal
2	160.411	-64.55	13.75	-50.80	-13.00	-37.80	Horizontal
3	255.478	-61.04	16.75	-44.29	-13.00	-31.29	Horizontal
4	43.041	-63.75	10.23	-53.52	-13.00	-40.52	Vertical
5	432.152	-63.32	17.75	-45.57	-13.00	-32.57	Vertical
6	496.521	-58.90	18.02	-40.88	-13.00	-27.88	Vertical
RMC 12.2kbps_ Highest Channel							
1	158.526	-63.43	13.75	-49.68	-13.00	-36.68	Horizontal
2	240.695	-62.28	16.75	-45.53	-13.00	-32.53	Horizontal
3	679.128	-59.68	19.01	-40.67	-13.00	-27.67	Horizontal
4	43.428	-64.07	10.23	-53.84	-13.00	-40.84	Vertical
5	421.436	-62.11	17.75	-44.36	-13.00	-31.36	Vertical
6	498.820	-59.49	18.02	-41.47	-13.00	-28.47	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA Band IV							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	155.142	-65.76	15.52	-50.24	-13.00	-37.24	Horizontal
2	240.362	-61.93	16.75	-45.18	-13.00	-32.18	Horizontal
3	754.854	-59.33	19.35	-39.98	-13.00	-26.98	Horizontal
4	46.785	-64.48	10.44	-54.04	-13.00	-41.04	Vertical
5	433.415	-61.61	17.75	-43.86	-13.00	-30.86	Vertical
6	502.362	-59.20	18.66	-40.54	-13.00	-27.54	Vertical
RMC 12.2kbps_ Middle Channel							
1	31.425	-63.45	9.78	-53.67	-13.00	-40.67	Horizontal
2	159.695	-63.81	13.75	-50.06	-13.00	-37.06	Horizontal
3	240.714	-62.41	16.75	-45.66	-13.00	-32.66	Horizontal
4	43.296	-63.65	10.23	-53.42	-13.00	-40.42	Vertical
5	433.342	-62.96	17.75	-45.21	-13.00	-32.21	Vertical
6	498.758	-59.49	18.02	-41.47	-13.00	-28.47	Vertical
RMC 12.2kbps_ Highest Channel							
1	143.52	-63.12	13.75	-49.37	-13.00	-36.37	Horizontal
2	215.744	-62.29	16.75	-45.54	-13.00	-32.54	Horizontal
3	660.142	-59.83	19.01	-40.82	-13.00	-27.82	Horizontal
4	41.528	-63.49	10.23	-53.26	-13.00	-40.26	Vertical
5	421.635	-61.40	17.75	-43.65	-13.00	-30.65	Vertical
6	488.746	-59.12	18.02	-41.10	-13.00	-28.10	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA Band V							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	132.525	-65.45	15.52	-49.93	-13.00	-36.93	Horizontal
2	212.851	-62.93	16.75	-46.18	-13.00	-33.18	Horizontal
3	696.521	-59.27	19.35	-39.92	-13.00	-26.92	Horizontal
4	45.362	-65.02	10.44	-54.58	-13.00	-41.58	Vertical
5	421.521	-61.28	17.75	-43.53	-13.00	-30.53	Vertical
6	552.362	-59.45	18.66	-40.79	-13.00	-27.79	Vertical
RMC 12.2kbps_ Middle Channel							
1	32.536	-63.30	9.78	-53.52	-13.00	-40.52	Horizontal
2	159.527	-62.92	13.75	-49.17	-13.00	-36.17	Horizontal
3	240.189	-62.07	16.75	-45.32	-13.00	-32.32	Horizontal
4	43.214	-64.16	10.23	-53.93	-13.00	-40.93	Vertical
5	431.362	-62.17	17.75	-44.42	-13.00	-31.42	Vertical
6	485.417	-59.30	18.02	-41.28	-13.00	-28.28	Vertical
RMC 12.2kbps_ Highest Channel							
1	165.759	-63.91	13.75	-50.16	-13.00	-37.16	Horizontal
2	228.141	-61.44	16.75	-44.69	-13.00	-31.69	Horizontal
3	652.433	-60.07	19.01	-41.06	-13.00	-28.06	Horizontal
4	42.213	-64.32	10.23	-54.09	-13.00	-41.09	Vertical
5	431.300	-61.43	17.75	-43.68	-13.00	-30.68	Vertical
6	496.710	-59.31	18.02	-41.29	-13.00	-28.29	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

The measurement Above 1GHz data as follows:

WCDMA Band II							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	3704.800	-82.83	31.09	-51.74	-13.00	-38.74	Horizontal
2	5557.200	-90.33	34.14	-56.19	-13.00	-43.19	Horizontal
3	3704.800	-81.12	33.13	-47.99	-13.00	-34.99	Vertical
4	5557.200	-86.10	32.66	-53.44	-13.00	-40.44	Vertical
RMC 12.2kbps_ Middle Channel							
1	3760.000	-79.60	31.09	-48.51	-13.00	-35.51	Horizontal
2	5640.000	-87.67	34.14	-53.53	-13.00	-40.53	Horizontal
3	3760.000	-79.96	33.13	-46.83	-13.00	-33.83	Vertical
4	5640.000	-85.00	32.66	-52.34	-13.00	-39.34	Vertical
RMC 12.2kbps_ Highest Channel							
1	3815.200	-83.55	31.09	-52.46	-13.00	-39.46	Horizontal
2	5722.800	-86.23	34.14	-52.09	-13.00	-39.09	Horizontal
3	3815.200	-82.89	33.13	-49.76	-13.00	-36.76	Vertical
4	5722.800	-83.36	32.66	-50.70	-13.00	-37.70	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA Band IV							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	3424.800	-90.22	32.11	-58.11	-13.00	-45.11	Horizontal
2	5137.200	-88.28	33.21	-55.07	-13.00	-42.07	Horizontal
3	3424.800	-90.24	32.09	-58.15	-13.00	-45.15	Vertical
4	5137.200	-87.59	34.03	-53.56	-13.00	-40.56	Vertical
RMC 12.2kbps_ Middle Channel							
1	3464.800	-88.64	32.11	-56.53	-13.00	-43.53	Horizontal
2	5197.200	-87.17	33.21	-53.96	-13.00	-40.96	Horizontal
3	3464.800	-90.11	32.09	-58.02	-13.00	-45.02	Vertical
4	5197.200	-87.09	34.03	-53.06	-13.00	-40.06	Vertical
RMC 12.2kbps_ Highest Channel							
1	3505.200	-89.16	32.11	-57.05	-13.00	-44.05	Horizontal
2	5257.800	-85.87	33.21	-52.66	-13.00	-39.66	Horizontal
3	3505.200	-89.15	32.09	-57.06	-13.00	-44.06	Vertical
4	5257.800	-86.20	34.03	-52.17	-13.00	-39.17	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

WCDMA Band V							
No.	Frequency	SA Reading	Correction factor	EIRP Result	Limit	Margin	Ant. Pol.
	(MHz)	(dBm)	(dB/m)	(dBm)	(dBm)	(dB)	
RMC 12.2kbps_ Lowest Channel							
1	1652.800	-84.05	23.12	-60.93	-13.00	-47.93	Horizontal
2	2479.200	-86.12	28.47	-57.65	-13.00	-44.65	Horizontal
3	1652.800	-83.81	23.12	-60.69	-13.00	-47.69	Vertical
4	2479.200	-83.27	28.47	-54.80	-13.00	-41.80	Vertical
RMC 12.2kbps_ Middle Channel							
1	1672.800	-81.41	23.12	-58.29	-13.00	-45.29	Horizontal
2	2509.200	-84.18	28.47	-55.71	-13.00	-42.71	Horizontal
3	1672.800	-82.81	23.12	-59.69	-13.00	-46.69	Vertical
4	2509.200	-82.18	28.47	-53.71	-13.00	-40.71	Vertical
RMC 12.2kbps_ Highest Channel							
1	1693.200	-80.75	23.12	-57.63	-13.00	-44.63	Horizontal
2	2539.800	-82.71	28.47	-54.24	-13.00	-41.24	Horizontal
3	1693.200	-80.94	23.12	-57.82	-13.00	-44.82	Vertical
4	2539.800	-81.22	28.47	-52.75	-13.00	-39.75	Vertical

Note:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test. Subsequently, only the worst case emissions are reported.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

14. Frequency Stability / Variation of Ambient Temperature

14.1 Provisions Applicable

14.1.1 For Hand carried battery powered equipment

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

14.1.2 For equipment powered by primary supply voltage

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a
2. reference).
3. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to
4. the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
5. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at
6. least one half-hour is provided to allow stabilization of the equipment at each temperature level.

14.2 Measurement Procedure

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.


1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on channel 20175 for LTE band 4 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
3. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
4. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.

5. Subject the EUT to overnight soak at +50°C.
6. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
7. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
8. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

14.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

14.4 Measurement Result

● Frequency Error vs. Voltage:

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt.(V)	Freq. Error (Hz)	Freq. vs Rated (ppm)	Limit (ppm)	Verdict
WCDMA850	UMTS	LCH	TN	VL	-1.04	-0.001258	±2.5	Pass
			TN	VN	-1.39	-0.001682	±2.5	Pass
			TN	VH	-1.12	-0.001355	±2.5	Pass
		MCH	TN	VL	-0.29	-0.000347	±2.5	Pass
			TN	VN	-0.34	-0.000407	±2.5	Pass
			TN	VH	-0.11	-0.000132	±2.5	Pass
		HCH	TN	VL	-0.46	-0.000543	±2.5	Pass
			TN	VN	-0.35	-0.000413	±2.5	Pass
			TN	VH	-0.29	-0.000343	±2.5	Pass

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt.(V)	Freq. Error (Hz)	Freq. vs Rated (ppm)	Verdict
WCDMA1700	UMTS	LCH	TN	VL	-2.10	-0.001226	Pass
			TN	VN	-2.05	-0.001197	Pass
			TN	VH	-2.31	-0.001349	Pass
		MCH	TN	VL	-2.43	-0.001403	Pass
			TN	VN	-2.20	-0.001270	Pass
			TN	VH	-1.90	-0.001097	Pass
		HCH	TN	VL	-1.70	-0.000970	Pass
			TN	VN	-2.13	-0.001215	Pass
			TN	VH	-1.86	-0.001061	Pass

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt.(V)	Freq. Error (Hz)	Freq. vs Rated (ppm)	Verdict
WCDMA1900	UMTS	LCH	TN	VL	8.44	0.004556	Pass
			TN	VN	9.23	0.004983	Pass
			TN	VH	10.17	0.005490	Pass
		MCH	TN	VL	-0.82	-0.000436	Pass
			TN	VN	-0.19	-0.000101	Pass
			TN	VH	-1.32	-0.000702	Pass
		HCH	TN	VL	-12.13	-0.006359	Pass
			TN	VN	-11.33	-0.005939	Pass
			TN	VH	-12.15	-0.006369	Pass

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

● **Frequency Error vs. Temperature:**

Test Band	Test Mode	Test Channel	Test Volt.	Test Tem. (°C)	Freq. Error (Hz)	Freq. vs rated (ppm)	Limit (ppm)	Verdict
WCDMA850	UMTS	LCH	VN	-30	-0.35	-0.000424	±2.5	Pass
			VN	-20	-0.49	-0.000593	±2.5	Pass
			VN	-10	-0.64	-0.000774	±2.5	Pass
			VN	0	-0.09	-0.000109	±2.5	Pass
			VN	10	-0.42	-0.000508	±2.5	Pass
			VN	20	-0.23	-0.000278	±2.5	Pass
			VN	30	-0.55	-0.000666	±2.5	Pass
			VN	40	-0.44	-0.000532	±2.5	Pass
			VN	50	-0.64	-0.000774	±2.5	Pass
WCDMA850	UMTS	MCH	VN	-30	-0.58	-0.000702	±2.5	Pass
			VN	-20	-0.66	-0.000799	±2.5	Pass
			VN	-10	-0.45	-0.000545	±2.5	Pass
			VN	0	-0.61	-0.000738	±2.5	Pass
			VN	10	-0.57	-0.000690	±2.5	Pass
			VN	20	-0.46	-0.000557	±2.5	Pass
			VN	30	-0.15	-0.000182	±2.5	Pass
			VN	40	-0.38	-0.000460	±2.5	Pass
			VN	50	-0.50	-0.000605	±2.5	Pass
WCDMA850	UMTS	HCH	VN	-30	-0.53	-0.000641	±2.5	Pass
			VN	-20	-0.64	-0.000774	±2.5	Pass
			VN	-10	-0.87	-0.001053	±2.5	Pass
			VN	0	-0.21	-0.000254	±2.5	Pass
			VN	10	-0.66	-0.000799	±2.5	Pass
			VN	20	-0.54	-0.000653	±2.5	Pass
			VN	30	-0.80	-0.000968	±2.5	Pass
			VN	40	-0.84	-0.001004	±2.5	Pass
			VN	50	-0.51	-0.000610	±2.5	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Band	Test Mode	Test Channel	Test Volt.	Test Tem. (°C)	Freq. Error (Hz)	Freq. vs Rated (ppm)	Verdict
WCDMA1700	UMTS	LCH	VN	-30	1.46	0.000853	Pass
			VN	-20	1.47	0.000858	Pass
			VN	-10	1.36	0.000794	Pass
			VN	0	1.82	0.001063	Pass
			VN	10	1.60	0.000934	Pass
			VN	20	1.61	0.000940	Pass
			VN	30	1.49	0.000870	Pass
			VN	40	1.49	0.000870	Pass
			VN	50	1.62	0.000946	Pass
WCDMA1700	UMTS	MCH	VN	-30	1.42	0.000829	Pass
			VN	-20	1.93	0.001127	Pass
			VN	-10	1.57	0.000917	Pass
			VN	0	2.14	0.001250	Pass
			VN	10	2.35	0.001372	Pass
			VN	20	1.65	0.000964	Pass
			VN	30	1.86	0.001086	Pass
			VN	40	1.62	0.000946	Pass
			VN	50	1.87	0.001092	Pass
WCDMA1700	UMTS	HCH	VN	-30	1.79	0.001045	Pass
			VN	-20	1.60	0.000934	Pass
			VN	-10	1.59	0.000929	Pass
			VN	0	1.82	0.001063	Pass
			VN	10	2.15	0.001256	Pass
			VN	20	1.91	0.001115	Pass
			VN	30	1.97	0.001150	Pass
			VN	40	1.72	0.000993	Pass
			VN	50	1.47	0.000848	Pass

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Band	Test Mode	Test Channel	Test Volt.	Test Tem. (°C)	Freq. Error (Hz)	Freq. vs Rated (ppm)	Verdict
WCDMA1900	UMTS	LCH	VN	-30	-4.17	-0.002251	Pass
			VN	-20	-4.07	-0.002197	Pass
			VN	-10	-4.33	-0.002338	Pass
			VN	0	-4.15	-0.002240	Pass
			VN	10	-4.17	-0.002251	Pass
			VN	20	-4.38	-0.002365	Pass
			VN	30	-4.26	-0.002300	Pass
			VN	40	-4.33	-0.002338	Pass
			VN	50	-3.95	-0.002132	Pass
WCDMA1900	UMTS	MCH	VN	-30	-4.38	-0.002365	Pass
			VN	-20	-4.63	-0.002499	Pass
			VN	-10	-4.09	-0.002208	Pass
			VN	0	-4.41	-0.002381	Pass
			VN	10	-4.16	-0.002246	Pass
			VN	20	-4.06	-0.002192	Pass
			VN	30	-4.24	-0.002289	Pass
			VN	40	-4.06	-0.002192	Pass
			VN	50	-3.93	-0.002122	Pass
WCDMA1900	UMTS	HCH	VN	-30	-4.16	-0.002246	Pass
			VN	-20	-4.06	-0.002192	Pass
			VN	-10	-3.94	-0.002127	Pass
			VN	0	-4.13	-0.002230	Pass
			VN	10	-3.68	-0.001987	Pass
			VN	20	-4.12	-0.002224	Pass
			VN	30	-3.92	-0.002116	Pass
			VN	40	-4.28	-0.002277	Pass
			VN	50	-4.00	-0.002128	Pass

Note: Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC02762230802AP02

Appendix II: Photographs of EUT

Refer to the Report No.: AGC02762230802AP04

-----End of Report-----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>