

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

**FCC PART 15 SUBPART C TEST REPORT****FCC PART 15.247****Report Reference No.....: GTS20191209006-2-11****FCC ID.....: 2AL6KBL-M8723DU1**

Compiled by

( position+printed name+signature)...: File administrators Peter Xiao

Supervised by

( position+printed name+signature)...: Test Engineer Moon Tan

Approved by

( position+printed name+signature)...: Manager Simon Hu

Date of issue.....: Dec.23, 2019

**Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

**Applicant's name.....: Shenzhen Bilian Electronic Co.,Ltd.**

Address .....: Building B1, Zhongxing Industrial Zone, Juling, Jutang Community, Guanlan street, LongHua district, Shenzhen, China

**Test specification .....**Standard .....: **FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description .....: IEEE 802.11b/g/n (1T1R) WiFi and Bluetooth Module**

Trade Mark .....: N/A

Manufacturer .....: Shenzhen Bilian Electronic Co.,Ltd.

Model/Type reference.....: BL-M8723DU1

Listed Models .....: N/A

Operation Frequency.....: From 2412MHz to 2462MHz

Hardware Version .....: 1.0

Software Version .....: V1.0

Rating .....: DC 3.3V

Result.....: **PASS**

**TEST REPORT**

|                                              |                               |
|----------------------------------------------|-------------------------------|
| <b>Test Report No. :</b> GTS20191209006-2-11 | Dec.23, 2019<br>Date of issue |
|----------------------------------------------|-------------------------------|

Equipment under Test : IEEE 802.11b/g/n (1T1R) WiFi and Bluetooth Module

Model /Type : BL-M8723DU1

Listed Models : N/A

**Applicant** : **Shenzhen Bilian Electronic Co.,Ltd.**

Address : Building B1, Zhongxing Industrial Zone, Juling, Jutang Community,  
Guanlan street, LongHua district, Shenzhen, China

**Manufacturer** : **Shenzhen Bilian Electronic Co.,Ltd.**

Address : Building B1, Zhongxing Industrial Zone, Juling, Jutang Community,  
Guanlan street, LongHua district, Shenzhen, China

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>1. TEST STANDARDS .....</b>                                 | <b>4</b>  |
| <b>2. SUMMARY .....</b>                                        | <b>5</b>  |
| 2.1. General Remarks .....                                     | 5         |
| 2.2. Product Description .....                                 | 5         |
| 2.3. Equipment Under Test .....                                | 6         |
| 2.4. Short description of the Equipment under Test (EUT) ..... | 6         |
| 2.5. EUT operation mode .....                                  | 6         |
| 2.6. Block Diagram of Test Setup .....                         | 6         |
| 2.7. Related Submittal(s) / Grant (s) .....                    | 6         |
| 2.8. Special Accessories .....                                 | 6         |
| 2.9. Modifications .....                                       | 6         |
| <b>3. TEST ENVIRONMENT .....</b>                               | <b>7</b>  |
| 3.1. Address of the test laboratory .....                      | 7         |
| 3.2. Test Facility .....                                       | 7         |
| 3.3. Environmental conditions .....                            | 7         |
| 3.4. Test Description .....                                    | 8         |
| 3.5. Statement of the measurement uncertainty .....            | 9         |
| 3.6. Equipments Used during the Test.....                      | 10        |
| <b>4. TEST CONDITIONS AND RESULTS .....</b>                    | <b>11</b> |
| 4.1. AC Power Conducted Emission .....                         | 11        |
| 4.2. Radiated Emission .....                                   | 13        |
| 4.3. Maximum Peak Output Power .....                           | 19        |
| 4.4. Power Spectral Density .....                              | 20        |
| 4.5. 6dB Bandwidth .....                                       | 23        |
| 4.6. Band Edge Compliance of RF Emission .....                 | 26        |
| 4.7. Antenna Requirement .....                                 | 31        |
| <b>5. TEST SETUP PHOTOS OF THE EUT .....</b>                   | <b>32</b> |
| <b>6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>        | <b>32</b> |

## **1. TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 DTS Meas Guidance v05r02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

## 2. SUMMARY

### 2.1. General Remarks

|                                |   |              |
|--------------------------------|---|--------------|
| Date of receipt of test sample | : | Dec.13, 2019 |
|                                | : |              |
| Testing commenced on           | : | Dec.13, 2019 |
|                                | : |              |
| Testing concluded on           | : | Dec.23, 2019 |

### 2.2. Product Description

|                      |                                                                                              |
|----------------------|----------------------------------------------------------------------------------------------|
| Product Name         | IEEE 802.11b/g/n (1T1R) WiFi and Bluetooth Module                                            |
| Trade Mark           | N/A                                                                                          |
| Model/Type reference | BL-M8723DU1                                                                                  |
| List Models          | N/A                                                                                          |
| Model Declaration    | N/A                                                                                          |
| Power supply:        | DC 3.3V                                                                                      |
| Bluetooth            |                                                                                              |
| Operation frequency  | 2402-2480MHz                                                                                 |
| Channel Number       | 79 channels for Bluetooth (DSS)<br>40 channels for Bluetooth (DTS)                           |
| Channel Spacing      | 1MHz for Bluetooth (DSS)<br>2MHz for Bluetooth (DTS)                                         |
| Modulation Type      | GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth (DSS)<br>GFSK for Bluetooth (DTS)                  |
| WIFI(2.4G Band)      |                                                                                              |
| Frequency Range      | 2412MHz ~ 2462MHz                                                                            |
| Channel Spacing      | 5MHz                                                                                         |
| Channel Number       | 11 Channel for 20MHz bandwidth(2412~2462MHz)<br>7 channels for 40MHz bandwidth(2422~2452MHz) |
| Modulation Type      | 802.11b: DSSS; 802.11g/n: OFDM                                                               |
| Antenna Description  | External Antenna , 2.0dBi(Max.)                                                              |

## 2.3. Equipment Under Test

### Power supply system utilised

|                      |   |                                                                   |                                   |
|----------------------|---|-------------------------------------------------------------------|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                                | <input type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 12 V DC                                     | <input type="radio"/> 24 V DC     |
|                      |   | <input checked="" type="radio"/> Other (specified in blank below) |                                   |

DC 3.3V

## 2.4. Short description of the Equipment under Test (EUT)

This is a IEEE 802.11b/g/n (1T1R) WiFi and Bluetooth Module.  
For more details, refer to the user's manual of the EUT.


## 2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 1       | 2412           | 8       | 2447           |
| 2       | 2417           | 9       | 2452           |
| 3       | 2422           | 10      | 2457           |
| 4       | 2427           | 11      | 2462           |
| 5       | 2432           |         |                |
| 6       | 2437           |         |                |
| 7       | 2442           |         |                |

## 2.6. Block Diagram of Test Setup



## 2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AL6KBL-M8723DU1** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.8. Special Accessories

| Manufacturer | Description | Model             | Serial Number | Certificate |
|--------------|-------------|-------------------|---------------|-------------|
| TOSHIBA      | PC          | Satellite S40Dt-A | --            | SDOC        |

The Computer and Displayer is provided by the laboratory.

## 2.9. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

#### **3.3. Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 15-35 ° C    |
|                       |              |
| Humidity:             | 30-60 %      |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

### 3.4. Test Description

| Test Specification clause | Test case                               | Test Mode                                          | Test Channel                                                                                                                            | Recorded In Report                                 |                                                                                                                                         | Pass                                                                                                              | Fail                     | NA                                  | NP                       | Remark   |
|---------------------------|-----------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------|--------------------------|----------|
| §15.247(b)(4)             | Antenna gain                            | 802.11b                                            | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b                                            | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(e)                | Power spectral density                  | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(a)(2)             | Spectrum bandwidth – 6 dB bandwidth     | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(b)(1)             | Maximum output power                    | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/><br><input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | Band edge compliance conducted          | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.205                   | Band edge compliance radiated           | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | TX spurious emissions conducted         | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/><br><input checked="" type="checkbox"/>                                        | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.247(d)                | TX spurious emissions radiated          | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | 802.11b<br>802.11g<br>802.11n HT20<br>802.11n HT40 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.109                   | RX spurious emissions radiated          | -/-                                                | -/-                                                                                                                                     | -/-                                                | -/-                                                                                                                                     | <input type="checkbox"/>                                                                                          | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | complies |
| §15.209(a)                | TX spurious Emissions radiated < 30 MHz | 802.11b                                            | -/-                                                                                                                                     | 802.11b                                            | -/-                                                                                                                                     | <input checked="" type="checkbox"/>                                                                               | <input type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/> | complies |
| §15.107(a)<br>§15.207     | Conducted Emissions < 30 MHz            | 802.11b                                            | -/-                                                                                                                                     | 802.11b                                            | -/-                                                                                                                                     | <input type="checkbox"/>                                                                                          | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | complies |

## Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                       | Mode            | Data Rate | Channel |
|--------------------------------------------------|-----------------|-----------|---------|
| Maximum Peak Conducted Output Power              | 11b/DSSS        | 1 Mbps    | 1/7/11  |
| Power Spectral Density                           | 11g/OFDM        | 6 Mbps    | 1/7/11  |
| 6dB Bandwidth                                    | 11n(20MHz)/OFDM | 6.5Mbps   | 1/7/11  |
| Spurious RF conducted emission                   | 11n(40MHz)/OFDM | 13.5Mbps  | 3/7/11  |
| Radiated Emission 9kHz~1GHz&                     |                 |           |         |
| Radiated Emission 1GHz~10 <sup>th</sup> Harmonic |                 |           |         |
| Band Edge                                        | 11b/DSSS        | 1 Mbps    | 1/11    |
|                                                  | 11g/OFDM        | 6 Mbps    | 1/11    |
|                                                  | 11n(20MHz)/OFDM | 6.5Mbps   | 1/11    |
|                                                  | 11n(40MHz)/OFDM | 13.5Mbps  | 3/9     |

### 3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test                  | Range      | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission     | 30~1000MHz | 4.10 dB                 | (1)   |
| Radiated Emission     | 1~18GHz    | 4.32 dB                 | (1)   |
| Radiated Emission     | 18-40GHz   | 5.54 dB                 | (1)   |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB                 | (1)   |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.6. Equipments Used during the Test


| Test Equipment             | Manufacturer                      | Model No.             | Serial No.      | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN                       | R&S                               | ENV216                | 3560.6550.08    | 2019/09/20       | 2020/09/19           |
| LISN                       | R&S                               | ESH2-Z5               | 893606/008      | 2019/09/20       | 2020/09/19           |
| EMI Test Receiver          | R&S                               | ESPI3                 | 101841-cd       | 2019/09/20       | 2020/09/19           |
| EMI Test Receiver          | R&S                               | ESCI7                 | 101102          | 2019/09/20       | 2020/09/19           |
| Spectrum Analyzer          | Agilent                           | N9020A                | MY48010425      | 2019/09/20       | 2020/09/19           |
| Spectrum Analyzer          | R&S                               | FSV40                 | 100019          | 2019/09/20       | 2020/09/19           |
| Vector Signal generator    | Agilent                           | N5181A                | MY49060502      | 2019/09/20       | 2020/09/19           |
| Signal generator           | Agilent                           | E4421B                | 3610AO1069      | 2019/09/20       | 2020/09/19           |
| Climate Chamber            | ESPEC                             | EL-10KA               | A20120523       | 2019/09/20       | 2020/09/19           |
| Controller                 | EM Electronics                    | Controller EM 1000    | N/A             | N/A              | N/A                  |
| Horn Antenna               | Schwarzbeck                       | BBHA 9120D            | 01622           | 2019/09/23       | 2020/09/22           |
| Active Loop Antenna        | Beijing Da Ze Technology Co.,Ltd. | ZN30900C              | 15006           | 2019/10/12       | 2020/10/11           |
| Bilog Antenna              | Schwarzbeck                       | VULB9163              | 000976          | 2019/05/26       | 2020/05/25           |
| Broadband Horn Antenna     | SCHWARZBECK                       | BBHA 9170             | 791             | 2019/09/20       | 2020/09/19           |
| Amplifier                  | Schwarzbeck                       | BBV 9743              | #202            | 2019/09/20       | 2020/09/19           |
| Amplifier                  | Schwarzbeck                       | BBV9179               | 9719-025        | 2019/09/20       | 2020/09/19           |
| Amplifier                  | EMCI                              | EMC051845B            | 980355          | 2019/09/20       | 2020/09/19           |
| Temperature/Humidity Meter | Gangxing                          | CTH-608               | 02              | 2019/09/20       | 2020/09/19           |
| High-Pass Filter           | K&L                               | 9SH10-2700/X12750-O/O | KL142031        | 2019/09/20       | 2020/09/19           |
| High-Pass Filter           | K&L                               | 41H10-1375/U12750-O/O | KL142032        | 2019/09/20       | 2020/09/19           |
| RF Cable(below 1GHz)       | HUBER+SUHNER                      | RG214                 | RE01            | 2019/09/20       | 2020/09/19           |
| RF Cable(above 1GHz)       | HUBER+SUHNER                      | RG214                 | RE02            | 2019/09/20       | 2020/09/19           |
| Data acquisition card      | Agilent                           | U2531A                | TW53323507      | 2019/09/20       | 2020/09/19           |
| Power Sensor               | Agilent                           | U2021XA               | MY5365004       | 2019/09/20       | 2020/09/19           |
| Test Control Unit          | Tonscend                          | JS0806-1              | 178060067       | 2019/06/20       | 2020/06/19           |
| Automated filter bank      | Tonscend                          | JS0806-F              | 19F8060177      | 2019/06/20       | 2020/06/19           |
| EMI Test Software          | Tonscend                          | JS1120-1              | Ver 2.6.8.0518  | /                | /                    |
| EMI Test Software          | Tonscend                          | JS1120-3              | Ver 2.5.77.0418 | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-CE               | Ver 2.5         | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-RE               | Ver 2.5.1.8     | /                | /                    |

Note: The Cal.Interval was one year.

## 4. TEST CONDITIONS AND RESULTS

### 4.1. AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 5V power from PC, the PC received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark: We measured Conducted Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode in AC 120V/60Hz , the worst case was recorded .


Power supply:

AC 120V/60Hz

Polarization

L

Test Graph



Final Data List

| NO. | Frequency<br>[MHz] | QP<br>Reading<br>[dBμV] | AVG.<br>Reading<br>[dBμV] | Factor<br>[dB] | QP<br>Result<br>[dBμV] | AVG.<br>Result<br>[dBμV] | QP<br>Limit<br>[dBμV] | AVG.<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AVG.<br>Margin<br>[dB] | Line | Remark |
|-----|--------------------|-------------------------|---------------------------|----------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|------|--------|
| 1   | 0.2003             | 32.08                   | 17.26                     | 10.15          | 42.23                  | 27.41                    | 63.60                 | 53.60                   | 21.37                | 26.19                  | L1   | PASS   |
| 2   | 0.5864             | 22.14                   | 18.57                     | 10.19          | 32.33                  | 28.76                    | 56.00                 | 46.00                   | 23.67                | 17.24                  | L1   | PASS   |
| 3   | 3.0985             | 19.55                   | 12.14                     | 10.34          | 29.89                  | 22.48                    | 56.00                 | 46.00                   | 26.11                | 23.52                  | L1   | PASS   |
| 4   | 7.0923             | 26.80                   | 16.93                     | 10.52          | 37.31                  | 27.44                    | 60.00                 | 50.00                   | 22.69                | 22.56                  | L1   | PASS   |
| 5   | 7.5894             | 29.23                   | 17.18                     | 10.55          | 39.78                  | 27.73                    | 60.00                 | 50.00                   | 20.22                | 22.27                  | L1   | PASS   |
| 6   | 14.1058            | 33.50                   | 24.70                     | 10.88          | 44.38                  | 35.58                    | 60.00                 | 50.00                   | 15.62                | 14.42                  | L1   | PASS   |

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


Power supply:

AC 120V/60Hz

Polarization

N

Test Graph



Final Data List

| NO. | Frequency<br>[MHz] | QP<br>Reading<br>[dBμV] | AVG.<br>Reading<br>[dBμV] | Factor<br>[dB] | QP<br>Result<br>[dBμV] | AVG.<br>Result<br>[dBμV] | QP<br>Limit<br>[dBμV] | AVG.<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AVG.<br>Margin<br>[dB] | Line | Remark |
|-----|--------------------|-------------------------|---------------------------|----------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|------|--------|
| 1   | 0.1921             | 31.28                   | 17.02                     | 10.16          | 41.44                  | 27.18                    | 63.95                 | 53.95                   | 22.51                | 26.77                  | N    | PASS   |
| 2   | 0.5958             | 25.84                   | 23.68                     | 10.19          | 36.03                  | 33.87                    | 56.00                 | 46.00                   | 19.97                | 12.13                  | N    | PASS   |
| 3   | 1.1051             | 24.06                   | 16.17                     | 10.21          | 34.27                  | 26.38                    | 56.00                 | 46.00                   | 21.73                | 19.62                  | N    | PASS   |
| 4   | 5.6832             | 36.13                   | 27.79                     | 10.44          | 46.58                  | 38.24                    | 60.00                 | 50.00                   | 13.42                | 11.76                  | N    | PASS   |
| 5   | 7.5385             | 35.95                   | 24.46                     | 10.54          | 46.50                  | 35.01                    | 60.00                 | 50.00                   | 13.50                | 14.99                  | N    | PASS   |
| 6   | 14.1250            | 30.85                   | 22.17                     | 10.89          | 41.73                  | 33.05                    | 60.00                 | 50.00                   | 18.27                | 16.95                  | N    | PASS   |


Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


## 4.2. Radiated Emission

### TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 30MHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 30MHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type          | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna        | 3             |
| 30MHz-1GHz           | Ultra-Broadband Antenna    | 3             |
| 1GHz-18GHz           | Double Ridged Horn Antenna | 3             |
| 18GHz-25GHz          | Horn Antenna               | 1             |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

|                           |                                            |
|---------------------------|--------------------------------------------|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude    | AG = Amplifier Gain                        |
| AF = Antenna Factor       |                                            |

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

**RADIATION LIMIT**


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m)                            | Radiated (µV/m)       |
|-----------------|-------------------|----------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz})) + 40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz})) + 40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30) + 40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                         | 100                   |
| 88-216          | 3                 | 43.5                                         | 150                   |
| 216-960         | 3                 | 46.0                                         | 200                   |
| Above 960       | 3                 | 54.0                                         | 500                   |

**TEST RESULTS**


Remark: We measured Radiated Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode from 30 MHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

**For 30MHz-1GHz****Horizontal****Test Graph****Suspected List**

| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity   | Remark |
|-----|-----------------|------------------|-------------|-----------------|----------------|-------------|-------------|-----------|----------|------------|--------|
| 1   | 44.0650         | 31.67            | -6.53       | 25.14           | 40.00          | 14.86       | 100         | 210       | PK       | Horizontal | PASS   |
| 2   | 350.5850        | 36.87            | -5.95       | 30.92           | 46.00          | 15.08       | 100         | 60        | PK       | Horizontal | PASS   |
| 3   | 406.8450        | 39.35            | -5.10       | 34.25           | 46.00          | 11.75       | 100         | 170       | PK       | Horizontal | PASS   |
| 4   | 576.1100        | 35.85            | -2.48       | 33.37           | 46.00          | 12.63       | 100         | 270       | PK       | Horizontal | PASS   |
| 5   | 799.6950        | 33.06            | 1.20        | 34.26           | 46.00          | 11.74       | 100         | 120       | PK       | Horizontal | PASS   |
| 6   | 850.6200        | 34.73            | 1.63        | 36.36           | 46.00          | 9.64        | 100         | 60        | PK       | Horizontal | PASS   |

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

**Vertical****Test Graph****Suspected List**

| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity | Remark |
|-----|-----------------|------------------|-------------|-----------------|----------------|-------------|-------------|-----------|----------|----------|--------|
| 1   | 45.0350         | 31.50            | -6.51       | 24.99           | 40.00          | 15.01       | 100         | 280       | PK       | Vertical | PASS   |
| 2   | 345.2500        | 35.66            | -6.02       | 29.64           | 46.00          | 16.36       | 100         | 20        | PK       | Vertical | PASS   |
| 3   | 418.4850        | 38.94            | -4.82       | 34.12           | 46.00          | 11.88       | 100         | 30        | PK       | Vertical | PASS   |
| 4   | 576.1100        | 35.26            | -2.48       | 32.78           | 46.00          | 13.22       | 100         | 320       | PK       | Vertical | PASS   |
| 5   | 782.7200        | 34.61            | 0.94        | 35.55           | 46.00          | 10.45       | 100         | 200       | PK       | Vertical | PASS   |
| 6   | 930.1600        | 30.68            | 5.35        | 36.03           | 46.00          | 9.97        | 100         | 160       | PK       | Vertical | PASS   |

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

## For 1GHz to 25GHz

IEEE 802.11b

Channel 1 / 2412 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 50.53        | 32.44          | 30.25        | 7.95         | 60.67           | 74.00        | -13.33    | Peak    | Horizontal |
| 4824.00   | 35.63        | 32.44          | 30.25        | 7.95         | 45.77           | 54.00        | -8.23     | Average | Horizontal |
| 4824.00   | 54.56        | 32.44          | 30.25        | 7.95         | 64.70           | 74.00        | -9.30     | Peak    | Vertical   |
| 4824.00   | 35.38        | 32.44          | 30.25        | 7.95         | 45.52           | 54.00        | -8.48     | Average | Vertical   |

Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 50.60        | 32.52          | 30.31        | 8.12         | 60.93           | 74.00        | -13.07    | Peak    | Horizontal |
| 4874.00   | 36.62        | 32.52          | 30.31        | 8.12         | 46.95           | 54.00        | -7.05     | Average | Horizontal |
| 4874.00   | 51.46        | 32.52          | 30.31        | 8.12         | 61.79           | 74.00        | -12.21    | Peak    | Vertical   |
| 4874.00   | 36.30        | 32.52          | 30.31        | 8.12         | 46.63           | 54.00        | -7.37     | Average | Vertical   |

Channel 11 / 2462 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 51.70        | 32.68          | 30.27        | 7.88         | 61.99           | 74.00        | -12.01    | Peak    | Horizontal |
| 4924.00   | 35.41        | 32.68          | 30.27        | 7.88         | 45.70           | 54.00        | -8.30     | Average | Horizontal |
| 4924.00   | 49.83        | 32.68          | 30.27        | 7.88         | 60.12           | 74.00        | -13.88    | Peak    | Vertical   |
| 4924.00   | 31.27        | 32.68          | 30.27        | 7.88         | 41.56           | 54.00        | -12.44    | Average | Vertical   |

IEEE 802.11g

Channel 1 / 2412 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 50.30        | 32.44          | 30.25        | 7.95         | 60.44           | 74.00        | -13.56    | Peak    | Horizontal |
| 4824.00   | 35.26        | 32.44          | 30.25        | 7.95         | 45.40           | 54.00        | -8.60     | Average | Horizontal |
| 4824.00   | 53.20        | 32.44          | 30.25        | 7.95         | 63.34           | 74.00        | -10.66    | Peak    | Vertical   |
| 4824.00   | 36.10        | 32.44          | 30.25        | 7.95         | 46.24           | 54.00        | -7.76     | Average | Vertical   |

Channel 6 / 2437 MHz

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.61        | 32.52          | 30.31        | 8.12         | 59.94           | 74.00        | -14.06    | Peak    | Horizontal |
| 4874.00   | 37.85        | 32.52          | 30.31        | 8.12         | 48.18           | 54.00        | -5.82     | Average | Horizontal |
| 4874.00   | 50.84        | 32.52          | 30.31        | 8.12         | 61.17           | 74.00        | -12.83    | Peak    | Vertical   |
| 4874.00   | 36.75        | 32.52          | 30.31        | 8.12         | 47.08           | 54.00        | -6.92     | Average | Vertical   |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 50.78        | 32.68          | 30.27        | 7.88         | 61.07           | 74.00        | -12.93    | Peak    | Horizontal |
| 4924.00   | 35.64        | 32.68          | 30.27        | 7.88         | 45.93           | 54.00        | -8.07     | Average | Horizontal |
| 4924.00   | 48.79        | 32.68          | 30.27        | 7.88         | 59.08           | 74.00        | -14.92    | Peak    | Vertical   |
| 4924.00   | 31.57        | 32.68          | 30.27        | 7.88         | 41.86           | 54.00        | -12.14    | Average | Vertical   |

*IEEE802.11 n HT20**Channel 1 / 2412 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4824.00   | 50.66        | 32.44          | 30.25        | 7.95         | 60.80           | 74.00        | -13.20    | Peak    | Horizontal |
| 4824.00   | 35.45        | 32.44          | 30.25        | 7.95         | 45.59           | 54.00        | -8.41     | Average | Horizontal |
| 4824.00   | 54.69        | 32.44          | 30.25        | 7.95         | 64.83           | 74.00        | -9.17     | Peak    | Vertical   |
| 4824.00   | 35.04        | 32.44          | 30.25        | 7.95         | 45.18           | 54.00        | -8.82     | Average | Vertical   |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.52        | 32.52          | 30.31        | 8.12         | 59.85           | 74.00        | -14.15    | Peak    | Horizontal |
| 4874.00   | 36.60        | 32.52          | 30.31        | 8.12         | 46.93           | 54.00        | -7.07     | Average | Horizontal |
| 4874.00   | 51.92        | 32.52          | 30.31        | 8.12         | 62.25           | 74.00        | -11.75    | Peak    | Vertical   |
| 4874.00   | 36.35        | 32.52          | 30.31        | 8.12         | 46.68           | 54.00        | -7.32     | Average | Vertical   |

*Channel 11 / 2462 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4924.00   | 50.70        | 32.68          | 30.27        | 7.88         | 60.99           | 74.00        | -13.01    | Peak    | Horizontal |
| 4924.00   | 35.40        | 32.68          | 30.27        | 7.88         | 45.69           | 54.00        | -8.31     | Average | Horizontal |
| 4924.00   | 49.01        | 32.68          | 30.27        | 7.88         | 59.30           | 74.00        | -14.70    | Peak    | Vertical   |
| 4924.00   | 30.79        | 32.68          | 30.27        | 7.88         | 41.08           | 54.00        | -12.92    | Average | Vertical   |

*IEEE802.11 n HT40**Channel 3 / 2422 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4844.00   | 50.35        | 32.44          | 30.25        | 7.95         | 60.49           | 74.00        | -13.51    | Peak    | Horizontal |
| 4844.00   | 34.91        | 32.44          | 30.25        | 7.95         | 45.05           | 54.00        | -8.95     | Average | Horizontal |
| 4844.00   | 53.88        | 32.44          | 30.25        | 7.95         | 64.02           | 74.00        | -9.98     | Peak    | Vertical   |
| 4844.00   | 34.62        | 32.44          | 30.25        | 7.95         | 44.76           | 54.00        | -9.24     | Average | Vertical   |

*Channel 6 / 2437 MHz*

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4874.00   | 49.79        | 32.52          | 30.31        | 8.12         | 60.12           | 74.00        | -13.88    | Peak    | Horizontal |
| 4874.00   | 37.04        | 32.52          | 30.31        | 8.12         | 47.37           | 54.00        | -6.63     | Average | Horizontal |
| 4874.00   | 51.80        | 32.52          | 30.31        | 8.12         | 62.13           | 74.00        | -11.87    | Peak    | Vertical   |
| 4874.00   | 36.56        | 32.52          | 30.31        | 8.12         | 46.89           | 54.00        | -7.11     | Average | Vertical   |

*Channel 9 / 2452 MHz*


| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4904.00   | 50.12        | 32.68          | 30.27        | 7.88         | 60.41           | 74.00        | -13.59    | Peak    | Horizontal |
| 4904.00   | 36.08        | 32.68          | 30.27        | 7.88         | 46.37           | 54.00        | -7.63     | Average | Horizontal |
| 4904.00   | 48.85        | 32.68          | 30.27        | 7.88         | 59.14           | 74.00        | -14.86    | Peak    | Vertical   |
| 4904.00   | 32.40        | 32.68          | 30.27        | 7.88         | 42.69           | 54.00        | -11.31    | Average | Vertical   |

## REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

### 4.3. Maximum Peak Output Power

#### TEST CONFIGURATION



#### TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2. and Average conducted output power, 9.2.3.1.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The maximum Average conducted output power may be measured using a wideband RF power meter with a thermocouple detector or equivalent. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### LIMIT

The Maximum Peak Output Power Measurement is 30dBm.


#### TEST RESULTS

| Type          | Channel | Output power PK (dBm) | Output power AV (dBm) | Limit (dBm) | Result |
|---------------|---------|-----------------------|-----------------------|-------------|--------|
| 802.11b       | 01      | 16.07                 | 13.29                 | 30.00       | Pass   |
|               | 06      | 16.93                 | 13.32                 |             |        |
|               | 11      | 16.27                 | 13.93                 |             |        |
| 802.11g       | 01      | 16.60                 | 13.34                 | 30.00       | Pass   |
|               | 06      | 16.22                 | 13.95                 |             |        |
|               | 11      | 16.68                 | 13.95                 |             |        |
| 802.11n(HT20) | 01      | 15.71                 | 11.19                 | 30.00       | Pass   |
|               | 06      | 15.83                 | 11.74                 |             |        |
|               | 11      | 15.15                 | 11.89                 |             |        |
| 802.11n(HT40) | 03      | 14.20                 | 9.04                  | 30.00       | Pass   |
|               | 06      | 14.12                 | 9.40                  |             |        |
|               | 09      | 14.18                 | 9.65                  |             |        |

Note: 1.The test results including the cable lose.  
Duty cycle used in all test items: 100%

#### 4.4. Power Spectral Density

##### TEST CONFIGURATION



##### TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.







1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.







##### LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

##### TEST RESULTS


| Type          | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|---------------|---------|-----------------------------------|------------------|--------|
| 802.11b       | 01      | -13.65                            | 8.00             | Pass   |
|               | 06      | -12.56                            |                  |        |
|               | 11      | -13.85                            |                  |        |
| 802.11g       | 01      | -19.69                            | 8.00             | Pass   |
|               | 06      | -17.95                            |                  |        |
|               | 11      | -19.95                            |                  |        |
| 802.11n(HT20) | 01      | -19.70                            | 8.00             | Pass   |
|               | 06      | -18.76                            |                  |        |
|               | 11      | -20.15                            |                  |        |
| 802.11n(HT40) | 03      | -19.43                            | 8.00             | Pass   |
|               | 06      | -19.10                            |                  |        |
|               | 09      | -18.85                            |                  |        |





#### 4.5. 6dB Bandwidth

##### TEST CONFIGURATION



##### TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.

The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


##### LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz


##### TEST RESULTS

| Type        | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|-------------|---------|---------------------|-------------|--------|
| 802.11b     | 01      | 8.120               | $\geq 500$  | Pass   |
|             | 06      | 8.120               |             |        |
|             | 11      | 8.120               |             |        |
| 802.11g     | 01      | 16.440              | $\geq 500$  | Pass   |
|             | 06      | 16.400              |             |        |
|             | 11      | 16.400              |             |        |
| 802.11nHT20 | 01      | 17.640              | $\geq 500$  | Pass   |
|             | 06      | 17.680              |             |        |
|             | 11      | 17.400              |             |        |
| 802.11nHT40 | 03      | 36.240              | $\geq 500$  | Pass   |
|             | 06      | 36.160              |             |        |
|             | 09      | 36.160              |             |        |


802.11b



CH01




CH06




CH11


802.11g



CH01




CH06



CH11

## 802.11n HT20



CH01




CH06




CH11


## 802.11n HT40



CH03



CH06



CH09

## 4.6. Band Edge Compliance of RF Emission

### TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### TEST PROCEDURE

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies  $\leq 30$  MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies  $> 1000$  MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:  

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB $\mu$ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.

### LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

**TEST RESULTS****4.6.1 For Radiated Bandedge Measurement****802.11b**

| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
|-----------------|-------------------------|----|----------------|-------------|--------------------|----------------------|------------------|-----------------------|-------------------|---------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 46.12                   | PK | 74.00          | -27.88      | 1                  | 125                  | 51.43            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 33.92                   | AV | 54.00          | -20.08      | 1                  | 125                  | 39.23            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 45.57                   | PK | 74.00          | -28.43      | 1                  | 247                  | 50.88            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 34.07                   | AV | 54.00          | -19.93      | 1                  | 247                  | 39.38            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 48.44                   | PK | 74.00          | -25.56      | 1                  | 153                  | 54.16            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 36.55                   | AV | 54.00          | -17.45      | 1                  | 153                  | 42.27            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 49.37                   | PK | 74.00          | -24.63      | 1                  | 203                  | 55.09            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 36.87                   | AV | 54.00          | -17.13      | 1                  | 203                  | 42.59            | 27.45                 | 3.38              | 36.55         | -5.72                    |

**802.11g**

| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
|-----------------|-------------------------|----|----------------|-------------|--------------------|----------------------|------------------|-----------------------|-------------------|---------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 46.57                   | PK | 74.00          | -27.43      | 1                  | 154                  | 51.88            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 33.82                   | AV | 54.00          | -20.18      | 1                  | 154                  | 39.13            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 47.13                   | PK | 74.00          | -26.87      | 1                  | 266                  | 52.44            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 35.40                   | AV | 54.00          | -18.60      | 1                  | 266                  | 40.71            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 49.90                   | PK | 74.00          | -24.10      | 1                  | 175                  | 55.62            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 35.08                   | AV | 54.00          | -18.92      | 1                  | 175                  | 40.80            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 49.79                   | PK | 74.00          | -24.21      | 1                  | 255                  | 55.51            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 35.10                   | AV | 54.00          | -18.90      | 1                  | 255                  | 40.82            | 27.45                 | 3.38              | 36.55         | -5.72                    |



## 802.11n HT20


| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
|-----------------|-------------------------|----|----------------|-------------|--------------------|----------------------|------------------|-----------------------|-------------------|---------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 46.19                   | PK | 74.00          | -27.81      | 1                  | 135                  | 51.50            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 35.11                   | AV | 54.00          | -18.89      | 1                  | 135                  | 40.42            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2412           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 46.33                   | PK | 74.00          | -27.67      | 1                  | 217                  | 51.64            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 35.17                   | AV | 54.00          | -18.83      | 1                  | 217                  | 40.48            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 49.19                   | PK | 74.00          | -24.81      | 1                  | 166                  | 54.91            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 35.01                   | AV | 54.00          | -18.99      | 1                  | 166                  | 40.73            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| Frequency(MHz): |                         |    | 2462           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 48.87                   | PK | 74.00          | -25.13      | 1                  | 111                  | 54.59            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 36.43                   | AV | 54.00          | -17.57      | 1                  | 111                  | 42.15            | 27.45                 | 3.38              | 36.55         | -5.72                    |

## 802.11n HT40

| Frequency(MHz): |                         |    | 2422           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
|-----------------|-------------------------|----|----------------|-------------|--------------------|----------------------|------------------|-----------------------|-------------------|---------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 46.26                   | PK | 74.00          | -27.74      | 1                  | 118                  | 51.57            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 35.30                   | AV | 54.00          | -18.70      | 1                  | 118                  | 40.61            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2422           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2390.00         | 45.16                   | PK | 74.00          | -28.84      | 1                  | 74                   | 50.47            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| 2390.00         | 34.32                   | AV | 54.00          | -19.68      | 1                  | 74                   | 39.63            | 27.49                 | 3.32              | 36.12         | -5.31                    |
| Frequency(MHz): |                         |    | 2452           |             |                    | Polarity:            |                  |                       | HORIZONTAL        |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 48.70                   | PK | 74.00          | -25.30      | 1                  | 182                  | 54.42            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 36.01                   | AV | 54.00          | -17.99      | 1                  | 182                  | 41.73            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| Frequency(MHz): |                         |    | 2452           |             |                    | Polarity:            |                  |                       | VERTICAL          |               |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier | Correction Factor (dB/m) |
| 2483.50         | 49.48                   | PK | 74.00          | -24.52      | 1                  | 232                  | 55.20            | 27.45                 | 3.38              | 36.55         | -5.72                    |
| 2483.50         | 35.10                   | AV | 54.00          | -18.90      | 1                  | 232                  | 40.82            | 27.45                 | 3.38              | 36.55         | -5.72                    |

4.6.2 For Conducted Bandedge Measurement





## 4.7. Antenna Requirement

### Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **Antenna Information**

The antenna is External Antenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 2.0dBi.

Reference to the test report No. **GTS20191209006-2-9**

## **5. TEST SETUP PHOTOS OF THE EUT**

Reference to the TEST SETUP PHOTOS

## **6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT**

Reference to the EXTERNAL AND INTERNAL PHOTOS

.....End of Report.....