



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.407

Report Reference No.....: GTS20190613008-1-8

FCC ID..... : 2AL6KBL-R8812RD3

Compiled by

(position+printed name+signature)..: File administrators Tracy Hu

Supervised by

(position+printed name+signature)..: Test Engineer Moon Tan

Approved by

(position+printed name+signature)..: Manager Simon Hu



Date of issue.....: Aug. 30, 2019

Representative Laboratory Name ..: Shenzhen Global Test Service Co.,Ltd.

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name ..: Shenzhen Bilian Electronic Co.,Ltd.

Address ..: Building B1,Zhongxing Industrial Zone,Juling,Jutang Community, Guanlan street,Longhua New District, Shenzhen,Guangdong,P.R. China

Test specification ..:

Standard ..: **FCC Part 15.407: UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description ..: 1200Mbps WIRELESS USB ADAPTER

Trade Mark ..: /

Manufacturer ..: Shenzhen Bilian Electronic Co.,Ltd.

Model/Type reference.....: BL-R8812RD3

Listed Models ..: N/A

Operation Frequency.....: From 5180MHz to 5240MHz/ 5745MHz to 5825MHz

Rating ..: DC 5V

Result.....: **PASS**

TEST REPORT

Test Report No. : GTS20190613008-1-8	Aug. 30, 2019
	Date of issue

Equipment under Test : 1200Mbps WIRELESS USB ADAPTER

Model /Type : BL-R8812RD3

Listed Models : N/A

Applicant : **Shenzhen Bilian Electronic Co.,Ltd.**

Address : Building B1,Zhongxing Industrial Zone,Juling,Jutang Community,
Guanlan street,Longhua New District, Shenzhen,Guangdong,P.R.
China

Manufacturer : **Shenzhen Bilian Electronic Co.,Ltd.**

Address : Building B1,Zhongxing Industrial Zone,Juling,Jutang Community,
Guanlan street,Longhua New District, Shenzhen,Guangdong,P.R.
China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	5
2.4. Short description of the Equipment under Test (EUT)	6
2.5. EUT operation mode	6
2.6. Block Diagram of Test Setup	6
2.7. Related Submittal(s) / Grant (s)	6
2.8. Special Accessories	6
2.9. Modifications	6
3. TEST ENVIRONMENT	7
3.1. Address of the test laboratory	7
3.2. Test Facility	7
3.3. Environmental conditions	7
3.4. Test Description	8
3.5. Statement of the measurement uncertainty	9
3.6. Equipments Used during the Test.....	10
4. TEST CONDITIONS AND RESULTS	11
4.1. AC Power Conducted Emission	11
4.2. Radiated Emission	13
4.3. Duty Cycle	20
4.4. Maximum Average Output Power	24
4.5. Power Spectral Density	28
4.6. 6dB Bandwidth	46
4.7. 26dBc Bandwidth	54
4.8. Band Edge Compliance	62
4.9. Antenna Requirement	73
5. TEST SETUP PHOTOS OF THE EUT	74
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	75

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Aug. 19, 2019
Testing commenced on	:	Aug. 29 2019
Testing concluded on	:	Aug. 30, 2019

2.2. Product Description

Product Name:	1200Mbps WIRELESS USB ADAPTER
Trade Mark:	/
Model/Type reference:	BL-R8812RD3
List Model:	N/A
Power supply:	DC 5V
WIFI	
WLAN	Supported 802.11 a/b/g/n HT20/n HT40/ac VHT20/ac VHT40/ac VHT80
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM,QPSK, BPSK) IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM,QPSK,BPSK) IEEE 802.11ac20/40/80: OFDM(64QAM, 16QAM, 256QAM,QPSK, BPSK)
Operation frequency	IEEE 802.11a:5180-5240MHz 5745-5825MHz IEEE 802.11b:2412-2472MHz IEEE 802.11g:2412-2472MHz IEEE 802.11n HT20:2412-2472MHz, 5180-5240MHz 5745-5825MHz IEEE 802.11n HT40:2422-2462MHz, 5190-5230MHz 5755-5795MHz IEEE 802.11ac20:5180-5240MHz 5745-5825MHz IEEE 802.11ac40:5190-5230MHz 5755-5795MHz IEEE 802.11ac80:5210MHz 5775MHz
Channel number	13 Channels for WIFI 20MHz Bandwidth(802.11b/g/n-HT20) 9 Channels for WIFI 40MHz Bandwidth(802.11n-HT40) 4 channels for 20MHz bandwidth(5180-5240MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 1 channels for 80MHz bandwidth(5210MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna Description	Two same PCB Antenna,2.00dBi(Max.)

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 5V

2.4. Short description of the Equipment under Test (EUT)

This is a 1200Mbps WIRELESS USB ADAPTER.
 For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

IEEE 802.11a/ac20/ac40/ac80/n20/n40:

UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AL6KBL-R8812RD3** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
DELL	Notebook	LAPTITU	6699565657	DELL

2.9. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.203	Antenna gain	802.11ac	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11ac	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Power spectral density	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Spectrum bandwidth – 26 dB bandwidth	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(e)	Spectrum bandwidth – 6 dB bandwidth	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Maximum output power	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(b)	Band edge compliance conducted	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(b)	Band edge compliance radiated	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	TX spurious emissions conducted	-/-	-/-	-/-	-/-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	TX spurious emissions radiated	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(g)	Frequency Stability	-/-	-/-	-/-	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth 26dB Bandwidth Radiated Emission 30M~1GHz & Radiated Emission 1GHz~10 th Harmonic	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0
Band Edge	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2018/09/28	2019/09/27
LISN	R&S	ESH2-Z5	893606/008	2018/09/27	2019/09/26
By-log Antenna	SCHWARZBECK	VULB9163	000976	2018/09/29	2019/09/28
EMI Test Receiver	R&S	ESCI	101102	2018/09/26	2019/09/25
Spectrum Analyzer	Agilent	N9020A	MY48010425	2018/09/17	2019/09/16
Spectrum Analyzer	R&S	FSV40-N	101800	2018/09/17	2019/09/16
Controller	EM Electronics	Controller EM 1000	N/A	2018/09/21	2019/09/20
Double Ridged Horn Antenna (1~18GHz)	SCHWARZBECK	BBHA 9120D	01622	2018/09/19	2019/09/18
Double Ridged Horn Antenna	Rohde&Schwarz	HF907	100265	2018/09/19	2019/09/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2018/09/19	2019/09/18
Horn Antenna (18GHz~40GHz)	ETS	3116	00086467	2018/12/29	2019/12/28
Amplifier (26.5GHz~40GHz)	EMCI	EMC2654045	980028	2018/09/18	2019/09/17
Amplifier (0.1GHz~26.5GHz)	EMCI	EMC012645SE	980355	2018/09/19	2019/09/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2018/09/20	2019/09/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2018/09/20	2019/09/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2018/09/20	2019/09/19
Data acquisition card	Agilent	U2531A	TW53323507	2018/09/20	2019/09/19
Power Sensor	Agilent	U2021XA	MY5365004	2018/09/20	2019/09/19
RF Cable	HUBER+SUHNER	RG214	N/A	2018/09/20	2019/09/19
Broadband Antenna	SCHWARZBECK	VULB 9163	00976	2018/09/29	2019/09/28
Conducted Emission	ES-K1	V1.71	N/A	N/A	N/A
Radiated Emission	JS32-RE	V2.5.0.9	N/A	N/A	N/A

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 5V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit



For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS


Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .




4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 5825MHz.so radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at all mode from 30MHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

For 30MHz-1GHz



For 1GHz to 40GHz
5150-5250MHz:

802.11a Mode_Channel 36_ 5180 MHz Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10360	35.12	38.55	33.13	11.26	51.8	68.2	16.4	Peak	Horizontal
1	10360	25.01	38.55	33.13	11.26	41.69	68.2	26.51	Peak	Vertical

802.11a Mode_Channel 40_ 5200 MHz Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10400	35.21	38.55	33.13	11.26	51.89	68.2	16.31	Peak	Horizontal
1	10400	25.35	38.55	33.13	11.26	42.03	68.2	26.17	Peak	Vertical

802.11a Mode_Channel 48_ 5240 MHz Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10480	35.29	38.55	33.13	11.26	51.97	68.2	16.23	Peak	Horizontal
1	10480	24.98	38.55	33.13	11.26	41.66	68.2	26.54	Peak	Vertical

802.11a Mode_Channel 36_ 5180 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10360	35.44	38.55	33.13	11.26	52.12	68.2	16.08	Peak	Horizontal
1	10360	25.29	38.55	33.13	11.26	41.97	68.2	26.23	Peak	Vertical

802.11a Mode_Channel 40_ 5200 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10400	34.66	38.55	33.13	11.26	51.34	68.2	16.86	Peak	Horizontal
1	10400	25.82	38.55	33.13	11.26	42.50	68.2	25.70	Peak	Vertical

802.11a Mode_Channel 48_ 5240 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10480	34.58	38.55	33.13	11.26	51.26	68.2	16.94	Peak	Horizontal
1	10480	24.64	38.55	33.13	11.26	41.32	68.2	26.88	Peak	Vertical

802.11n20 Mode_Channel 36_ 5180 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10360	34.93	38.55	33.13	11.26	51.61	68.2	16.59	Peak	Horizontal
1	10360	24.46	38.55	33.13	11.26	41.14	68.2	27.06	Peak	Vertical

802.11n20 Mode_Channel 40_ 5200 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Margin (dB)	Detector	Polarization
1	10400	35.38	38.55	33.13	11.26	52.06	68.2	16.14	Peak	Horizontal
1	10400	25.44	38.55	33.13	11.26	42.12	68.2	26.08	Peak	Vertical

802.11n20 Mode_Channel 48_ 5240 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10480	35.80	38.55	33.13	11.26	52.48	68.2	15.72	Peak	Horizontal
1	10480	25.32	38.55	33.13	11.26	42.00	68.2	26.20	Peak	Vertical

802.11n40 Mode_Channel 38_ 5190 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10380	35.00	38.55	33.13	11.26	51.68	68.2	16.52	Peak	Horizontal
1	10380	24.96	38.55	33.13	11.26	41.64	68.2	26.56	Peak	Vertical

802.11n40 Mode_Channel 46_ 5230 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10460	35.12	38.55	33.13	11.26	51.80	68.2	16.40	Peak	Horizontal
1	10460	24.38	38.55	33.13	11.26	41.06	68.2	27.14	Peak	Vertical

802.11ac20 Mode_Channel 36_ 5180 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10360	35.18	38.55	33.13	11.26	51.86	68.2	16.34	Peak	Horizontal
1	10360	24.87	38.55	33.13	11.26	41.55	68.2	26.65	Peak	Vertical

802.11ac20 Mode_Channel 40_ 5200 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10400	34.44	38.55	33.13	11.26	51.12	68.2	17.08	Peak	Horizontal
1	10400	24.89	38.55	33.13	11.26	41.57	68.2	26.63	Peak	Vertical

802.11ac20 Mode_Channel 48_ 5240 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10480	35.34	38.55	33.13	11.26	52.02	68.2	16.18	Peak	Horizontal
1	10480	24.37	38.55	33.13	11.26	41.05	68.2	27.15	Peak	Vertical

802.11ac40 Mode_Channel 38_ 5190 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10380	35.51	38.55	33.13	11.26	52.19	68.2	16.01	Peak	Horizontal
1	10380	25.27	38.55	33.13	11.26	41.95	68.2	26.25	Peak	Vertical

802.11ac40 Mode_Channel 46_ 5230 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10460	35.35	38.55	33.13	11.26	52.03	68.2	16.17	Peak	Horizontal
1	10460	25.74	38.55	33.13	11.26	42.42	68.2	25.78	Peak	Vertical

802.11ac80 Mode_Channel 42_ 5210 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10420	34.64	38.55	33.13	11.26	51.32	68.2	16.88	Peak	Horizontal
1	10420	25.33	38.55	33.13	11.26	42.01	68.2	26.19	Peak	Vertical

5725-5850MHz:

802.11a Mode_Channel 149_5745 MHz Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	35.34	38.41	33.13	11.26	51.88	74	22.12	Peak	Horizontal
1	11490	24.53	38.41	33.13	11.26	41.07	54	12.93	AV	Horizontal

802.11a Mode_Channel 157_5785 MHz Antenna 0 Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	35.12	38.41	33.13	11.26	51.66	74	22.34	Peak	Horizontal
1	11570	25.34	38.41	33.13	11.26	41.88	54	12.12	AV	Horizontal

802.11a Mode_Channel 165_5825 MHz Antenna 0

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	35.19	38.41	33.13	11.26	51.73	74	22.27	Peak	Horizontal
1	11650	24.81	38.41	33.13	11.26	41.35	54	12.65	AV	Horizontal

802.11a Mode_Channel 149_5745 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	36.15	38.41	33.13	11.26	52.69	74	21.31	Peak	Horizontal
1	11490	25.36	38.41	33.13	11.26	41.90	54	12.10	AV	Horizontal

802.11a Mode_Channel 157_5785 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	35.79	38.41	33.13	11.26	52.33	74	21.67	Peak	Horizontal
1	11570	25.76	38.41	33.13	11.26	42.30	54	11.70	AV	Horizontal

802.11a Mode_Channel 165_5825 MHz Antenna 1

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	35.74	38.41	33.13	11.26	52.28	74	21.72	Peak	Horizontal
1	11650	24.52	38.41	33.13	11.26	41.06	54	12.94	AV	Horizontal

802.11n20 Mode_Channel 149_5745 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	34.77	38.41	33.13	11.26	51.31	74	22.69	Peak	Horizontal
1	11490	24.99	38.41	33.13	11.26	41.53	54	12.47	AV	Horizontal

802.11n20 Mode_Channel 157_5785 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	35.24	38.41	33.13	11.26	51.78	74	22.22	Peak	Horizontal
1	11570	25.54	38.41	33.13	11.26	42.08	54	11.92	AV	Horizontal

802.11n20 Mode_Channel 165_5825 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	35.42	38.41	33.13	11.26	51.96	74	22.04	Peak	Horizontal
1	11650	25.64	38.41	33.13	11.26	42.18	54	11.82	AV	Horizontal

802.11n40 Mode_Channel 151_ 5755 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11510	34.94	38.41	33.13	11.26	51.48	74	22.52	Peak	Horizontal
1	11510	25.74	38.41	33.13	11.26	42.28	54	11.72	AV	Horizontal

802.11n40 Mode_Channel 159_ 5795MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11590	35.64	38.41	33.13	11.26	52.18	74	21.82	Peak	Horizontal
1	11590	24.26	38.41	33.13	11.26	40.80	54	13.20	AV	Horizontal

802.11ac20 Mode_Channel 149_ 5745 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	34.80	38.41	33.13	11.26	51.34	74	22.66	Peak	Horizontal
1	11490	24.82	38.41	33.13	11.26	41.36	54	12.64	AV	Horizontal

802.11ac20 Mode_Channel 157_ 5785 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	34.48	38.41	33.13	11.26	51.02	74	22.98	Peak	Horizontal
1	11570	24.35	38.41	33.13	11.26	40.89	54	13.11	AV	Horizontal

802.11ac20 Mode_Channel 165_ 5825 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	36.12	38.41	33.13	11.26	52.66	74	21.34	Peak	Horizontal
1	11650	24.72	38.41	33.13	11.26	41.26	54	12.74	AV	Horizontal

802.11ac40 Mode_Channel 151_ 5755 MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11510	34.84	38.41	33.13	11.26	51.38	74	22.62	Peak	Horizontal
1	11510	25.24	38.41	33.13	11.26	41.78	54	12.22	AV	Horizontal

802.11ac40 Mode_Channel 159_ 5795MHz MIMO

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11590	34.11	38.41	33.13	11.26	50.65	74	23.35	Peak	Horizontal
1	11590	25.37	38.41	33.13	11.26	41.91	54	12.09	AV	Horizontal

802.11ac80 Mode_Channel 155_ 5775 MHz MIMO


Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11550	34.67	38.41	33.13	11.26	51.21	74	22.79	Peak	Horizontal
1	11550	24.30	38.41	33.13	11.26	40.84	54	13.16	AV	Horizontal

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. The other emission levels were very low against the limit.
3. Detector AV is setting spectrum/receiver. RBW=1MHz/BW=10Hz/Sweep time=Auto/Detector=Peak;

4.3. Duty Cycle

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 B Duty Cycle (x), Transmission Duration (T):

- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- b. The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq EBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

Antenna 0

802.11a Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11ac20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0

802.11ac80 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
42	5210	1.00	0

Antenna 1

802.11a Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11ac20 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
40	5200	1.00	0

802.11n HT40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0







802.11ac40 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
38	5190	1.00	0



802.11ac80 Test Mode

Channel	Frequency (MHz)	Duty Cycle	Duty factor (dB)
42	5210	1.00	0

Antenna 0





Antenna 1





Date: 27.AUG.2019 16:34:58

Date: 27.AUG.2019 16:35:11



Date: 27.AUG.2019 16:36:27

Date: 27.AUG.2019 16:37:20




Date: 27.AUG.2019 16:37:46

Date: 27.AUG.2019 16:38:28

4.4. Maximum Average Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 Section E3 Measurement using a Power Meter (PM):

- a. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
 - 1. The EUT is configured to transmit continuously or to transmit with a constant duty cycle
 - 2. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - 3. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b. If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B
- c. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed: 1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)

Note: The maximum e.i.r.p at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)

TEST RESULTS

Antenna 0

5150-5250MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
36	5180	4.53	0	4.53	24.00	PASS
40	5200	4.41	0	4.41	24.00	PASS
48	5240	4.31	0	4.31	24.00	PASS
802.11n20						
36	5180	4.60	0	4.60	24.00	PASS
40	5200	4.45	0	4.45	24.00	PASS
48	5240	4.57	0	4.57	24.00	PASS
802.11ac20						
36	5180	4.41	0	4.41	24.00	PASS
40	5200	4.57	0	4.57	24.00	PASS
48	5240	4.29	0	4.29	24.00	PASS
802.11n40						
38	5190	4.48	0	4.48	24.00	PASS
46	5230	4.51	0	4.51	24.00	PASS
802.11ac40						
38	5190	4.39	0	4.39	24.00	PASS
46	5230	4.59	0	4.59	24.00	PASS
802.11ac80						
42	5210	4.45	0	4.45	24.00	24.00

5725-5850MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
149	5745	4.34	0	4.34	30.00	PASS
157	5785	4.45	0	4.45	30.00	PASS
165	5825	4.39	0	4.39	30.00	PASS
802.11n20						
149	5745	4.57	0	4.57	30.00	PASS
157	5785	4.49	0	4.49	30.00	PASS
165	5825	4.49	0	4.49	30.00	PASS
802.11ac20						
149	5745	4.58	0	4.58	30.00	PASS
157	5785	4.44	0	4.44	30.00	PASS
165	5825	4.51	0	4.51	30.00	PASS
802.11n40						
151	5755	4.55	0	4.55	30.00	PASS
159	5795	4.53	0	4.53	30.00	PASS
802.11ac40						
151	5755	4.58	0	4.58	30.00	PASS
159	5795	4.42	0	4.42	30.00	PASS
802.11ac80						
155	5775	4.55	0	4.55	30.00	PASS

Antenna 1

5150-5250MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
36	5180	4.37	0	4.37	24.00	PASS
40	5200	4.47	0	4.47	24.00	PASS
48	5240	4.36	0	4.36	24.00	PASS
802.11n20						
36	5180	4.30	0	4.30	24.00	PASS
40	5200	4.53	0	4.53	24.00	PASS
48	5240	4.51	0	4.51	24.00	PASS
802.11ac20						
36	5180	4.46	0	4.46	24.00	PASS
40	5200	4.55	0	4.55	24.00	PASS
48	5240	4.52	0	4.52	24.00	PASS
802.11n40						
38	5190	4.45	0	4.45	24.00	PASS
46	5230	4.29	0	4.29	24.00	PASS
802.11ac40						
38	5190	4.54	0	4.54	24.00	PASS
46	5230	4.29	0	4.29	24.00	PASS
802.11ac80						
42	5210	4.32	0	4.32	24.00	PASS

5725-5850MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
149	5745	4.45	0	4.45	30.00	PASS
157	5785	4.57	0	4.57	30.00	PASS
165	5825	4.50	0	4.50	30.00	PASS
802.11n20						
149	5745	4.29	0	4.29	30.00	PASS
157	5785	4.31	0	4.31	30.00	PASS
165	5825	4.39	0	4.39	30.00	PASS
802.11ac20						
149	5745	4.37	0	4.37	30.00	PASS
157	5785	4.42	0	4.42	30.00	PASS
165	5825	4.45	0	4.45	30.00	PASS
802.11n40						
151	5755	4.38	0	4.38	30.00	PASS
159	5795	4.36	0	4.36	30.00	PASS
802.11ac40						
151	5755	4.41	0	4.41	30.00	PASS
159	5795	4.47	0	4.47	30.00	PASS
802.11ac80						
155	5775	4.38	0	4.38	30.00	PASS

MIMO*2

5150-5250MHz:


Type	Channel	Power (dBm) ANT0	Power (dBm) ANT1	Total (dBm)	Limit (dBm)	Result
802.11n HT20	36	4.6	4.3	7.46	24.00	Pass
	40	4.45	4.53	7.50		
	48	4.57	4.51	7.55		
802.11ac20	36	4.41	4.46	7.45	24.00	Pass
	40	4.57	4.55	7.57		
	48	4.29	4.52	7.42		
802.11n HT40	38	4.48	4.45	7.48	24.00	Pass
	46	4.51	4.29	7.41		
802.11ac40	38	4.39	4.54	7.48	24.00	Pass
	46	4.59	4.29	7.45		
802.11ac80	42	4.45	4.32	7.40	24.00	Pass

5725-5850MHz:

Type	Channel	Power (dBm) ANT0	Power (dBm) ANT1	Total (dBm)	Limit (dBm)	Result
802.11n HT20	36	4.57	4.29	7.44	30.00	Pass
	40	4.49	4.31	7.41		
	48	4.49	4.39	7.45		
802.11ac20	36	4.58	4.37	7.49	30.00	Pass
	40	4.44	4.42	7.44		
	48	4.51	4.45	7.49		
802.11n HT40	38	4.55	4.38	7.48	30.00	Pass
	46	4.53	4.36	7.46		
802.11ac40	38	4.58	4.41	7.51	30.00	Pass
	46	4.42	4.47	7.46		
802.11ac80	42	4.55	4.38	7.48	30.00	Pass

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 789033 D02 General UNII Test Procedures New Rules v01 F: The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...”. (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- c. Make the following adjustments to the peak value of the spectrum, if applicable:
 1. If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 2.) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d. The result is the Maximum PSD over 1 MHz reference bandwidth.
- e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:
 1. Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
 2. Set $VBW \geq 3 RBW$.
 3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500kHz/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1MHz/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 KHz$ is available on nearly all spectrum analyzers.
- f. Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Other than Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz

TEST RESULTS**Antenna 0****5150-5250MHz:****802.11a Test Mode**

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-6.03	0	0	-6.03	11	PASS
40	5200	-5.50	0	0	-5.50	11	PASS
48	5240	-4.52	0	0	-4.52	11	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-5.87	0	0	-5.87	11	PASS
40	5200	-5.50	0	0	-5.50	11	PASS
48	5240	-4.04	0	0	-4.04	11	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-5.74	0	0	-5.74	11	PASS
40	5200	-5.45	0	0	-5.45	11	PASS
48	5240	-4.10	0	0	-4.10	11	PASS

802.11n40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-9.71	0	0	-9.71	11	PASS
46	5230	-8.79	0	0	-8.79	11	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-10.44	0	0	-10.44	11	PASS
46	5230	-9.56	0	0	-9.56	11	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
42	5210	-12.19	0	0	-12.19	11	PASS

5725-5850MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-11.49	0	2.2	-9.29	30	PASS
157	5785	-12.33	0	2.2	-10.13	30	PASS
165	5825	-11.73	0	2.2	-9.53	30	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-11.29	0	2.2	-9.09	30	PASS
157	5785	-11.87	0	2.2	-9.67	30	PASS
165	5825	-11.82	0	2.2	-9.62	30	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-12.20	0	2.2	-10.00	30	PASS
157	5785	-13.11	0	2.2	-10.91	30	PASS
165	5825	-11.91	0	2.2	-9.71	30	PASS

802.11n40Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-15.98	0	2.2	-13.78	30	PASS
157	5795	-15.61	0	2.2	-13.41	30	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-15.21	0	2.2	-13.01	30	PASS
157	5795	-14.81	0	2.2	-12.61	30	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
155	5775	-18.18	0	2.2	-15.98	30	PASS

Antenna 1

5150-5250MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-5.50	0	0	-5.50	11	PASS
40	5200	-5.35	0	0	-5.35	11	PASS
48	5240	-4.17	0	0	-4.17	11	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-5.35	0	0	-5.35	11	PASS
40	5200	-5.24	0	0	-5.24	11	PASS
48	5240	-4.24	0	0	-4.24	11	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
36	5180	-5.38	0	0	-5.38	11	PASS
40	5200	-5.13	0	0	-5.13	11	PASS
48	5240	-3.98	0	0	-3.98	11	PASS

802.11n40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-9.64	0	0	-9.64	11	PASS
46	5230	-8.73	0	0	-8.73	11	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
38	5190	-10.26	0	0	-10.26	11	PASS
46	5230	-8.93	0	0	-8.93	11	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/1MHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/1MHz)	Limits (dBm/1MHz)	Verdict
42	5210	-12.09	0	0	-12.09	11	PASS

5725-5850MHz:

802.11a Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-11.31	0	2.2	-9.11	30	PASS
157	5785	-11.65	0	2.2	-9.45	30	PASS
165	5825	-11.05	0	2.2	-8.85	30	PASS

802.11n HT20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-11.39	0	2.2	-9.19	30	PASS
157	5785	-11.95	0	2.2	-9.75	30	PASS
165	5825	-10.67	0	2.2	-8.47	30	PASS

802.11ac20 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5745	-11.52	0	2.2	-9.32	30	PASS
157	5785	-12.06	0	2.2	-9.86	30	PASS
165	5825	-11.44	0	2.2	-9.24	30	PASS

802.11n40Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-15.56	0	2.2	-13.36	30	PASS
157	5795	-15.34	0	2.2	-13.14	30	PASS

802.11ac40 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
149	5755	-14.74	0	2.2	-12.54	30	PASS
157	5795	-14.68	0	2.2	-12.48	30	PASS

802.11ac80 Test Mode

Channel	Frequency (MHz)	Report PSD (dBm/300KHz)	Duty factor (dB)	RBW factor (dB)	Report PSD+ Duty factor+ RBW factor (dBm/500kHz)	Limits (dBm/500kHz)	Verdict
155	5775	-18.64	0	2.2	-16.44	30	PASS

MIMO*2

5150-5250MHz:

Type	Channel	PSD (dBm/MHz) ANT0	PSD (dBm/MHz) ANT1	Total (dBm/MHz)	Limit (dBm/MHz)	Result
802.11n HT20	36	-5.87	-5.35	-2.59	11	Pass
	40	-5.50	-5.24	-2.36		
	48	-4.04	-4.24	-1.13		
802.11ac20	36	-5.74	-5.38	-2.55	11	Pass
	40	-5.45	-5.13	-2.28		
	48	-4.10	-3.98	-1.03		
802.11n HT40	38	-9.71	-9.64	-6.66	11	Pass
	46	-8.79	-8.73	-5.75		
802.11ac40	38	-10.44	-10.26	-7.34	11	Pass
	46	-9.56	-8.93	-6.22		
802.11ac80	42	-12.19	-12.09	-9.13	11	Pass

5725-5850MHz:








Type	Channel	PSD (dBm/500KHz) ANT0	PSD (dBm/500KHz) ANT1	Total (dBm/500KHz)	Limit (dBm/500KHz)	Result
802.11n HT20	149	-9.09	-9.19	-6.13	30	Pass
	157	-9.67	-9.75	-6.70		
	165	-9.62	-8.47	-6.00		
802.11ac20	149	-10.00	-9.32	-6.64	30	Pass
	157	-10.91	-9.86	-7.34		
	165	-9.71	-9.24	-6.46		
802.11n HT40	149	-13.78	-13.36	-10.55	30	Pass
	157	-13.41	-13.14	-10.26		
802.11ac40	149	-13.01	-12.54	-9.76	30	Pass
	157	-12.61	-12.48	-9.53		
802.11ac80	155	-15.98	-16.44	-13.19	30	Pass








Note:

1. The test results including the cable lose.

Antenna 0


5150-5250MHz:






802.11ac40

802.11ac80




Date: 27.AUG.2019 16:23:12



Date: 27.AUG.2019 16:20:26

CH 38

CH 42
















Date: 27.AUG.2019 16:22:46

CH 46



5725-5850MHz:







CH 165


802.11ac40

802.11ac80



CH 151

CH 155

















CH 159



Antenna 1



5150-5250MHz:





802.11ac40

802.11ac80




Date: 27.AUG.2019 16:23:20

Date: 27.AUG.2019 16:20:45

CH 38

CH 42

















Date: 27.AUG.2019 16:22:56

CH 46




5725-5850MHz:






802.11ac40




Date: 28.AUG.2019 09:09:53

802.11ac80




Date: 28.AUG.2019 09:05:29

CH 151




Date: 28.AUG.2019 09:09:05

CH 155




CH 159



4.6. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a. Set RBW = 100 kHz.
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

LIMIT

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz

TEST RESULTS

Antenna 0

Type	Channel	99%Bandwidth (MHz)	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	149	16.50	16.52	≥500	Pass
	157	16.50	16.52		
	165	16.46	16.56		
802.11nHT20	149	17.66	17.72	≥500	Pass
	157	17.66	17.68		
	165	17.66	17.80		
802.11ac20	149	17.66	17.76	≥500	Pass
	157	17.66	17.80		
	165	17.66	17.80		
802.11n40	151	36.20	36.56	≥500	Pass
	159	36.20	36.56		
802.11ac40	151	36.20	36.48	≥500	Pass
	159	36.20	36.48		
802.11ac80	155	75.28	76.00	≥500	Pass



Antenna 1

Type	Channel	99%Bandwidth (MHz)	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	149	16.50	16.56	≥500	Pass
	157	16.50	16.60		
	165	16.46	16.60		
802.11nHT20	149	17.66	17.80	≥500	Pass
	157	17.66	17.72		
	165	17.66	17.84		
802.11ac20	149	17.66	17.80	≥500	Pass
	157	17.66	17.84		
	165	17.66	17.84		
802.11n40	151	36.20	36.64	≥500	Pass
	159	36.20	36.64		
802.11ac40	151	36.20	36.64	≥500	Pass
	159	36.20	36.56		
802.11ac80	155	75.28	76.16	≥500	Pass

Antenna 0

802.11a

802.11n HT20





Date: 27.AUG.2019 17:37:34

Date: 27.AUG.2019 17:50:25

CH149

CH149




Date: 27.AUG.2019 17:39:27

Date: 27.AUG.2019 17:49:23

CH157

CH157



Date: 27.AUG.2019 17:40:46



Date: 27.AUG.2019 17:47:29

CH165

CH165

802.11ac20

802.11n HT40





Date: 27.AUG.2019 17:51:43

Date: 28.AUG.2019 08:56:52

CH149

CH151




Date: 27.AUG.2019 17:52:54

Date: 28.AUG.2019 08:58:28

CH157

CH159





Date: 27.AUG.2019 17:55:26

CH165



802.11ac40

802.11ac80



Date: 28.AUG.2019 09:01:21

Date: 28.AUG.2019 09:03:02

CH151

CH155



Date: 28.AUG.2019 08:59:47



CH159

CH159

Antenna 1

802.11a

802.11n HT20





Date: 27.AUG.2019 17:38:18

Date: 27.AUG.2019 17:50:36

CH149

CH149





Date: 27.AUG.2019 17:39:42

Date: 27.AUG.2019 17:49:37

CH157

CH157




Date: 27.AUG.2019 17:40:56

Date: 27.AUG.2019 17:47:51

CH165

802.11ac20



Date: 27.AUG.2019 17:51:54


CH165

802.11n HT40



Date: 28.AUG.2019 08:57:18

CH149




Date: 27.AUG.2019 17:53:09

CH151



Date: 28.AUG.2019 08:58:39

CH157





Date: 27.AUG.2019 17:55:36

CH159

CH165

802.11ac40

802.11ac80



Date: 28.AUG.2019 09:01:40

Date: 28.AUG.2019 09:03:15

CH151

CH155



Date: 28.AUG.2019 08:59:58

CH159