

FCC RADIO TEST REPORT

FCC ID: 2AL6KBL-WN650BT

Product: Bluetooth 4.2+AC650M Nano Wireless
USB Adapter

Trade Mark: N/A

Model No.: BL-WN650BT

Family Model: N/A

Report No.: S24091906607004

Issue Date: Nov. 05, 2024

Prepared for

Shenzhen Bilian Electronic Co.,Ltd.

Room 501, Building 3, No. 32, Dafu Road, Zhangge Community, Fucheng
Street, Longhua District, Shenzhen City,China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Bilian Electronic Co.,Ltd.Address : Room 501, Building 3, No. 32, Dafu Road, Zhangge Community,
Fucheng Street, Longhua District, Shenzhen City,China**Manufacturer's Name**..... : Shenzhen Bilian Electronic Co.,Ltd.Address : Room 501, Building 3, No. 32, Dafu Road, Zhangge Community,
Fucheng Street, Longhua District, Shenzhen City,China**Product description**

Product name : Bluetooth 4.2+AC650M Nano Wireless USB Adapter

Trademark : N/A

Model and/or type reference : BL-WN650BT

Family Model : N/A

Test Sample Number S240919066007

Standards..... : FCC Part15.407

Test procedure ANSI C63.10-2013

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

KDB 905462 D03 Client Without DFS New Rules v01r02

KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Sept. 19, 2024 ~ Nov. 05, 2024

Date of Issue Nov. 05, 2024

Test Result..... **Pass**

Prepared By : 
Mary Hu
(Project Engineer)

Reviewed By : 
Aaron Cheng
(Supervisor)

Approved By : 
Alex Li
(Manager)

Table of Contents

	Page
1. SUMMARY OF TEST RESULTS	7
1.1 FACILITIES AND ACCREDITATIONS	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	13
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14
3. EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.1.1 APPLICABLE STANDARD	16
3.1.2 CONFORMANCE LIMIT	16
3.1.3 TEST CONFIGURATION	16
3.1.4 TEST PROCEDURE	17
3.2 RADIATED EMISSION MEASUREMENT	26
3.2.1 APPLICABLE STANDARD	26
3.2.2 CONFORMANCE LIMIT	26
3.2.3 MEASURING INSTRUMENTS	26
3.2.4 TEST CONFIGURATION	27
3.2.5 TEST PROCEDURE	28
3.2.6 TEST RESULTS (9KHZ – 30 MHZ)	29
3.2.7 TEST RESULTS (30MHZ – 1GHZ)	30
3.2.9 TEST RESULTS (18GHZ-40GHZ)	42
4 POWER SPECTRAL DENSITY TEST	53
4.1 APPLIED PROCEDURES / LIMIT	53
4.2 TEST PROCEDURE	54
4.3 DEVIATION FROM STANDARD	54
4.4 TEST SETUP	54
4.5 EUT OPERATION CONDITIONS	54
4.6 TEST RESULTS	55
5. 26DB & 99% EMISSION BANDWIDTH	56
5.1 APPLIED PROCEDURES / LIMIT	56
5.2 TEST PROCEDURE	56
5.3 EUT OPERATION CONDITIONS	57
5.4 TEST RESULTS	57

Table of Contents

	Page
6. MINIMUM 6 DB BANDWIDTH	58
6.1 APPLIED PROCEDURES / LIMIT	58
6.2 EST PROCEDURE	58
6.3 DEVIATION FROM STANDARD	58
6.4 TEST SETUP	58
6.5 EUT OPERATION CONDITIONS	58
6.6 TEST RESULTS	59
7. MAXIMUM CONDUCTED OUTPUT POWER	60
7.1 PPLIED PROCEDURES / LIMIT	60
7.6 TEST RESULTS	62
8. OUT OF BAND EMISSIONS	63
8.1 APPLICABLE STANDARD	63
8.2 TEST PROCEDURE	63
8.3 DEVIATION FROM STANDARD	64
8.4 TEST SETUP	64
8.5 EUT OPERATION CONDITIONS	64
8.6 TEST RESULTS	65
9. FREQUENCY STABILITY MEASUREMENT	66
9.1 LIMIT	66
9.2 TEST PROCEDURES	66
9.3 TEST SETUP LAYOUT	66
9.4 EUT OPERATION DURING TEST	66
9.5 TEST RESULTS	67
10. DYNAMIC FREQUENCY SELECTION(DFS)	79
10.1 APPLICABILITY OF DFS REQUIREMENTS	79
10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE NOTEBOOKING	79
10.3 DFS RESPONSE REQUIREMENT VALUES	80
10.4 SHORT PULSE RADAR TEST WAVEFORMS	80
10.5 CALIBRATION SETUP AND DFS TEST RESULTS	81
10.6 CONDUCTED CALIBRATION SETUP	81
10.7 RADAR WAVEFORM CALIBRATION RESULT	81
10.8 IN-SERVICE NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD	82
10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME	

Table of Contents

	Page
AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST	83
11. ANTENNA REQUIREMENT	84
11.1 STANDARD REQUIREMENT	84
11.2 EUT ANTENNA	84

Revision History

Report No.	Version	Description	Issued Date
S24091906607004	Rev.01	Initial issue of report	Nov. 05, 2024

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4) 15.407(b)(8)(9)	Spurious Radiated Emissions	PASS	
15.407 (a)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)	Maximum Conducted Output Power	PASS	
15.407 (b)(1) 15.407 (b)(2) 15.407 (b)(3) 15.407 (b)(4)	Band Edge	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.407(g)	Frequency Stability Measurement	PASS	
15.407(h)	Dynamic Frequency Selection(DFS)	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	(Note 3)

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) This device operates with a duty cycle greater than 99%
- (3) The product is a client device, and the data transmission is limited by the AP.
When the information to be sent is missing or the operation fails,
the device will automatically stop sending and directly connect to the AP correctly again.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong,
People's Republic of China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and
CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier: CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a
standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of
approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
5	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
6	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
7	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
8	Temperature	$\pm 0.5^\circ\text{C}$
9	Humidity	$\pm 2\%$
10	Radio Frequency	$\pm 0.2\text{ppm}$
11	Occupied bandwidth	$\pm 3.7\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	
Trade Mark	N/A	
Model Name	BL-WN650BT	
Family Model	N/A	
Model Difference	N/A	
FCC ID	2AL6KBL-WN650BT	
Product Description	Mode Supported	☒ 802.11a ☒ 802.11n(HT20) ☒ 802.11n(HT40) ☒ 802.11ac(HT20) ☒ 802.11ac(HT40) ☒ 802.11ac(HT80)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS7; 802.11ac(VHT20): NSS1, MCS0-MCS8 802.11ac(VHT40/VHT80):NSS1, MCS0-MCS9
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
	Operating Frequency Range	☒ U-NII-1: 5150 MHz ~5250MHz ☒ U-NII-2A: 5250MHz~5350MHz ☒ U-NII-2C: 5470MHz~5725MHz ☒ U-NII-3: 5725 MHz ~5850 MHz
	Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P ☒ Client
	DFS type:	☐ master devices ☐ Slave devices with radar detection ☒ Slave devices without radar detection
	Support TPC	☐ YES ☒ NO
	Antenna Type	PIFA ANT
	Antenna Gain	0.5 dBi
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	N/A	
Battery	N/A	
Rating	DC 5V	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	N/A	
SW Version	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. All configurations are tested, only showing the worst data 8GB+64GB.
3. Frequency and Channel list:

Band	20MHz		40MHz		80MHz	
	Channel	Frequency	Channel	Frequency	Channel	Frequency
U-NII-1	36	5180 MHz	38	5190 MHz	42	5210 MHz
	40	5200 MHz	46	5230 MHz	-	-
	44	5220 MHz				
	48	5240 MHz				
U-NII-2A	52	5260 MHz	54	5270 MHz	58	5290 MHz
	56	5280 MHz	62	5310 MHz		
	60	5300 MHz				
	64	5320 MHz				
U-NII-2C	100	5500 MHz	102	5510 MHz	106	5530 MHz
	104	5520 MHz	110	5550 MHz	122	5610 MHz
	108	5540 MHz	118	5590 MHz		
	112	5560 MHz	126	5630 MHz		
	116	5580 MHz	134	5670 MHz		
	120	5600 MHz				
	124	5620 MHz				
	128	5640 MHz				
	132	5660 MHz				
	136	5680 MHz				
	140	5700 MHz				
U-NII-3	149	5745 MHz	151	5755 MHz	155	5775 MHz
	153	5765 MHz	159	5795 MHz		
	157	5785 MHz				
	161	5805 MHz				
	165	5825 MHz				

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155


For Conducted Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n/ ac 20 CH36/ CH40/ CH48/CH52/CH56/CH64/CH100/CH120/CH140/CH149/ CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46/CH54/CH62/CH102/CH118/CH134/CH151/ CH159
Mode 4	802.11ac80 CH42/CH58/CH106/CH122/CH155

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	PA-1650-72	8SSA10J20136L1CZ7780ZGN	Peripherals
AE-2	Notebook	ThinkPadE450	PF-OHLDUZ 16/03	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	YES	1.2m
C-2	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2024.04.26	2025.04.25	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.04.25	2025.04.24	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2024.04.25	2025.04.24	1 year
4	Test Receiver	R&S	ESPI7	101318	2024.04.26	2025.04.25	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2024.05.12	2025.05.11	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2024.04.25	2025.04.24	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15100041SN084	2024.04.25	2025.04.24	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2024.04.26	2025.04.25	1 year
2	LISN	R&S	ENV216	101313	2024.04.25	2025.04.24	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2024.04.25	2025.04.24	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4℃	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	41.38	9.89	51.27	65.79	-14.52	QP
0.1539	20.26	9.89	30.15	55.79	-25.64	AVG
0.1986	35.06	9.99	45.05	63.67	-18.62	QP
0.1986	14.46	9.99	24.45	53.67	-29.22	AVG
0.5100	25.88	10.64	36.52	56.00	-19.48	QP
0.5100	17.50	10.64	28.14	46.00	-17.86	AVG
1.5940	15.05	12.85	27.90	56.00	-28.10	QP
1.5940	5.14	12.85	17.99	46.00	-28.01	AVG
3.1220	14.32	9.70	24.02	56.00	-31.98	QP
3.1220	0.90	9.70	10.60	46.00	-35.40	AVG
18.1820	35.16	9.87	45.03	60.00	-14.97	QP
18.1820	22.55	9.87	32.42	50.00	-17.58	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4℃	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	43.26	10.01	53.27	66.00	-12.73	QP
0.1500	22.65	10.01	32.66	56.00	-23.34	AVG
0.2380	33.07	10.19	43.26	62.17	-18.91	QP
0.2380	11.61	10.19	21.80	52.17	-30.37	AVG
0.5100	25.53	10.73	36.26	56.00	-19.74	QP
0.5100	14.95	10.73	25.68	46.00	-20.32	AVG
1.4740	16.93	12.68	29.61	56.00	-26.39	QP
1.4740	6.45	12.68	19.13	46.00	-26.87	AVG
5.3100	12.87	9.78	22.65	60.00	-37.35	QP
5.3100	1.39	9.78	11.17	50.00	-38.83	AVG
18.1580	33.22	9.93	43.15	60.00	-16.85	QP
18.1580	20.55	9.93	30.48	50.00	-19.52	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4℃	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1556	38.18	9.91	48.09	65.70	-17.61	QP
0.1556	16.79	9.91	26.70	55.70	-29.00	AVG
0.5140	25.31	10.64	35.95	56.00	-20.05	QP
0.5140	15.71	10.64	26.35	46.00	-19.65	AVG
1.4620	15.20	12.58	27.78	56.00	-28.22	QP
1.4620	3.55	12.58	16.13	46.00	-29.87	AVG
3.1220	14.02	9.70	23.72	56.00	-32.28	QP
3.1220	0.14	9.70	9.84	46.00	-36.16	AVG
8.7340	3.92	9.77	13.69	60.00	-46.31	QP
8.7340	16.70	9.77	26.47	50.00	-23.53	AVG
17.9619	36.76	9.87	46.63	60.00	-13.37	QP
17.9619	23.27	9.87	33.14	50.00	-16.86	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4°C	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.3G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	41.99	10.01	52.00	65.79	-13.79	QP
0.1539	23.82	10.01	33.83	55.79	-21.96	AVG
0.2460	32.12	10.21	42.33	61.89	-19.56	QP
0.2460	12.35	10.21	22.56	51.89	-29.33	AVG
0.5100	24.42	10.73	35.15	56.00	-20.85	QP
0.5100	16.47	10.73	27.20	46.00	-18.80	AVG
1.5300	17.74	12.80	30.54	56.00	-25.46	QP
1.5300	8.02	12.80	20.82	46.00	-25.18	AVG
18.2340	32.62	9.93	42.55	60.00	-17.45	QP
18.2340	21.21	9.93	31.14	50.00	-18.86	AVG
25.3700	24.77	10.05	34.82	60.00	-25.18	QP
25.3700	15.37	10.05	25.42	50.00	-24.58	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4℃	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1660	37.49	9.93	47.42	65.16	-17.74	QP
0.1660	18.58	9.93	28.51	55.16	-26.65	AVG
0.1980	35.13	9.99	45.12	63.69	-18.57	QP
0.1980	17.13	9.99	27.12	53.69	-26.57	AVG
0.2260	32.16	10.06	42.22	62.60	-20.38	QP
0.2260	13.62	10.06	23.68	52.60	-28.92	AVG
0.5140	24.81	10.64	35.45	56.00	-20.55	QP
0.5140	16.10	10.64	26.74	46.00	-19.26	AVG
1.4620	14.70	12.58	27.28	56.00	-28.72	QP
1.4620	5.42	12.58	18.00	46.00	-28.00	AVG
18.3900	35.74	9.89	45.63	60.00	-14.37	QP
18.3900	22.25	9.89	32.14	50.00	-17.86	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4℃	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.6G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1500	40.85	10.01	50.86	66.00	-15.14	QP
0.1500	22.32	10.01	32.33	56.00	-23.67	AVG
0.2460	31.62	10.21	41.83	61.89	-20.06	QP
0.2460	11.85	10.21	22.06	51.89	-29.83	AVG
0.5100	23.42	10.73	34.15	56.00	-21.85	QP
0.5100	15.47	10.73	26.20	46.00	-19.80	AVG
1.5300	20.74	12.80	33.54	56.00	-22.46	QP
1.5300	10.94	12.80	23.74	46.00	-22.26	AVG
18.2340	32.12	9.93	42.05	60.00	-17.95	QP
18.2340	20.71	9.93	30.64	50.00	-19.36	AVG
25.3700	22.77	10.05	32.82	60.00	-27.18	QP
25.3700	13.37	10.05	23.42	50.00	-26.58	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4 °C	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	39.15	9.91	49.06	65.57	-16.51	QP
0.1580	20.44	9.91	30.35	55.57	-25.22	AVG
0.2220	33.43	10.04	43.47	62.74	-19.27	QP
0.2220	12.38	10.04	22.42	52.74	-30.32	AVG
0.5180	25.79	10.66	36.45	56.00	-19.55	QP
0.5180	17.99	10.66	28.65	46.00	-17.35	AVG
0.8340	19.11	11.30	30.41	56.00	-25.59	QP
0.8340	7.72	11.30	19.02	46.00	-26.98	AVG
2.0420	17.72	9.68	27.40	56.00	-28.60	QP
2.0420	5.83	9.68	15.51	46.00	-30.49	AVG
18.2939	34.33	9.88	44.21	60.00	-15.79	QP
18.2939	22.52	9.88	32.40	50.00	-17.60	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	24.4 °C	Relative Humidity :	51.3%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1539	39.12	10.01	49.13	65.79	-16.66	QP
0.1539	19.90	10.01	29.91	55.79	-25.88	AVG
0.1819	35.13	10.07	45.20	64.40	-19.20	QP
0.1819	14.65	10.07	24.72	54.40	-29.68	AVG
0.3580	21.75	10.41	32.16	58.77	-26.61	QP
0.3580	9.34	10.41	19.75	48.77	-29.02	AVG
0.5180	26.53	10.75	37.28	56.00	-18.72	QP
0.5180	18.04	10.75	28.79	46.00	-17.21	AVG
1.6420	16.97	13.02	29.99	56.00	-26.01	QP
1.6420	9.17	13.02	22.19	46.00	-23.81	AVG
18.0980	30.92	9.93	40.85	60.00	-19.15	QP
18.0980	19.74	9.93	29.67	50.00	-20.33	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407 and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407: radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure:	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25.1℃	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.2G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	52.2078	5.41	19.49	24.90	40.00	-15.10	QP
V	129.4677	11.12	14.90	26.02	43.50	-17.48	QP
V	187.0956	7.06	16.99	24.05	43.50	-19.45	QP
V	397.6334	5.32	22.90	28.22	46.00	-17.78	QP
V	547.0976	7.16	25.50	32.66	46.00	-13.34	QP
V	900.1474	6.76	31.00	37.76	46.00	-8.24	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	46.0162	6.78	19.66	26.44	40.00	-13.56	QP
H	106.7587	5.09	18.05	23.14	43.50	-20.36	QP
H	212.2694	6.03	18.24	24.27	43.50	-19.23	QP
H	336.0351	5.85	21.46	27.31	46.00	-18.69	QP
H	504.7062	5.90	24.69	30.59	46.00	-15.41	QP
H	945.4400	5.30	31.28	36.58	46.00	-9.42	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11a” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25.1℃	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.3G)- 802.11ac20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39.8542	6.46	18.60	25.06	40.00	-14.94	QP
V	66.9670	6.38	17.19	23.57	40.00	-16.43	QP
V	154.2785	10.46	14.71	25.17	43.50	-18.33	QP
V	325.5958	5.91	21.02	26.93	46.00	-19.07	QP
V	530.1013	5.46	25.24	30.70	46.00	-15.30	QP
V	925.7562	6.17	31.14	37.31	46.00	-8.69	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	46.0162	6.78	19.66	26.44	40.00	-13.56	QP
H	99.5281	5.35	17.89	23.24	43.50	-20.26	QP
H	199.9855	5.80	18.11	23.91	43.50	-19.59	QP
H	365.5390	5.41	22.19	27.60	46.00	-18.40	QP
H	545.1825	7.28	25.46	32.74	46.00	-13.26	QP
H	942.1304	5.87	31.26	37.13	46.00	-8.87	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11ac20” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25.1℃	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.6G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	30.1053	8.12	16.87	24.99	40.00	-15.01	QP
V	57.1914	6.17	19.18	25.35	40.00	-14.65	QP
V	127.6645	11.60	15.08	26.68	43.50	-16.82	QP
V	407.5144	6.31	23.09	29.40	46.00	-16.60	QP
V	668.1422	6.08	27.73	33.81	46.00	-12.19	QP
V	912.8620	6.21	31.02	37.23	46.00	-8.77	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	50.9420	5.18	19.60	24.78	40.00	-15.22	QP
H	109.0286	5.86	17.91	23.77	43.50	-19.73	QP
H	202.8104	6.28	18.12	24.40	43.50	-19.10	QP
H	354.1831	6.38	21.94	28.32	46.00	-17.68	QP
H	625.0780	5.86	26.59	32.45	46.00	-13.55	QP
H	952.0937	5.84	31.37	37.21	46.00	-8.79	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11a” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25.1℃	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.8G)- 802.11ac20(Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39.9941	6.86	18.63	25.49	40.00	-14.51	QP
V	61.1315	7.51	18.72	26.23	40.00	-13.77	QP
V	108.6470	7.19	17.91	25.10	43.50	-18.40	QP
V	134.0880	11.99	14.65	26.64	43.50	-16.86	QP
V	603.5390	8.25	26.33	34.58	46.00	-11.42	QP
V	955.4380	6.51	31.38	37.89	46.00	-8.11	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	59.0251	5.63	18.93	24.56	40.00	-15.44	QP
H	107.1337	5.32	18.00	23.32	43.50	-20.18	QP
H	452.7196	4.93	23.84	28.77	46.00	-17.23	QP
H	568.6126	6.45	25.78	32.23	46.00	-13.77	QP
H	709.1820	5.50	28.61	34.11	46.00	-11.89	QP
H	942.1304	5.53	31.26	36.79	46.00	-9.21	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11ac20” mode is the worst mode.

(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.2G) - 802.11a mode		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3015	55.81	5.94	35.40	44.00	53.15	68.2	-15.05	Pk
Vertical	10360	57.07	8.46	39.75	44.50	60.78	68.2	-7.42	Pk
Vertical	15540	49.76	10.12	38.80	44.10	54.58	74	-19.42	Pk
Vertical	15540	44.67	10.12	38.80	42.70	50.89	54	-3.11	AV
Horizontal	2981	55.78	5.94	35.18	44.00	52.90	68.2	-15.30	Pk
Horizontal	10360	51.59	8.46	38.71	44.50	54.26	68.2	-13.94	Pk
Horizontal	15540	50.78	10.12	38.38	44.10	55.18	74	-18.82	Pk
Horizontal	15540	43.59	10.12	38.38	44.10	47.99	54	-6.01	AV
middle Channel (5200 MHz)-Above 1G									
Vertical	3561	52.55	6.48	36.35	44.05	51.33	68.2	-16.87	Pk
Vertical	10400	56.95	8.47	37.88	44.51	58.79	68.2	-9.41	Pk
Vertical	15600	58.93	10.12	38.8	44.1	63.75	74	-10.25	Pk
Vertical	15600	43.95	10.12	38.8	42.7	50.17	54	-3.83	AV
Horizontal	3363	57.11	6.48	36.37	44.05	55.91	68.2	-12.29	Pk
Horizontal	10400	57.53	8.47	38.64	44.5	60.14	68.2	-8.06	Pk
Horizontal	15600	55.09	10.12	38.38	44.1	59.49	74	-14.51	Pk
Horizontal	15600	43.13	10.12	38.38	44.1	47.53	54	-6.47	AV
High Channel (5240 MHz)-Above 1G									
Vertical	3926	59.07	7.1	37.24	43.5	59.91	74	-14.09	Pk
Vertical	3926	46.29	7.1	37.24	43.5	47.13	54	-6.87	AV
Vertical	10480	50.67	8.46	37.68	44.5	52.31	68.2	-15.89	Pk
Vertical	15720	49.52	10.12	38.8	44.1	54.34	74	-19.66	Pk
Vertical	15720	46.60	10.12	38.8	42.7	52.82	54	-1.18	AV
Horizontal	3885	57.91	7.1	37.24	43.5	58.75	74	-15.25	Pk
Horizontal	3885	48.98	7.1	37.24	43.5	49.82	54	-4.18	AV
Horizontal	10480	61.64	8.46	38.57	44.5	64.17	68.2	-4.03	Pk

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.3G) - 802.11ac20 mode		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G									
Vertical	4633.53	59.88	5.44	35.40	44.00	56.72	74.00	-17.28	Pk
Vertical	4633.53	45.93	5.74	35.40	44.00	43.07	54.00	-10.93	AV
Vertical	10520.40	60.56	8.26	39.75	44.50	64.07	68.20	-4.13	Pk
Vertical	15780.62	58.18	10.12	38.80	44.10	63.00	74.00	-11.00	Pk
Vertical	15780.62	43.15	9.62	38.80	42.70	48.87	54.00	-5.13	AV
Horizontal	4366.43	58.85	5.57	35.18	44.00	55.60	74.00	-18.40	Pk
Horizontal	4366.43	51.08	5.74	35.18	44.00	48.00	54.00	-6.00	AV
Horizontal	10520.54	59.10	8.38	38.71	44.50	61.69	68.20	-6.51	Pk
Horizontal	15780.62	51.38	9.88	38.38	44.10	55.54	74.00	-18.46	Pk
Horizontal	15780.62	40.73	9.94	38.38	44.10	44.95	54.00	-9.05	AV
middle Channel (5280 MHz)-Above 1G									
Vertical	4122.62	59.54	6.08	36.35	44.05	57.92	74.00	-16.08	Pk
Vertical	4122.62	44.97	6.39	36.35	44.05	43.66	54.00	-10.34	AV
Vertical	10560.47	61.86	8.28	37.88	44.51	63.51	68.20	-4.69	Pk
Vertical	15840.64	49.94	9.79	38.8	44.10	54.43	74.00	-19.57	Pk
Vertical	15840.64	45.39	9.70	38.8	42.70	51.19	54.00	-2.81	AV
Horizontal	3869.76	56.25	6.11	36.37	44.05	54.68	74.00	-19.32	Pk
Horizontal	3869.76	43.57	6.27	36.37	44.05	42.16	54.00	-11.84	AV
Horizontal	10561.02	61.56	8.33	38.64	44.50	64.03	68.20	-4.17	Pk
Horizontal	15840.65	51.58	9.99	38.38	44.10	55.85	74.00	-18.15	Pk
Horizontal	15840.65	35.92	9.81	38.38	44.10	40.01	54.00	-13.99	AV
High Channel (5320 MHz)-Above 1G									
Vertical	5366.80	55.44	6.96	37.24	43.50	56.14	74.00	-17.86	Pk
Vertical	5366.80	43.32	7.07	37.24	43.50	44.13	54.00	-9.87	AV
Vertical	10640.86	54.65	8.14	37.68	44.50	55.97	74.00	-18.03	Pk
Vertical	10640.86	49.47	8.35	37.68	44.50	51.00	54.00	-3.00	AV
Vertical	15960.69	58.44	10.11	38.8	44.10	63.25	74.00	-10.75	Pk
Vertical	15960.69	45.14	9.64	38.8	42.70	50.88	54.00	-3.12	AV
Horizontal	5436.87	56.16	7.05	37.24	43.50	56.95	74.00	-17.05	Pk
Horizontal	5436.87	43.88	7.05	37.24	43.50	44.67	54.00	-9.33	AV
Horizontal	10640.52	55.17	8.20	38.57	44.50	57.44	74.00	-16.56	Pk
Horizontal	10640.52	49.19	8.03	38.57	44.50	51.29	54.00	-2.71	AV

Note:"802.11ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX(5.6G) - 802.11a mode		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500MHz)-Above 1G									
Vertical	5433.30	65.22	5.61	35.40	44.00	62.23	74.00	-11.77	Pk
Vertical	5433.30	47.15	5.61	35.40	44.00	44.16	54.00	-9.84	AV
Vertical	11020.32	59.55	8.24	39.75	44.50	63.04	74.00	-10.96	Pk
Vertical	11020.32	41.69	8.35	39.75	44.50	45.29	54.00	-8.71	AV
Vertical	16530.12	58.71	10.05	38.80	44.10	63.46	68.20	-4.74	Pk
Horizontal	5126.75	62.78	5.78	35.18	44.00	59.74	74.00	-14.26	Pk
Horizontal	5126.75	50.46	5.66	35.18	44.00	47.30	54.00	-6.70	AV
Horizontal	11020.32	52.05	8.22	38.71	44.50	54.48	74.00	-19.52	Pk
Horizontal	11020.32	43.92	8.14	38.71	44.50	46.27	54.00	-7.73	AV
Horizontal	16530.12	56.07	10.04	38.38	44.10	60.39	68.20	-7.81	Pk
middle Channel (5600 MHz)-Above 1G									
Vertical	5647.61	58.15	6.79	37.24	43.50	58.68	68.20	-9.52	Pk
Vertical	11200.71	50.80	8.10	37.68	44.50	52.08	74.00	-21.92	Pk
Vertical	11200.71	48.97	8.23	37.68	44.50	50.38	54.00	-3.62	AV
Vertical	16770.00	43.73	9.70	38.80	44.10	48.13	68.20	-20.07	Pk
Horizontal	5433.54	55.26	6.74	37.24	43.50	55.74	74.00	-18.26	Pk
Horizontal	5433.54	48.04	6.74	37.24	43.50	48.52	54.00	-5.48	AV
Horizontal	11200.71	52.75	8.25	38.57	44.50	55.07	74.00	-18.93	Pk
Horizontal	11200.71	47.14	8.25	38.57	44.50	49.46	54.00	-4.54	AV
Horizontal	16770.00	58.26	10.09	38.38	44.10	62.63	68.20	-5.57	Pk
High Channel (5700MHz)-Above 1G									
Vertical	5647.61	57.16	6.79	37.24	43.50	57.69	68.20	-10.51	Pk
Vertical	11340.54	58.68	8.10	37.68	44.50	59.96	74.00	-14.04	Pk
Vertical	11340.54	48.82	8.23	37.68	44.50	50.23	54.00	-3.77	AV
Vertical	17010.36	59.38	9.70	38.80	44.10	63.78	68.20	-4.42	Pk
Horizontal	5433.54	52.20	6.74	37.24	43.50	52.68	74.00	-21.32	Pk
Horizontal	5433.54	49.20	6.74	37.24	43.50	49.68	54.00	-4.32	AV
Horizontal	11340.54	49.76	8.25	38.57	44.50	52.08	74.00	-21.92	Pk
Horizontal	11340.54	49.91	8.25	38.57	44.50	52.23	54.00	-1.77	AV
Horizontal	17010.36	59.85	10.09	38.38	44.10	64.22	68.20	-3.98	Pk

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V,
Test Mode :	TX (5.8G) -- 802.11ac20 mode		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)- Above 1G									
Vertical	2806.9	52.75	5.94	35.40	44.00	50.09	74.00	-23.91	Pk
Vertical	2806.9	45.38	5.94	35.40	44.00	42.72	54.00	-11.28	AV
Vertical	11490.56	52.10	8.46	39.75	44.50	55.81	74.00	-18.19	Pk
Vertical	11490.56	48.10	8.46	39.75	44.50	51.81	54.00	-2.19	AV
Vertical	17235.32	46.10	10.12	38.80	44.10	50.92	68.20	-17.28	Pk
Horizontal	2911.524	58.50	5.94	35.18	44.00	55.62	68.20	-12.58	Pk
Horizontal	11490.56	58.90	8.46	38.71	44.50	61.57	74.00	-12.43	Pk
Horizontal	11490.56	48.09	8.46	38.71	44.50	50.76	54.00	-3.24	AV
Horizontal	17235.56	46.50	10.12	38.38	44.10	50.90	68.20	-17.30	Pk
middle Channel (5785 MHz)- Above 1G									
Vertical	3763.083	59.18	6.48	36.35	44.05	57.96	74.00	-16.04	Pk
Vertical	3763.083	44.12	6.48	36.35	44.05	42.90	54.00	-11.10	AV
Vertical	11570.56	49.68	8.47	37.88	44.51	51.52	74.00	-22.48	Pk
Vertical	11570.56	48.02	8.47	37.88	44.51	49.86	54.00	-4.14	AV
Vertical	17355.56	59.49	10.12	38.8	44.10	64.31	68.20	-3.89	Pk
Horizontal	3561.585	60.06	6.48	36.37	44.05	58.86	68.20	-9.34	Pk
Horizontal	11570.56	57.40	8.47	38.64	44.50	60.01	74.00	-13.99	Pk
Horizontal	11570.56	42.72	8.47	38.64	44.50	45.33	54.00	-8.67	AV
Horizontal	17355.56	50.72	10.12	38.38	44.10	55.12	74.00	-18.88	Pk
Horizontal	17355.35	39.66	10.12	38.38	44.10	44.06	54.00	-9.94	AV
High Channel (5825 MHz)- Above 1G									
Vertical	3907.168	58.91	7.10	37.24	43.50	59.75	74.00	-14.25	Pk
Vertical	3907.168	51.72	7.10	37.24	43.50	52.56	54.00	-1.44	AV
Vertical	11650.54	54.61	8.46	37.68	44.50	56.25	74.00	-17.75	Pk
Vertical	11650.54	48.98	8.46	37.68	44.50	50.62	54.00	-3.38	AV
Vertical	17475.54	59.89	10.12	38.8	44.10	64.71	68.20	-3.49	Pk
Horizontal	3912.779	57.12	7.10	37.24	43.50	57.96	74.00	-16.04	Pk
Horizontal	3912.779	42.40	7.10	37.24	43.50	43.24	54.00	-10.76	AV
Horizontal	11650.54	53.75	8.46	38.57	44.50	56.28	74.00	-17.72	Pk
Horizontal	11650.54	48.24	8.46	38.57	44.50	50.77	54.00	-3.23	AV
Horizontal	17475.54	59.43	10.12	38.38	44.10	63.83	68.20	-4.37	Pk

Note:"802.11ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5.2G)-802.11a ;TX (5.3G)-802.11ac20 TX (5.6G)-802.11a;TX (5.8G)-802.11ac20		

All the modulation modes have been tested, and the worst result was report as below:


Low Channel (5180 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35072.000	55.68	7.05	62.73	68.2	-5.47	peak


Vertical



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37932.000	53.17	8.8	61.97	68.2	-6.23	peak


High Channel (5240 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37932.000	53.53	7.33	60.86	68.2	-7.34	peak

Vertical




Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37030.000	54.54	7.18	61.72	68.2	-6.48	peak

Note:802.11a mode is the worst mode.


Low Channel (5260 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37030.000	54.54	7.18	61.72	68.2	-6.48	peak


Vertical



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37030.000	54.54	7.18	61.72	68.2	-6.48	peak


High Channel (5320 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
38724.000	55.61	7.13	62.74	68.2	-5.46	peak

Vertical




Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
38724.000	53.55	10.22	63.77	68.2	-4.43	peak

Note:802.11ac20 mode is the worst mode.


Low Channel (5500 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35600.000	56.27	6.06	62.33	68.2	-5.87	peak


Vertical



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35600.000	56.27	6.06	62.33	68.2	-5.87	peak


High Channel (5700 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37052.000	54.68	7.22	61.9	68.2	-6.3	peak

Vertical




Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35600.000	54.68	7.22	61.9	68.2	-6.3	peak

Note:802.11a mode is the worst mode.


Low Channel (5745 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35908.000	57.01	6.2	63.21	68.2	-4.99	peak


Vertical



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
34654.000	57.13	6.36	63.49	68.2	-4.71	peak


High Channel (5825 MHz)-Above 1G

Horizontal



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
35490.000	56.1	6.2	62.3	68.2	-5.9	Peak

Vertical



Frequency MHz	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
37888.000	54.5	8.69	63.19	68.2	-5.01	peak

Note:802.11ac20 mode is the worst mode.

3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5.2G)-802.11a		

All the modulation modes have been tested, The report just record the worst data mode.

These modulation modes have been tested. The report just record the worst data mode.

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
5.2G WIFI-802.11a (5180 MHz) Mode									
4500	63.56	5.2	35.6	44.2	60.16	74	-13.84	Pk	Horizontal
4500	46.57	5.2	35.6	44.2	43.17	54	-10.83	AV	Horizontal
4500	53.65	5.2	35.6	44.2	50.25	74	-23.75	Pk	Horizontal
4500	40.20	5.2	35.6	44.2	36.80	54	-17.20	AV	Horizontal
5150	69.72	5.36	35.66	44.22	66.52	74	-7.48	Pk	Horizontal
5150	52.32	5.36	35.66	44.22	49.12	54	-4.88	AV	Horizontal
5150	69.74	5.36	35.66	44.22	66.54	74	-7.46	Pk	Vertical
5150	50.76	5.36	35.66	44.22	47.56	54	-6.44	AV	Vertical
5350	62.37	5.68	35.68	44.22	59.51	74	-14.49	Pk	Vertical
5350	40.82	5.68	35.68	44.22	37.96	54	-16.04	AV	Vertical
5350	54.56	5.68	35.68	44.22	51.70	74	-22.30	Pk	Horizontal
5350	38.50	5.68	35.68	44.22	35.64	54	-18.36	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11a " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5.3G)-802.11ac20		

All the modulation modes have been tested, The report just record the worst data mode.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel (5320 MHz)-Above 1G									
Vertical	5350.00	59.61	6.96	37.24	43.50	60.31	74.00	-13.69	Pk
Vertical	5350.00	40.45	7.07	37.24	43.50	41.26	54.00	-12.74	AV
Horizontal	5350.00	52.62	7.05	37.24	43.50	53.41	74.00	-20.59	Pk
Horizontal	5350.00	37.74	7.05	37.24	43.50	38.53	54.00	-15.47	AV

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5.6G)-802.11a		

All the modulation modes have been tested, The report just record the worst data mode.

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel (5500 MHz)-Above 1G									
Vertical	5460.00	60.94	5.61	35.40	44.00	57.95	74.00	-16.05	Pk
Vertical	5460.00	42.84	5.76	35.40	44.00	40.00	54.00	-14.00	AV
Horizontal	5460.00	53.32	5.78	35.18	44.00	50.28	74.00	-23.72	Pk
Horizontal	5460.00	38.94	5.66	35.18	44.00	35.78	54.00	-18.22	AV

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11a " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

4 POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

For the band 5.15-5.25 GHz,

- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

- (3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3$ RBW.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C (5470-5725MHz), Band 3 (5745-5825MHz)		

Test data reference attachment.

5. 26DB & 99% EMISSION BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2 TEST PROCEDURE

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

- Set center frequency to the nominal EUT channel center frequency.
- Set span = 1.5 times to 5.0 times the OBW.
- Set RBW = 1 % to 5 % of the OBW
- Set VBW $\geq 3 \cdot$ RBW
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99 % power bandwidth function of the instrument (if available).
- If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz), Band 2C(5470-5725MHz), Band 3(5725-5850MHz)		

Test data reference attachment.

6. MINIMUM 6 DB BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

6.2 EST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5G) Mode Frequency Band 3 (5725-5850MHz)		

Test data reference attachment.

7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5250~5350	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5470~5725	250 mW or 11 dBm + 10 log B Note: The limit is the smaller of the two, "B" represents -26dB bandwidth.
5725~5850	1W


7.2 TEST PROCEDURE

- Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:
 - a) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
 - b) If the transmitter does not transmit continuously, measure the duty cycle D of the transmitter output signal as described in 12.2.
 - c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
 - d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle {e.g., $[10 \log (1 / 0.25)]$, if the duty cycle is 25%}.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX (5G) Mode Frequency Band 1 (5150-5250MHz), Band 2A (5250-5350MHz) Band 2C, (5470-5725MHz), Band 3 (5725-5850MHz)		

Test data reference attachment.

8. OUT OF BAND EMISSIONS

8.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

8.2 TEST PROCEDURE


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.

3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name :	BL-WN650BT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 5V

Test data reference attachment.


9. Frequency Stability Measurement

9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
 2. EUT have transmitted absence of modulation signal and fixed channelize.
 3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
 4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
 5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm
 - t6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
 7. Extreme temperature is -20°C~70°C.
- ### 9.3 TEST SETUP LAYOUT



9.4 EUT OPERATION DURING TEST

1. The EUT was programmed to be in continuously un-modulation transmitting mode.

9.5 TEST RESULTS

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5180.0005	5180	0.0005	0.1046
		V max (V)	5.5	5180.0015	5180	0.0015	0.2887
		V min (V)	4.5	5180.0007	5180	0.0007	0.1354
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5180.0005	5180	0.0005	0.1014
		T (°C)	-10	5180.0017	5180	0.0017	0.3300
		T (°C)	0	5180.0004	5180	0.0004	0.0688
		T (°C)	10	5180.0008	5180	0.0008	0.1502
		T (°C)	20	5180.0014	5180	0.0014	0.2611
		T (°C)	30	5180.0008	5180	0.0008	0.1580
		T (°C)	40	5180.0012	5180	0.0012	0.2398
		T (°C)	50	5180.0001	5180	0.0001	0.0190
		T (°C)	60	5180.0002	5180	0.0002	0.0458
		T (°C)	70	5180.0006	5180	0.0006	0.1161
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5200.0001	5200	0.0001	0.0285
		V max (V)	5.5	5200.0015	5200	0.0015	0.2807
		V min (V)	4.5	5200.0005	5200	0.0005	0.0937
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5200.0000	5200	0.0000	0.0007
		T (°C)	-10	5200.0005	5200	0.0005	0.0961
		T (°C)	0	5200.0005	5200	0.0005	0.0964
		T (°C)	10	5200.0006	5200	0.0006	0.1068
		T (°C)	20	5200.0004	5200	0.0004	0.0838
		T (°C)	30	5200.0010	5200	0.0010	0.2003
		T (°C)	40	5200.0014	5200	0.0014	0.2781
		T (°C)	50	5200.0016	5200	0.0016	0.3158
		T (°C)	60	5200.0011	5200	0.0011	0.2043
		T (°C)	70	5200.0005	5200	0.0005	0.0937
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5240.0012	5240	0.0012	0.2325
		V max (V)	5.5	5240.0004	5240	0.0004	0.0728
		V min (V)	4.5	5240.0002	5240	0.0002	0.0410
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5240.0014	5240	0.0014	0.2749
		T (°C)	-10	5240.0002	5240	0.0002	0.0361
		T (°C)	0	5240.0014	5240	0.0014	0.2681
		T (°C)	10	5240.0015	5240	0.0015	0.2836
		T (°C)	20	5240.0001	5240	0.0001	0.0121
		T (°C)	30	5240.0015	5240	0.0015	0.2936
		T (°C)	40	5240.0007	5240	0.0007	0.1408
		T (°C)	50	5240.0011	5240	0.0011	0.2161
		T (°C)	60	5240.0005	5240	0.0005	0.0912
		T (°C)	70	5240.0007	5240	0.0007	0.1285
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency Band 2A (5250-5350MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5260.0006	5260	0.0006	0.1077
		V max (V)	5.5	5260.0012	5260	0.0012	0.2215
		V min (V)	4.5	5260.0016	5260	0.0016	0.2964
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5260MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5260.0013	5260	0.0013	0.2486
		T (°C)	-10	5260.0009	5260	0.0009	0.1626
		T (°C)	0	5260.0002	5260	0.0002	0.0389
		T (°C)	10	5260.0006	5260	0.0006	0.1046
		T (°C)	20	5260.0001	5260	0.0001	0.0224
		T (°C)	30	5260.0018	5260	0.0018	0.3493
		T (°C)	40	5260.0011	5260	0.0011	0.2062
		T (°C)	50	5260.0016	5260	0.0016	0.3099
		T (°C)	60	5260.0018	5260	0.0018	0.3450
		T (°C)	70	5260.0019	5260	0.0019	0.3676
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5280.0019	5280	0.00185	0.3505
		V max (V)	5.5	5280.0011	5280	0.00112	0.2127
		V min (V)	4.5	5280.0004	5280	0.00037	0.0699
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5280MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5280.0002	5280	0.0002	0.0461
		T (°C)	-10	5280.0012	5280	0.0012	0.2288
		T (°C)	0	5280.0012	5280	0.0012	0.2246
		T (°C)	10	5280.0002	5280	0.0002	0.0327
		T (°C)	20	5280.0007	5280	0.0007	0.1297
		T (°C)	30	5280.0016	5280	0.0016	0.3060
		T (°C)	40	5280.0020	5280	0.0020	0.3732
		T (°C)	50	5280.0007	5280	0.0007	0.1293
		T (°C)	60	5280.0016	5280	0.0016	0.3065
		T (°C)	70	5280.0003	5280	0.0003	0.0532
Limits				Within 5250-5350MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5320.0010	5320	0.0010	0.1892
		V max (V)	5.5	5320.0002	5320	0.0002	0.0431
		V min (V)	4.5	5320.0015	5320	0.0015	0.2750
Limits				Within 5250-5350MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5320MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5320.0006	5320	0.0006	0.1210
		T (°C)	-10	5320.0016	5320	0.0016	0.2921
		T (°C)	0	5320.0019	5320	0.0019	0.3631
		T (°C)	10	5320.0008	5320	0.0008	0.1425
		T (°C)	20	5320.0007	5320	0.0007	0.1350
		T (°C)	30	5320.0009	5320	0.0009	0.1641
		T (°C)	40	5320.0014	5320	0.0014	0.2669
		T (°C)	50	5320.0002	5320	0.0002	0.0398
		T (°C)	60	5320.0015	5320	0.0015	0.2815
		T (°C)	70	5320.0019	5320	0.0019	0.3531
Limits				Within 5250-5350MHz			
Result				Complies			

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency Band 2C (5470-5725MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5500.0020	5500	0.0020	0.3570
		V max (V)	5.5	5500.0005	5500	0.0005	0.0872
		V min (V)	4.5	5500.0018	5500	0.0018	0.3340
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5500MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5500.0001	5500	0.0001	0.0124
		T (°C)	-10	5500.0001	5500	0.0001	0.0119
		T (°C)	0	5500.0004	5500	0.0004	0.0658
		T (°C)	10	5500.0018	5500	0.0018	0.3189
		T (°C)	20	5500.0014	5500	0.0014	0.2540
		T (°C)	30	5500.0007	5500	0.0007	0.1229
		T (°C)	40	5500.0006	5500	0.0006	0.1180
		T (°C)	50	5500.0002	5500	0.0002	0.0308
		T (°C)	60	5500.0009	5500	0.0009	0.1656
		T (°C)	70	5500.0010	5500	0.0010	0.1855
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5600.0019	5600	0.0019	0.3461
		V max (V)	5.5	5600.0004	5600	0.0004	0.0688
		V min (V)	4.5	5600.0015	5600	0.0015	0.2741
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5600MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5600.0015	5600	0.0015	0.2692
		T (°C)	-10	5600.0019	5600	0.0019	0.3306
		T (°C)	0	5600.0020	5600	0.0020	0.3540
		T (°C)	10	5600.0015	5600	0.0015	0.2674
		T (°C)	20	5600.0014	5600	0.0014	0.2547
		T (°C)	30	5600.0010	5600	0.0010	0.1870
		T (°C)	40	5600.0006	5600	0.0006	0.1029
		T (°C)	50	5600.0015	5600	0.0015	0.2593
		T (°C)	60	5600.0011	5600	0.0011	0.2020
		T (°C)	70	5600.0000	5600	0.0000	0.0071
Limits				Within 5470-5725MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5700.0013	5700	0.0013	0.2368
		V max (V)	5.5	5700.0003	5700	0.0003	0.0455
		V min (V)	4.5	5700.0017	5700	0.0017	0.2903
Limits				Within 5470-5725MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5700MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5700.0010	5700	0.0010	0.1758
		T (°C)	-10	5700.0001	5700	0.0001	0.0220
		T (°C)	0	5700.0020	5700	0.0020	0.3444
		T (°C)	10	5700.0020	5700	0.0020	0.3428
		T (°C)	20	5700.0012	5700	0.0012	0.2144
		T (°C)	30	5700.0004	5700	0.0004	0.0714
		T (°C)	40	5700.0009	5700	0.0009	0.1583
		T (°C)	50	5700.0003	5700	0.0003	0.0584
		T (°C)	60	5700.0019	5700	0.0019	0.3339
		T (°C)	70	5700.0014	5700	0.0014	0.2389
Limits				Within 5470-5725MHz			
Result				Complies			

EUT :	Bluetooth 4.2+AC650M Nano Wireless USB Adapter	Model Name. :	BL-WN650BT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX Frequency(5745-5850MHz)		

Voltage vs. Frequency Stability

Page VS: Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5745.0002	5745	0.0002	0.0295
		V max (V)	5.5	5745.0018	5745	0.0018	0.3141
		V min (V)	4.5	5745.0016	5745	0.0016	0.2799
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5745.0019	5745	0.0019	0.3344
		T (°C)	-10	5745.0009	5745	0.0009	0.1628
		T (°C)	0	5745.0006	5745	0.0006	0.1049
		T (°C)	10	5745.0015	5745	0.0015	0.2586
		T (°C)	20	5745.0017	5745	0.0017	0.2898
		T (°C)	30	5745.0020	5745	0.0020	0.3442
		T (°C)	40	5745.0001	5745	0.0001	0.0111
		T (°C)	50	5745.0001	5745	0.0001	0.0212
		T (°C)	60	5745.0013	5745	0.0013	0.2333
		T (°C)	70	5745.0006	5745	0.0006	0.1042
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5785.0015	5785	0.00145	-0.2509
		V max (V)	5.5	5785.0011	5785	0.00110	-0.1904
		V min (V)	4.5	5785.0003	5785	0.00025	-0.0432
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5785.0013	5785	0.0013	0.2206
		T (°C)	-10	5785.0017	5785	0.0017	0.2908
		T (°C)	0	5785.0015	5785	0.0015	0.2573
		T (°C)	10	5785.0012	5785	0.0012	0.2120
		T (°C)	20	5785.0011	5785	0.0011	0.1833
		T (°C)	30	5785.0000	5785	0.0000	0.0040
		T (°C)	40	5785.0018	5785	0.0018	0.3158
		T (°C)	50	5785.0020	5785	0.0020	0.3372
		T (°C)	60	5785.0003	5785	0.0003	0.0483
		T (°C)	70	5785.0007	5785	0.0007	0.1229
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	5	5825.0015	5825	0.0015	0.2644
		V max (V)	5.5	5825.0020	5825	0.0020	0.3416
		V min (V)	4.5	5825.0012	5825	0.0012	0.2058
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	5	T (°C)	-20	5825.0005	5825	0.0005	0.0863
		T (°C)	-10	5825.0005	5825	0.0005	0.0808
		T (°C)	0	5825.0006	5825	0.0006	0.1041
		T (°C)	10	5825.0016	5825	0.0016	0.2738
		T (°C)	20	5825.0006	5825	0.0006	0.1035
		T (°C)	30	5825.0016	5825	0.0016	0.2696
		T (°C)	40	5825.0005	5825	0.0005	0.0871
		T (°C)	50	5825.0018	5825	0.0018	0.3152
		T (°C)	60	5825.0009	5825	0.0009	0.1617
		T (°C)	70	5825.0002	5825	0.0002	0.0407
Limits				Within 5745-5850MHz			
Result				Complies			

10. DYNAMIC FREQUENCY SELECTION(DFS)

10.1 APPLICABILITY OF DFS REQUIREMENTS

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	N/A	Yes	Yes

Additional requirements for devices with multiple bandwidth modes	Operational Mode	
	Master or Client With Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

10.2 INTERFERENCE THRESHOLD VALUES, MASTER OR CLIENT INCORPORATING IN-SERVICE NOTEBOOKING

Maximum Transmit Power	Value (see notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain.	

10.3 DFS RESPONSE REQUIREMENT VALUES

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth See Note 3.

Note 1: The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar Burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate Channel changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

10.4 SHORT PULSE RADAR TEST WAVEFORMS

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B		60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.


If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

10.5 CALIBRATION SETUP AND DFS TEST RESULTS

Radar Waveform Calibration Procedure

- 1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- 2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 3.69\text{dB} = -58.31\text{dBm}$ that had been taken into account the output power range and antenna gain.
- 3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- 4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 3.69\text{dB} + 1\text{dB} = -57.31\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

10.6 CONDUCTED CALIBRATION SETUP



Wireless AP	Manufacturer	ASUSTek Computer Inc
	Model NO.	AX5400
	FCC ID	MSQ-RTAXJ300

Note:1. The Slave device associated with the EUT during these tests does not have radar detection capability.

2. WLAN traffic is generated by using the iperf software to send packets from the Master IP address to the Slave IP address.

3. The time required for the master and slave devices to fully start up is 120s.

4. EUT does not support TPC.


10.7 RADAR WAVEFORM CALIBRATION RESULT

Test data reference attachment.

10.8 IN-SERVICE NOTEBOOKING: CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD

TEST CONFIGURATION:

Setup for Client with injection at the Master



TEST PROCEDURE:

1. The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device
3. A trigger is provided from the pulse generator to the DFS Notebooking system in order to capture the traffic and the occurrence of the radar pulse.
4. EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is Streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
5. When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom In 600ms plot of the Short Pulse Radar Type
7. Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
8. Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

TEST MODE:

Mode	Frequency (MHz)
ac80	5290
ac80	5530
n40	5310
n40	5510
a	5320
a	5500

10.9 RESULT OF CHANNEL MOVE TIME, CHANNEL CLOSING TRANSMISSION TIME AND NON-OCCUPANCY PERIOD FOR CLIENT BEACON TEST

Test data reference attachment.

11. ANTENNA REQUIREMENT**11.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.2 EUT ANTENNA

The EUT antenna is PIFA ANT. It comply with the standard requirement.

END OF REPORT