

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	Tablet PC
Model Name	TITAN X2
FCC ID	2AL6Y-TITANX2

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

According to the follow transmitter output power (  $P_t$  ) formula :

WiFi

According to the report AGC05465170401FE04,  
 $P_t=9.65\text{dBm}=9.23\text{mW}$

The result for RF exposure evaluation

$\text{SAR} = (9.23\text{mW} / 5\text{mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.90 < 3.0 \text{ for 1-g SAR}$

BT

According to the report AGC05465170401FE03,  
 $P_t=-4.95\text{dBm}=0.32\text{mW}$

The result for RF exposure evaluation

$\text{SAR} = (0.32\text{mW} / 5\text{mm}) \cdot [\sqrt{2.48(\text{GHz})}] = 0.1 < 3.0 \text{ for 1-g SAR}$

Simultaneous transmission between Bluetooth and WiFi transmitter

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg, for test separation distances } \leq 50 \text{ mm;}$   
where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.

$\text{SAR} = (0.1 + 2.9) / 7.5 = 0.4 \text{ W/kg} < 1.6 \text{ W/kg}$

### 4. CONCLUSION

The SAR evaluation is not required.