

Appendix 10

Prüfbericht - Nr.:
19660350 001
Seite 1 von 2
Test Report No.
Page 1 of 2

RF Exposure Report

FCC ID: 2AL7J-FMHOMN0041

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached. Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

F= Frequency in MHz
Friis Formula

Appendix 10

Prüfbericht - Nr.:

19660350 001

Seite 2 von 2

Test Report No.

Page 2 of 2

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 50cm.

EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

Classification

The antenna of this product, under normal use condition, is at least 50cm away from the body of the user. Warning statement to the user for keeping at least 50cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as fixed device.

Note: EUT shall be installed at a minimum height of 2.5 m from the ground plane

Test Results

TDD band 41

Antenna Gain (In Linear Scale) 14.5dBi = 28.1838

Manufacturer has declared the tune-up value as $\pm 2.7\text{dB}$ is considered in MPE calculation.

Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Tune-up Scaling factor (dB)	Antenna Gain in Linear Scale	Maximum Tune Up tolerance (mW)/dBm	Total Power Density (mW/cm^2)	Limit (mW/cm^2)
26.97	497.7370	2.7	28.1838	926.83/29.67	0.8314	1.000