



# FCC Part 15C **Measurement and Test Report**

## For

Shenzhen QianChuan Smart Technology Co., Ltd

2/F, Bldg #13, Wangtang Industrial park, Xinwei Village, Xili Str.,

Nanshan District, Shenzhen, China

FCC ID: 2AL7SSS001KS

FCC Rule(s): FCC Part 15.249

**Product Description:** Wireless Switch

**Tested Model:** SS001KS

**Report No.:** STR17058240I

**Tested Date:** 2017-05-16 to 2017-05-25

**Issued Date:** 2017-05-25

Tested By: Leo Lee / Engineer

Silin Chen / EMC Manager **Reviewed By:** 

Leo Lee Silin chen Jumyso Approved & Authorized By: Jandy So / PSQ Manager

**Prepared By:** 

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.





## TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 TEST STANDARDS	
1.3 TEST METHODOLOGY	4
1.4 Test Facility	
1.5 EUT SETUP AND TEST MODE	
1.6 MEASUREMENT UNCERTAINTY	
1.7 TEST EQUIPMENT LIST AND DETAILS	6
2. SUMMARY OF TEST RESULTS	7
3. ANTENNA REQUIREMENTS	8
3.1 STANDARD APPLICABLE	8
3.2 TEST RESULT	
4. RADIATED EMISSIONS	
4.1 STANDARD APPLICABLE	
4.2 TEST PROCEDURE.	
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	
4.4 Environmental Conditions	
4.5 SUMMARY OF TEST RESULTS/PLOTS	
5. OUT OF BAND EMISSIONS	15
5.1 STANDARD APPLICABLE	
5.2 Test Procedure.	
5.3 ENVIRONMENTAL CONDITIONS	
5.4 SUMMARY OF TEST RESULTS/PLOTS	
6. EMISSION BANDWIDTH	17
6.1 STANDARD APPLICABLE.	
6.2 TEST PROCEDURE	17
6.3 ENVIRONMENTAL CONDITIONS	
6.4 SUMMARY OF TEST RESULTS/PLOTS	17



### 1. GENERAL INFORMATION

## 1.1 Product Description for Equipment Under Test (EUT)

**Client Information** 

Applicant: Shenzhen QianChuan Smart Technology Co., Ltd

Address of applicant: 2/F, Bldg #13, Wangtang Industrial park, Xinwei Village,

Xili Str., Nanshan District, Shenzhen, China

Manufacturer: Shenzhen QianChuan Smart Technology Co., Ltd

Address of manufacturer: 2/F, Bldg #13, Wangtang Industrial park, Xinwei Village,

Xili Str., Nanshan District, Shenzhen, China

General Description of EUT	
Product Name:	Wireless Switch
Brand Name:	/
Model No.:	SS001KS
Adding Model(s):	SS001KS-915, SS001KS-915BLK,
	SS001KS-915WHI
Rated Voltage:	DC 3.0 by button battery
Power Adapter:	/
Software Version:	/
Hardware Version:	QC-CMT215A-T-V1.2

Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model SS001KS, but the circuit and the electronic construction do not change, declared by the manufacturer.

Technical Characteristics of EUT	
Frequency Range:	915MHz
Max. Field Strength:	92.48dBuV/m(3m)
Modulation:	FSK
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency of EUT:	26MHz

Report No.: STR17058240I Page 3 of 18 FCC Part 15.249



#### 1.2 Test Standards

The following report is prepared on behalf of the Shenzhen QianChuan Smart Technology Co., Ltd in accordance with FCC Part 15, Subpart B, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.107,15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 1.4 Test Facility

#### FCC - Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

#### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

#### CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

Report No.: STR17058240I Page 4 of 18 FCC Part 15.249

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	915MHz

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	±2.88dB
Transmitter Spurious Emissions	Radiated	±5.1dB

Report No.: STR17058240I Page 5 of 18 FCC Part 15.249



## 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	<b>Due Date</b>
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03



## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

N/A: not applicable



## 3. Antenna Requirements

## 3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

## 3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

Report No.: STR17058240I Page 8 of 18 FCC Part 15.249



## 4. Radiated Emissions

## 4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental	Field strength of Harmonics
	(milli-volts/meter)	(micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


#### 4.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

Report No.: STR17058240I Page 9 of 18 FCC Part 15.249







Frequency:9kHz-30MHz

RBW=10KHz,

VBW = 30KHz

Sweep time= Auto

 $Trace = max \ hold$ 

 $Detector\ function = peak$ 

Frequency:30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

 $Trace = max \ hold$ 

Detector function = peak, QP

Frequency : Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

 $Trace = max \ hold$ 

Detector function = peak, AV



## 4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss - Ampl. Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of  $-6dB\mu V$  means the emission is  $6dB\mu V$  below the maximum limit. The equation for margin calculation is as follows:

#### **4.4 Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar

### 4.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst margin of:

-1.52 dB at 916.0687 MHz in the Horizontal polarization, 30 kHz to 1 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Report No.: STR17058240I Page 11 of 18 FCC Part 15.249




## Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: Wireless Switch

Tested Model: SS001KS

Operating Condition: Transmitting (915MHz)
Comment: DC 3.0 by button battery


Test Specification: Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	39.9942	19.19	4.93	24.12	40.00	-15.88	20	100	peak
2	43.3534	18.42	4.94	23.36	40.00	-16.64	297	100	peak
3	55.2207	17.15	5.02	22.17	40.00	-17.83	100	100	peak
4	123.2655	14.19	4.55	18.74	43.50	-24.76	314	100	peak
5	393.4723	16.47	12.39	28.86	46.00	-17.14	180	100	peak
6	645.1195	17.78	17.94	35.72	46.00	-10.28	183	100	peak
7	916.0687	78.34	14.14	92.48	94.00	-1.52	284	101	Fundamental

Report No.: STR17058240I Page 12 of 18 FCC Part 15.249

Test Specification: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	36.0007	19.35	4.33	23.68	40.00	-16.32	259	100	peak
2	62.8708	20.72	4.44	25.16	40.00	-14.84	128	100	peak
3	96.0986	16.18	4.34	20.52	43.50	-22.98	54	100	peak
4	114.5146	15.54	4.85	20.39	43.50	-23.11	181	100	peak
5	327.8873	16.08	11.71	27.79	46.00	-18.21	78	100	peak
6	714.1734	16.60	17.63	34.23	46.00	-11.77	308	100	peak
7	916.0687	66.52	14.14	80.66	94.00	-13.34	111	101	Fundamental



## Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector		
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V			
	Transmitting Channel-915MHz								
1830	60.27	-6.58	53.69	74	-20.31	Н	PK		
1830	53.79	-6.58	47.21	54	-6.79	Н	AV		
2745	54.67	-4.17	50.5	74	-23.5	Н	PK		
2745	50.89	-4.17	46.72	54	-7.28	Н	AV		
1830	56.51	-6.58	49.93	74	-24.07	V	PK		
1830	49.17	-6.58	42.59	54	-11.41	V	AV		
2745	50.26	-4.17	46.09	74	-27.91	V	PK		
2745	44.87	-4.17	40.7	54	-13.3	V	AV		

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Report No.: STR17058240I Page 14 of 18 FCC Part 15.249



## 5. Out of Band Emissions

## **5.1 Standard Applicable**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### **5.2 Test Procedure**

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

### **5.3 Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar


## 5.4 Summary of Test Results/Plots

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.

Please refer to the test plots as below.



## Bandedge - Horizontal (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	902.0000	22.49	15.10	37.59	46.00	-8.41	Peak Detector
2	914.8470	75.57	14.21	89.78	/	/	Fundamental
3	928.0000	24.20	14.14	38.34	46.00	-7.66	Peak Detector



## 6. Emission Bandwidth

## 6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

#### **6.2 Test Procedure**

According to the ANSI 63.4-2014, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW ≥1% 20dB Bandwidth, VBW ≥RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

#### **6.3 Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


### 6.4 Summary of Test Results/Plots

Frequency	20dB Bandwidth	99% Bandwidth		
MHz	kHz	kHz		
915	311.499	425.7021		

Report No.: STR17058240I Page 17 of 18 FCC Part 15.249



Please refer to the following test plots



\*\*\*\*\* END OF REPORT \*\*\*\*\*