





MPE TEST REPORT

Applicant LUXROBO

FCC ID 2AL85-LUX-32

Product Wifi/BT module

Brand LUXROBO

Model LUX-32

Report No. RXA1704-0126MPE01R1

Issue Date July 14, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Jiang peng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test	t Laboratory	3
	1.1	Notes of the Test Report	3
	1.2	Test facility	3
	1.3	Testing Location	4
	1.4	Laboratory Environment	4
2	Des	cription of Equipment under Test	5
3	Max	kimum conducted output power (measured) and antenna Gain	6



Test Report No: RXA1704-0126MPE01R1

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology** (shanghai) co., Ltd. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein . Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by CNAS or any government agencies.

1.2 Test facility

CNAS (accreditation number:L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (recognition number is 428261)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

MPE Test Report No: RXA1704-0126MPE01R1

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000
Website: http://www.ta-shanghai.com

E-mail: xukai@ta-shanghai.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C		
Relative humidity	Min. = 30%, Max. = 70%		
Ground system resistance	< 0.5 Ω		

Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.



2 Description of Equipment under Test

Client Information

Applicant	LUXROBO
Applicant address	50, 63-ro, Yeoungdeungpo-gu, 63city 4th floor, Seoul, South
Applicant address	Korea
Manufacturer	LUXROBO
Manufacturer address	50, 63-ro, Yeoungdeungpo-gu, 63city 4th floor, Seoul, South
	Korea

General Technologies

Model	LUX-32
SN	1
Hardware Version	HW V1.0
Software Version	SW V1.0



Test Report No: RXA1704-0126MPE01R1

3 Maximum conducted output power (measured) and antenna Gain

the numeric gain (G) of the antenna with a gain specified in dB is determined by Numeric gain (G)= $10^{(antenna gain/10)}$

Antenna 1

Band		Maximum Conducted Output Power (dBm)	Antenna Gain (dBi)	Numeric gain (dB)
	802.11b	17.0	0.5	1.122
2.4G	802.11g	17.0	0.5	1.122
2.46	802.11n HT20	17.0	0.5	1.122
	802.11n HT40	17.0	0.5	1.122
	Bluetooth	0.0	0.5	1.122
Bluetooth (Low Energy)		-3.0	0.5	1.122

PE Test Report No: RXA1704-0126MPE01R1

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following


TABLE 1 - LIMITS FOR MAXIMUN PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field Magnetic Field		Power Density	Averaging Time	
(MHz)	Strength	Strength		125- 125	
	(V/m)	(A/m)	(mW/cm2)	(minutes)	
	(A) Limits for Occu	upational/Controlle	d Exposures		
0.3-3.0	614	1.63	*(100)	6	
3-30	1842/f	4.89/f	*(900/f2)	6	
30-300	61.4	0.163	1.0	6	
300-1500			f/300	6	
1500-100,000			5	6	
(B)	Limits for General	Population/Uncont	rolled Exposure		
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	*(180/f2)	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = frequency in MHz

- Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.
- Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

^{* =} Plane-wave equivalent power density



The maximum permissible exposure for 1500~100,000MHz is 1.0.So

Band	The maximum permissible exposure	
Wi-Fi / BT/ BLE	1.0mW/cm ²	

Report No: RXA1704-0126MPE01R1

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.



RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4 \square R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Wi-Fi / BT/ BLE PG =1730dBm + (1.122dB) = 18.122 dBm=64.89mW

Band	PG (mW)	Test Result (mW/cm ²)	Limit Value (mW/cm²)	The MPE ratio
Wi-Fi / BT/ BLE	64.89	0.013	1.0	0.013
Note: The MPE ratio = Mac Test Result÷Limit Value				

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.