

FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: 2AL8JEL-001

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: *f* is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time $ E ^2$, $ H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric) =10log(dBi	Power Density (S) (mW/ cm2)	Total Power Density (S) (mW/ cm2)	Limit of Power Density (S) (mW/ cm2)	Result
802.11b ANT1	17±1	18	63.10	3.16 (5.00dBi)	0.03969	/	1	Pass
802.11b ANT2	17±1	18	63.10	3.16 (5.00dBi)	0.03969	/	1	Pass
802.11g ANT1	15±1	16	39.81	3.16 (5.00dBi)	0.02505	/	1	Pass
802.11g ANT2	15±1	16	39.81	3.16 (5.00dBi)	0.02505	/	1	Pass
802.11n(H T20) ANT1	11±1	12	15.85	6.32 (8.01dBi)	0.01994	0.03988	1	Pass
802.11n(H T20) ANT2	11±1	12	15.85	6.32 (8.01dBi)	0.01994			
802.11n(H T40) ANT1	10±1	11	12.59	6.32 (8.01dBi)	0.01584	0.03168	1	Pass
802.11n(H T40) ANT2	10±1	11	12.59	6.32 (8.01dBi)	0.01584			

The MIMO mode only support 802.11n, the Directional Gain=5.0dBi+10log(2)=8.01dBi.