



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Villa Door Station

MODEL NUMBER: OEU-201S-HMK-Z

SERIES MODEL NUMBER: OEU-201S-HMK-Z-xxxxxxxx-yyy-yyyyy-zzz
("x", "y", "z" can be 0-9, A-Z, a-z or blank, - may be blank)

PROJECT NUMBER: 4791412166

REPORT NUMBER: 4791412166-1

FCC ID: 2AL8S-0235C8XE

ISSUE DATE: Aug. 26, 2024

Prepared for

ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China

Tel: +86 512-6808 6400

Fax: +86 512-6808 4099

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	08/26/2024	Initial Issue	

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	Transmitter AC Conducted Emissions	Part 15.207	PASS
2	Transmitter Fundamental Field Strength	Part 15.225(a)(b)(c)(d)	PASS
3	Transmitter Radiated Emissions	Part 15.209(a)/ 15.225(d)	PASS
4	Transmitter 20dB Bandwidth	Part 15.215 (c)	PASS
5	Transmitter Frequency Stability (Temperature & Voltage Variation)	Part 15.225(e)	PASS
6	Antenna Requirement	FCC 15.203	PASS
Note: The measurement result for the sample received is < Pass > according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15 > when < Simple Acceptance > decision rule is applied.			

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT.....	9
5.2. MAXIMUM FIELD STRENGTH	10
5.3. CHANNEL LIST	10
5.4. DESCRIPTION OF AVAILABLE ANTENNAS	10
5.5. TEST ENVIRONMENT.....	10
5.6. DESCRIPTION OF TEST SETUP.....	11
5.7. MEASURING INSTRUMENT AND SOFTWARE USED	13
6. TEST RESULTS.....	14
6.1. AC Conducted Spurious Emissions.....	14
6.2. RADIATED EMISSION.....	19
6.2.1. FUNDAMENTAL FIELD STRENGTH.....	24
6.2.2. SPURIOUS EMISSIONS BELOW 1G.....	25
6.2.3. SPURIOUS EMISSIONS BELOW 30M.....	27
6.3. 20dB BANDWIDTH	30
6.4. TRANSMITTER FREQUENCY STABILITY	32
7. ANTENNA REQUIREMENTS	35

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD.
Address: No. 369, Xietong Road, Xixing Sub-district, Binjiang District,
Hangzhou City, 310051, Zhejiang Province, China

Manufacturer Information

Company Name: ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD.
Address: No. 369, Xietong Road, Xixing Sub-district, Binjiang District,
Hangzhou City, 310051, Zhejiang Province, China

Factory Information-1

Company Name: Zhejiang Uniview System Technology Co., Ltd.
Address: No.1277 Qingfeng South Road (South), Tongxiang Economic
Development Zone, Tongxiang City, Jiaxing City, 314500,
Zhejiang, China

Factory Information-2

Company Name: TDG Technology Co., Ltd.
Address: No. 1, Yatai Road, Nanhu district, Jiaxing, Zhejiang 314050, China

Factory Information-3

Company Name: TOP-TEK TECHNOLOGY(VIETNAM) CO., LTD.
Address: No.5, Street 7, Vsip II, Hoa Phu Ward, Tdm Town, Binh Duong
Province, Vietnam- 820000

EUT Description

Product Name: Villa Door Station
Model Name: OEU-201S-HMK-Z
Series Model No.: OEU-201S-HMK-Z-xxxxxxx-yyy-yyyy-zzz
("x", "y", "z" can be 0-9, A-Z, a-z or blank, - may be blank)
Model Difference: Their electrical circuit design, layout, components used and
internal wiring are identical, only the color and model name is
different. The model OEU-201S-HMK-Z was selected as the
representative model for compliance test.
Sample Number: 7426774
Data of Receipt Sample: Jul. 22, 2024
Test Date: Jul. 22, 2024~ Aug. 26, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	PASS

Prepared By:

Tom Tang

Tom Tang

Reviewed By:

Emily Wang

Emily Wang

Authorized By:

Kevin Shen

Kevin Shen

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 414788 D01 Radiated Test Site v01r01.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China.

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conducted emission	3.1dB
Radiation Emission test (include Fundamental emission) (9kHz-30MHz)	3.4dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	3.4dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Product Name:	Villa Door Station
Model No.:	OEU-201S-HMK-Z
Sample Type:	Normal production

5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Number of Transmit Chains (NTX)	Frequency (MHz)	Channel Number	Max. Field Strength (dB μ V/m)
13.56	1	13.56	1	6.16

5.3. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	13.56	2	/	3	/	4	/

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	13.56	FPC Antenna	0

Frequency (MHz)	Transmit and Receive Mode	Description
13.56	☒ 1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.

Remark: For the product, there is only one work mode and channel, and only data of the one mode was test and recorded in the report.

5.5. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity:	55 ~ 65%	
Atmospheric Pressure:	101kPa	
Temperature:	TN	23 ~ 28°C
Voltage:	VL	N/A
	VN	AC 120V
	VH	N/A

Note: VL= Lower Extreme Test Voltage
VN= Nominal Voltage
VH= Upper Extreme Test Voltage
TN= Normal Temperature

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Description
1	Laptop	ThinkPad	E590	/
2	Alarm Light	N/A	N/A	Supplied by UL Lab
3	Electric-magnetic Lock	N/A	N/A	Supplied by UL Lab

I/O PORT

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	LAN	LAN	LAN	100cm Length	/

ACCESSORY


Item	Accessory	Brand Name	Model Name	Description
1	DC Adapter	HONOTO	ADS-24S-12 1224GPBR	INPUT:100-240V~50/60Hz 0.7A Max OUTPUT:12.0V=2.0A

The EUT can continue work normally when a card touched.

TEST SETUP

The EUT can work in a engineering mode.

NFC support both ISO /IEC 14443A and ISO /IEC 14443B. All lowest and highest data rates as per the standards are supported - 106 kbps, 212 kbps, 424 kbps and 848 kbps, all the modes had been tested, but only the worst data (ISO 14443A 106 kbps) was recorded in the report. The EUT has been test with tag mode and without tag mode, but only the worst data with tag mode was recorded in the report.

SETUP DIAGRAM FOR TESTS

5.7. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	EMI Test Receiver	R&S	ESR3	126700	2022-11-26	2023-11-25	2024-11-24
☒	Two-Line V-Network	R&S	ENV216	126701	2022-11-26	2023-11-25	2024-11-24
☒	Artificial Mains Networks	R&S	ENY81	126712	2022-09-27	2023-09-26	2024-09-25
Software							
Used	Description		Manufacturer		Name	Version	
☒	Test Software for Conducted disturbance		R&S		EMC32	9.25.00	
Radiated Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	EMI test receiver	R&S	ESR7	222993	2023-04-08	2024-03-23	2025-03-22
☒	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	155456	2021-06-03	2024-05-27	2027-05-26
☒	Receiver Antenna (30MHz-1GHz)	Schwarzbeck	VULB 9168	171952	2021-06-28	2024-07-04	2027-07-03
Software							
Used	Description		Manufacturer		Name	Version	
☒	Test Software for Radiated disturbance		Tonscend		JS32-RE	5.0.0.2	
Other instruments							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9010B	155368	2023-04-08	2024-03-23	2025-03-22
☒	Attenuator	PASTERNACK	PE7087-6	1624	2023-04-08	2024-03-23	2025-03-22

6. TEST RESULTS


6.1. AC Conducted Spurious Emissions

LIMITS

FCC Reference:	Part 15.207
Test Method Used:	ANSI C63.10 Section 6.2

FREQUENCY (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE




The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz. The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

RESULTS WITH THE ANTENNA CONNECTED


LINE L RESULTS (WORST-CASE CONFIGURATION)



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.167413	---	27.52	55.09	27.57	1000.0	9.000	L1	OFF	9.6
0.167413	39.86	---	65.09	25.23	1000.0	9.000	L1	OFF	9.6
0.319150	---	24.60	49.73	25.13	1000.0	9.000	L1	OFF	9.6
0.319150	29.11	---	59.73	30.61	1000.0	9.000	L1	OFF	9.6
2.580288	---	12.79	46.00	33.21	1000.0	9.000	L1	OFF	9.5
2.580288	18.55	---	56.00	37.45	1000.0	9.000	L1	OFF	9.5
3.373800	---	12.58	46.00	33.42	1000.0	9.000	L1	OFF	9.5
3.373800	18.94	---	56.00	37.06	1000.0	9.000	L1	OFF	9.5
3.955875	---	12.39	46.00	33.61	1000.0	9.000	L1	OFF	9.5
3.955875	16.99	---	56.00	39.01	1000.0	9.000	L1	OFF	9.5
13.560113	---	43.22	50.00	6.78	1000.0	9.000	L1	OFF	9.5
13.560113	50.64	---	60.00	9.36	1000.0	9.000	L1	OFF	9.5

- Note: 1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. The frequency 13.560113MHz is the fundamental carrier frequency.

LINE N RESULTS (WORST-CASE CONFIGURATION)




Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.150000	---	29.00	56.00	27.00	1000.0	9.000	N	OFF	9.6
0.150000	42.56	---	66.00	23.44	1000.0	9.000	N	OFF	9.6
0.294275	---	26.32	50.40	24.08	1000.0	9.000	N	OFF	9.5
0.294275	30.19	---	60.40	30.21	1000.0	9.000	N	OFF	9.5
0.324125	---	19.75	49.60	29.85	1000.0	9.000	N	OFF	9.5
0.324125	28.27	---	59.60	31.33	1000.0	9.000	N	OFF	9.5
2.540488	---	13.30	46.00	32.70	1000.0	9.000	N	OFF	9.4
2.540488	18.87	---	56.00	37.13	1000.0	9.000	N	OFF	9.4
3.993188	---	12.18	46.00	33.82	1000.0	9.000	N	OFF	9.4
3.993188	16.50	---	56.00	39.50	1000.0	9.000	N	OFF	9.4
13.560113	---	42.98	50.00	7.02	1000.0	9.000	N	OFF	9.5
13.560113	50.48	---	60.00	9.52	1000.0	9.000	N	OFF	9.5

- Note: 1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. The frequency 13.560113MHz is the fundamental carrier frequency.

RESULTS WITH A DUMMY LOAD IN LIEU OF THE ANTENNA


LINE L RESULTS (WORST-CASE CONFIGURATION)



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.150000	---	31.71	56.00	24.29	1000.0	9.000	L1	OFF	9.6
0.150000	41.84	---	66.00	24.16	1000.0	9.000	L1	OFF	9.6
0.172388	---	30.19	54.85	24.65	1000.0	9.000	L1	OFF	9.6
0.172388	39.02	---	64.85	25.82	1000.0	9.000	L1	OFF	9.6
0.237063	---	24.11	52.20	28.09	1000.0	9.000	L1	OFF	9.6
0.237063	28.96	---	62.20	33.24	1000.0	9.000	L1	OFF	9.6
0.281838	---	20.40	50.76	30.36	1000.0	9.000	L1	OFF	9.6
0.281838	23.85	---	60.76	36.91	1000.0	9.000	L1	OFF	9.6
0.304225	---	32.88	50.13	17.25	1000.0	9.000	L1	OFF	9.6
0.304225	34.82	---	60.13	25.31	1000.0	9.000	L1	OFF	9.6
0.321638	---	25.89	49.66	23.77	1000.0	9.000	L1	OFF	9.6
0.321638	30.35	---	59.66	29.31	1000.0	9.000	L1	OFF	9.6

Note: 1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz-150 kHz), 9 kHz (150 kHz-30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.

LINE N RESULTS (WORST-CASE CONFIGURATION)



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.150000	---	31.64	56.00	24.36	1000.0	9.000	N	OFF	9.6
0.150000	41.81	---	66.00	24.19	1000.0	9.000	N	OFF	9.6
0.172388	---	30.13	54.85	24.71	1000.0	9.000	N	OFF	9.6
0.172388	38.76	---	64.85	26.09	1000.0	9.000	N	OFF	9.6
0.194775	---	29.31	53.83	24.52	1000.0	9.000	N	OFF	9.6
0.194775	36.06	---	63.83	27.77	1000.0	9.000	N	OFF	9.6
0.217163	---	27.21	52.93	25.72	1000.0	9.000	N	OFF	9.5
0.217163	32.48	---	62.93	30.45	1000.0	9.000	N	OFF	9.5
0.301738	---	32.55	50.20	17.64	1000.0	9.000	N	OFF	9.5
0.301738	34.31	---	60.20	25.89	1000.0	9.000	N	OFF	9.5
0.321638	---	25.39	49.66	24.28	1000.0	9.000	N	OFF	9.5
0.321638	30.04	---	59.66	29.62	1000.0	9.000	N	OFF	9.5

Note: 1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz-150 kHz), 9 kHz (150 kHz-30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.

6.2. RADIATED EMISSION

TEST PROCEDURE

Fundamental field strength

FCC Reference:	Part 15.225(a)(b)(c)(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Sections 6.3, 6.4 and 6.5

Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) at 30M
13.553-13.567	15848	84
13.410-13.553/13.567-13.710	334	50.47
13.110-13.410/13.710-14.010	106	40.51

Note(s):

1. The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.
2. The limit is specified at a test distance of 30 meters. However, as specified by FCC Section 15.31 (f)(2) / RSS-Gen Section 6.4, measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).

Radiation Disturbance Test Limit for FCC (Class B) (9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			


Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

FCC Reference:	Part 15.225(a)(b)(c)(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Sections 6.3 and 6.5

TEST SETUP

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m OFS. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G




The setting of the spectrum analyser:

RBW	120kHz
VBW	300kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT had been tested in X axis position according to the user manual that the product should be installed in X axis position.

RESULTS


TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC120V

Remark: Through pre-testing all test polarizations, including Horizontal, Face-on and Face-off polarizations of the antenna, but only the data of the worst case is included in this test report.

6.2.1. FUNDAMENTAL FIELD STRENGTH


Face-on (THE WORST CASE-FACE ON)



No.	Frequency [MHz]	Reading [dBμV]	Correct [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1	13.3477	10.03	-21.60	-11.57	40.51	-52.08	peak
2	13.4530	12.80	-21.60	-8.80	50.47	-59.27	peak
3	13.5588	27.76	-21.60	6.16	84.00	-77.84	peak
4	13.6650	14.20	-21.58	-7.38	50.47	-57.85	peak
5	13.7708	11.47	-21.58	-10.11	40.51	-50.62	peak

Note: Result = Reading + Correct Factor.


6.2.2. SPURIOUS EMISSIONS BELOW 1G



No.	Frequency	Reading	Factor	Result	Limit	Margin	Remark
	[MHz]	[dBμV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dB]	
1	98.3918	15.23	15.37	30.60	43.50	-12.90	peak
2	191.8122	21.75	17.51	39.26	43.50	-4.24	peak
3	212.8633	21.39	17.23	38.62	43.50	-4.88	peak
4	237.8918	19.95	18.66	38.61	46.00	-7.39	peak
5	284.7475	17.87	20.72	38.59	46.00	-7.41	peak
6	440.6421	15.37	24.90	40.27	46.00	-5.73	peak

- Note: 1. Result Level = Read Level + Correct Factor.
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
3. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

Vertical




No.	Frequency	Reading	Factor	Result	Limit	Margin	Remark
	[MHz]	[dBμV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dB]	
1	45.2305	11.65	20.19	31.84	40.00	-8.16	peak
2	51.0511	11.12	20.53	31.65	40.00	-8.35	peak
3	98.3918	12.70	15.37	28.07	43.50	-15.43	peak
4	145.2475	11.79	20.34	32.13	43.50	-11.37	peak
5	284.7475	12.64	20.72	33.36	46.00	-12.64	peak
6	456.6487	10.99	25.16	36.15	46.00	-9.85	peak

Note: 1. Result Level = Read Level + Correct Factor.
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
3. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

6.2.3. SPURIOUS EMISSIONS BELOW 30M


9kHz~ 150kHz



No.	Frequency [MHz]	Reading [dBμV]	Factor [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1	0.0229	37.69	-61.71	-24.02	40.40	-64.42	peak
2	0.0415	31.48	-61.60	-30.12	35.24	-65.36	peak
3	0.0461	30.81	-61.60	-30.79	34.32	-65.11	peak
4	0.0651	29.81	-61.61	-31.80	31.33	-63.13	peak
5	0.0869	26.80	-61.64	-34.84	28.82	-63.66	peak
6	0.1263	22.89	-61.72	-38.83	25.58	-64.41	peak

- Note: 1. Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, the test data of Face-on was the worst and recorded in the report.


150kHz ~ 490kHz



No.	Frequency	Reading	Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dB]	
1	0.1789	32.52	-61.76	-29.24	22.55	-51.79	peak
2	0.2501	31.39	-61.80	-30.41	19.64	-50.05	peak
3	0.2501	31.39	-61.80	-30.41	19.64	-50.05	peak
4	0.3411	29.03	-61.83	-32.80	16.94	-49.74	peak
5	0.4259	27.94	-61.85	-33.91	14.79	-48.70	peak
6	0.4848	29.66	-61.88	-32.22	13.21	-45.43	peak

- Note: 1. Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, the test data of Face-on was the worst and recorded in the report.

490kHz ~ 30MHz



No.	Frequency	Reading	Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dB]	
1	0.5697	31.93	-21.89	10.04	32.49	-22.45	peak
2	0.7025	22.02	-21.87	0.15	30.67	-30.52	peak
3	0.9711	19.38	-21.87	-2.49	27.86	-30.35	peak
4	1.1747	21.96	-21.85	0.11	26.21	-26.10	peak
5	1.7177	18.89	-21.84	-2.95	29.54	-32.49	peak
6	13.5583	27.66	-21.60	6.06	/	/	fundamental

- Note: 1. Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, the test data of Face-on was the worst and recorded in the report.
4. The frequency 13.5583MHz is the fundamental carrier frequency.

6.3. 20dB BANDWIDTH

LIMITS

FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
Part 15.215 (c)	20 Bandwidth	For reporting purposes only.
RSS-GEN Clause 6.7	99% Bandwidth (Just for reference only)	For reporting purposes only.


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20dB Occupied Bandwidth: 1% to 5% of the 20 dB bandwidth For 99% Occupied Bandwidth: 1% to 5% of the occupied bandwidth
VBW	For 20dB Occupied Bandwidth: approximately $3 \times \text{RBW}$ For 99% Occupied Bandwidth: $\geq 3 \times \text{RBW}$
Span	Between 2 times and 5 times the 20dB OBW. Between 1.5 times and 5 times the 99% OBW.
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 99% relative to the maximum level measured in the fundamental emission.

TEST SETUP




TEST ENVIRONMENT

Temperature	23°C	Relative Humidity	56%
Atmosphere Pressure	102kPa	Test Voltage	AC120V

RESULTS

Frequency (MHz)	99% bandwidth (kHz)	20dB bandwidth (kHz)
13.56	2.280	2.672



Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW. And the signal was narrowband, therefore it was impossible to set RBW within 1% ~ 5%.

6.4. TRANSMITTER FREQUENCY STABILITY

LIMITS

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

TEST SETUP AND PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	10kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.

TEST SETUP



TEST ENVIRONMENT

Temperature	23°C	Relative Humidity	56%
Atmosphere Pressure	102kPa	Test Voltage	AC120V

TEST RESULTS

Maximum frequency error of the EUT with variations in ambient temperature

Temperature (°C)	Time After (Mins)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
-20	0	13.5602	200	0.001	0.01	0.009	Pass
	2	13.5605	500	0.004	0.01	0.006	Pass
	5	13.5603	300	0.002	0.01	0.008	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
-10	0	13.5603	300	0.002	0.01	0.008	Pass
	2	13.5603	300	0.002	0.01	0.008	Pass
	5	13.5604	400	0.003	0.01	0.007	Pass
	10	13.5604	400	0.003	0.01	0.007	Pass
0	0	13.5604	400	0.003	0.01	0.007	Pass
	2	13.5605	500	0.004	0.01	0.006	Pass
	5	13.5605	500	0.004	0.01	0.006	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
10	0	13.5605	500	0.004	0.01	0.006	Pass
	2	13.5603	300	0.002	0.01	0.008	Pass
	5	13.5604	400	0.003	0.01	0.007	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
20	0	13.5604	400	0.003	0.01	0.007	Pass
	2	13.5604	400	0.003	0.01	0.007	Pass
	5	13.5605	500	0.004	0.01	0.006	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
30	0	13.5605	500	0.004	0.01	0.006	Pass
	2	13.5603	300	0.002	0.01	0.008	Pass
	5	13.5605	500	0.004	0.01	0.006	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
40	0	13.5603	300	0.002	0.01	0.008	Pass
	2	13.5604	400	0.003	0.01	0.007	Pass
	5	13.5604	400	0.003	0.01	0.007	Pass
	10	13.5603	300	0.002	0.01	0.008	Pass
50	0	13.5602	200	0.001	0.01	0.009	Pass
	2	13.5603	300	0.002	0.01	0.008	Pass
	5	13.5604	400	0.003	0.01	0.007	Pass
	10	13.5602	200	0.001	0.01	0.009	Pass

Maximum frequency error of the EUT with variations in nominal operating voltage at an ambient normal temperature(20°C)

Supply Voltage (V)	Time After (Mins)	Nominal Frequency (MHz)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (%)	Limit (%)	Margin (%)	Result
102	0	13.56	13.5602	200	0.001	0.01	0.009	Pass
	2	13.56	13.5604	400	0.003	0.01	0.007	Pass
	5	13.56	13.5604	400	0.003	0.01	0.007	Pass
	10	13.56	13.5603	300	0.002	0.01	0.008	Pass
120	0	13.56	13.5602	200	0.001	0.01	0.009	Pass
	2	13.56	13.5604	400	0.003	0.01	0.007	Pass
	5	13.56	13.5604	400	0.003	0.01	0.007	Pass
	10	13.56	13.5603	300	0.002	0.01	0.008	Pass
138	0	13.56	13.5603	300	0.002	0.01	0.008	Pass
	2	13.56	13.5605	500	0.004	0.01	0.006	Pass
	5	13.56	13.5603	300	0.002	0.01	0.008	Pass
	10	13.56	13.5603	300	0.002	0.01	0.008	Pass

7. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

ANTENNA CONNECTOR

The antenna uses a unique coupling to the intentional radiator

END OF REPORT