



TEST REPORT

Reference No...... : WTF23F12271059W
FCC ID : 2ALA3-PWM44LR
Applicant..... : Casambi Technologies Oy
Address..... : Bertel Jungin Aukio 1 C, 02600 Espoo, Finland
Manufacturer : TEPCOMP Oü
Address..... : Pihlta tee 43, 93815 Kuressaare, Saaremaa, Estonia
Product Name..... : 4ch PWM Controller
Model No..... : CBU-PWM4-4-LR
Test specification..... : FCC CFR47 Part 15 Subpart C (Section 15.247)
Date of Receipt sample : 2023-12-26
Date of Test : 2024-01-08 to 2024-03-22
Date of Issue..... : 2024-06-14
Test Report Form No. : WEW-15247A-01B
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Foshan) Co., Ltd.

Address: 1/F., Building 19, Sunlink Machinery City, Xingye 4 Road,
Guanglong Industrial Park, Chihua Neighborhood Committee, Chencun Town,
Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398

Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Tested by:

Roy Hong

Approved by:

Danny Zhou



1 Revision History

Test Report No.	Date of Issue	Description	Status
WTF23F12271059W	2024-06-14	Original	Valid

WALTEK



2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T	4
3.2 TECHNICAL CHARACTERISTICS OF EUT	4
3.3 STANDARDS APPLICABLE FOR TESTING.....	4
3.4 TEST FACILITY	5
3.5 SUBCONTRACTED	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
3.7 DISCLAIMER.....	5
4 EUT SETUP AND TEST MODE.....	6
5 EQUIPMENT USED DURING TEST.....	7
5.1 EQUIPMENT LIST	7
5.2 TEST SOFTWARE	8
5.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
5.4 MEASUREMENT UNCERTAINTY	8
6 SUMMARY OF TEST RESULT	9
6.1 ANTENNA REQUIREMENT	10
6.2 RADIATED SPURIOUS EMISSIONS	11
6.3 POWER SPECTRAL DENSITY	42
6.4 DTS BANDWIDTH.....	47
6.5 RF OUTPUT POWER.....	52
6.6 OUT OF BAND EMISSIONS.....	57
7 PHOTOGRAPHS TEST SETUP.....	71
7.1 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP.....	71
8 PHOTOGRAPHS – EUT CONSTRUCTIONAL DETAILS.....	72



3 General Information

3.1 General Description of E.U.T

Product Name	4ch PWM Controller
Model No.	CBU-PWM4-4-LR
Model Description	---
Rating	Input: 12-24VDC, 4.0A, <0.3W (No-load Standby power) Output: 12-24VDC, Max. 96W@24VDC, Max. 48W@12VDC
Battery Capacity	---
Power Adapter	---

3.2 Technical Characteristics of EUT

Bluetooth Version	V5.3 (BLE mode)
Frequency Range	2402-2480MHz
RF Output Power	7.842dBm (Conducted)@125kbps
Modulation	GFSK
Data Rate	1Mbps, 2Mbps, 500kbps, 125kbps
Quantity of Channels	40
Channel Separation	2MHz
Type of Antenna	PCB Antenna
Antenna Gain	0.12dBi

3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC Rules Part 15.247	Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
558074 D01 15.247 Meas Guidance v05r02	Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The FCC Rules
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices



3.4 Test Facility

The test facility has a test site registered with the following organizations:

- **ISED – Registration No.: 21895**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Innovation, Science and Economic Development Canada (ISED). The acceptance letter from the ISED is maintained in our files. Registration ISED number: 21895, March 12, 2019

- **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

- **FCC – Designation No.: CN5034**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No. CN5034.

- **NVLAP – Lab Code: 600191-0**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

3.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

3.6 Abnormalities from Standard Conditions

None.

3.7 Disclaimer

The antenna gain information is provided by the customer. The laboratory is not responsible for the accuracy of the antenna gain information.



4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List

Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2480MHz

Test Conditions

Temperature:	22~25°C
Relative Humidity:	50~55%
Atmospheric pressure:	101.9kPa

WALTEK



5 Equipment Used during Test

5.1 Equipment List

☐ Conducted Emissions 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESR3	102423	2024-01-05	2025-01-04
2.	LISN	R&S	ENV216	101343	2024-01-05	2025-01-04
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	223NN624	2024-01-04	2025-01-03
4.	Switch	CD	RSU-A4 18G	RSUA4008	2024-01-04	2025-01-03
☐ Conducted Emissions 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESCI	101178	2024-01-06	2025-01-05
2.	LISN	R&S	ENV216	101215	2024-01-05	2025-01-04
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	6102701	2024-01-04	2025-01-03
4.	Switch	ESE	RSU/M2	---	2024-01-04	2025-01-03
☐ Conducted Emissions 3#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESR3	102842	2024-01-05	2025-01-04
2.	LISN	R&S	ENV216	101542	2024-01-05	2025-01-04
3.	Cable	YIHENG	LMR195UF-NMNM-2.5	---	2024-01-04	2025-01-03
4.	Manual RF Switch	YIHENG	SW-2	RSU0402	2024-01-04	2025-01-03
☒ Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	3m Semi-anechoic Chamber	CHANGCHUANG	9m×6m×6m	-	2024-01-05	2025-01-04
2.	EMI Test Receiver	RS	ESR7	101566	2024-01-06	2025-01-05
3.	EMC Analyzer	Agilent	N9020A	MY48011796	2024-01-04	2025-01-03
4.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	2024-01-05	2025-01-04
5.	Trilog Broadband Antenna	SCHWARZBECK	VULB 9162	9162-117	2024-01-05	2025-01-04
6.	Coaxial Cable (below 1GHz)	H+S	CBL3-NN-12+3 m	214NN320	2024-01-06	2025-01-05
7.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	01561	2024-01-05	2025-01-04
8.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	01119	2024-01-05	2025-01-04
9.	Coaxial Cable (above 1GHz)	Times-Microwave	CBL5-NN	-	2024-01-04	2025-01-03
10.	Amplifier	Lunar E M	LNA1G18-40	20160501002	2024-01-04	2025-01-03



☒ RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2024-01-04	2025-01-03
2.	Analog Signal Generator	Agilent	N5181A	MY48180720	2024-01-04	2025-01-03
3.	RF Control Unit	CHANGCHUANG	JS0806-2	-	2024-01-04	2025-01-03

☐: Not Used

☒: Used

5.2 Test Software

Description	Manufacturer	Model	Version
EMI Test Software (Conducted Emission 1#)	FARATRONIC	EZ-EMC	EMEC-3A1
EMI Test Software (Conducted Emission 2#)	FARATRONIC	EZ-EMC	CON-03A1
EMI Test Software (Conducted Emission 3#)	FARATRONIC	EZ-EMC	COM 3A1.1
EMI Test Software (Radiated Emission)	FARATRONIC	EZ-EMC	RA-03A1-1
RF Conducted Test Software	TONSCEND	JS1120-2	V2.6

5.3 Special Accessories and Auxiliary Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.
1.	/	/	/	/

5.4 Measurement Uncertainty

Parameter	Uncertainty
RF Output Power	±2.2dB
Occupied Bandwidth	±1.5%
Conducted Emission	±2.6dB
Transmitter Spurious Emission	±3.8dB (for 25MHz-1GHz)
	±5.0dB (for 1GHz-18GHz)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



6 Summary of Test Result

Test Items	FCC Rules	Result
Antenna Requirement	§15.203; §15.247(b)(4)(i)	Compliant
Restricted Band of Operation	§15.205	Compliant
Conducted Emissions	§15.207(a)	N/A
Radiated Spurious Emissions	§15.209(a)	Compliant
Power Spectral Density	§15.247(e)	Compliant
DTS Bandwidth	§15.247(a)(2)	Compliant
RF Output Power	§15.247(b)(1)	Compliant
Band edge (Out of Band Emissions)	§15.247(d)	Compliant

Remark:

Pass Test item meets the requirement

Fail Test item does not meet the requirement

N/A Test case does not apply to the test object

WALTEK




6.1 Antenna Requirement

6.1.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

6.1.2 Evaluation Information

The EUT has a PCB Antenna, the gain is 0.12 dBi, fulfil the requirement of this section.





6.2 Radiated Spurious Emissions

6.2.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

6.2.2 Test Procedure

- 1) The EUT is placed on a turntable, which is 0.8m(Below 1G) 1.5m(above 1G)above ground plane.
- 2) The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3) EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- 4) Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5) And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6) Repeat above procedures until the measurements for all frequencies are complete.
- 7) The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.




6.2.3 Test Setup

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The test setup for emission measurement below 30MHz.




The test setup for emission measurement from 30 MHz to 1 GHz.





The test setup for emission measurement above 1 GHz.



6.2.4 Spectrum Analyzer Setup

9KHz-30MHz

RBW=10kHz

VBW=30kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak

30MHz-1GHz

RBW=120kHz

VBW=300kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak, QP

Above 1GHz

RBW=1MHz

VBW=3MHz(Peak), 10MHz(AV)

Sweep time=Auto

Trace=Max hold

Detector function=peak, AV

6.2.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Corr. Factor}$$

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$




6.2.6 Test Results

Data Rate: 125kbps


Test Frequency: Below 1GHz

Test Channel: Low


Polarization: Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.9502	5.11	12.24	17.35	40.00	-22.65	QP	
2	52.2078	-0.18	13.39	13.21	40.00	-26.79	QP	
3	66.5922	4.54	11.39	15.93	40.00	-24.07	QP	
4	72.0085	5.25	10.39	15.64	40.00	-24.36	QP	
5	79.9963	3.03	10.31	13.34	40.00	-26.66	QP	
6	133.2445	2.01	10.97	12.98	43.50	-30.52	QP	

**Data Rate:** 125kbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Horizontal


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	45.0267	-2.12	15.43	13.31	40.00	-26.69	QP	
2	53.5803	-2.24	14.47	12.23	40.00	-27.77	QP	
3	105.1610	-1.54	14.15	12.61	43.50	-30.89	QP	
4	210.4167	-1.12	13.15	12.03	43.50	-31.47	QP	
5	338.5187	-0.26	17.41	17.15	46.00	-28.85	QP	
6	656.2997	-0.92	22.66	21.74	46.00	-24.26	QP	

**Data Rate:** 125kbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.9628	2.85	12.24	15.09	40.00	-24.91	QP	
2	51.1030	-1.78	13.39	11.61	40.00	-28.39	QP	
3	66.5455	2.70	11.40	14.10	40.00	-25.90	QP	
4	72.0084	6.64	10.39	17.03	40.00	-22.97	QP	
5	79.9963	2.45	10.31	12.76	40.00	-27.24	QP	
6	133.2912	3.04	10.97	14.01	43.50	-29.49	QP	

**Data Rate:** 125kbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Horizontal


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	40.4170	-3.26	14.85	11.59	40.00	-28.41	QP	
2	44.4307	-3.08	15.43	12.35	40.00	-27.65	QP	
3	58.2233	-2.50	13.80	11.30	40.00	-28.70	QP	
4	102.9355	-1.74	14.05	12.31	43.50	-31.19	QP	
5	200.5473	-2.10	12.82	10.72	43.50	-32.78	QP	
6	341.0206	-1.75	17.46	15.71	46.00	-30.29	QP	

**Data Rate:** 125kbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.7115	2.81	12.18	14.99	40.00	-25.01	QP	
2	48.7743	-1.82	13.49	11.67	40.00	-28.33	QP	
3	66.5922	3.70	11.39	15.09	40.00	-24.91	QP	
4	71.9832	5.12	10.39	15.51	40.00	-24.49	QP	
5	120.0237	-0.90	12.46	11.56	43.50	-31.94	QP	
6	239.4829	-1.66	15.35	13.69	46.00	-32.31	QP	

**Data Rate:** 125kbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Horizontal


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.9502	-3.50	15.41	11.91	40.00	-28.09	QP	
2	56.9512	-2.19	13.99	11.80	40.00	-28.20	QP	
3	105.7897	-2.73	14.05	11.32	43.50	-32.18	QP	
4	199.2155	-2.56	12.78	10.22	43.50	-33.28	QP	
5	244.1463	-2.40	14.37	11.97	46.00	-34.03	QP	
6	332.2855	-1.20	17.06	15.86	46.00	-30.14	QP	

**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.7740	1.54	12.19	13.73	40.00	-26.27	QP	
2	51.5529	-1.78	13.39	11.61	40.00	-28.39	QP	
3	66.5922	2.92	11.39	14.31	40.00	-25.69	QP	
4	71.9832	6.64	10.39	17.03	40.00	-22.97	QP	
5	133.2912	1.43	10.97	12.40	43.50	-31.10	QP	
6	264.7456	-2.00	15.78	13.78	46.00	-32.22	QP	


**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Horizontal

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	39.6034	-2.60	14.70	12.10	40.00	-27.90	QP	
2	45.9196	-2.92	15.44	12.52	40.00	-27.48	QP	
3	58.4483	-2.89	13.75	10.86	40.00	-29.14	QP	
4	106.0870	-2.07	14.01	11.94	43.50	-31.56	QP	
5	184.6192	-1.45	11.78	10.33	43.50	-33.17	QP	
6	342.0985	-2.10	17.43	15.33	46.00	-30.67	QP	


**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Vertical

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.8746	5.63	12.22	17.85	40.00	-22.15	QP	
2	47.9939	-2.05	13.56	11.51	40.00	-28.49	QP	
3	66.6156	3.81	11.39	15.20	40.00	-24.80	QP	
4	72.0337	2.79	10.38	13.17	40.00	-26.83	QP	
5	133.2912	2.41	10.97	13.38	43.50	-30.12	QP	
6	263.0799	-1.40	15.77	14.37	46.00	-31.63	QP	

**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Horizontal

**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Vertical

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.6863	0.60	12.18	12.78	40.00	-27.22	QP	
2	51.7884	-2.09	13.39	11.30	40.00	-28.70	QP	
3	66.4290	2.81	11.42	14.23	40.00	-25.77	QP	
4	71.9328	1.97	10.40	12.37	40.00	-27.63	QP	
5	133.3378	-0.25	10.96	10.71	43.50	-32.79	QP	
6	258.5982	-2.10	15.78	13.68	46.00	-32.32	QP	

**Data Rate:** 500kbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Horizontal

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.6126	-3.04	15.36	12.32	40.00	-27.68	QP	
2	51.9157	-2.64	14.70	12.06	40.00	-27.94	QP	
3	93.6042	-2.71	13.17	10.46	43.50	-33.04	QP	
4	104.8297	-3.15	14.17	11.02	43.50	-32.48	QP	
5	242.5252	-2.15	14.33	12.18	46.00	-33.82	QP	
6	434.3695	-1.73	19.09	17.36	46.00	-28.64	QP	




Data Rate: 1Mbps


Test Frequency: Below 1GHz

Test Channel: Low

Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.9376	1.11	12.24	13.35	40.00	-26.65	QP	
2	51.6976	-2.50	13.39	10.89	40.00	-29.11	QP	
3	66.5455	3.69	11.40	15.09	40.00	-24.91	QP	
4	72.0337	2.19	10.38	12.57	40.00	-27.43	QP	
5	126.0187	1.61	11.75	13.36	43.50	-30.14	QP	
6	244.3177	-2.27	15.56	13.29	46.00	-32.71	QP	


**Data Rate:** 1Mbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Horizontal

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.4245	-2.81	13.92	11.11	40.00	-28.89	QP	
2	47.5917	-2.90	15.22	12.32	40.00	-27.68	QP	
3	62.4093	-1.30	12.85	11.55	40.00	-28.45	QP	
4	102.3237	-2.93	14.00	11.07	43.50	-32.43	QP	
5	219.7677	-2.10	13.47	11.37	46.00	-34.63	QP	
6	380.3140	-1.52	17.85	16.33	46.00	-29.67	QP	



Data Rate: 1Mbps
Test Channel: Middle

Test Frequency: Below 1GHz
Polarization: Vertical






Data Rate: 1Mbps


Test Frequency: Below 1GHz

Test Channel: Middle


Polarization: Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	44.2129	-3.24	15.42	12.18	40.00	-27.82	QP	
2	52.2993	-3.22	14.66	11.44	40.00	-28.56	QP	
3	93.0805	-3.16	13.11	9.95	43.50	-33.55	QP	
4	104.4626	-3.12	14.14	11.02	43.50	-32.48	QP	
5	218.7682	-1.93	13.43	11.50	46.00	-34.50	QP	
6	348.6381	-2.08	17.25	15.17	46.00	-30.83	QP	

**Data Rate:** 1Mbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.7364	2.14	12.19	14.33	40.00	-25.67	QP	
2	66.4290	3.85	11.42	15.27	40.00	-24.73	QP	
3	71.9832	2.59	10.39	12.98	40.00	-27.02	QP	
4	95.9637	0.42	11.12	11.54	43.50	-31.96	QP	
5	125.9745	0.69	11.75	12.44	43.50	-31.06	QP	
6	288.9006	-0.41	16.36	15.95	46.00	-30.05	QP	

**Data Rate:** 1Mbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Horizontal


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	46.8138	-1.92	15.33	13.41	40.00	-26.59	QP	
2	49.0660	-2.66	15.06	12.40	40.00	-27.60	QP	
3	66.6389	-1.62	11.72	10.10	40.00	-29.90	QP	
4	106.8709	-3.10	13.89	10.79	43.50	-32.71	QP	
5	174.3017	-1.01	11.05	10.04	43.50	-33.46	QP	
6	373.5731	-2.04	17.68	15.64	46.00	-30.36	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.7238	3.91	12.18	16.09	40.00	-23.91	QP	
2	51.7702	-1.70	13.39	11.69	40.00	-28.31	QP	
3	66.6389	4.36	11.38	15.74	40.00	-24.26	QP	
4	71.9579	2.34	10.40	12.74	40.00	-27.26	QP	
5	95.0929	-1.05	11.12	10.07	43.50	-33.43	QP	
6	126.0187	1.42	11.75	13.17	43.50	-30.33	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** Low**Polarization:** Horizontal


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	42.8997	-3.26	15.24	11.98	40.00	-28.02	QP	
2	48.4844	-3.25	15.12	11.87	40.00	-28.13	QP	
3	91.8806	-2.34	12.98	10.64	43.50	-32.86	QP	
4	104.4626	-3.05	14.14	11.09	43.50	-32.41	QP	
5	220.7718	-2.19	13.51	11.32	46.00	-34.68	QP	
6	343.1800	-2.29	17.39	15.10	46.00	-30.90	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Vertical


No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.5116	2.23	12.14	14.37	40.00	-25.63	QP	
2	48.7914	-1.20	13.49	12.29	40.00	-27.71	QP	
3	66.5221	3.75	11.41	15.16	40.00	-24.84	QP	
4	93.9989	-1.00	11.11	10.11	43.50	-33.39	QP	
5	126.0187	0.25	11.75	12.00	43.50	-31.50	QP	
6	247.0746	-2.23	15.68	13.45	46.00	-32.55	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** Middle**Polarization:** Horizontal

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	47.4917	-2.72	15.24	12.52	40.00	-27.48	QP	
2	53.3179	-2.63	14.51	11.88	40.00	-28.12	QP	
3	85.2980	-2.26	11.90	9.64	40.00	-30.36	QP	
4	102.5391	-3.18	14.01	10.83	43.50	-32.67	QP	
5	203.3087	-2.47	12.94	10.47	43.50	-33.03	QP	
6	316.7000	-3.01	16.26	13.25	46.00	-32.75	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Vertical

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	35.9376	4.18	12.24	16.42	40.00	-23.58	QP	
2	66.5922	4.27	11.39	15.66	40.00	-24.34	QP	
3	95.9301	-1.09	11.12	10.03	43.50	-33.47	QP	
4	125.9745	0.37	11.75	12.12	43.50	-31.38	QP	
5	214.1384	-1.40	14.53	13.13	43.50	-30.37	QP	
6	307.6154	-1.70	16.51	14.81	46.00	-31.19	QP	

**Data Rate:** 2Mbps**Test Frequency:** Below 1GHz**Test Channel:** High**Polarization:** Horizontal

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.7503	-3.37	15.38	12.01	40.00	-27.99	QP	
2	48.3316	-2.68	15.13	12.45	40.00	-27.55	QP	
3	99.2145	-2.43	13.76	11.33	43.50	-32.17	QP	
4	113.7142	-1.80	12.84	11.04	43.50	-32.46	QP	
5	228.0901	-1.13	13.74	12.61	46.00	-33.39	QP	
6	328.3473	-2.20	16.86	14.66	46.00	-31.34	QP	



Test Frequency: Above 1GHz

Data Rate 125kbps							
Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4804	35.86	PK	H	-6.71	29.15	74	-44.85
4804	26.96	AV	H	-6.71	20.25	54	-33.75
7206	40.85	PK	H	-1.46	39.39	74	-34.61
7206	31.18	AV	H	-1.46	29.72	54	-24.28
4804	36.11	PK	V	-6.71	29.4	74	-44.6
4804	27.69	AV	V	-6.71	20.98	54	-33.02
7206	41.15	PK	V	-1.46	39.69	74	-34.31
7206	30.57	AV	V	-1.46	29.11	54	-24.89
Middle Channel							
4880	35.24	PK	H	-6.5	28.74	74	-45.26
4880	26.21	AV	H	-6.5	19.71	54	-34.29
7320	40.09	PK	H	-1.12	38.97	74	-35.03
7320	30.86	AV	H	-1.12	29.74	54	-24.26
4880	36.69	PK	V	-6.5	30.19	74	-43.81
4880	26.74	AV	V	-6.5	20.24	54	-33.76
7320	41.26	PK	V	-1.12	40.14	74	-33.86
7320	31.56	AV	V	-1.12	30.44	54	-23.56
High Channel							
4960	35.91	PK	H	-6.29	29.62	74	-44.38
4960	26.53	AV	H	-6.29	20.24	54	-33.76
7440	40.58	PK	H	-0.8	39.78	74	-34.22
7440	30.19	AV	H	-0.8	29.39	54	-24.61
4960	36.42	PK	V	-6.29	30.13	74	-43.87
4960	27.22	AV	V	-6.29	20.93	54	-33.07
7440	41.37	PK	V	-0.8	40.57	74	-33.43
7440	31.55	AV	V	-0.8	30.75	54	-23.25



Data Rate 500kbps							
Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4804	36.94	PK	H	-6.71	30.23	74	-43.77
4804	26.91	AV	H	-6.71	20.2	54	-33.8
7206	40.38	PK	H	-1.46	38.92	74	-35.08
7206	30.58	AV	H	-1.46	29.12	54	-24.88
4804	36.85	PK	V	-6.71	30.14	74	-43.86
4804	26.42	AV	V	-6.71	19.71	54	-34.29
7206	41.32	PK	V	-1.46	39.86	74	-34.14
7206	30.66	AV	V	-1.46	29.2	54	-24.8
Middle Channel							
4880	36.2	PK	H	-6.5	29.7	74	-44.3
4880	26.33	AV	H	-6.5	19.83	54	-34.17
7320	40.93	PK	H	-1.12	39.81	74	-34.19
7320	31.58	AV	H	-1.12	30.46	54	-23.54
4880	36.31	PK	V	-6.5	29.81	74	-44.19
4880	26.02	AV	V	-6.5	19.52	54	-34.48
7320	40.73	PK	V	-1.12	39.61	74	-34.39
7320	31.55	AV	V	-1.12	30.43	54	-23.57
High Channel							
4960	35.25	PK	H	-6.29	28.96	74	-45.04
4960	26.88	AV	H	-6.29	20.59	54	-33.41
7440	41.91	PK	H	-0.8	41.11	74	-32.89
7440	30.15	AV	H	-0.8	29.35	54	-24.65
4960	36.77	PK	V	-6.29	30.48	74	-43.52
4960	28.17	AV	V	-6.29	21.88	54	-32.12
7440	41.06	PK	V	-0.8	40.26	74	-33.74
7440	30.12	AV	V	-0.8	29.32	54	-24.68



Data Rate 1Mbps							
Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4804	35.08	PK	H	-6.71	28.37	74	-45.63
4804	25.26	AV	H	-6.71	18.55	54	-35.45
7206	40.81	PK	H	-1.46	39.35	74	-34.65
7206	32.26	AV	H	-1.46	30.8	54	-23.2
4804	36.96	PK	V	-6.71	30.25	74	-43.75
4804	26.34	AV	V	-6.71	19.63	54	-34.37
7206	41.23	PK	V	-1.46	39.77	74	-34.23
7206	31.24	AV	V	-1.46	29.78	54	-24.22
Middle Channel							
4880	35.27	PK	H	-6.5	28.77	74	-45.23
4880	25.46	AV	H	-6.5	18.96	54	-35.04
7320	40.79	PK	H	-1.12	39.67	74	-34.33
7320	32.21	AV	H	-1.12	31.09	54	-22.91
4880	36.73	PK	V	-6.5	30.23	74	-43.77
4880	27.82	AV	V	-6.5	21.32	54	-32.68
7320	41.23	PK	V	-1.12	40.11	74	-33.89
7320	30.49	AV	V	-1.12	29.37	54	-24.63
High Channel							
4960	36.14	PK	H	-6.29	29.85	74	-44.15
4960	26.27	AV	H	-6.29	19.98	54	-34.02
7440	41.33	PK	H	-0.8	40.53	74	-33.47
7440	30.34	AV	H	-0.8	29.54	54	-24.46
4960	35.63	PK	V	-6.29	29.34	74	-44.66
4960	26.84	AV	V	-6.29	20.55	54	-33.45
7440	41.59	PK	V	-0.8	40.79	74	-33.21
7440	30.01	AV	V	-0.8	29.21	54	-24.79



Data Rate 2Mbps							
Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4804	36.35	PK	H	-6.71	29.64	74	-44.36
4804	26.84	AV	H	-6.71	20.13	54	-33.87
7206	41.98	PK	H	-1.46	40.52	74	-33.48
7206	31.09	AV	H	-1.46	29.63	54	-24.37
4804	35.89	PK	V	-6.71	29.18	74	-44.82
4804	26.11	AV	V	-6.71	19.4	54	-34.6
7206	41.78	PK	V	-1.46	40.32	74	-33.68
7206	31.41	AV	V	-1.46	29.95	54	-24.05
Middle Channel							
4880	36.78	PK	H	-6.5	30.28	74	-43.72
4880	25.06	AV	H	-6.5	18.56	54	-35.44
7320	40.14	PK	H	-1.12	39.02	74	-34.98
7320	30.91	AV	H	-1.12	29.79	54	-24.21
4880	37.53	PK	V	-6.5	31.03	74	-42.97
4880	26.55	AV	V	-6.5	20.05	54	-33.95
7320	40.51	PK	V	-1.12	39.39	74	-34.61
7320	31.16	AV	V	-1.12	30.04	54	-23.96
High Channel							
4960	36.65	PK	H	-6.29	30.36	74	-43.64
4960	26.04	AV	H	-6.29	19.75	54	-34.25
7440	41.76	PK	H	-0.8	40.96	74	-33.04
7440	30.62	AV	H	-0.8	29.82	54	-24.18
4960	37.52	PK	V	-6.29	31.23	74	-42.77
4960	27.85	AV	V	-6.29	21.56	54	-32.44
7440	42.42	PK	V	-0.8	41.62	74	-32.38
7440	31.72	AV	V	-0.8	30.92	54	-23.08

Note:

1. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
2. Average measurement was not performed if peak level is lower than average limit 54 dBuV/m) for above 1GHz.



6.3 Power Spectral Density

6.3.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


6.3.3 Test Result

Data Rate	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
125kbps	Low	0.721	8
	Middle	1.150	8
	High	1.786	8
500kbps	Low	0.591	8
	Middle	1.074	8
	High	1.643	8
1Mbps	Low	-6.180	8
	Middle	-5.755	8
	High	-5.126	8
2Mbps	Low	-7.366	8
	Middle	-6.765	8
	High	-6.202	8




Test Plot:


125kbps_Power Spectral Density_Low Channel






125kbps_Power Spectral Density_Middle Channel




125kbps_Power Spectral Density_High Channel




**500kbps_Power Spectral Density_Low Channel****500kbps_Power Spectral Density_Middle Channel****500kbps_Power Spectral Density_High Channel**




1Mbps_Power Spectral Density_Low Channel



1Mbps_Power Spectral Density_Middle Channel




1Mbps_Power Spectral Density_High Channel







2Mbps_Power Spectral Density_Low Channel



2Mbps_Power Spectral Density_Middle Channel



2Mbps_Power Spectral Density_High Channel





6.4 DTS Bandwidth

6.4.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4.3 Test Result

Data Rate	Test Channel	6dB Bandwidth MHz	Limit kHz
125kbps	Low	0.728	≥ 500
	Middle	0.664	≥ 500
	High	0.728	≥ 500
500kbps	Low	0.652	≥ 500
	Middle	0.744	≥ 500
	High	0.664	≥ 500
1Mbps	Low	0.656	≥ 500
	Middle	0.712	≥ 500
	High	0.692	≥ 500
2Mbps	Low	0.736	≥ 500
	Middle	0.792	≥ 500
	High	0.760	≥ 500



Test Plot:

125kbps_6dB Bandwidth_Low Channel



125kbps_6dB Bandwidth_Middle Channel



125kbps_6dB Bandwidth_High Channel







500kbps_6dB Bandwidth_Low Channel



500kbps_6dB Bandwidth_Middle Channel



500kbps_6dB Bandwidth_High Channel







1Mbps_6dB Bandwidth_Low Channel



1Mbps_6dB Bandwidth_Middle Channel




1Mbps_6dB Bandwidth_High Channel






2Mbps_6dB Bandwidth_Low Channel



2Mbps_6dB Bandwidth_Middle Channel



2Mbps_6dB Bandwidth_High Channel





6.5 RF Output Power

6.5.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.5.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.


6.5.3 Test Result

Data Rate	Test Channel	Reading (dBm)	Output Power (mW)	Limit (mW)
125kbps	Low	6.826	4.815	1000
	Middle	7.264	5.326	1000
	High	7.842	6.084	1000
500kbps	Low	6.819	4.807	1000
	Middle	7.278	5.343	1000
	High	7.830	6.067	1000
1Mbps	Low	6.845	4.836	1000
	Middle	7.267	5.330	1000
	High	7.828	6.065	1000
2Mbps	Low	6.820	4.808	1000
	Middle	7.271	5.335	1000
	High	7.837	6.077	1000




Test Plot:


125kbps_RF Output Power_Low Channel



125kbps_RF Output Power_Middle Channel




125kbps_RF Output Power_High Channel







500kbps_RF Output Power_Low Channel



500kbps_RF Output Power_Middle Channel




500kbps_RF Output Power_High Channel







1Mbps_RF Output Power_Low Channel



1Mbps_RF Output Power_Middle Channel




1Mbps_RF Output Power_High Channel







2Mbps_RF Output Power_Low Channel



2Mbps_RF Output Power_Middle Channel



2Mbps_RF Output Power_High Channel





6.6 Out of Band Emissions

6.6.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

6.6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge,

as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz

for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emissions must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205.



Note that the method of measurement KDB publication number: 913591 may be used for the radiated band edge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1.



6.6.3 Test Result

Radiated Test


Test Channel Low Channel@125kbps Polarization Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	10.62	31.96	42.58	74.00	-31.42	peak	
2	2310.000	-11.75	31.96	20.21	54.00	-33.79	AVG	
3	2390.000	11.62	32.32	43.94	74.00	-30.06	peak	
4	2390.000	-9.48	32.32	22.84	54.00	-31.16	AVG	
5	2400.000	22.84	32.36	55.20	74.00	-18.80	peak	
6	2400.000	-6.58	32.36	25.78	54.00	-28.22	AVG	
7	2402.000	52.79	32.37	85.16	74.00	11.16	peak	




Test Channel High Channel@125kbps **Polarization** Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2480.000	54.19	32.72	86.91	74.00	12.91	peak	
2	2483.500	10.54	32.73	43.27	74.00	-30.73	peak	
3	2483.500	-10.93	32.73	21.80	54.00	-32.20	AVG	
4	2500.000	10.67	32.80	43.47	74.00	-30.53	peak	
5	2500.000	-11.35	32.80	21.45	54.00	-32.55	AVG	




Test Channel Low Channel@500kbps **Polarization** Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	10.63	31.96	42.59	74.00	-31.41	peak	
2	2310.000	-11.78	31.96	20.18	54.00	-33.82	AVG	
3	2390.000	11.99	32.32	44.31	74.00	-29.69	peak	
4	2390.000	-11.49	32.32	20.83	54.00	-33.17	AVG	
5	2400.000	20.47	32.36	52.83	74.00	-21.17	peak	
6	2400.000	-8.67	32.36	23.69	54.00	-30.31	AVG	
7	2402.000	50.65	32.37	83.02	74.00	9.02	peak	



Test Channel High Channel@500kbps Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2480.000	54.11	32.72	86.83	74.00	12.83	peak	
2	2483.500	11.94	32.73	44.67	74.00	-29.33	peak	
3	2483.500	-11.08	32.73	21.65	54.00	-32.35	AVG	
4	2500.000	10.63	32.80	43.43	74.00	-30.57	peak	
5	2500.000	-11.35	32.80	21.45	54.00	-32.55	AVG	

**Test Channel** Low Channel@1Mbps **Polarization** Horizontal (worst case)

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	10.27	31.96	42.23	74.00	-31.77	peak	
2	2310.000	-11.66	31.96	20.30	54.00	-33.70	AVG	
3	2390.000	10.31	32.32	42.63	74.00	-31.37	peak	
4	2390.000	-11.37	32.32	20.95	54.00	-33.05	AVG	
5	2400.000	23.33	32.36	55.69	74.00	-18.31	peak	
6	2400.000	-8.39	32.36	23.97	54.00	-30.03	AVG	
7	2402.000	54.80	32.37	87.17	74.00	13.17	peak	




Test Channel High Channel@1Mbps Polarization Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2480.000	50.06	32.72	82.78	74.00	8.78	peak	
2	2483.500	11.72	32.73	44.45	74.00	-29.55	peak	
3	2483.500	-11.16	32.73	21.57	54.00	-32.43	AVG	
4	2500.000	11.78	32.80	44.58	74.00	-29.42	peak	
5	2500.000	-11.14	32.80	21.66	54.00	-32.34	AVG	




Test Channel Low Channel@2Mbps Polarization Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	11.21	31.96	43.17	74.00	-30.83	peak	
2	2310.000	-11.72	31.96	20.24	54.00	-33.76	AVG	
3	2390.000	11.35	32.32	43.67	74.00	-30.33	peak	
4	2390.000	-11.44	32.32	20.88	54.00	-33.12	AVG	
5	2400.000	22.39	32.36	54.75	74.00	-19.25	peak	
6	2400.000	-7.40	32.36	24.96	54.00	-29.04	AVG	
7	2402.000	45.44	32.37	77.81	74.00	3.81	peak	



Test Channel High Channel@2Mbps Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2480.000	48.99	32.72	81.71	74.00	7.71	peak	
2	2483.500	11.33	32.73	44.06	74.00	-29.94	peak	
3	2483.500	-11.34	32.73	21.39	54.00	-32.61	AVG	
4	2500.000	11.00	32.80	43.80	74.00	-30.20	peak	
5	2500.000	-11.36	32.80	21.44	54.00	-32.56	AVG	




Conducted Test

Low Channel@125kbps




High Channel@125kbps






Low Channel@500kbps




High Channel@500kbps






Low Channel@1Mbps




High Channel@1Mbps






Low Channel@2Mbps



High Channel@2Mbps





7 Photographs Test Setup

7.1 Photographs - Radiated Emission Test Setup

30MHz-1GHz



Above 1GHz





8 Photographs – EUT Constructional Details

Please refer to “ANNEX”.

=====End of Report=====

WALTEK