

# 1 SAR Evaluation

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

#### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

For BT:

#### Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	3.22
Middle	3.33
Highest	3.04
$\pi/4$ DQPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	1.58
Middle	1.77
Highest	1.55
8DPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	1.73
Middle	1.88
Highest	1.67

The Max Conducted Peak Output Power is 3.33dBm in middle channel(2.441GHz);

The best case gain of the antenna is 1.2dBi.

EIRP= 3.33dBm + 1.2dBi = 4.53dBm

4.53dBm logarithmic terms convert to numeric result is nearly 2.838mW

According to the formula. calculate the EIRP test result:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

General RF Exposure =  $(2.838\text{mW} / 5 \text{ mm}) \times \sqrt{2.441\text{GHz}} = 0.887$  ①

SAR requirement:

S= 3.0 ② ;

① < ②.

So the SAR report is not required.

Remark: The Max Conducted Peak Output Power data refer to report CQASZ170201315E-01.