

FCC Part 15C Test Report

FCC ID: 2ALIU-DR1Y1

Product Name:	томо
Trademark:	N/A
Model Name :	DR1YGEN01
Prepared For :	Beijing Today Innovation Technology Co., Ltd.
Address :	No.118, Floor 1, Building 1, No.7, North Ritan Road, Chaoyang District, Beijing, PRC
Prepared By:	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	Jun. 12 – Jun. 19, 2017
Date of Report :	Jun. 19, 2017
Report No.:	BCTC-FY170805941E



CERTIFICATION

Applicant's name...... Beijing Today Innovation Technology Co., Ltd.

District, Beijing, PRC

Manufacture's Name...... SHEN ZHEN RYDER ELECTRONICS CO.,LTD.

Address Building 3rd, Huaming Industrial Park, Huaming Road, Dalang,

Longhua, Shenzhen, Guangdong, China

Product description

Product name: TOMO

Trademark: N/A

Model Name: DR1YGEN01

Test Standards: FCC Part15.249

ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Test Result..... Pass

Prepared by(Engineer): Eric Yang

Reviewer(Supervisor): Jade Yang

Approved(Manager): Carson Zhang





Shenzhen	BCTC	Technology	C_{Ω}	I td
OHIGHZHIGH	0010	1 CCI II ICIOQ y	OU	Lu.

Report No.: BCTC-FY170805941E

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	7
	_
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3 . EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 3.1.2 TEST PROCEDURE	10 11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	11
3.1.5 EUT OPERATING CONDITIONS	11
3.1.6 TEST RESULTS	12
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS 3.2.2 TEST PROCEDURE	14 15
3.2.3 DEVIATION FROM TEST STANDARD	15
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS	18
4 . BANDWIDTH TEST	22
4.1 APPLIED PROCEDURES / LIMIT	22
4.1.1 TEST PROCEDURE 4.1.2 DEVIATION FROM STANDARD	22 22
4.1.3 TEST SETUP	22
4.1.4 EUT OPERATION CONDITIONS	22
4.1.5 TEST RESULTS	23
5 . BAND EDGE EMISSION	25
5.1 DEVIATION FROM STANDARD	25
5.2 EUT OPERATION CONDITIONS	25 26
5.3 TEST RESULTS	∠ 0



Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-FY170805941E

Table of Contents	Page
6 . ANTENNA REQUIREMENT	29
6.1 STANDARD REQUIREMENT	29
6.2 EUT ANTENNA	29
7 . EUT TEST PHOTO	30
8 PHOTOS OF THE FUT	32



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C				
Standard Section	Test Item	Judgment	Remark	
15.207(a)	Conducted Emission	PASS		
15.209(a)&&15.249(a) &15.249(c)&15.205(a)	Fundamental &Radiated Spurious Emission Measurement	PASS		
15.215(c)	Bandwidth	PASS		
15.249(d)	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

Shenzhen BCTC Technology Co., Ltd.

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add.:No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registration No.:187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately $\mathbf{95}$ % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	томо		
Trademark	N/A		
Model Name	DR1YGEN01		
Serial Model	N/A		
Model Difference	N/A		
	Operation Frequency:	2402~2480 MHz	
	Modulation Type:	GFSK	
	Bit Rate of Transmitter	2M	
	Number Of Channel	40 CH	
Product Description	Antenna Designation:	Please see Note 3.	
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.		
Power Source	DC 9V		
Connecting I/O Port(s)	Please refer to the User's Manual		
hardware version			
Software version			

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	11	2422	21	2442
02	2404	12	2424	22	2444
03	2406	13	2426	23	2446
~	~	~	~	~	~
09	2418	19	2438	39	2478
10	2420	20	2440	40	2480

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	0	



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted & Radiated Emission			
Final Test Mode	Description		
Mode 1	CH01		
Mode 2	CH20		
Mode 3	CH40		
Mode 4	Link Mode		

Shenzhen BCTC Technology Co., Ltd.

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test


2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS


Frequency	2402 MHz	2440 MHz	2480 MHz
Channel	Low	Middle	High

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Spurious Emission Test



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	ТОМО	N/A	DR1YGEN01	N/A	EUT
E-2	Personal computer	Lenovo	S2	N/A	Lab Provide
E-3	Adapter	Lenovo	SA10E75793	N/A	2001101100

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	USB cable unshielded
C2	NO	NO	1.5M	DC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	ation Test equip Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45108040	2016.08.27	2017.08.26
2	Test Receiver (9kHz-7GHz)		ESPI	101318	2016.08.27	2017.08.26
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB 9168	VULB91 68-438	2016.08.27	2017.08.26
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1201	2016.09.03	2017.09.03
5	Horn Antenna (14GHz-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	2016.09.03	2017.09.03
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2016.08.27	2017.08.26
7	Amplifier (1GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2016.08.27	2017.08.26
8	Amplifier (18GHz-40GHz)	SCHWARZBECK	BBV 9721	9721-205	2016.08.27	2017.08.26
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	00014	2016.09.03	2017.09.03
10	RF cables1 (9kHz-1GHz)	R&S	R203	R20X	2016.08.27	2017.08.26
11	RF cables2 (1GHz-40GHz)	R&S	R204	R21X	2016.08.27	2017.08.26
12	Antenna connector	Florida RF Labs	N/A	RF 01#	2016.08.27	2017.08.26
13	Power Metter	ANRITSU	ML2487A	6K00001568	2016.08.27	2017.08.26
14	Power Sensor (AV)	ANRITSU	ML2491A	030989	2016.08.27	2017.08.26
15	Signal Analyzer 9kHz-26.5GHz	Agilent	N9010A	MY48030494	2016.08.27	2017.08.26
16	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	2016.08.27	2017.08.26
17	D.C. Power Supply	LongWei	PS-305D	010964729	2016.08.27	2017.08.26

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-1011 65-ha	2016.08.27	2017.08.26
2	LISN	SCHWARZBECK	NSLK8127	8127739	2016.08.27	2017.08.26
3	LISN	R&S	NSLK8126	8126487	2016.08.27	2017.08.26
4	RF cables	R&S	R204	R20X	2016.08.27	2017.08.26
5	Attenuator	R&S	ESH3-Z2	143206	2016.08.27	2017.08.26

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (d	Standard	
FREQUENCT (IVITIZ)	Quas -peak	Average	Stariuaru
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		

3.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

Shenzhen BCTC Technology Co., Ltd.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



3.1.6 TEST RESULTS

Temperature :	25℃	Relative Humidity:	54%	
Pressure :	1010hPa	Phase :	L	
Test Voltage :	AC120V/60Hz	Test Mode:	Mode 4	




Remark:

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.

No. M	k. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over			
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1	0.1635	41.91	9.66	51.57	65.28	-13.71	QP		
2	0.1635	23.75	9.66	33.41	55.28	-21.87	AVG		
3	0.4110	25.53	9.67	35.20	57.63	-22.43	QP		
4	0.4110	12.71	9.67	22.38	47.63	-25.25	AVG		
5	0.5235	25.16	9.68	34.84	56.00	-21.16	QP		
6	0.5235	14.80	9.68	24.48	46.00	-21.52	AVG		
7	1.7115	24.28	9.70	33.98	56.00	-22.02	QP		
8	1.7115	12.30	9.70	22.00	46.00	-24.00	AVG		
9	8.3580	21.21	9.81	31.02	60.00	-28.98	QP		
10	8.3580	14.17	9.81	23.98	50.00	-26.02	AVG		
11 *	17.0430	46.27	9.89	56.16	60.00	-3.84	QP		
12	17.0430	34.90	9.89	44.79	50.00	-5.21	AVG		



Temperature :	25 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC120V/60Hz	Test Mode:	Mode 4



Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over			
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment	
1		0.1590	39.59	9.67	49.26	65.52	-16.26	QP		
2		0.1590	13.85	9.67	23.52	55.52	-32.00	AVG		
3		0.1835	39.53	9.66	49.19	64.33	-15.14	QP		
4		0.1835	22.15	9.66	31.81	54.33	-22.52	AVG		
5		0.2310	33.54	9.65	43.19	62.41	-19.22	QP		
6		0.2310	16.58	9.65	26.23	52.41	-26.18	AVG		
7		0.4785	24.55	9.68	34.23	56.37	-22.14	QP		
8		0.4785	12.49	9.68	22.17	46.37	-24.20	AVG		
9		14.4780	34.77	9.86	44.63	60.00	-15.37	QP		
10		14.4780	26.08	9.86	35.94	50.00	-14.06	AVG		
11	*	17.2860	48.38	9.88	58.26	60.00	-1.74	QP		
12		17.2860	36.41	9.88	46.29	50.00	-3.71	AVG		

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

tollowed.							
Frequencies	Field Strength	Measurement Distance					
(MHz)	(micorvolts/meter)	(meters)					
0.009~0.490	2400/F(KHz)	300					
0.490~1.705	24000/F(KHz)	30					
1.705~30.0	30	30					
30~88	100	3					
88~216	150	3					
216~960	200	3					
Above 960	500	3					

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

EDEOLIENCY (MH-7)	Limit (dBuV/m) (at 3M)		
FREQUENCY (MHz)	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook 1 MHz / 10Hz for Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
 - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

Report No.: BCTC-FY170805941E


Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-FY170805941E


3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS

Radiated Spurious Emission (Below 30MHz)

Temperature:	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Polarization :	
Test Voltage :	DC 9V		
Test Mode :	Link Mode		

Shenzhen BCTC Technology Co., Ltd.

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Radiated Spurious Emission (Between 30MHz – 1GHz)

Temperature:	26 ℃	Relative Humidity:	54%
Pressure :	1010 hPa	Polarization:	Horizontal
Test Voltage :	DC 9V		
Test Mode : (Worst)	Link Mode		




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∀	dB	dBuV/m	dB/m	dB	Detector
1		95.7622	27.53	-16.34	11.19	43.50	-32.31	QP
2		159.7844	38.19	-19.08	19.11	43.50	-24.39	QP
3	*	239.9874	49.28	-15.52	33.76	46.00	-12.24	QP
4		304.6099	44.37	-13.49	30.88	46.00	-15.12	QP
5		432.5457	43.50	-10.84	32.66	46.00	-13.34	QP
6		576.6443	31.33	-7.05	24.28	46.00	-21.72	QP

Temperature :	26 ℃	Relative Humidity:	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 9V		
Test Mode : (Worst)	Link Mode		



Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∀	dB	dBuV/m	dB/m	dB	Detector
1		34.1561	30.65	-16.55	14.10	40.00	-25.90	QP
2		96.0986	33.24	-16.28	16.96	43.50	-26.54	QP
3		159.7844	44.98	-19.08	25.90	43.50	-17.60	QP
4	*	239.9874	52.39	-15.52	36.87	46.00	-9.13	QP
5		432.5457	31.57	-10.84	20.73	46.00	-25.27	QP
6	;	574.6258	38.07	-7.10	30.97	46.00	-15.03	QP



Radiated Spurious Emission (1GHz to 10th harmonics)

GFSK

Polar	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector
(H/V)	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	Type
	, ,	(11 11)	, ,		nnel 2402M		(20 20 2)	()	
V	2402.00	116.47	38.06	7.42	20.15	105.98	114.00	-8.02	PK
V	2402.00	92.25	38.06	7.42	20.15	81.76	94.00	-12.24	AV
V	4804.00	59.23	38.53	7.78	23.25	51.73	74.00	-22.27	PK
V	4804.00	46.24	38.53	7.78	23.25	38.74	54.00	-15.26	AV
V	16132.00	44.35	38.75	10.36	26.57	42.53	74.00	-31.47	PK
Н	2402.00	115.45	38.06	7.42	20.15	104.96	114.00	-9.04	PK
Н	2402.00	94.19	38.06	7.42	20.15	83.70	94.00	-10.30	AV
Н	4804.00	58.15	38.53	7.78	23.25	50.65	74.00	-23.35	PK
Н	4804.00	46.02	38.53	7.78	23.25	38.52	54.00	-15.48	AV
Н	16132.00	45.53	38.75	10.36	26.57	43.71	74.00	-30.29	PK
			ı	Middle Ch	annel 2440l	ИHz			
V	2440.00	115.21	38.11	7.44	20.36	104.90	114.00	-9.10	PK
V	2440.00	92.23	38.11	7.44	20.36	81.92	94.00	-12.08	AV
V	4880.00	57.14	38.65	7.80	23.61	49.90	74.00	-24.10	PK
V	4880.00	47.72	38.65	7.80	23.61	40.48	54.00	-13.52	AV
V	16132.00	46.53	38.75	10.36	26.57	44.71	74.00	-29.29	PK
Н	2440.00	114.67	38.11	7.44	20.36	104.36	114.00	-9.64	PK
Н	2440.00	94.21	38.11	7.44	20.36	83.90	94.00	-10.10	AV
Н	4880.00	59.53	38.65	7.80	23.61	52.29	74.00	-21.71	PK
Н	4880.00	45.45	38.65	7.80	23.61	38.21	54.00	-15.79	AV
Н	16132.00	44.65	38.75	10.36	26.57	42.83	74.00	-31.17	PK
				High Cha	nnel 2480M	Hz			
V	2480.00	116.13	38.17	7.47	20.51	105.94	114.00	-8.06	PK
V	2480.00	91.65	38.17	7.47	20.51	81.46	94.00	-12.54	AV
V	4960.00	59.27	38.69	7.83	23.83	52.24	74.00	-21.76	PK
V	4960.00	45.32	38.69	7.83	23.83	38.29	54.00	-15.71	AV
V	16132.00	46.86	38.75	10.36	26.57	45.04	74.00	-28.96	PK
Н	2480.00	115.24	38.17	7.47	20.51	105.05	114.00	-8.95	PK
Н	2480.00	93.57	38.17	7.47	20.51	83.38	94.00	-10.62	AV
Н	4960.00	56.36	38.69	7.83	23.83	49.33	74.00	-24.67	PK
Н	4960.00	47.57	38.69	7.83	23.83	40.54	54.00	-13.46	AV
Н	16132.00	46.28	38.75	10.36	26.57	44.46	74.00	-29.54	PK

Remark:

- 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss Pre-amplifier, Margin= Emission Level Limit
- 2. If peak below the average limit, the average emission was no test.
- 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.249	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS	

Shenzhen BCTC Technology Co., Ltd.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100KHz
VB	≥RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW≥ RBW, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS


Temperature:	25 ℃	Relative Humidity:	54%
Pressure:	1012 hPa	Test Voltage :	DC 9V
Test Mode :	CH01 / CH20 /CH40		

	Frequency	20dB Bandwidth (MHz)	Result
	2402 MHz	1.215	PASS
GFSK	2440 MHz	1.224	PASS
	2480 MHz	1.218	PASS

GFSK









5. BAND EDGE EMISSION

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- f. For the radiated emission test above 1GHz:
 - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
 - The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- g Spectrum Setting : RBW= 1MHz, VBW=3MHz, Sweep time = Auto for peak RBW= 1MHz, VBW=10Hz, Sweep time = Auto for average

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.1 DEVIATION FROM STANDARD

No deviation.

5.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.3 TEST RESULTS

Temperature:	25 ℃	Relative Humidity:	54%
Pressure :	1012 hPa	Test Voltage :	DC 9V
Test Mode :	CH01/CH40		


Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
		(dbdv) (db)	(GD)	(dB)	(45/11)	PK	PK	AV	
	Low Channel 2402MHz								
Н	2390.00	59.35	38.06	7.42	20.15	48.86	74.00	54.00	PASS
Н	2400.00	60.53	38.06	7.42	20.15	50.04	74.00	54.00	PASS
V	2390.00	57.67	38.06	7.42	20.15	47.18	74.00	54.00	PASS
V	2400.00	63.52	38.06	7.42	20.15	53.03	74.00	54.00	PASS
	High Channel 2480MHz								
Н	2483.50	56.39	38.17	7.45	20.54	46.21	74.00	54.00	PASS
Н	2450.00	57.84	38.17	7.45	20.54	47.66	74.00	54.00	PASS
V	2483.50	59.76	38.20	7.45	20.54	49.55	74.00	54.00	PASS
V	2450.00	57.91	38.20	7.45	20.54	47.70	74.00	54.00	PASS


Remark:

^{1.} Emission Level = Meter Reading + Antenna Factor + Cable Loss - Pre-amplifier, Margin= Emission Level - Limit


^{2.} If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.









2402MHz Vertical











6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


6.2 EUT ANTENNA

The EUT antenna is Integral PCB antenna. It complies with the standard requirement.

Report No.: BCTC-FY170805941E


Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-FY170805941E


7. EUT TEST PHOTO















8. PHOTOS OF THE EUT





*** ** END OF REPORT ****