



Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China
Tel: +86)-0755-23284990 Email: att@att-lab.com Http: // www.att-lab.cn

FCC RADIO TEST REPORT

FCC ID: 2ALLU-WK40

Product : Wi-Fi Smart Socket

Trade Name : WOOSONE

Model Name : WK40

Serial Model : WK41, WK42, WK43, WK44, WK45, WK46, C108, C118, C128

Prepared for

ShenZhen Woosone Technology Co., Ltd.

Rm 1013, Dynamic World Building, Zhenhua Rd, Futian District,
Shenzhen, China

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,
Shenzhen, China

Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990
Http: www.att-lab.cn



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 2 of 81 -

TEST RESULT CERTIFICATION

Manufacturer's Name... ShenZhen Woosone Technology Co., Ltd.

Address Rm 1013, Dynamic World Building, Zhenhua Rd, Futian District, Shenzhen, China

Product description

Product name Wi-Fi Smart Socket

Model and/or type reference WK40

Additional Model WK41, WK42, WK43, WK44, WK45, WK46, C108, C118, C128

Standards FCC Part15.247

Test procedure ANSI C63.10-2013

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Mar. 12 2017 ~Jul. 12 2017

Date of Issue Jul. 12 2017

Test Result **Pass**

Testing Engineer : Jack Yu

(Jack Yu)

Technical Manager : Jerry You

(Jerry You)

Authorized Signatory : Can Liu

(Can Liu)



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 3 of 81 -

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
3.1.2 TEST PROCEDURE	16
3.1.3 DEVIATION FROM TEST STANDARD	16
3.1.4 TEST SETUP	16
3.1.5 EUT OPERATING CONDITIONS	16
3.1.6 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	23
3.2.4 TEST SETUP	24
3.2.5 EUT OPERATING CONDITIONS	25
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	26
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	27
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	29
4 . POWER SPECTRAL DENSITY TEST	53
4.1 APPLIED PROCEDURES / LIMIT	53
4.1.1 TEST PROCEDURE	53
4.1.2 DEVIATION FROM STANDARD	53
4.1.3 TEST SETUP	53



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 4 of 81 -

Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS	53
4.1.5 TEST RESULTS	54
5 . BANDWIDTH TEST	60
5.1 APPLIED PROCEDURES / LIMIT	60
5.1.1 TEST PROCEDURE	60
5.1.2 EUT OPERATION CONDITIONS	60
5.1.3 TEST RESULTS	61
6 . PEAK OUTPUT POWER TEST	67
6.1 APPLIED PROCEDURES / LIMIT	67
6.1.1 TEST PROCEDURE	67
6.1.2 DEVIATION FROM STANDARD	67
6.1.3 TEST SETUP	67
6.1.4 EUT OPERATION CONDITIONS	67
6.1.5 TEST RESULTS	68
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	69
7.1 DEVIATION FROM STANDARD	69
7.2 TEST SETUP	69
7.3 EUT OPERATION CONDITIONS	69
7.4 TEST RESULTS	70
8 . ANTENNA REQUIREMENT	74
8.1 STANDARD REQUIREMENT	74
8.2 EUT ANTENNA	74
9 . EUT TEST PHOTO	75
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 5 of 81 -

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Test Item	FCC Part No.	Requirements	Verdict
DTS (6 dB) Bandwidth	15.247(a)(2)	≥ 500 kHz.	PASS
Maximum Peak Conducted Output Power	15.247(b)(3)	For directional gain:< 30dBm – (G[dBi] –6 [dB]),peak; Otherwise :< 30dBm, peak.	PASS
Maximum Power Spectral Density Level	15.247(e)	For directional gain :< 8dBm/3 kHz – (G[dBi] –6[dB]), peak. Otherwise :< 8dBm/3 kHz, peak.	PASS
Band Edges Compliance	15.247(d)	< -20dB/100 kHz if total peak power \leq power limit.	PASS
Unwanted Emissions into Non-Restricted Frequency Bands	15.247(d)	< -20dB/100 kHz if total peak power \leq power limit.	PASS
Unwanted Emissions into Restricted Frequency Bands (Conducted)	15.247(d) 15.209	< -20dB/100 kHz if total peak power \leq power limit.	PASS
Unwanted Emissions into Restricted Frequency Bands (Radiated)	15.247(d) 15.209	FCC Part 15.209 field strength limit;	PASS
AC Power Line Conducted Emissions	15.207	FCC Part 15.207 conducted limit;	PASS

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(e)	Power spectral density	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(a)(1)	Spectrum bandwidth – 6 dB bandwidth	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 6 of 81 -

b)(1)	power	802.11n HT20	<input checked="" type="checkbox"/> Highest	802.11n HT20	<input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>				
§15.247(d)	Band edge compliance conducted	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.205	Band edge compliance radiated	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions conducted	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions radiated	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 7 of 81 -

1.1 TEST FACILITY

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % 。

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 8 of 81 -

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wi-Fi Smart Socket
Model Name	WK40
Serial number	S10001
Serial Model	WK41, WK42, WK43, WK44, WK45, WK46, C108, C118, C128
Model Difference	All models are identical except model name.
WLAN FCC Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz
WLAN FCC Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna	0dbi, PCB antenna
Ratings	125V~,60Hz, 10A max.
Adapter	N/A
Battery	N/A
HW:	V1.0
SW:	V1.1



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 9 of 81 -

2.2 DESCRIPTION OF TEST MODES

IEEE 802.11b/g/n: The product support thirteen channels but only use Eleventh channels in USA.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

2.2.1 TEST MODES

Test Case	Test Conditions	
	Configuration	Description
DTS (6 dB) Bandwidth	Measurement Method	FCC KDB 558074 §8.2 Option 2
	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
Maximum Peak Conducted Output Power	Measurement Method	FCC KDB 558074§9.1.2
	Test Environment	NTNV
	Test Setup	Test Setup 1
Maximum Power Spectral Density Level	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
	Measurement Method	FCC KDB 558074 §10.2 (peak PSD).
	Test Environment	NTNV
Unwanted Emissions into Non-Restricted Frequency Bands	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
	Measurement Method	FCC KDB 558074§11.0.
	Test Environment	NTNV
Unwanted Emissions into Restricted Frequency Bands (Conducted)	Test Setup	Test Setup 1
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
	Measurement Method	FCC KDB 558074§12.2, Conducted (antenna-port).
Unwanted Emissions into Restricted Frequency Bands (Conducted)	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 10 of 81 -

		11n HT20_L, 11n HT20_M, 11n HT20_H
Unwanted Emissions into Restricted	Measurement Method	FCC KDB 558074§12.1, Radiated(cabinet/case emissions with Impedance matching for antenna-port).
	Test Environment	NTNV
	EUT Configuration	11b_L, 11b_M, 11b_H 11g_L, 11g_M, 11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H

Test Case	Test Conditions	
	Configuration	Description
AC Power Line Conducted Emissions	Measurement Method	AC mains conducted.
	Test Environment	NTNV
	EUT Configuration	11g_M (Worst Conf.).

Remark:

1. For Radiated Emissions, By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.
2. Typical working modes for each IEEE 802.11 mode are selected to perform tests. The manufacturer provide special test software(WLAN facility) to control TX duty cycle >98% for TX test. Set the output power to max(PK) as Prescribed by the manufacturer.

Test Mode	Test Modes Description
IEEE 802.11b	IEEE 802.11b with data rate of 1 Mbps using SISO mode.
IEEE 802.11g	IEEE 802.11g with data rate of 6 Mbps using SISO mode.
IEEE 802.11n HT20	IEEE 802.11n with data rate of MCS0 and bandwidth of 20MHz using SISO mode.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 11 of 81 -

2.2.2 EUT operation mode

Test Mode	RF Ch.	TX Freq. [MHz]	RX Freq. [MHz]	Ch. BW [MHz]
IEEE 802.11b	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20
IEEE 802.11g	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20
IEEE 802.11n HT20	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20


2.2.3 EUT configuratio

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 12 of 81 -

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Wi-Fi Smart Socket	WOOSONE	WK40	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 13 of 81 -

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Equipment No.	Instrument	Manufacturer	Model Name	Serial Number	Specification	Cal. Data	due date
1	Semi-anechoic chamber	Changzhou Chengyu	EC3088	N/A	9*6*6m	10/25/2016	10/24/2017
2	Broadband antenna	R&S	VULB 9160	VULB91 60-516	30MHz-1500 MHz	10/25/2016	10/24/2017
3	Horn antenna	R&S	BBHA 9120D	10087	1GHz-18GHz	06/05/2016	10/24/2017
4	Test receiver	R&S	ESCI	101686	9KHz-3GHz	10/25/2016	10/24/2017
5	EMI Measuring Receiver	R&S	ESR	101660	9KHz-40GHz	10/25/2016	10/24/2017
6	Multi-device controller	MF	MF-7868	MF78680 8762	N/A	10/25/2016	10/24/2017
7	Amplifier	EM	EM-30180	060538	1GHz-18GHz	10/25/2016	10/24/2017
8	Amplifier	Schwarzbeck	BBV 9475	BBV 9475-663	1GHz-18GHz	06/05/2016	06/04/2017
9	Spectrum Analyzer	agilent	E4440B	US44300368	1GHz-26.5GHz	06/05/2016	06/04/2017
10	Test receiver	R&S	ESCI	101689	9KHz-3GHz	10/25/2016	10/24/2017
11	LISN	R&S	NSLK81 26	8126466	9k-30MHz	10/25/2016	10/24/2017
12	LISN	Narda	L2-16B	5589756	9k-30MHz	10/25/2016	10/24/2017
13	Power Meter	Anritsu	ML2495A	N/A	40MHz	10/25/2016	10/24/2017
14	Power sensor	Anritsu	MA2411B	N/A	40MHz	10/25/2016	10/24/2017
15	Radiated Cable 1#	FUJIKURA	5D-2W	01	30MHz-1GHz	10/25/2016	10/24/2017

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 14 of 81 -

16	Radiated Cable 2#	FUJIKURA	10D2W	02	1GHz -25GHz	10/25/2016	10/24/2017
17	Conducted Cable 1#	FUJIKURA	1D-2W	01	9KHz-30MHz	10/25/2016	10/24/2017
18	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	10/25/2016	10/24/2017

Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.

The Cal.Interval was one year



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 15 of 81 -

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)			Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 16 of 81 -


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 17 of 81 -


3.1.6 TEST RESULTS

Phase : L Test Voltage : AC 120V/60Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dB	Detector	Comment
1		0.1720	57.82	2.48	60.30	64.86	-4.56	QP
2		0.2139	43.60	2.00	45.60	53.05	-7.45	AVG
3	*	1.2259	51.50	0.85	52.35	56.00	-3.65	QP
4		1.3340	37.45	0.85	38.30	46.00	-7.70	AVG
5		4.3939	15.91	10.08	25.99	46.00	-20.01	AVG
6		4.4458	35.24	10.08	45.32	56.00	-10.68	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT2017SZ0301041F
- Page 18 of 81 -

Phase : N Test Voltage : AC 120V/60Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dB	Detector	Comment
1		0.1516	53.19	3.81	57.00	65.91	-8.91	QP
2		0.1564	47.16	3.16	50.32	55.65	-5.33	AVG
3		0.2908	52.05	1.45	53.50	60.50	-7.00	QP
4		0.3149	43.89	1.17	45.06	49.84	-4.78	AVG
5	*	0.7179	51.26	0.89	52.15	56.00	-3.85	QP
6		0.7179	36.06	0.89	36.95	46.00	-9.05	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 19 of 81 -

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane for below 1GHz and 1.50m above ground plane for above 1GHz.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 20 of 81 -

2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9 KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Anternna	3

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto	Peak
	Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

More procedure as follows;

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premereasurement:

- The turntable rotates from 0° to 315° using 45° steps.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 21 of 81 -

--- The antenna height is 1.0 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QP detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 4 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 22 of 81 -

described by manufacturer.

- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

Field Strength Calculation

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 23 of 81 -

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{FS = RA + AF + CL - AG}$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude		AG = Amplifier Gain
AF = Antenna Factor		

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 25 of 81 -

(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 26 of 81 -

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	Wi-Fi Smart Socket	Model Name. :	WK40
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
Limit line = specific limits(dBuV) + distance extrapolation factor.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 27 of 81 -

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Polarization:	Horizontal	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2412		




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Comment
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		49.8814	34.53	-18.67	15.86	40.00	-24.14	QP		
2		69.6005	38.35	-19.02	19.33	40.00	-20.67	QP		
3		107.5101	30.26	-13.48	16.78	40.00	-23.22	QP		
4		319.9370	28.76	-8.80	19.96	47.00	-27.04	QP		
5		601.4265	31.55	-0.89	30.66	47.00	-16.34	QP		
6	*	952.0937	32.85	3.77	36.62	47.00	-10.38	QP		



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 28 of 81 -

Polarization:	Vertical	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2412		



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	
1	38.3462	31.56	-14.46	17.10	40.00	-22.90	QP		
2	69.1141	33.93	-18.72	15.21	40.00	-24.79	QP		
3	181.9202	31.59	-11.58	20.01	40.00	-19.99	QP		
4	440.1963	31.94	-6.68	25.26	47.00	-21.74	QP		
5	670.4893	30.96	-0.88	30.08	47.00	-16.92	QP		
6 *	938.8326	33.07	3.51	36.58	47.00	-10.42	QP		

Note: test perform on 802.11b/g/n mode, "802.11b TX2412" mode is the worst mode and has been reported.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 29 of 81 -

3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Polarization:	Horizontal	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2412		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		1112.170	55.42	-8.90	46.52	74.00	-27.48
2		1112.170	44.52	-8.90	35.62	54.00	-18.38
3		4824.120	51.26	8.14	59.40	74.00	-14.60
4		4824.120	33.68	8.14	41.82	54.00	-12.18
5		7236.110	44.67	11.73	56.40	74.00	-17.60
6		7236.110	29.22	11.73	40.95	54.00	-13.05
7		9648.000	39.72	17.68	57.40	74.00	-16.60
8	*	9648.000	24.15	17.68	41.83	54.00	-12.17


Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 30 of 81 -

Polarization:	Vertical	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2412		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		1112.170	63.77	-8.90	54.87	74.00	-19.13 peak
2		1112.170	46.25	-8.90	37.35	54.00	-16.65 AVG
3		4824.120	49.47	8.14	57.61	74.00	-16.39 peak
4		4824.120	36.77	8.14	44.91	54.00	-9.09 AVG
5		7236.110	46.35	11.73	58.08	74.00	-15.92 peak
6		7236.110	32.81	11.73	44.54	54.00	-9.46 AVG
7		9648.000	43.22	17.68	60.90	74.00	-13.10 peak
8	*	9648.000	29.37	17.68	47.05	54.00	-6.95 AVG


Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 31 of 81 -

Polarization:	Horizontal	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2437		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		4874.000	45.27	8.17	53.44	74.00	-20.56 peak
2		4874.000	30.56	8.17	38.73	54.00	-15.27 AVG
3		7311.000	43.33	12.07	55.40	74.00	-18.60 peak
4		7311.110	28.64	12.07	40.71	54.00	-13.29 AVG
5		9748.000	35.45	18.20	53.65	74.00	-20.35 peak
6	*	9748.000	23.18	18.20	41.38	54.00	-12.62 AVG


Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 32 of 81 -

Polarization:	Vertical	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2437		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4874.000	46.71	8.17	54.88	74.00	-19.12 peak
2		4874.000	32.11	8.17	40.28	54.00	-13.72 AVG
3		7311.000	42.69	12.07	54.76	74.00	-19.24 peak
4	*	7311.110	29.24	12.07	41.31	54.00	-12.69 AVG
5		9748.000	34.02	18.20	52.22	74.00	-21.78 peak
6		9748.000	21.19	18.20	39.39	54.00	-14.61 AVG


Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 33 of 81 -

Polarization:	Horizontal	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2462		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4924.000	47.18	8.20	55.38	74.00	-18.62 peak
2		4924.000	33.69	8.20	41.89	54.00	-12.11 AVG
3		7386.000	46.55	12.41	58.96	74.00	-15.04 peak
4	*	7386.000	34.28	12.41	46.69	54.00	-7.31 AVG
5		9848.000	35.36	18.71	54.07	74.00	-19.93 peak
6		9848.000	22.61	18.71	41.32	54.00	-12.68 AVG


Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 34 of 81 -

Polarization:	Vertical	Test Voltage :	AC 120V/60Hz
Test Mode :	802.11B TX 2462		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4924.000	48.65	8.20	56.85	74.00	-17.15 peak
2		4924.000	34.66	8.20	42.86	54.00	-11.14 AVG
3		7386.000	47.95	12.41	60.36	74.00	-13.64 peak
4	*	7386.000	35.36	12.41	47.77	54.00	-6.23 AVG
5		9848.000	33.11	18.71	51.82	74.00	-22.18 peak
6		9848.000	21.96	18.71	40.67	54.00	-13.33 AVG



Note: test perform on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 10G.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 35 of 81 -



Conducted Spurious Emissions at Antenna Port: 802.11b Low Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 36 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 37 of 81 -



802.11b Middle Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 38 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 39 of 81 -



802.11b High Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 40 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 41 of 81 -



802.11g Low Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 42 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 43 of 81 -



802.11g Middle Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 44 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 45 of 81 -



802.11g High Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 46 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 47 of 81 -



802.11n(HT20) Low Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 48 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 49 of 81 -



802.11n(HT20) Middle Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 50 of 81 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 51 of 81 -

802.11n(HT20) High Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0301041F
- Page 52 of 81 -

