

# TEST REPORT

|                                              |                                                                                                                                                      |                                                                                       |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>FCC ID.</b> .....                         | 2ALNA-BTH24                                                                                                                                          |                                                                                       |
| <b>Test Report No.</b> .....                 | TCT250604E050                                                                                                                                        |                                                                                       |
| <b>Date of issue</b> .....                   | Jun. 11, 2025                                                                                                                                        |                                                                                       |
| <b>Testing laboratory</b> .....              | SHENZHEN TONGCE TESTING LAB                                                                                                                          |                                                                                       |
| <b>Testing location/ address:</b>            | 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China |                                                                                       |
| <b>Applicant's name</b> .....                | Shenzhen Thousandshores Technology Co., Ltd.                                                                                                         |                                                                                       |
| <b>Address</b> .....                         | Room 1101, Building B, Lotus Plaza, No. 3186 Nanshan Avenue, Majialong Community, Nantou Street, Nanshan District, Shenzhen, China                   |                                                                                       |
| <b>Manufacturer's name</b> ...               | Shenzhen Thousandshores Technology Co., Ltd.                                                                                                         |                                                                                       |
| <b>Address</b> .....                         | Room 1101, Building B, Lotus Plaza, No. 3186 Nanshan Avenue, Majialong Community, Nantou Street, Nanshan District, Shenzhen, China                   |                                                                                       |
| <b>Standard(s)</b> .....                     | FCC CFR Title 47 Part 15 Subpart C Section 15.247<br>FCC KDB 558074 D01 15.247 Meas Guidance v05r02<br>ANSI C63.10:2020                              |                                                                                       |
| <b>Product Name</b> .....                    | Wireless Headphones                                                                                                                                  |                                                                                       |
| <b>Trade Mark</b> .....                      | iClever                                                                                                                                              |                                                                                       |
| <b>Model/Type reference</b> .....            | BTH24                                                                                                                                                |                                                                                       |
| <b>Rating(s)</b> .....                       | Rechargeable Li-ion Battery DC 3.7V                                                                                                                  |                                                                                       |
| <b>Date of receipt of test item</b> .....    | Jun. 04, 2025                                                                                                                                        |                                                                                       |
| <b>Date (s) of performance of test</b> ..... | Jun. 04, 2025 ~ Jun. 11, 2025                                                                                                                        |                                                                                       |
| <b>Tested by (+signature)</b> ...            | Yannie ZHONG                                                                                                                                         |  |
| <b>Check by (+signature)</b> ....            | Beryl ZHAO                                                                                                                                           |  |
| <b>Approved by (+signature):</b>             | Tomsin                                                                                                                                               |  |



## General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

|                                                    |          |
|----------------------------------------------------|----------|
| <b>1. General Product Information .....</b>        | <b>3</b> |
| 1.1. EUT description .....                         | 3        |
| 1.2. Model(s) list.....                            | 3        |
| 1.3. Operation Frequency .....                     | 4        |
| <b>2. Test Result Summary .....</b>                | <b>5</b> |
| <b>3. General Information.....</b>                 | <b>6</b> |
| 3.1. Test environment and mode.....                | 6        |
| 3.2. Description of Support Units.....             | 6        |
| <b>4. Facilities and Accreditations .....</b>      | <b>7</b> |
| 4.1. Facilities .....                              | 7        |
| 4.2. Location .....                                | 7        |
| <b>5. Measurement Uncertainty .....</b>            | <b>7</b> |
| <b>6. Test Results and Measurement Data .....</b>  | <b>8</b> |
| 6.1. Antenna requirement .....                     | 8        |
| 6.2. Conducted Emission.....                       | 9        |
| 6.3. Conducted Output Power .....                  | 13       |
| 6.4. 20dB Occupy Bandwidth .....                   | 14       |
| 6.5. Carrier Frequencies Separation .....          | 15       |
| 6.6. Hopping Channel Number .....                  | 16       |
| 6.7. Dwell Time.....                               | 17       |
| 6.8. Pseudorandom Frequency Hopping Sequence.....  | 18       |
| 6.9. Conducted Band Edge Measurement.....          | 19       |
| 6.10. Conducted Spurious Emission Measurement..... | 20       |
| 6.11. Radiated Spurious Emission Measurement ..... | 21       |

**Appendix A: Test Result of Conducted Test**

**Appendix B: Photographs of Test Setup**

**Appendix C: Photographs of EUT**

## 1. General Product Information

### 1.1. EUT description

|                             |                                     |
|-----------------------------|-------------------------------------|
| Product Name.....:          | Wireless Headphones                 |
| Model/Type reference.....:  | BTH24                               |
| Sample Number.....:         | TCT250604E050-0101                  |
| Bluetooth Version .....     | V6.0                                |
| Operation Frequency .....   | 2402MHz~2480MHz                     |
| Transfer Rate .....         | 1/2/3 Mbits/s                       |
| Number of Channel .....     | 79                                  |
| Modulation Type .....       | GFSK, $\pi/4$ -DQPSK, 8DPSK         |
| Modulation Technology ..... | FHSS                                |
| Antenna Type.....:          | PCB Antenna                         |
| Antenna Gain.....:          | 3.87dBi                             |
| Rating(s).....:             | Rechargeable Li-ion Battery DC 3.7V |

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

None.

### 1.3. Operation Frequency

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 0       | 2402MHz   | 20      | 2422MHz   | 40      | 2442MHz   | 60      | 2462MHz   |
| 1       | 2403MHz   | 21      | 2423MHz   | 41      | 2443MHz   | 61      | 2463MHz   |
| ...     | ...       | ...     | ...       | ...     | ...       | ...     | ...       |
| 10      | 2412MHz   | 30      | 2432MHz   | 50      | 2452MHz   | 70      | 2472MHz   |
| 11      | 2413MHz   | 31      | 2433MHz   | 51      | 2453MHz   | 71      | 2473MHz   |
| ...     | ...       | ...     | ...       | ...     | ...       | ...     | ...       |
| 18      | 2420MHz   | 38      | 2440MHz   | 58      | 2460MHz   | 78      | 2480MHz   |
| 19      | 2421MHz   | 39      | 2441MHz   | 59      | 2461MHz   | -       |           |

Remark: Channel 0, 39 & 78 have been tested for GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation mode.

## 2. Test Result Summary

| Requirement                      | CFR 47 Section      | Result |
|----------------------------------|---------------------|--------|
| Antenna Requirement              | §15.203/§15.247 (c) | PASS   |
| AC Power Line Conducted Emission | §15.207             | PASS   |
| Conducted Peak Output Power      | §15.247 (b)(1)      | PASS   |
| 20dB Occupied Bandwidth          | §15.247 (a)(1)      | PASS   |
| Carrier Frequencies Separation   | §15.247 (a)(1)      | PASS   |
| Hopping Channel Number           | §15.247 (a)(1)      | PASS   |
| Dwell Time                       | §15.247 (a)(1)      | PASS   |
| Radiated Emission                | §15.205/§15.209     | PASS   |
| Band Edge                        | §15.247(d)          | PASS   |

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. General Information

#### 3.1. Test environment and mode

| Operating Environment:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                       |                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|-------------------|
| Condition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Conducted Emission                                                                                    | Radiated Emission |
| Temperature:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 24.4 °C                                                                                               | 25.7 °C           |
| Humidity:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 53 % RH                                                                                               | 51 % RH           |
| Atmospheric Pressure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1010 mbar                                                                                             | 1010 mbar         |
| Test Software:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                       |                   |
| Software Information:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | BT_Tool V1.1.0                                                                                        |                   |
| Power Level:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 3                                                                                                     |                   |
| Test Mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                       |                   |
| Engineer mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery. |                   |
| The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case (Z axis) are shown in Test Results of the following pages.<br>DH1 DH3 DH5 all have been tested. only worse case DH1 is reported. |                                                                                                       |                   |

#### 3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No.     | FCC ID | Trade Name |
|-----------|-----------|----------------|--------|------------|
| Adapter   | EP-TA200  | R37M4PR7QD4SE3 | /      | SAMSUNG    |

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 4. Facilities and Accreditations

### 4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

### 4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

## 5. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                                    | MU              |
|-----|-----------------------------------------|-----------------|
| 1   | Conducted Emission                      | $\pm 3.10$ dB   |
| 2   | RF power, conducted                     | $\pm 0.12$ dB   |
| 3   | Spurious emissions, conducted           | $\pm 0.11$ dB   |
| 4   | All emissions, radiated(<1 GHz)         | $\pm 4.56$ dB   |
| 5   | All emissions, radiated(1 GHz - 18 GHz) | $\pm 4.22$ dB   |
| 6   | All emissions, radiated(18 GHz- 40 GHz) | $\pm 4.36$ dB   |
| 7   | Dwell Time                              | $\pm 2$         |
| 8   | Occupied Bandwidth                      | $\pm 57.74$ kHz |



## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

**Standard requirement:**

FCC Part15 C Section 15.203 /247(c)

**15.203 requirement:**


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**15.247(c) (1)(i) requirement:**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**E.U.T Antenna:**

The Bluetooth antenna is PCB antenna which permanently attached, and the best case gain of the antenna is 3.87dBi.





## 6.2. Conducted Emission

### 6.2.1. Test Specification

| Test Requirement:     | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method:          | ANSI C63.10:2020                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Frequency Range:      | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Receiver setup:       | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Limits:               | <table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>                                                                                                                                                                                                                                                                                                                                                                                                           | Frequency range (MHz) | Limit (dBuV) |  | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|                       | Quasi-peak                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Average               |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.15-0.5              | 66 to 56*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 56 to 46*             |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.5-5                 | 56                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 46                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 5-30                  | 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 50                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Setup:           | <div><p>Reference Plane</p><p>40cm</p><p>E.U.T</p><p>AC power</p><p>80cm</p><p>LISN</p><p>Filter</p><p>AC power</p><p>EMI Receiver</p><p>Test table/Insulation plane</p><p>Remark:<br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                           |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Mode:            | Charging + Transmitting Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Procedure:       | <div><div>1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.</div></div> |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Result:          | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |


## 6.2.2. Test Instruments

| Conducted Emission Shielding Room Test Site (843) |              |           |               |               |               |
|---------------------------------------------------|--------------|-----------|---------------|---------------|---------------|
| Equipment                                         | Manufacturer | Model     | Serial Number | Date of Cal.  | Due Date      |
| EMI Test Receiver                                 | R&S          | ESCI3     | 100898        | Jun. 27, 2024 | Jun. 26, 2025 |
| LISN                                              | Schwarzbeck  | NSLK 8126 | 8126453       | Jan. 21, 2025 | Jan. 20, 2026 |
| Attenuator                                        | N/A          | 10dB      | 164080        | Jun. 27, 2024 | Jun. 26, 2025 |
| Line-5                                            | TCT          | CE-05     | /             | Jun. 27, 2024 | Jun. 26, 2025 |
| EMI Test Software                                 | EZ_EMG       | EMEC-3A1  | 1.1.4.2       | /             | /             |

## 6.2.3. Test data

Please refer to following diagram for individual

### Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 24.4 (°C)

Humidity: 53 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 5 V(Adapter Input AC 120 V/60 Hz)

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1580       | 28.60                    | 9.95                    | 38.55                    | 65.57         | -27.02     | QP       |         |
| 2   |     | 0.1580       | 10.64                    | 9.95                    | 20.59                    | 55.57         | -34.98     | AVG      |         |
| 3   |     | 0.2779       | 23.15                    | 9.94                    | 33.09                    | 60.88         | -27.79     | QP       |         |
| 4   |     | 0.2779       | 4.46                     | 9.94                    | 14.40                    | 50.88         | -36.48     | AVG      |         |
| 5   |     | 0.6900       | 23.94                    | 9.90                    | 33.84                    | 56.00         | -22.16     | QP       |         |
| 6   | *   | 0.6900       | 17.42                    | 9.90                    | 27.32                    | 46.00         | -18.68     | AVG      |         |
| 7   |     | 2.0100       | 13.38                    | 10.01                   | 23.39                    | 56.00         | -32.61     | QP       |         |
| 8   |     | 2.0100       | 7.20                     | 10.01                   | 17.21                    | 46.00         | -28.79     | AVG      |         |
| 9   |     | 4.1779       | 12.09                    | 10.12                   | 22.21                    | 56.00         | -33.79     | QP       |         |
| 10  |     | 4.1779       | 4.45                     | 10.12                   | 14.57                    | 46.00         | -31.43     | AVG      |         |
| 11  |     | 12.8339      | 24.61                    | 10.36                   | 34.97                    | 60.00         | -25.03     | QP       |         |
| 12  |     | 12.8339      | 14.10                    | 10.36                   | 24.46                    | 50.00         | -25.54     | AVG      |         |

#### Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

## Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 24.4 (°C)

Humidity: 53 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 5 V(Adapter Input AC 120 V/60 Hz)

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBμV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBμV | Limit<br>dBμV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1580       | 28.05                    | 9.94                    | 37.99                    | 65.57         | -27.58     | QP       |         |
| 2   |     | 0.1580       | 10.06                    | 9.94                    | 20.00                    | 55.57         | -35.57     | AVG      |         |
| 3   |     | 0.2380       | 23.53                    | 9.93                    | 33.46                    | 62.17         | -28.71     | QP       |         |
| 4   |     | 0.2380       | 6.23                     | 9.93                    | 16.16                    | 52.17         | -36.01     | AVG      |         |
| 5   |     | 0.6900       | 19.22                    | 9.94                    | 29.16                    | 56.00         | -26.84     | QP       |         |
| 6   | *   | 0.6900       | 14.75                    | 9.94                    | 24.69                    | 46.00         | -21.31     | AVG      |         |
| 7   |     | 2.0300       | 9.46                     | 10.03                   | 19.49                    | 56.00         | -36.51     | QP       |         |
| 8   |     | 2.0300       | 3.44                     | 10.03                   | 13.47                    | 46.00         | -32.53     | AVG      |         |
| 9   |     | 4.3580       | 9.54                     | 10.12                   | 19.66                    | 56.00         | -36.34     | QP       |         |
| 10  |     | 4.3580       | 2.01                     | 10.12                   | 12.13                    | 46.00         | -33.87     | AVG      |         |
| 11  |     | 12.7940      | 23.97                    | 10.42                   | 34.39                    | 60.00         | -25.61     | QP       |         |
| 12  |     | 12.7940      | 13.28                    | 10.42                   | 23.70                    | 50.00         | -26.30     | AVG      |         |

### Note1:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

### Note2:

Measurements were conducted in all three channels (high, middle, low) and two modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (Middle channel and GFSK) was submitted only.

## 6.3. Conducted Output Power

### 6.3.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (b)(1)                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Limit:</b>            | Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.                           |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                       |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Test Procedure:</b>   | <p>Use the following spectrum analyzer settings:</p> <p>Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</p> <p>RBW &gt; the 20 dB bandwidth of the emission being measured</p> <p>VBW ≥ RBW</p> <p>Sweep = auto</p> <p>Detector function = peak</p> <p>Trace = max hold</p> <p>Allow the trace to stabilize.</p> <p>Use the marker-to-peak function to set the marker to the peak of the emission.</p> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### 6.3.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFtest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |

## 6.4. 20dB Occupy Bandwidth

### 6.4.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Limit:</b>            | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.<br/>Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;<br/><math>1\% \leq RBW \leq 5\%</math> of the 20 dB bandwidth; <math>VBW \geq 3RBW</math>;<br/>Sweep = auto; Detector function = peak; Trace = max hold.</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

### 6.4.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFTest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |

## 6.5. Carrier Frequencies Separation

### 6.5.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Limit:</b>            | Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.                                                                                                                                                                                                                                                                                                                          |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Test Mode:</b>        | Hopping mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings:<br/>Span = wide enough to capture the peaks of two adjacent channels; RBW is set to approximately 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel; VBW≥RBW; Sweep = auto;<br/>Detector function = peak; Trace = max hold.</li> <li>5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Record the value in report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 6.5.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFtest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |



## 6.6. Hopping Channel Number

### 6.6.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Limit:</b>            | Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Test Mode:</b>        | Hopping mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings: Span = the frequency band of operation; set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller; VBW<math>\geq</math>RBW; Sweep = auto; Detector function = peak; Trace = max hold.</li> <li>5. The number of hopping frequency used is defined as the number of total channel.</li> <li>6. Record the measurement data in report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

### 6.6.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFTest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |

## 6.7. Dwell Time

### 6.7.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Limit:</b>            | The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Setup:</b>       |  <p>The diagram illustrates the test setup. On the left is a green Spectrum Analyzer with a blue screen. A black RF cable connects its right side to a yellow rectangular box on the right, which is labeled 'EUT'.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Test Mode:</b>        | Hopping mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW shall be <math>\leq</math> channel spacing and where possible RBW should be set <math>\gg 1 / T</math>, where T is the expected dwell time per channel; VBW <math>\geq</math> RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.</li> <li>5. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

### 6.7.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFTest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |

## 6.8. Pseudorandom Frequency Hopping Sequence

### Test Requirement:

### FCC Part15 C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 6.9. Conducted Band Edge Measurement

### 6.9.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Limit:</b>            | In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.                                                                                                                                                                                                                                                                                                                               |
| <b>Test Setup:</b>       |  <p>Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>2. Set RBW = 100 kHz (<math>\geq 1\%</math> span=10MHz), VBW = 300 kHz (<math>\geq</math>RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.</li> <li>3. Enable hopping function of the EUT and then repeat step 2 and 3.</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

### 6.9.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFTest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |

## 6.10. Conducted Spurious Emission Measurement

### 6.10.1. Test Specification


|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Method:</b>      | KDB 558074 D01 v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Limit:</b>            | In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.</li> <li>4. Measure and record the results in the test report.</li> <li>5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |


### 6.10.2. Test Instruments

| Equipment          | Manufacturer | Model No.  | Serial Number | Date of Cal.  | Due Date      |
|--------------------|--------------|------------|---------------|---------------|---------------|
| Spectrum Analyzer  | Agilent      | N9020A     | MY49100619    | Jun. 27, 2024 | Jun. 26, 2025 |
| Power detector box | MWRFtest     | MW100-RFCB | MW210531TCT   | Jan. 21, 2025 | Jan. 20, 2026 |


## 6.11. Radiated Spurious Emission Measurement

### 6.11.1. Test Specification

|                       |                             |                                                                                      |                                   |               |                               |          |
|-----------------------|-----------------------------|--------------------------------------------------------------------------------------|-----------------------------------|---------------|-------------------------------|----------|
| Test Requirement:     | FCC Part15 C Section 15.209 |                                                                                      |                                   |               |                               |          |
| Test Method:          | ANSI C63.10:2020            |                                                                                      |                                   |               |                               |          |
| Frequency Range:      | 9 kHz to 25 GHz             |                                                                                      |                                   |               |                               |          |
| Measurement Distance: | 3 m                         |                                                                                      |                                   |               |                               |          |
| Antenna Polarization: | Horizontal & Vertical       |                                                                                      |                                   |               |                               |          |
| Receiver Setup:       | Frequency                   | Detector                                                                             | RBW                               | VBW           | Remark                        |          |
|                       | 9kHz- 150kHz                | Quasi-peak                                                                           | 200Hz                             | 1kHz          | Quasi-peak Value              |          |
|                       | 150kHz- 30MHz               | Quasi-peak                                                                           | 9kHz                              | 30kHz         | Quasi-peak Value              |          |
|                       | 30MHz-1GHz                  | Quasi-peak                                                                           | 120KHz                            | 300KHz        | Quasi-peak Value              |          |
|                       | Above 1GHz                  | Peak                                                                                 | 1MHz                              | 3MHz          | Peak Value                    |          |
| Peak                  |                             | 1MHz                                                                                 | 10Hz                              | Average Value |                               |          |
| Limit:                | Frequency                   |                                                                                      | Field Strength (microvolts/meter) |               | Measurement Distance (meters) |          |
|                       | 0.009-0.490                 |                                                                                      | 2400/F(KHz)                       |               | 300                           |          |
|                       | 0.490-1.705                 |                                                                                      | 24000/F(KHz)                      |               | 30                            |          |
|                       | 1.705-30                    |                                                                                      | 30                                |               | 30                            |          |
|                       | 30-88                       |                                                                                      | 100                               |               | 3                             |          |
|                       | 88-216                      |                                                                                      | 150                               |               | 3                             |          |
|                       | 216-960                     |                                                                                      | 200                               |               | 3                             |          |
|                       | Above 960                   |                                                                                      | 500                               |               | 3                             |          |
|                       | Frequency                   |                                                                                      | Field Strength (microvolts/meter) |               | Measurement Distance (meters) | Detector |
|                       | Above 1GHz                  |                                                                                      | 500                               |               | 3                             | Average  |
|                       |                             |                                                                                      | 5000                              |               | 3                             | Peak     |
|                       | Test setup:                 | For radiated emissions below 30MHz                                                   |                                   |               |                               |          |
|                       |                             |  |                                   |               |                               |          |
| 30MHz to 1GHz         |                             |                                                                                      |                                   |               |                               |          |



Above 1GHz



**Test Mode:**

Transmitting mode with modulation

**Test Procedure:**

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10:2020 Measurement Guidelines.
2. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.  
For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission



|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | <p>and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Set to the maximum power setting and enable the EUT transmit continuously.</p> <p>4. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=120 kHz for <math>f &lt; 1</math> GHz, RBW=1MHz for <math>f &gt; 1</math>GHz ; VBW<math>\geq</math>RBW;<br/>Sweep = auto; Detector function = peak; Trace = max hold for peak</p> <p>(3) For average measurement: use duty cycle correction factor method per<br/>15.35(c). Duty cycle = On time/100 milliseconds<br/>On time = <math>N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n</math><br/>Where <math>N_1</math> is number of type 1 pulses, <math>L_1</math> is length of type 1 pulses, etc.<br/>Average Emission Level = Peak Emission Level + <math>20 \cdot \log(\text{Duty cycle})</math><br/>Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> |
| Test results: | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## 6.11.2. Test Instruments


| Radiated Emission Test Site (966) |              |               |                |               |               |
|-----------------------------------|--------------|---------------|----------------|---------------|---------------|
| Equipment                         | Manufacturer | Model         | Serial Number  | Date of Cal.  | Due Date      |
| EMI Test Receiver                 | R&S          | ESCI7         | 100529         | Jan. 21, 2025 | Jan. 20, 2026 |
| Spectrum Analyzer                 | R&S          | FSQ40         | 200061         | Jun. 27, 2024 | Jun. 26, 2025 |
| Pre-amplifier                     | SKET         | LNPA_0118G-45 | SK2021012102   | Jan. 21, 2025 | Jan. 20, 2026 |
| Pre-amplifier                     | SKET         | LNPA_1840G-50 | SK202109203500 | Jan. 21, 2025 | Jan. 20, 2026 |
| Pre-amplifier                     | HP           | 8447D         | 2727A05017     | Jun. 27, 2024 | Jun. 26, 2025 |
| Loop antenna                      | Schwarzbeck  | FMZB1519B     | 00191          | Jun. 27, 2024 | Jun. 26, 2025 |
| Broadband Antenna                 | Schwarzbeck  | VULB9163      | 340            | Jun. 29, 2024 | Jun. 28, 2025 |
| Horn Antenna                      | Schwarzbeck  | BBHA 9120D    | 631            | Jun. 29, 2024 | Jun. 28, 2025 |
| Horn Antenna                      | Schwarzbeck  | BBHA 9170     | 00956          | Jan. 23, 2025 | Jan. 22, 2026 |
| Coaxial cable                     | SKET         | RE-03-D       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Coaxial cable                     | SKET         | RE-03-M       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Coaxial cable                     | SKET         | RE-03-L       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Coaxial cable                     | SKET         | RE-04-D       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Coaxial cable                     | SKET         | RE-04-M       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Coaxial cable                     | SKET         | RE-04-L       | /              | Jun. 27, 2024 | Jun. 26, 2025 |
| Antenna Mast                      | Keleto       | RE-AM         | /              | /             | /             |
| EMI Test Software                 | EZ_EMCC      | FA-03A2 RE+   | 1.1.4.2        | /             | /             |

## 6.11.3. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber1

Polarization: **Horizontal**


Temperature: 25.7(C) Humidity: 51 %

Limit: FCC Part 15C RE\_3m

Power: DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 40.5591         | 24.50          | -12.03        | 12.47          | 40.00          | -27.53      | QP       | P   |        |
| 2   | 47.9940         | 25.45          | -12.19        | 13.26          | 40.00          | -26.74      | QP       | P   |        |
| 3   | 144.3348        | 26.63          | -11.92        | 14.71          | 43.50          | -28.79      | QP       | P   |        |
| 4   | 293.0842        | 24.80          | -11.19        | 13.61          | 46.00          | -32.39      | QP       | P   |        |
| 5 * | 647.3856        | 26.46          | -4.05         | 22.41          | 46.00          | -23.59      | QP       | P   |        |
| 6   | 986.0717        | 25.51          | 0.18          | 25.69          | 54.00          | -28.31      | QP       | P   |        |

Vertical:



Site: 3m Anechoic Chamber1

Polarization: **Vertical**

Temperature: 25.7(C)

Humidity: 51 %

Limit: FCC Part 15C RE\_3m

Power: DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 38.0783         | 24.81          | -12.24        | 12.57          | 40.00          | -27.43      | QP       | P   |        |
| 2   | 49.7068         | 24.76          | -12.27        | 12.49          | 40.00          | -27.51      | QP       | P   |        |
| 3   | 144.3348        | 28.75          | -11.92        | 16.83          | 43.50          | -26.67      | QP       | P   |        |
| 4   | 309.9977        | 24.50          | -10.82        | 13.68          | 46.00          | -32.32      | QP       | P   |        |
| 5   | 437.1199        | 26.04          | -8.43         | 17.61          | 46.00          | -28.39      | QP       | P   |        |
| 6 * | 755.3873        | 26.09          | -3.51         | 22.58          | 46.00          | -23.42      | QP       | P   |        |

**Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

2. Measurements were conducted in all three channels (high, middle, low) and three modulation (GFSK, Pi/4 DQPSK, 8DPSK) and the worst case Mode (Middle channel and GFSK) was submitted only.

3. Freq. = Emission frequency in MHz

Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

Limit (dBuV/m) = Limit stated in standard


Over (dB) = Measurement (dBuV/m) – Limits (dBuV/m)

\* is meaning the worst frequency has been tested in the test frequency range.

## Test Result of Radiated Spurious at Band edges

Lowest channel 2402:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 21.6(°C)


Humidity: 48 %

Limit: FCC part 15.247 bandedge(peak)

Power:DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 2390.000        | 53.10          | -16.26        | 36.84          | 74.00          | -37.16      | peak     | P   |        |
| 2 * | 2390.000        | 44.34          | -16.26        | 28.08          | 54.00          | -25.92      | AVG      | P   |        |

Vertical:



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 21.6(°C)

Humidity: 48 %


Limit: FCC part 15.247 bandedge(peak)

Power:DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 2390.000        | 56.77          | -16.26        | 40.51          | 74.00          | -33.49      | peak     | P   |        |
| 2 * | 2390.000        | 45.40          | -16.26        | 29.14          | 54.00          | -24.86      | AVG      | P   |        |

Highest channel 2480:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 21.6(°C)

Humidity: 48 %


Limit: FCC part 15.247 bandedge(peak)

Power:DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 2483.500        | 62.97          | -15.91        | 47.06          | 74.00          | -26.94      | peak     | P   |        |
| 2 * | 2483.500        | 60.79          | -15.91        | 44.88          | 54.00          | -9.12       | AVG      | P   |        |



Vertical:



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 21.6(°C)

Humidity: 48 %

Limit: FCC part 15.247 bandedge(peak)

Power:DC 3.7 V

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|--------|
| 1   | 2483.500        | 64.31          | -15.91        | 48.40          | 74.00          | -25.60      | peak     | P   |        |
| 2 * | 2483.500        | 62.12          | -15.91        | 46.21          | 54.00          | -7.79       | AVG      | P   |        |

**Note:** Measurements were conducted in all three modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (8DPSK) was submitted only.

## Above 1GHz

Modulation Type: GFSK

Low channel: 2402 MHz

| Frequency (MHz) | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|-----------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
|                 |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4804            | H             | 56.01               | ---               | -9.51                    | 46.50          | ---         | 74                  | 54                | -7.50       |
| 7206            | H             | 45.33               | ---               | -1.41                    | 43.92          | ---         | 74                  | 54                | -10.08      |
| ---             | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4804            | V             | 56.58               | ---               | -9.51                    | 47.07          | ---         | 74                  | 54                | -6.93       |
| 7206            | V             | 46.40               | ---               | -1.41                    | 44.99          | ---         | 74                  | 54                | -9.01       |
| ---             | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

Middle channel: 2441 MHz

| Frequency (MHz) | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|-----------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
|                 |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4882            | H             | 54.22               | ---               | -9.36                    | 44.86          | ---         | 74                  | 54                | -9.14       |
| 7323            | H             | 45.09               | ---               | -1.14                    | 43.95          | ---         | 74                  | 54                | -10.05      |
| ---             | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4882            | V             | 55.34               | ---               | -9.36                    | 45.98          | ---         | 74                  | 54                | -8.02       |
| 7323            | V             | 46.50               | ---               | -1.14                    | 45.36          | ---         | 74                  | 54                | -8.64       |
| ---             | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

High channel: 2480 MHz

| Frequency (MHz) | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|-----------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
|                 |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4960            | H             | 55.44               | ---               | -9.20                    | 46.24          | ---         | 74                  | 54                | -7.76       |
| 7440            | H             | 46.11               | ---               | -0.96                    | 45.15          | ---         | 74                  | 54                | -8.85       |
| ---             | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4960            | V             | 55.89               | ---               | -9.20                    | 46.69          | ---         | 74                  | 54                | -7.31       |
| 7440            | V             | 45.33               | ---               | -0.96                    | 44.37          | ---         | 74                  | 54                | -9.63       |
| ---             | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

### Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. Measurements were conducted in all three modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (GFSK) was submitted only.
7. All the restriction bands are compliance with the limit of 15.209.


## Appendix A: Test Result of Conducted Test

### Maximum Conducted Output Power


| Condition | Mode  | Frequency (MHz) | Conducted Power (dBm) | Limit (dBm) | Verdict |
|-----------|-------|-----------------|-----------------------|-------------|---------|
| NVNT      | 1-DH1 | 2402            | -1.28                 | 30          | Pass    |
| NVNT      | 1-DH1 | 2441            | -1.10                 | 30          | Pass    |
| NVNT      | 1-DH1 | 2480            | -1.16                 | 30          | Pass    |
| NVNT      | 2-DH1 | 2402            | -1.62                 | 21          | Pass    |
| NVNT      | 2-DH1 | 2441            | -1.34                 | 21          | Pass    |
| NVNT      | 2-DH1 | 2480            | -1.36                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2402            | -1.69                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2441            | -1.37                 | 21          | Pass    |
| NVNT      | 3-DH1 | 2480            | -1.46                 | 21          | Pass    |

## Test Graphs


### Power NVNT 1-DH1 2402MHz




### Power NVNT 1-DH1 2441MHz




## Power NVNT 1-DH1 2480MHz




## Power NVNT 2-DH1 2402MHz




## Power NVNT 2-DH1 2441MHz




## Power NVNT 2-DH1 2480MHz




## Power NVNT 3-DH1 2402MHz



## Power NVNT 3-DH1 2441MHz








**-20dB Bandwidth**


| Condition | Mode  | Frequency (MHz) | -20 dB Bandwidth (MHz) | Verdict |
|-----------|-------|-----------------|------------------------|---------|
| NVNT      | 1-DH1 | 2402            | 0.873                  | Pass    |
| NVNT      | 1-DH1 | 2441            | 0.873                  | Pass    |
| NVNT      | 1-DH1 | 2480            | 0.867                  | Pass    |
| NVNT      | 2-DH1 | 2402            | 1.178                  | Pass    |
| NVNT      | 2-DH1 | 2441            | 1.177                  | Pass    |
| NVNT      | 2-DH1 | 2480            | 1.178                  | Pass    |
| NVNT      | 3-DH1 | 2402            | 1.170                  | Pass    |
| NVNT      | 3-DH1 | 2441            | 1.167                  | Pass    |
| NVNT      | 3-DH1 | 2480            | 1.099                  | Pass    |

## Test Graphs


### -20dB Bandwidth NVNT 1-DH1 2402MHz




### -20dB Bandwidth NVNT 1-DH1 2441MHz




## -20dB Bandwidth NVNT 1-DH1 2480MHz




## -20dB Bandwidth NVNT 2-DH1 2402MHz




## -20dB Bandwidth NVNT 2-DH1 2441MHz




## -20dB Bandwidth NVNT 2-DH1 2480MHz




## -20dB Bandwidth NVNT 3-DH1 2402MHz



## -20dB Bandwidth NVNT 3-DH1 2441MHz






### Carrier Frequencies Separation


| Condition | Mode  | Hopping Freq1 (MHz) | Hopping Freq2 (MHz) | HFS (MHz) | Limit (MHz) | Verdict |
|-----------|-------|---------------------|---------------------|-----------|-------------|---------|
| NVNT      | 1-DH1 | 2402.017            | 2403.018            | 1.001     | 0.873       | Pass    |
| NVNT      | 1-DH1 | 2441.016            | 2442.015            | 0.999     | 0.873       | Pass    |
| NVNT      | 1-DH1 | 2479.019            | 2480.017            | 0.998     | 0.873       | Pass    |
| NVNT      | 2-DH1 | 2402.016            | 2403.016            | 1.000     | 0.785       | Pass    |
| NVNT      | 2-DH1 | 2441.018            | 2442.016            | 0.998     | 0.785       | Pass    |
| NVNT      | 2-DH1 | 2479.020            | 2480.016            | 0.996     | 0.785       | Pass    |
| NVNT      | 3-DH1 | 2402.004            | 2403.001            | 0.997     | 0.780       | Pass    |
| NVNT      | 3-DH1 | 2441.016            | 2442.018            | 1.002     | 0.780       | Pass    |
| NVNT      | 3-DH1 | 2479.034            | 2480.033            | 0.999     | 0.780       | Pass    |

## Test Graphs



### CFS NVNT 1-DH1 2402MHz







### CFS NVNT 1-DH1 2441MHz















**Band Edge**


| Condition | Mode  | Frequency (MHz) | Hopping Mode | Max Value (dBc) | Limit (dBc) | Verdict |
|-----------|-------|-----------------|--------------|-----------------|-------------|---------|
| NVNT      | 1-DH1 | 2402            | No-Hopping   | -54.22          | -20         | Pass    |
| NVNT      | 1-DH1 | 2480            | No-Hopping   | -52.68          | -20         | Pass    |
| NVNT      | 2-DH1 | 2402            | No-Hopping   | -49.98          | -20         | Pass    |
| NVNT      | 2-DH1 | 2480            | No-Hopping   | -32.49          | -20         | Pass    |
| NVNT      | 3-DH1 | 2402            | No-Hopping   | -50.72          | -20         | Pass    |
| NVNT      | 3-DH1 | 2480            | No-Hopping   | -28.25          | -20         | Pass    |

### Test Graphs


#### Band Edge NVNT 1-DH1 2402MHz No-Hopping Ref




#### Band Edge NVNT 1-DH1 2402MHz No-Hopping Emission




## Band Edge NVNT 1-DH1 2480MHz No-Hopping Ref




## Band Edge NVNT 1-DH1 2480MHz No-Hopping Emission



## Band Edge NVNT 2-DH1 2402MHz No-Hopping Ref




## Band Edge NVNT 2-DH1 2402MHz No-Hopping Emission







## Band Edge NVNT 2-DH1 2480MHz No-Hopping Ref




## Band Edge NVNT 2-DH1 2480MHz No-Hopping Emission




## Band Edge NVNT 3-DH1 2402MHz No-Hopping Ref




## Band Edge NVNT 3-DH1 2402MHz No-Hopping Emission



## Band Edge NVNT 3-DH1 2480MHz No-Hopping Ref



## Band Edge NVNT 3-DH1 2480MHz No-Hopping Emission




**Band Edge(Hopping)**


| Condition | Mode  | Frequency (MHz) | Hopping Mode | Max Value (dBc) | Limit (dBc) | Verdict |
|-----------|-------|-----------------|--------------|-----------------|-------------|---------|
| NVNT      | 1-DH1 | 2402            | Hopping      | -46.04          | -20         | Pass    |
| NVNT      | 1-DH1 | 2480            | Hopping      | -33.26          | -20         | Pass    |
| NVNT      | 2-DH1 | 2402            | Hopping      | -50.88          | -20         | Pass    |
| NVNT      | 2-DH1 | 2480            | Hopping      | -32.51          | -20         | Pass    |
| NVNT      | 3-DH1 | 2402            | Hopping      | -49.74          | -20         | Pass    |
| NVNT      | 3-DH1 | 2480            | Hopping      | -31.69          | -20         | Pass    |

## Test Graphs

### Band Edge(Hopping) NVNT 1-DH1 2402MHz Hopping Ref




### Band Edge(Hopping) NVNT 1-DH1 2402MHz Hopping Emission



## Band Edge(Hopping) NVNT 1-DH1 2480MHz Hopping Ref




## Band Edge(Hopping) NVNT 1-DH1 2480MHz Hopping Emission



## Band Edge(Hopping) NVNT 2-DH1 2402MHz Hopping Ref




## Band Edge(Hopping) NVNT 2-DH1 2402MHz Hopping Emission



## Band Edge(Hopping) NVNT 2-DH1 2480MHz Hopping Ref




## Band Edge(Hopping) NVNT 2-DH1 2480MHz Hopping Emission






## Band Edge(Hopping) NVNT 3-DH1 2402MHz Hopping Ref




## Band Edge(Hopping) NVNT 3-DH1 2402MHz Hopping Emission



## Band Edge(Hopping) NVNT 3-DH1 2480MHz Hopping Ref



## Band Edge(Hopping) NVNT 3-DH1 2480MHz Hopping Emission




### Conducted RF Spurious Emission


| Condition | Mode  | Frequency (MHz) | Max Value (dBc) | Limit (dBc) | Verdict |
|-----------|-------|-----------------|-----------------|-------------|---------|
| NVNT      | 1-DH1 | 2402            | -26.69          | -20         | Pass    |
| NVNT      | 1-DH1 | 2441            | -27.97          | -20         | Pass    |
| NVNT      | 1-DH1 | 2480            | -26.15          | -20         | Pass    |
| NVNT      | 2-DH1 | 2402            | -36.17          | -20         | Pass    |
| NVNT      | 2-DH1 | 2441            | -27.93          | -20         | Pass    |
| NVNT      | 2-DH1 | 2480            | -29.63          | -20         | Pass    |
| NVNT      | 3-DH1 | 2402            | -32.35          | -20         | Pass    |
| NVNT      | 3-DH1 | 2441            | -28.76          | -20         | Pass    |
| NVNT      | 3-DH1 | 2480            | -29.33          | -20         | Pass    |

## Test Graphs


### Tx. Spurious NVNT 1-DH1 2402MHz Ref




### Tx. Spurious NVNT 1-DH1 2402MHz Emission




## Tx. Spurious NVNT 1-DH1 2441MHz Ref




## Tx. Spurious NVNT 1-DH1 2441MHz Emission



## Tx. Spurious NVNT 1-DH1 2480MHz Ref




## Tx. Spurious NVNT 1-DH1 2480MHz Emission




## Tx. Spurious NVNT 2-DH1 2402MHz Ref




## Tx. Spurious NVNT 2-DH1 2402MHz Emission



## Tx. Spurious NVNT 2-DH1 2441MHz Ref



## Tx. Spurious NVNT 2-DH1 2441MHz Emission







## Tx. Spurious NVNT 2-DH1 2480MHz Ref




## Tx. Spurious NVNT 2-DH1 2480MHz Emission



## Tx. Spurious NVNT 3-DH1 2402MHz Ref




## Tx. Spurious NVNT 3-DH1 2402MHz Emission



## Tx. Spurious NVNT 3-DH1 2441MHz Ref




## Tx. Spurious NVNT 3-DH1 2441MHz Emission



## Tx. Spurious NVNT 3-DH1 2480MHz Ref



## Tx. Spurious NVNT 3-DH1 2480MHz Emission




**Number of Hopping Channel**


| Condition | Mode  | Hopping Number | Limit | Verdict |
|-----------|-------|----------------|-------|---------|
| NVNT      | 1-DH1 | 79             | 15    | Pass    |
| NVNT      | 2-DH1 | 79             | 15    | Pass    |
| NVNT      | 3-DH1 | 79             | 15    | Pass    |

### Test Graphs


#### Hopping No. NVNT 1-DH1 2441MHz



#### Hopping No. NVNT 2-DH1 2441MHz



## Hopping No. NVNT 3-DH1 2441MHz




### Dwell Time

| Condition | Mode  | Frequency (MHz) | Pulse Time (ms) | Total Dwell Time (ms) | Burst Count | Period Time (ms) | Limit (ms) | Verdict |
|-----------|-------|-----------------|-----------------|-----------------------|-------------|------------------|------------|---------|
| NVNT      | 1-DH1 | 2441            | 0.41            | 129.97                | 317         | 31600            | 400        | Pass    |
| NVNT      | 1-DH3 | 2441            | 1.66            | 263.94                | 159         | 31600            | 400        | Pass    |
| NVNT      | 1-DH5 | 2441            | 2.91            | 291.00                | 100         | 31600            | 400        | Pass    |
| NVNT      | 2-DH1 | 2441            | 0.42            | 132.72                | 316         | 31600            | 400        | Pass    |
| NVNT      | 2-DH3 | 2441            | 1.67            | 278.89                | 167         | 31600            | 400        | Pass    |
| NVNT      | 2-DH5 | 2441            | 2.92            | 324.12                | 111         | 31600            | 400        | Pass    |
| NVNT      | 3-DH1 | 2441            | 0.42            | 132.30                | 315         | 31600            | 400        | Pass    |
| NVNT      | 3-DH3 | 2441            | 1.67            | 267.20                | 160         | 31600            | 400        | Pass    |
| NVNT      | 3-DH5 | 2441            | 2.92            | 324.12                | 111         | 31600            | 400        | Pass    |






## Test Graphs



### Dwell NVNT 1-DH1 2441MHz One Burst







### Dwell NVNT 1-DH1 2441MHz Accumulated

















## Dwell NVNT 3-DH1 2441MHz One Burst




## Dwell NVNT 3-DH1 2441MHz Accumulated





## Dwell NVNT 3-DH3 2441MHz One Burst



## Dwell NVNT 3-DH3 2441MHz Accumulated







## Appendix B: Photographs of Test Setup

Please refer to document Appendix No.: TCT250604E050-A

## Appendix C: Photographs of EUT

Please refer to document Appendix No.: TCT250604E050-B & TCT250604E050-C

**\*\*\*\*\*END OF REPORT\*\*\*\*\***