

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : NINGBO JIN YU ELECTRICAL APPLIANCECO.,LTD
NO.88,JINFENGROAD,SOUTHERNECONOMICDEVELOPMENT
ZONE, YUYAO, ZHEJIANG,CHINA

Manufacturer : NINGBO JIN YU ELECTRICAL APPLIANCECO.,LTD
NO.88,JINFENGROAD,SOUTHERNECONOMICDEVELOPMENT
ZONE, YUYAO, ZHEJIANG,CHINA

Equipment : Coffee Maker

Type/Model : KCM009BT, RJ14-BUZZ

Test Result : Pass

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm^2

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 170301754SHA-001

Frequency band (MHz)	Max power	Antenna Gain	R	S
2400-2483.5MHz	-3.10dBm	0.489mW	-0.61dBi	0.87

For the device can support simultaneous transmission, according to 447498 D01 General RF Exposure Guidance v06,

The sum of the MPE ratios = 0.0000846 mW/cm^2

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Date of issue: April 20, 2017

Prepared by:

Jesse

Jesse Xu (*Project Engineer*)

Reviewed by:



Daniel Zhao (*Reviewer*)



FCC ID: 2ALOB-001
IC: 22576-001

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.