

Declaration of RF Exposure Compliance for SAR exclusion

ATTESTATION:

I attest that the radiocommunication apparatus meets the exclusion from the routine evaluation limits in Section 4.3 of KDB 447498 D01 v06; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR limits of FCC part 1.1310

Signature:



Date:

May 29, 2017

NAME (Please print or type):

Deokha Ryu

TITLE (Please print or type):

Chief Engineer

COMPANY (Please print or type):

Nemko Korea Co.Ltd.

Model Number (Please print or type):

S1, S2, S3

FCC ID (Please print or type):

2ALPA305001BF

Signature:



Date:

June 01, 2017

NAME (Please print or type):

Brian Nguyen

TITLE (Please print or type):

CEO

COMPANY (Please print or type):

RYNAN Technologies Pte Ltd

Model Number (Please print or type):

S1, S2, S3

FCC ID (Please print or type):

2ALPA305001BF

Note: The submission of this document is only required if the device meets the exemption limits for the routine evaluation in Section 4.3 of KDB 447498 D01 v06

Technical Brief - Exclusion from Routine Evaluation Limits – SAR Evaluation

As detailed in Section 4.3 of KDB 447498 D01 v06, the information contained in this RF exposure technical brief is limited to information that demonstrates how the output power of the device was derived to justify the exclusion from the routine evaluation.

The output power and operating frequency of the device are:

Frequency	Power	
	Maximum conducted output power	
2480 MHz	5.60 dBm	3.63 mW
<input checked="" type="checkbox"/> The Maximum conducted output power was derived from measurement of output power at the antenna port.		

The Minimum Separation distance: 5mm

SAR Test Exclusion calculation result : 1.144

- * SAR Test Exclusion Threshold is determined according to the following equation as specified KDB 447498 D01 4.3.1).
 - * The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by:
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$$
$$\cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

Conclusion

As the SAR Test Exclusion calculation result is below SAR test exclusion thresholds, the SAR evaluation is not required.