FCC TEST REPORT

FCC Part 22 /Part 24

Report Reference No.....:: LCS190920053AEA

FCC ID.....:: **2ALPI-ETS6688**

Date of Issue.:: **September 30, 2019**

Testing Laboratory Name Shenzhen LCS Compliance Testing Laboratory Ltd.

1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Address....:

Bao'an District, Shenzhen, Guangdong, China

Applicant's name..... Shenzhen Etross telecom Co., Itd.

301, Block B, Yuetong Comprehensive Bldg, Meilong Road, Address....:

Longhua Town, Bao'an District, shenzhen, China

Test specification:

FCC Part 22: Public Mobile Services Standard:

FCC Part 24: Personal Communication Services

Test Report Form No: LCSEMC-1.0

Shenzhen LCS Compliance Testing Laboratory Ltd. TRF Originator....:

Master TRF....: Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

3G Fixed Wireless Phone

Trade Mark: N/A

Test Model....: ETS-6688

Listed Models: N/A

DC 3.7V by Rechargeable Li-ion Battery(800mAh) Ratings....:

Recharged by DC 5V Adapter

Hardware version: 0.4,2017/09/05

Software version: YTL_BW_B1258_0007_20190730.pac

Frequency..... GSM 850MHz; PCS 1900MHz

PASS Result....:

Compiled by:

Supervised by:

Approved by:

Leo Lee/ Administrators

Aking Jin/ Technique principal

Gavin Liang/ Manager

TEST REPORT

September 30, 2019 Test Report No.: LCS190920053AEA Date of issue

Equipment under Test 3G Fixed Wireless Phone

Test Model ETS-6688

Listed Models : N/A

Model Declaration N/A

Applicant : Shenzhen Etross telecom Co., Itd.

301, Block B, Yuetong Comprehensive Bldg, Meilong Road, Address

Longhua Town, Bao'an District, shenzhen, China

Manufacturer : Shenzhen Etross telecom Co., Itd.

301, Block B, Yuetong Comprehensive Bldg, Meilong Road, Address

Longhua Town, Bao'an District, shenzhen, China

Factory Address

Test Result: PASS	Test Result:	PASS
-------------------	--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revison History

Revision	Issue Date	Revisions	Revised By
000	September 30, 2019	Initial Issue	Gavin Liang

Contents

<u>1</u>	TEST STANDARDS	<u> 5</u>
<u>2</u>	SUMMARY	6
<u> </u>	30 W W A R T	0
2.1	General Remarks	6
2.2	Product Description	6
2.3	Equipment under Test	7
2.4	Short description of the Equipment under Test (EUT)	7
2.5	Internal Identification of AE used during the test	7
2.6	Normal Accessory setting	8
2.7 2.8	EUT configuration Related Submittal(s) / Grant (s)	8 8
2.0	Modifications	8
2.10	General Test Conditions/Configurations	8
<u>3</u>	TEST ENVIRONMENT	q
<u>~</u>		
3.1	Address of the test laboratory	9
3.1	Address of the test laboratory Test Facility	9
3.3	Environmental conditions	9
3.4	Test Description	9
3.5	Equipments Used during the Test	11
3.6	Measurement uncertainty	12
<u>4</u>	TEST CONDITIONS AND RESULTS	13
		40
4.1 4.2	Output Power	13 17
4.2	Radiated Spurious Emssion Occupied Bandwidth and Emission Bandwidth	21
4.4	Band Edge Complicance	24
4.5	Spurious Emssion on Antenna Port	27
4.6	Frequency Stability Test	37
4.7	Peak-to-Average Ratio (PAR)	40
<u>5</u>	TEST SETUP PHOTOGRAPHS OF EUT	43
<u>~</u>	TEGI GETGI THOTOGRAFING GI EGITHILITINI	
<u>6</u>	EXTERIOR PHOTOGRAPHS OF THE EUT	43
<u>7</u>	INTERIOR PHOTOGRAPHS OF THE EUT	4 <u>3</u>

TEST STANDARDS

The tests were performed according to following standards:

FCC Part 22 (10-1-16 Edition): Private Land Mobile Radio Services.

FCC Part 24(10-1-16 Edition): Public Mobile Services.

TIA-603-E March 2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

47 CFR FCC Part 15 Subpart B: Unintentional Radiators.

FCC Part 2: Frequency Allocations And Radio Treaty Matters: General Rules And Regulations.

ANSI C63.4:2014: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	September 23, 2019
Testing commenced on	:	September 23, 2019
Testing concluded on	:	September 27, 2019

2.2 Product Description

The Shenzhen Etross telecom Co., Itd.'s Model: ETS-6688 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

, ,	details, refer to the user's manual of the EOT.		
Name of EUT	3G Fixed Wireless Phone		
Test Model	ETS-6688		
Modulation Type	GMSK for GSM/GPRS; 8-PSK for EDGE; QPSK for UMTS		
	2.0dBi (max.) For GSM 850; 2.0dBi (max.) For GSM 900;		
Antenna Gain	2.0dBi (max.) For DCS 1800; 2.0dBi (max.) For PCS 1900;		
	2.0dBi for WCDMA Band II; 2.0dBi for WCDMA Band V		
Hardware version	0.4,2017/09/05		
Software version	YTL_BW_B1258_0007_20190730.pac		
GSM/EDGE/GPRS Operation	GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900		
Frequency Band	GSM050/PCS1900/GPRS050/GPRS1900/EDGE050/EDGE1900		
UMTS Operation Frequency Band	UMTS FDD Band II/V		
LTE Operation Frequency Band	Not Supported		
GSM/EDGE/GPRS	Supported GSM/GPRS/EDGE		
GSM Release Version	R99		
GSM/EDGE/GPRS Power Class	GSM850:Power Class 4/ PCS1900:Power Class 1		
GPRS/EDGE Multislot Class	GPRS/EDGE: Multi-slot Class 12		
GPRS operation mode	Class B		
WCDMA Release Version	R8		
HSDPA Release Version	Release 8		
HSUPA Release Version	Release 6		
DC-HSUPA Release Version	Not Supported		
LTE Release Version	Not Supported		
LTE/UMTS Power Class	Class 3		
WLAN FCC Modulation Type	Not Supported		
WLAN FCC Operation frequency	Not Supported		
Antenna Type	Not Supported		
BT Modulation Type	Not Supported		
Extreme temp. Tolerance	-20°C to +55°C		
GPS function	Not Supported		
FM function	Not Supported		
NFC Function	Not Supported		
Extreme vol. Limits	3.40VDC to 4.20VDC (nominal: 3.70VDC)		

2.3 Equipment under Test

Power supply system utilised

Power supply voltage	• •	0	120V / 60 Hz	0	115V / 60Hz
		0	12 V DC	0	24 V DC
		•	Other (specified in blank bel	ow))

DC 3.70V

Test frequency list

Test Mode	TX/RX					
i est ivioue	I A/KA	Low(L)	Middle (M)	High (H)		
	TX	Channel 128	Channel 190	Channel 251		
GSM850	IA	824.2 MHz	836.6 MHz	848.8 MHz		
GSIVIOSU	RX	Channel 128	Channel 190	Channel 251		
	NΛ	869.2 MHz	881.6 MHz	893.8 MHz		
Test Mode	Took Mode TV/DV		RF Channel			
i est ivioue	Test Mode TX/RX	Low(L)	Middle (M)	High (H)		
	TX	Channel 512	Channel 661	Channel 810		
GSM1900	17	1850.2 MHz	1880.0 MHz	1909.8 MHz		
G31V11900	DV	Channel 512	Channel 661	Channel 810		
	RX		1960.0 MHz	1989.8 MHz		

2.4 Short description of the Equipment under Test (EUT)

2.4.1 General Description

ETS-6688 is subscriber equipment in the GSM/WCDMA system. The GSM/GPRS/EDGE frequency band includes GSM850, GSM900, DCS1800 and PCS1900. The HSPA/UMTS frequency band is Band II/V. The GSM/GPRS/EDGE frequency band includes GSM850, GSM900, DCS1800 and PCS1900 bands but only the GSM850 and PCS1900 band test data included in this report.

2.5 Internal Identification of AE used during the test

AE ID*	Description	
AE1	Rechargeable Li-ion Battery	
AE2	AC/DC ADAPTER	

Model: ETS-618

INPUT: AC 100-240V, 50/60Hz, 0.2A Max

OUTPUT: DC 5V, 500mA

*AE ID: is used to identify the test sample in the lab internally.

Normal Accessory setting 2.6

Fully charged battery was used during the test.

2.7 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- O supplied by the lab

0	Power Cable	Length (m):	/
		Shield:	/
		Detachable :	/
0	Multimeter	Manufacturer:	/
		Model No.:	/

Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2ALPI-ETS6688 filing to comply with FCC Part 22 and Part 24 Rules.

2.9 **Modifications**

No modifications were implemented to meet testing criteria.

2.10 General Test Conditions/Configurations

2.10.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description		
GSM/TM1	GSM system, GSM,GMSK modulation		
GSM/TM2	GSM system, GPRS, GMSK modulation		
GSM/TM3	GSM system, EDGE, 8PSK modulation		

Note:

- 1. This EUT owns one SIM card slot only.
- 2. As GSM and GPRS with the same emission designator, test result recorded in this report at the worst case GSM/TM1 only after exploratory scan.

2.10.2 Test Environment

Environment Parameter	Selected Values During Tests			
Relative Humidity	Ambient			
Temperature	TN Ambient			
Voltage	VL	3.40V		
	VN	3.70V		
	VH	4.20V		

NOTE: VL=lower extreme test voltage VN=nominal voltage VH=upper extreme test voltage TN=normal temperature

TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen LCS Compliance Testing Laboratory Ltd

1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong,

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC Registration Number is 254912.

Industry Canada Registration Number is 9642A-1.

EMSD Registration Number is ARCB0108.

UL Registration Number is 100571-492.

TUV SUD Registration Number is SCN1081.

TUV RH Registration Number is UA 50296516-001.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier: CN0071

3.3 **Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

3.4.1 Cellular Band (824-849MHz paired with 869-894MHz)

FCC: ERP ≤ 7W. ISED: ERP ≤ 11.5W. Digital modulation OBW: No limit. EBW: No limit. ≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to	Pass N/A Pass
Digital modulation OBW: No limit. EBW: No limit. ≤-13dBm/1%*EBW, in 1MHz bands	N/A Pass
OBW: No limit. EBW: No limit. ≤-13dBm/1%*EBW, in 1MHz bands	Pass
EBW: No limit. ≤-13dBm/1%*EBW, in 1MHz bands	
· · ·	Page
The frequency block.	1 055
≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
≤ -13dBm/100kHz.	Pass
≤ ±2.5ppm.	Pass
IC:Limit≤13dB	Pass
	≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges. ≤ -13dBm/100kHz. ≤ ±2.5ppm.

3.4.2 PCS Band (1850-1915MHz paired with 1930-1995MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	Pass
Peak-Average Ratio	§2.1046, §24.232	≤13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤-13dBm/1MHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	Pass
Frequency Stability	§2.1055, §24.235	≤ ±2.5ppm.	Pass
NOTE 1: For the verdict, the "I	V/A" denotes "no	ot applicable", the "N/T" de notes "not tested".	

Remark: 1. The measurement uncertainty is not included in the test result.

Equipments Used during the Test 3.5

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2019-06-11	2020-06-10
2	Power Sensor	R&S	NRV-Z81	100458	2019-06-11	2020-06-10
3	Power Sensor	R&S	NRV-Z32	10057	2019-06-11	2020-06-10
4	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
5	RF Control Unit	Tonscend	JS0806	158060009	2019-06-11	2020-06-10
6	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2018-11-15	2019-11-14
7	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2019-06-11	2020-06-10
8	DC Power Supply	Agilent	E3642A	N/A	2018-11-15	2019-11-14
9	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
10	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12	2020-06-11
11	Positioning Controller	MF	MF-7082	N/A	2019-06-12	2020-06-11
12	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2019-07-25	2020-07-24
13	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2019-07-25	2020-07-24
14	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2019-07-01	2020-06-30
15	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2018-09-20	2019-09-19
16	Broadband Preamplifier	SCHWARZBECK	BBV 9719	9719-025	2018-09-20	2019-09-19
17	EMI Test Receiver	R&S	ESR 7	101181	2019-06-12	2020-06-11
18	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2018-11-15	2019-11-14
19	Broadband Preamplifier	phx	BP-01M18G	P190501	2019-07-01	2020-06-30
20	RF Cable-R03m	Jye Bao	RG142	CB021	2019-06-12	2020-06-11
21	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2019-06-12	2020-06-11
22	6dB Attenuator	/	100W/6dB	1172040	2019-06-11	2020-06-10
23	3dB Attenuator	/	2N-3dB	/	2019-06-11	2020-06-10
24	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2018-10-10	2019-10-09

3.6 **Measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen LCS Compliance Testing Laboratory Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.10 dB	(1)
Radiated Emission	1~18GHz	3.80 dB	(1)
Radiated Emission	18-40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	1.63 dB	(1)
Conducted Power	9KHz~18GHz	0.61 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	1.22 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	1.22 dB	(1)
Occuiped Bandwidth	9KHz~40GHz	-	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

TEST CONDITIONS AND RESULTS


4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1 Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a CMW 500 by an Att.
- EUT Communicate with CMW 500 then selects a channel for testing.
- d) Add a correction factor to the display CMW 500, and then test.

TEST RESULTS

		Burst Average Conducted power (dBm)					
GS	M 850	Channel/Frequency(MHz)					
		128/824.2	190/836.6	251/848.8			
G	SSM	32.55	32.69	32.44			
	1TX slot	32.43	32.61	32.35			
GPRS	2TX slot	30.75	30.99	30.67			
(GMSK)	3TX slot	29.84	29.90	29.81			
	4TX slot	28.34	28.47	28.29			
	1TX slot	26.38	26.52	26.25			
EDGE	2TX slot	24.17	24.25	24.05			
(8PSK)	3TX slot	22.67	22.70	22.50			
	4TX slot	21.18	21.23	21.05			

		Burst Average Conducted power (dBm)					
GSM	1900	Channel/Frequency(MHz)					
		512/1850.2	661/1880	810/1909.8			
GS	M	29.61	29.68	29.43			
	1TX slot	29.39	29.42	29.33			
GPRS	2TX slot	27.76	27.85	27.57			
(GMSK)	3TX slot	26.84	26.94	26.78			
	4TX slot	25.40	25.50	25.24			
	1TX slot	25.84	26.02	25.71			
EDGE	2TX slot	23.61	23.73	23.48			
(8PSK)	3TX slot	22.13	22.27	22.02			
	4TX slot	20.68	20.76	20.55			

4.1.2 Radiated Output Power


TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Per rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Per rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

TEST CONFIGURATION



TEST PROCEDURE

- 1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
- 2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
- The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the

- previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pci), the Substitution Antenna Gain (Ga) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

- Power(EIRP)= P_{Mea} + P_{Ag} P_{cl} + G_a
- This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

TEST LIMIT

According to 22.913(a), 24.232(c), the ERP should be not exceed following table limits:

GSM850(GPRS850,EDGE850)								
Function	Power Step	Burst Peak ERP (dBm)						
GSM	5	FCC: ≤38.45dBm (7W)						
GPRS	3	FCC: ≤38.45dBm (7W)						
EDGE	8	FCC: ≤38.45dBm (7W)						

PCS1900(GPRS1900,EDGE1900)									
Function	Power Step	Burst Peak EIRP (dBm)							
GSM	0	≤33.01dBm (2W)							
GPRS	3	≤33.01dBm (2W)							
EDGE	2	≤33.01dBm (2W)							

TEST RESULTS

Remark:

- 1. We were tested all Configuration refer 3GPP TS151 010.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Aq}(dB)+G_a(dBi)$
- 3. ERP = EIRP 2.15dBi as EIRP by subtracting the gain of the dipole.
- 4. Margin = Emission Level Limit
- 5. We test the H direction and V direction recorded worst case.

GSM/TM1/GSM850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-6.97	3.45	8.45	2.15	33.79	29.67	38.45	-8.78	V
836.60	-6.93	3.49	8.45	2.15	33.85	29.73	38.45	-8.72	V
848.80	-7.04	3.55	8.36	2.15	33.88	29.50	38.45	-8.95	V

GSM/TM3/EDGE850

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Burst Average ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-12.03	3.45	8.45	2.15	33.79	24.61	38.45	-13.84	V
836.60	-11.95	3.49	8.45	2.15	33.85	24.71	38.45	-13.74	V
848.80	-12.01	3.55	8.36	2.15	33.88	24.53	38.45	-13.92	V

GSM/TM1/GSM1900

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-12.01	4.03	8.38	35.51	27.85	33.01	-5.16	V
1880.00	-11.93	4.08	8.33	35.56	27.88	33.01	-5.13	V
1909.80	-11.95	4.14	8.26	35.63	27.80	33.01	-5.21	V

GSM/TM3/EDGE1900


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-17.08	4.03	8.38	35.51	22.78	33.01	-10.23	V
1880.00	-16.91	4.08	8.33	35.56	22.90	33.01	-10.11	V
1909.80	-17.05	4.14	8.26	35.63	22.70	33.01	-10.31	V

4.2 **Radiated Spurious Emssion**

TEST APPLICABLE

According to the TIA-603-E:2016 and FCC Part 2.1033 test method, The Receiver or Spectrum was scanned from lowest frequency frequency generated within the equipment to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917, RSS-132 §5.5 and RSS-133 §6.5. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

TEST CONFIGURATION



TEST PROCEDURE

- 1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
- 2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
- The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (P_{Aq}) should be recorded after test.
 - The measurement results are obtained as described below:
 - Power(EIRP)= P_{Mea} + P_{Ag} P_{cl} + G_a
- This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.
- 8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
TM1/GSM 850	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
TM1/GSM 1900	2~5	1 MHz	3 MHz	3
1 W17GSW1 1900	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

TEST LIMITS

According to 24.238 and 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
	Low	9KHz -10GHz	PASS
TM1/GSM 850	Middle	9KHz -10GHz	PASS
	High	9KHz -10GHz	PASS
	Low	9KHz -20GHz	PASS
TM1/GSM 1900	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS

TEST RESULTS

Remark:

- 1. We were tested all refer 3GPP TS151 010.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+G_a(dBi)$
- 3. We were not recorded other points as values lower than limits.
- 4. Margin = EIRP Limit

GSM/TM1/GSM850_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-43.32	3.86	3.00	8.56	-38.62	-13.00	-25.62	Н
2472.60	-44.60	4.29	3.00	6.98	-41.91	-13.00	-28.91	Н
1648.40	-39.71	3.86	3.00	8.56	-35.01	-13.00	-22.01	V
2472.60	-41.74	4.29	3.00	6.98	-39.05	-13.00	-26.05	V

GSM/TM1/GSM850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-41.57	3.9	3.00	8.58	-36.89	-13.00	-23.89	Н
2509.80	-46.20	4.32	3.00	6.8	-43.72	-13.00	-30.72	Н
1673.20	-37.76	3.9	3.00	8.58	-33.08	-13.00	-20.08	V
2509.80	-43.24	4.32	3.00	6.8	-40.76	-13.00	-27.76	V

GSM/TM1/GSM850 High Channel

	0.11, 1.111.17	<u> </u>	9 0						
F	requency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
	1697.60	-46.98	3.91	3.00	9.06	-41.83	-13.00	-28.83	Н
	2546.40	-49.55	4.32	3.00	6.65	-47.22	-13.00	-34.22	Н
	1697.60	-43.00	3.91	3.00	9.06	-37.85	-13.00	-24.85	V
	2546.40	-45.15	4.32	3.00	6.65	-42.82	-13.00	-29.82	V

GSM/TM3/GSM850_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-45.49	3.86	3.00	8.56	-40.79	-13.00	-27.79	Н
2472.60	-46.40	4.29	3.00	6.98	-43.71	-13.00	-30.71	Н
1648.40	-41.74	3.86	3.00	8.56	-37.04	-13.00	-24.04	V
2472.60	-43.83	4.29	3.00	6.98	-41.14	-13.00	-28.14	V

GSM/TM3/GSM850_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-43.75	3.9	3.00	8.58	-39.07	-13.00	-26.07	Н
2509.80	-48.44	4.32	3.00	6.8	-45.96	-13.00	-32.96	Н
1673.20	-39.54	3.9	3.00	8.58	-34.86	-13.00	-21.86	V
2509.80	-44.69	4.32	3.00	6.8	-42.21	-13.00	-29.21	V

GSM/TM3/GSM850_ High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-48.48	3.91	3.00	9.06	-43.33	-13.00	-30.33	Н
2546.40	-51.88	4.32	3.00	6.65	-49.55	-13.00	-36.55	Н
1697.60	-45.14	3.91	3.00	9.06	-39.99	-13.00	-26.99	V
2546.40	-47.07	4.32	3.00	6.65	-44.74	-13.00	-31.74	V

GSM/TM1/GSM1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-45.43	5.26	3.00	9.88	-40.81	-13.00	-27.81	Н
5550.60	-46.28	6.11	3.00	11.36	-41.03	-13.00	-28.03	Н
3700.40	-42.12	5.26	3.00	9.88	-37.50	-13.00	-24.50	V
5550.60	-44.22	6.11	3.00	11.36	-38.97	-13.00	-25.97	V

GSM/TM1/GSM1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-44.03	5.32	3.00	10.03	-39.32	-13.00	-26.32	Н
5640.00	-48.70	6.19	3.00	11.41	-43.48	-13.00	-30.48	Н
3760.00	-39.72	5.32	3.00	10.03	-35.01	-13.00	-22.01	V
5640.00	-45.35	6.19	3.00	11.41	-40.13	-13.00	-27.13	V

GSM/TM1/GSM1900 High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-49.03	5.36	3.00	9.62	-44.77	-13.00	-31.77	Н
5729.40	-51.56	6.24	3.00	11.46	-46.34	-13.00	-33.34	Н
3819.60	-45.12	5.36	3.00	9.62	-40.86	-13.00	-27.86	V
5729.40	-47.40	6.24	3.00	11.46	-42.18	-13.00	-29.18	V

GSM/TM3/GSM1900_ Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-47.63	5.26	3.00	9.88	-43.01	-13.00	-30.01	Н
5550.60	-48.63	6.11	3.00	11.36	-43.38	-13.00	-30.38	Н
3700.40	-43.91	5.26	3.00	9.88	-39.29	-13.00	-26.29	V
5550.60	-46.27	6.11	3.00	11.36	-41.02	-13.00	-28.02	V

GSM/TM3/GSM1900_ Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-46.03	5.32	3.00	10.03	-41.32	-13.00	-28.32	Н
5640.00	-50.29	6.19	3.00	11.41	-45.07	-13.00	-32.07	Н
3760.00	-41.25	5.32	3.00	10.03	-36.54	-13.00	-23.54	V
5640.00	-47.28	6.19	3.00	11.41	-42.06	-13.00	-29.06	V

GSM/TM3/GSM1900_ High Channel


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-50.81	5.36	3.00	9.62	-46.55	-13.00	-33.55	Н
5729.40	-53.72	6.24	3.00	11.46	-48.50	-13.00	-35.50	Н
3819.60	-47.57	5.36	3.00	9.62	-43.31	-13.00	-30.31	V
5729.40	-49.35	6.24	3.00	11.46	-44.13	-13.00	-31.13	V

Occupied Bandwidth and Emission Bandwidth 4.3

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% Bandwidth and -26dBc Bandwidth.

TEST CONFIGURATION



TEST PROCEDURE


- The EUT was set up for the max output power with pseudo random data modulation;
- The Occupied bandwidth and Emission Bandwidth were measured with Spectrum AnalyzerN9020A;
- Set RBW=5.1KHz, VBW=51KHz, Span=1MHz, SWT=Auto;
- Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth
- These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).


TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Occupied Bandwidth (99% BW) (KHz)	Emission Bandwidth (-26 dBc BW) (KHz)	Verdict
GSM/TM1	128	824.2	244.67	312.60	PASS
/GSM850	190	836.6	246.19	316.90	PASS
/G3IVI650	251	848.8	246.67	317.80	PASS
GSM/TM3	128	824.2	251.16	321.10	PASS
/EDGE850	190	836.6	253.27	315.30	PASS
/EDGE650	251	848.8	251.64	314.00	PASS
GSM/TM1	512	1850.2	245.45	314.90	PASS
/GSM1900	661	1880.0	246.06	311.70	PASS
/G3W1900	810	1909.8	245.00	308.00	PASS
CCM/TM2	512	1850.2	246.80	306.40	PASS
GSM/TM3 /EDGE1900	661	1880.0	246.94	311.10	PASS
/EDGE1900	810	1909.8	248.49	310.20	PASS

Remark:

- 1. Test results including cable loss;
- 2. Please refer to following plots;






Band Edge Complicance 4.4

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500) to ensure max power transmission and proper modulation.

TEST CONFIGURATION



TEST PROCEDURE


- 1. The EUT was set up for the max output power with pseudo random data modulation;
- The power was measured with Spectrum Analyzer N9020A;
- Set RBW=5.1KHz,VBW=51KHz,Span=1MHz,SWT=Auto, Dector: RMS;
- These measurements were done at 2 frequencies, 1850.20 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz and 848.80 MHz for GSM850 band. (bottom and top of operational frequency range).


TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Band Edg Compliance (dBm)	Limits (dBm)	Verdict	
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS	
G2101/ 1 101 1/G2101020	251	848.8	<-13dBm	-13dBm	PASS	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS	
GSIVI/TIVIS/EDGE630	251	848.8	<-13dBm	-13dBm	PASS	
CSM/TM1/CSM1000	512	1850.2	<-13dBm	-13dBm	PASS	
GSM/TM1/GSM1900	810	1909.8	<-13dBm	-13dBm	PASS	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS	
GSIVI/TIVIS/EDGE 1900	810	1909.8	<-13dBm	-13dBm	PASS	

Remark:

- 1. Test results including cable loss;
- 2. Please refer to following plots;






4.5 **Spurious Emssion on Antenna Port**

TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 and RSS-GEN the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 9 KHz to 20 GHz, data taken from 30 MHz to 20 GHz. For GSM850, this equates to a frequency range of 9 KHz to 9 GHz,data taken from 30 MHz to 9 GHz.
- 2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
- The procedure to get the conducted spurious emission is as follows: The trace mode is set to MaxHold to get the highest signal at each frequency; Wait 25 seconds: Get the result.
- 4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

TEST CONFIGURATION



TEST PROCEDURE

- The EUT was set up for the max output power with pseudo random data modulation:
- The power was measured with Spectrum Analyzer N9020A:
- These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST LIMIT


Part 24.238, Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict	
	128	824.2	<-13dBm	-13dBm		
GSM/TM1/GSM850	190	836.6	<-13dBm	-13dBm	PASS	
	251	848.8	<-13dBm	-13dBm		
	128	824.2	<-13dBm	-13dBm		
GSM/TM3/EDGE850	190	836.6	<-13dBm	-13dBm P		
	251	848.8	<-13dBm	-13dBm		
	512	1850.2	<-13dBm	-13dBm		
GSM/TM1/GSM1900	661	1880.0	0.0 <-13dBm		PASS	
	810	1909.8	<-13dBm	-13dBm		
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm		
	DGE1900 661		<-13dBm	-13dBm	PASS	
	810	1909.8	<-13dBm	-13dBm		


Remark:


- Test results including cable loss;
 Please refer to following plots;
- 3. Not reorded test plots from 9 KHz to 30 MHz as emission levels 20dB lower than emission limit;







Spurious Emssion on Antenna Port GSM/TM1/GSM1900 Channel 512 / 1850.2 MHz enter Freq 4.000000000 GHz | Freq | AVg Type: RMS Avg|Hold:>50/50 Avg Type: RMS Avg[Hold:>3/3 Mkr1 359.80 MHz -38.159 dBm Mkr2 2.662 GHz -42.690 dBm Ref Offset 7.98 dB Ref 25.00 dBm Ref Offset 8.15 dB Ref 25.00 dBm Center Free Center Fre Start Fre Stop Free Stop Free 7.000000000 GH CF Step 600.000000 MH: and subsequent works Freq Offse Freq Offse Start 30.0 MHz #Res BW 1.0 MHz Start 1.000 GHz #Res BW 1.0 MHz Stop 7.000 GHz #Sweep 5.000 s (1001 pts) #VBW 3.0 MHz* #VBW 3.0 MHz* 30 MHz - 1000 MHz 1 GHz - 7 GHz RL RF 50 Q AC enter Freq 10.300000000 GHz PHO: Fast Fraint.ow #Atten: 20 dB RL #F 500 AC enter Freq 16.800000000 GHz Fraint.ov #Atten: 20 dB Avg Type: RMS AvglHold: 3/3 AUGNAL Avg Type: RMS Avg|Hold: 3/3 Mkr1 12.761 8 GHz -60.459 dBm Auto Tun Mkr1 16.403 2 GHz -56.982 dBm Center Free Center Fre 16.800000000 GH Start Fred Start Fre Stop Free Stop Free CF Step 660.000000 MH: CF Step 640.000000 MHz sto Man **♦**¹ Freq Offse Stop 13.600 GHz #Sweep 5.000 s (1001 pts) Stop 20.000 GHz #Sweep 5.000 s (1001 pts) Start 7.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz* 13.6 GHz - 20 GHz 7 GHz - 13.6 GHz





Spurious Emssion on Antenna Port GSM/TM3/EDGE1900 Channel 512 / 1850.2 MHz RL RF SOO AK enter Freq 515.000000 MHz PRO: Fast IFGaint.ow #Atten: 36 dB AVg Type: RMS Avg|Hold:>50/50 Avg Type: RMS Avg[Hold:>3/3 Mkr1 414.12 MHz -38.350 dBm Auto Tur Mkr2 2.668 GHz -42.882 dBm Ref Offset 7.98 dB Ref 25.00 dBm Ref Offset 8.15 dB Ref 25.00 dBm Center Free Center Fre Start Free Start Fre Stop Free Stop Free 7.000000000 GH CF Step 600.000000 MH: Freq Offse Freq Offse Stop 1.0000 GHz Sweep 1.200 ms (1001 pts) Start 30.0 MHz #Res BW 1.0 MHz Start 1.000 GHz #Res BW 1.0 MHz Stop 7.000 GHz #Sweep 5.000 s (1001 pts) #VBW 3.0 MHz* #VBW 3.0 MHz* 30 MHz - 1000 MHz 1 GHz - 7 GHz RL RF SO R AC enter Freq 10.300000000 GHz PNO: Fast Foalind.w #Atten: 20 dB RL #F 500 AC enter Freq 16.800000000 GHz Fraint.ov #Atten: 20 dB Avg Type: RMS AvgIHold: 3/3 AUGNAL Avg Type: RMS Avg|Hold: 3/3 Mkr1 12.821 2 GHz -60.720 dBm Auto Tun Mkr1 16.428 8 GHz -56.979 dBm Center Free Center Fre 16.800000000 GH Start Free Start Fre Stop Free Stop Free CF Step 660.000000 MHz CF Step 640.000000 MHz sto Man ϕ^1 Freq Offse Stop 13.600 GHz #Sweep 5.000 s (1001 pts) Stop 20.000 GHz #Sweep 5.000 s (1001 pts) Start 7.000 GHz #Res BW 1.0 MHz #VBW 3.0 MHz* 13.6 GHz - 20 GHz 7 GHz - 13.6 GHz





4.6 Frequency Stability Test

TEST APPLICABLE


- 1. According to FCC Part 2 Section 2.1055 (a)(1) and RSS-GEN, the frequency stability shall be measured with variation of ambient temperature from -30°C to +50°C centigrade.
- 2. According to FCC Part 2 Section 2.1055 (E) (2) and RSS-GEN, for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- 3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 3.40V.

TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500).

- 1. Measure the carrier frequency at room temperature;
- 2. Subject the EUT to overnight soak at -30°C;
- With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on middle channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
- 4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
- 5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
- 6. Subject the EUT to overnight soak at +50°C;
- 7. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
- 8. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
- 9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure;

TEST CONFIGURATION



TEST LIMITS

For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.40VDC and 4.20VDC, with a nominal voltage of 3.70DC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

TEST RESULTS

GSM/TM1/GSM850								
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict			
3.40	25	-23	-0.027	±2.50	PASS			
3.70	25	16	0.020	±2.50	PASS			
4.20	25	45	0.054	±2.50	PASS			
3.70	-30	-9	-0.011	±2.50	PASS			
3.70	-20	34	0.041	±2.50	PASS			
3.70	-10	-38	-0.046	±2.50	PASS			
3.70	0	-28	-0.033	±2.50	PASS			
3.70	10	18	0.021	±2.50	PASS			
3.70	20	-46	-0.055	±2.50	PASS			
3.70	30	-30	-0.036	±2.50	PASS			
3.70	40	27	0.032	±2.50	PASS			
3.70	50	-10	-0.012	±2.50	PASS			

	GSM/TM3/EDGE850								
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict				
3.40	25	27	0.033	±2.50	PASS				
3.70	25	49	0.058	±2.50	PASS				
4.20	25	48	0.058	±2.50	PASS				
3.70	-30	34	0.040	±2.50	PASS				
3.70	-20	-12	-0.014	±2.50	PASS				
3.70	-10	10	0.012	±2.50	PASS				
3.70	0	-27	-0.033	±2.50	PASS				
3.70	10	-39	-0.047	±2.50	PASS				
3.70	20	19	0.022	±2.50	PASS				
3.70	30	33	0.039	±2.50	PASS				
3.70	40	-12	-0.014	±2.50	PASS				
3.70	50	-23	-0.028	±2.50	PASS				

GSM/TM1/GSM1900							
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict		
3.40	25	38	0.020	±2.50	PASS		
3.70	25	-11	-0.006	±2.50	PASS		
4.20	25	-5	-0.003	±2.50	PASS		
3.70	-30	22	0.012	±2.50	PASS		
3.70	-20	-13	-0.007	±2.50	PASS		
3.70	-10	41	0.022	±2.50	PASS		
3.70	0	-31	-0.016	±2.50	PASS		
3.70	10	-7	-0.004	±2.50	PASS		
3.70	20	-45	-0.024	±2.50	PASS		
3.70	30	-13	-0.007	±2.50	PASS		
3.70	40	-36	-0.019	±2.50	PASS		
3.70	50	20	0.011	±2.50	PASS		


	GSM/TM3/EDGE1900								
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict				
3.40	25	-28	-0.015	±2.50	PASS				
3.70	25	-35	-0.018	±2.50	PASS				
4.20	25	5	0.002	±2.50	PASS				
3.70	-30	-38	-0.020	±2.50	PASS				
3.70	-20	-49	-0.026	±2.50	PASS				
3.70	-10	-43	-0.023	±2.50	PASS				
3.70	0	-44	-0.023	±2.50	PASS				
3.70	10	-38	-0.020	±2.50	PASS				
3.70	20	-1	-0.001	±2.50	PASS				
3.70	30	-17	-0.009	±2.50	PASS				
3.70	40	-36	-0.019	±2.50	PASS				
3.70	50	24	0.013	±2.50	PASS				

4.7 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE


Use spectrum to measure the total peak power and record as P_{Pk}. Use spectrum to measure the total average power and record as P_{Avg}. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm).


Determine the PAPR from:

PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict
	512	1850.20	2.61	13.0	
GSM/TM1/GSM1900	661	1880.00	2.60	13.0	PASS
	810	1909.80	2.62	13.0	
	512	1850.20	5.71	13.0	
GSM/TM3/EDGE1900	661	1880.00	5.73	13.0	PASS
	810	1909.80	5.79	13.0	
	128	824.2	2.62	13.0	
GSM/TM1/GSM850	190	836.6	2.62	13.0	PASS
	251	848.8	2.60	13.0	
	128	824.2	5.31	13.0	
GSM/TM3/EDGE850	190	836.6	5.37	13.0	PASS
	251	848.8	5.29	13.0	





TEST SETUP PHOTOGRAPHS OF EUT 5

Please refer to separated files for Test Setup Photos of the EUT.

EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

7 INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

.....End of Report.....