## RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0

for 1-g SAR and  $\leqslant$  7.5 for 10-g extremity SAR, where

 $\ensuremath{\mbox{f(GHz)}}$  is the RF channel transmit frequency in  $\ensuremath{\mbox{GHz}}$ 

Power and distance are rounded to the nearest  ${\tt mW}$  and  ${\tt mm}$  before calculation

The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30 where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt
```

Field strength =89.89dBuV/m @3m Ant gain 0 dBi; so Ant numeric gain=1

So pt={ $[10^{(89.89/20)}/10^6 \text{ x3}]^2/30\text{x1}$ }x1000 mW =0.3mW So  $(0.3\text{mW}/5\text{mm}) \times \sqrt{2.44}$  GHz = 0.1 <3

Then SAR evaluation is not required