



BUREAU
VERITAS

Test Report No.: FS170314N100

RF EXPOSURE REPORT

Applicant	KAIZHENG TOYS FACTORY
Address	HUAIDONG INDUSTRIAL ZONE, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA

Manufacturer or Supplier	KAIZHENG TOYS FACTORY
Address	HUAIDONG INDUSTRIAL ZONE, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Product	REMOTE CONTROL AIRCRAFT CAMERA
Brand Name	N/A
Model	H98WH(Camera)
Additional Model & Model Difference	AV-DRC04-101, H98, H98C, H23, H23W, H8MINI, M15, M23, M25, XX1, XX2, XX3, XX5, XX6, XX7, XX8, XX9, XX10, XX12, XX13, XX15, XX18, XX19, XX20, XX21, XX22, XX23, XX25, KK2, KK3, KK4, KK5, KK6, KK8, KK9, KK10, KK12, KK13, 8229
Date of tests	Apr. 14, 2017 ~ May 12, 2017

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Approved by Breeze Jiang Project Engineer/ EMC Department	Approved by Chris Chen Manager / EMC Department

Date: May 12, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



BUREAU
VERITAS

Test Report No.: FS170314N100

Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



**BUREAU
VERITAS** Test Report No.: FS170314N100

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170314N100	Original release	May 12, 2017



BUREAU
VERITAS Test Report No.: FS170314N100

1. CERTIFICATION

FCC ID:	2ALSE-KAIZHENGH98C
PRODUCT:	REMOTE CONTROL AIRCRAFT CAMERA
BRAND NAME:	N/A
MODEL NO.:	H98WH(Camera)
ADDITIONAL NO.:	AV-DRC04-101, H98, H98C, H23, H23W, H8MINI, M15, M23, M25, XX1, XX2, XX3, XX5, XX6, XX7, XX8, XX9, XX10, XX12, XX13, XX15, XX18, XX19, XX20, XX21, XX22, XX23, XX25, KK2, KK3, KK4, KK5, KK6, KK8, KK9, KK10, KK12, KK13, 8229
TEST SAMPLE:	Engineering Sample
APPLICANT:	KAIZHENG TOYS FACTORY
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1



BUREAU
VERITAS

Test Report No.: FS170314N100

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Total Gain (dBi)	Antenna Type
Chain 0	0	0	Integral PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
2412-2462	14	+2	12	16

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2412	12.78
802.11g	2412	12.38

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	16	0	20	0.00792	1.0

--- END ---