



1601 North A.W. Grimes Blvd., Suite B
 Round Rock, TX 78665
 e-mail: info@ptitest.com
 (512) 244-3371 Fax: (512) 244-1846

1.0 Maximum Permissible Exposure Evaluation (Supplements the test report.)

The measured power is considered for the intended use of the device and resulting RF exposure to the user.

1.2 Criteria

Section Reference	Date
447498 D01 General RF Exposure Guidance v06	8 Feb 2018

1.3 Procedure

Using measurement of peak power and considering the intended application, determine the permissible exposure level, applicability of exclusion, or whether additional exposure tests (SAR) are indicated. When applicable justify conclusion for selected exposure level and separation distance.

1.4 Power to Exposure Calculation

Power is determined by conducted measurement. SAR exemption method is applied for 5 mm spacing assuming possibility of the detector being activate while being held and installed. Device is insulated in a sealed plastic bag. General public/uncontrolled exposure assumed.

Table 1.4.1 Power Calculation for Exposure (Highest frequency 0.91833 GHz)

Measured Conducted Power dBm	Source Duty Cycle Factor dB	Antenna Gain dBi	Calculated EIRP dBm	EIRP In Linear Terms mW
13.5	-16.5	0*	-30.0	0.001

1.5 SAR Exemption Calculation – FCC

Applicable requirement: KDB 447498 Clause 4.3.1 Section 1

Calculation (max power including tune up tolerance = 0.001 mW):

$$[(0.001 \text{ mW})/(5 \text{ mm})] \cdot [\sqrt{0.91833 \text{ (GHz)}}] = 0.0002$$

$$0.0002 \leq 3.0$$

Therefore, the device meets the applicable FCC SAR exemption requirements.

Signed:

A handwritten signature in black ink, appearing to read "Eric Lifsey". The signature is fluid and cursive, with a large, stylized 'E' at the beginning.

Eric Lifsey
