Report No.: AGC05843161101FE03 Page 1 of 38

FCC Test Report

Report No.: AGC00374170401FE03

FCC ID : 2ALSWQI1851

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Feature Phone

BRAND NAME : QUADE

MODEL NAME : QI1851

CLIENT: Shenzhen Uoshon Communication Technology Limited.

DATE OF ISSUE : May. 11, 2017

STANDARD(S) FCC Part 15 Rules

TEST PROCEDURE(S) DA 00-705

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC00374170401FE03 Page 2 of 38

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May. 11, 2017	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RECEIVER INPUT BANDWIDTH	7
2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE	7
2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR	7
2.6. RELATED SUBMITTAL(S) / GRANT (S)	8
2.7. TEST METHODOLOGY	8
2.8. SPECIAL ACCESSORIES	8
2.9. EQUIPMENT MODIFICATIONS	8
3. MEASUREMENT UNCERTAINTY	9
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF EUT SYSTEM	10
5.2. EQUIPMENT USED IN EUT SYSTEM	10
5.3. SUMMARY OF TEST RESULTS	
6. TEST FACILITY	11
7. PEAK OUTPUT POWER	13
7.1. MEASUREMENT PROCEDURE	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
7.3. LIMITS AND MEASUREMENT RESULT	
8. 20DB BANDWIDTH	15
8.1. MEASUREMENT PROCEDURE	15
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
8.3. LIMITS AND MEASUREMENT RESULTS	15
9. CONDUCTED SPURIOUS EMISSION	17
9.1. MEASUREMENT PROCEDURE	17
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
9.3. MEASUREMENT EQUIPMENT USED	17
9.4. LIMITS AND MEASUREMENT RESULT	17
10. RADIATED EMISSION	20
10.1. MEASUREMENT PROCEDURE	20
10.2. TEST SETUP	22
10.3. TEST RESULT	23

11. BAND EDGE EMISSION	26
11.1. MEASUREMENT PROCEDURE	26
11.2. TEST SET-UP	26
11.3. Radiated TEST RESULT	26
11.4 Conducted TEST RESULT	27
12. NUMBER OF HOPPING FREQUENCY	29
12.1. MEASUREMENT PROCEDURE	29
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	29
12.3. MEASUREMENT EQUIPMENT USED	29
12.4. LIMITS AND MEASUREMENT RESULT	29
13.1. MEASUREMENT PROCEDURE	30
13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	30
13.3. MEASUREMENT EQUIPMENT USED	30
13.4. LIMITS AND MEASUREMENT RESULT	30
Test Graph	31
14. FREQUENCY SEPARATION	32
14.1. MEASUREMENT PROCEDURE	32
14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	32
14.3. MEASUREMENT EQUIPMENT USED	32
14.4. LIMITS AND MEASUREMENT RESULT	32
15. FCC LINE CONDUCTED EMISSION TEST	33
15.1. LIMITS OF LINE CONDUCTED EMISSION TEST	33
15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	33
15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	34
15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	34
15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	35
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	37

Page 5 of 38

1. VERIFICATION OF CONFORMITY

Applicant	Shenzhen Uoshon Communication Technology Limited.		
ΔΛΛΓΔΘΘ	2/F,NO.A building,NO.139,Zhongxing Road, Bantian, Longgang, Shenzhen, China, 518129.		
Manufacturer	Shenzhen Newdell Science & Technology Co., Ltd.		
Address 4/F,NO.A building,NO.139,Zhongxing Road, Bantian, Longgang, Shenz China.			
Product Designation	Feature Phone		
Brand Name	QUADE		
Test Model	QI1851		
Date of test	Apr. 25, 2017~May. 10, 2017		
Deviation	None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Tested By	donjon strong	
	Donjon Huang(Huang Dongyang)	May. 10, 2017
Reviewed By	Bore xie	
	Bart Xie(Xie Xiaobin)	May. 11, 2017
Approved By	Solya shong	
	Solger Zhang(Zhang Hongyi) Authorized Officer	May. 11, 2017

Page 6 of 38

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is "Feature Phone" designed as a "Communication Device". It is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following

	<u> </u>
Operation Frequency	2.402 GHz to 2.480GHz
Bluetooth Version	V 2.1
Modulation	GFSK
Number of channels	79(For BR)
Hardware Version	FF777-MB-V0.1
Software Version	FF777M01_ND_S100_QUADE_V1_QI1851_20170426_1604
Antenna Designation	PIFA Antenna
Antenna Gain	1.2dBi
Power Supply	DC3.7V by Battery

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
2400~2483.5MHZ	39	2441 MHZ
	40	2442 MHZ
	••	:
	77	2479 MHZ
	78	2480 MHZ

Page 7 of 38

2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a 79 hopping sequence in data mode: 40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67 56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59 72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75 09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06 01, 51, 03, 55, 05, 04

2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For ehavior zation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire. LAP(24 bits), 4LSB's (4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate te Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following ehavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.

Page 8 of 38

2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ALSWQI1851** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in FCC DA 00-705. Radiated testing was performed at an antenna to EUT distance 3 meters.

2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 9 of 38

3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB Radiated measurement: +/- 3.2dB

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Normal Hopping

Note:

^{1.} All the test modes can be supply by Built-in Li-ion battery, only the result of the worst case was recorded in the report, if no other cases.


^{2.} For Radiated Emission, 3axis were chosen for testing for each applicable mode.

Report No.: AGC00374170401FE03 Page 10 of 38

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configuration:



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Note
1	Feature Phone	QI1851	2ALSWQI1851	EUT
2	Adapter	QI1851	DC5V /500mA	Accessory
3	Battery	QI1851	DC3.7V/800mAh	Accessory

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Peak Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Spurious Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant
§15.247	Frequency Separation	Compliant

Report No.: AGC00374170401FE03 Page 11 of 38

6. TEST FACILITY

Site Dongguan Precise Testing Service Co., Ltd.	
Location Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,	
FCC Registration No.	371540
Description The test site is constructed and calibrated to meet the FCC requirements ANSI C63.10:2013.	

ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017	
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 3, 2016	July 2, 2017	
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 3, 2016	July 2, 2017	
RF Cable	SCHWARZBECK	AK9515E	96221	July 3, 2016	July 2, 2017	
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 5, 2016	June 4, 2017	
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A	
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 5, 2016	June 4, 2017	
Spectrum analyzer	Agilent	E4407B	MY46185649	June 5, 2016	June 4, 2017	
Power Probe	R&S	NRP-Z23	100323	July 24,2016	July 23,2017	
RF attenuator	N/A	RFA20db	68	N/A	N/A	

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

	Radiated Emission Test Site												
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration								
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017								
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 10, 2016	July 9, 2017								
Spectrum Analyzer Agilent		E4411B	MY4511453	July 3, 2016	July 2, 2017								
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 6, 2016	July 5, 2017								
RF Cable	SCHWARZBECK	AK9515H	96220	July 7, 2016	July 6, 2017								
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 5, 2016	June 4, 2017								
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A								

Report No.: AGC00374170401FE03 Page 12 of 38

Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 5, 2016	June 4, 2017
Power Probe	R&S	NRP-Z23	100323	July 24,2016	July 23,2017
RF attenuator	N/A	RFA20db	68	N/A	N/A

Conducted Emission Test Site												
Name of Equipment	Manutacturer		Model Number Serial Number		Due Calibration							
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017							
Artificial Mains Network	Narda	L2-16B	000WX31025	July 7, 2016	July 6, 2017							
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 7, 2016	July 6, 2017							
RF Cable	SCHWARZBECK	AK9515E	96222	July 3, 2016	July 2, 2017							
Shielded Room	CHENGYU	843	PTS-002	June 5,2016	June 4,2017							

Report No.: AGC05843161101FE03

Page 13 of 38

7. PEAK OUTPUT POWER

7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, middle and the bottom operation frequency individually.
- 3. RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW.
- 4. Record the maximum power from the Spectrum Analyzer.


For average power test:

- 1. Connect EUT RF output port to power probe through an RF attenuator.
- 2. Connect the power probe to the PC.
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Record the maximum power from the software.

Note: The EUT was tested according to DA000705 for compliance to FCC 47CFR 15.247 requirements.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

PEAK POWER TEST SETUP



Report No.: AGC00374170401FE03 Page 14 of 38

7.3. LIMITS AND MEASUREMENT RESULT

Mode	Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
	2.402	0.005	30	Pass
GFSK	2.441	-0.263	30	Pass
	2.480	-0.913	30	Pass


Page 15 of 38

8. 20DB BANDWIDTH

8.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




8.3. LIMITS AND MEASUREMENT RESULTS

Mode	Channel.	EBW [KHz]	Verdict
	LCH	833.7	PASS
GFSK	MCH	834.4	PASS
	НСН	834.5	PASS

Test Graph





Page 17 of 38

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- 3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
 RBW = 100 kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak.
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to DA000705 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW > RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW > RBW) are conform to the requirement.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2


9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6


9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT										
Applicable Limite	Measurement Result									
Applicable Limits	Test Data	Criteria								
In any 100 KHz Bandwidth Outside the	At least -20dBc than the limit									
frequency band in which the spread spectrum	Specified on the BOTTOM	PASS								
intentional radiator is operating, the radio frequency	Channel									
power that is produce by the intentional radiator										
shall be at least 20 dB below that in 100KHz										
bandwidth within the band that contains the highest										
level of the desired power.	At least -20dBc than the limit	DACC								
In addition, radiation emissions which fall in the	Specified on the TOP Channel	PASS								
restricted bands, as defined in §15.205(a), must also										
comply with the radiated emission limits specified										
in§15.209(a))										


Test Graph











Page 20 of 38

10. RADIATED EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC00374170401FE03 Page 21 of 38

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting				
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP				
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP				
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP				
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average				

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 22 of 38

10.2. TEST SETUP

RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz




Page 23 of 38

10.3. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		49.4000	0.46	11.28	11.74	40.00	-28.26	peak			
2		97.9000	3.67	8.38	12.05	43.50	-31.45	peak			
3		139.9333	0.39	15.17	15.56	43.50	-27.94	peak			
4		571.5833	0.39	23.02	23.41	46.00	-22.59	peak			
5		793.0667	1.56	27.22	28.78	46.00	-17.22	peak			
6	*	953.1167	1.05	29.97	31.02	46.00	-14.98	peak			

RESULT: PASS

Page 24 of 38

RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		41.3166	12.88	8.81	21.69	40.00	-18.31	peak			
2		88.2000	9.32	4.74	14.06	43.50	-29.44	peak			
3		151.2500	5.89	15.27	21.16	43.50	-22.34	peak			
4		207.8333	10.57	9.77	20.34	43.50	-23.16	peak			
5		481.0500	1.77	20.93	22.70	46.00	-23.30	peak			
6	*	804.3832	1.34	27.32	28.66	46.00	-17.34	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The GFSK mode at low channel is the worst case and recorded in the report.

Page 25 of 38

RADIATED EMISSION TEST- (ABOVE 1GHZ)

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Common		
Low Channel (2402 MHz)									
4804	63.86	-3.62	60.24	74	-13.76	Pk	Vertical		
4804	42.87	-3.62	39.25	54	-14.75	AV	Vertical		
7206	63.39	-0.9	62.49	74	-11.51	pk	Vertical		
7206	41.58	-0.9	40.68	54	-13.32	AV	Vertical		
4804	63.27	-3.64	59.63	74	-14.37	Pk	Horizontal		
4804	45.88	-3.64	42.24	54	-11.76	AV	Horizontal		
			Mid Channel (2441	MHz)					
4882	65.28	-3.65	61.63	74	-12.37	Pk	Vertical		
4882	43.55	-3.65	39.90	54	-14.10	AV	Vertical		
7323	61.84	-0.82	61.02	74	-12.98	Pk	Vertical		
7323	41.75	-0.82	40.93	54	-13.07	AV	Vertical		
4882	64.65	-3.68	60.97	74	-13.03	Pk	Horizontal		
4882	43.40	-3.68	39.72	54	-14.28	AV	Horizontal		
		ŀ	High Channel (248	0 MHz)					
4960	62.56	-3.59	58.97	74	-15.03	pk	Vertical		
4960	43.89	-3.59	40.30	54	-13.70	AV	Vertical		
4960	62.10	-3.59	58.51	74	-15.49	pk	Horizontal		
4960	42.12	-3.59	38.53	54	-15.47	AV	Horizontal		

Note:

- 1) 30MHz~25GHz:(All modes were tested, only the worst case record in the report.)
- 2) Factor = Antenna Factor + Cable Loss Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Leve - Limit

RESULT: PASS

Page 26 of 38

11. BAND EDGE EMISSION


11.1. MEASUREMENT PROCEDURE

- 1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100kHz. The video bandwidth is set to 300kHz.
- 2. Transmitter set to the normal hopping mode at 2.4 and 2.4835 GHz.

11.2. TEST SET-UP

Radiated same as 10.2

Conducted set up



11.3. Radiated TEST RESULT

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	
			GF	SK			
2399.9	63.76	-12.99	50.77	74	-23.23	peak	Vertical
2399.9	53.51	-12.99	40.52	54	-13.48	AVG	Vertical
2399.9	62.13	-12.99	49.14	74	-24.86	peak	Horizontal
2399.9	47.97	-12.99	34.98	54	-19.02	AVG	Horizontal
2483.6	62.23	-12.78	49.45	74	-24.55	peak	Vertical
2483.6	53.20	-12.78	40.42	54	-13.58	AVG	Vertical
2483.6	62.91	-12.78	50.13	74	-23.87	peak	Horizontal
2483.6	53.24	-12.78	40.46	54	-13.54	AVG	Horizontal

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.


Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The "Factor" value can be calculated automatically by software of measurement system.

Report No.: AGC00374170401FE03 Page 27 of 38

11.4 Conducted TEST RESULT

Test Graph





Note: All modes were tested, only the worst case record in the report.

Report No.: AGC00374170401FE03 Page 29 of 38

12. NUMBER OF HOPPING FREQUENCY

12.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz
- 4. Set the Spectrum Analyzer as RBW>=1%span, VBW>=RBW.

12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

12.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6

12.4. LIMITS AND MEASUREMENT RESULT

Mode	Channel.	Number of Hopping Channel	Verdict	
GFSK	Нор	79	PASS	

Note: All modes were tested, only the worst case record in the report.

Test Graph



Page 30 of 38

13. TIME OF OCCUPANCY (DWELL TIME)

13.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: Zero span, centered on a hopping channel.
- 2. RBW shall be ≤channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- 4. Detector function: Peak. Trace: Max hold.
- 5. Use the marker-delta function to determine the transmit time per hop.
- 6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) \times (period specified in the requirements / analyzer sweep time)

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

13.4. LIMITS AND MEASUREMENT RESULT

Channel.	Burst Width [ms/hop/ch]	Number of hops in the period specified in the requirements	Dwell Time[ms]	Verdict	Limit (ms)
LCH	2.900	10*6.32	183.28	PASS	400
MCH	2.905	7*6.32	128.5172	PASS	400
HCH	2.900	10*6.32	183.28	PASS	400


Note: The GFSK(DH5) modulation is the worst case and recorded in the report.


(period specified in the requirements / analyzer sweep time)=(79*0.4)/5=6.32


(Number of hops in the period specified in the requirements)=6.32* number of hops on spectrum analyzer

Dwell Time= Burst Width*(Number of hops in the period specified in the requirements)

Test Graph







Report No.: AGC05843161101FE03

Page 32 of 38

14. FREQUENCY SEPARATION

14.1. MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold

14.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

14.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.3

14.4. LIMITS AND MEASUREMENT RESULT

Mode	Channel.	Carrier Frequency Separation [MHz]	Verdict
GFSK	Нор	1.002	PASS

Note: All modes were tested, only the worst case record in the report.

Test Graph



Page 33 of 38

15. FCC LINE CONDUCTED EMISSION TEST


15.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage							
Frequency	Q.P.(dBuV)	Average(dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	56	46						
5MHz~30MHz	60	50						

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

15.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 34 of 38

15.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter which received 120V/60Hzpower by a LISN...
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


15.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

Page 35 of 38


15.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



No.	Freq. (MHz)		iding_L (dBuV)		Correct Factor		asurer (dBuV)		1	mit uV)		rgin fB)	P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4540	32.89		25.78	10.37	43.26		36.15	56.80	46.80	-13.54	-10.65	Р	
2	0.9140	29.29		15.86	10.40	39.69		26.26	56.00	46.00	-16.31	-19.74	Р	
3	1.8776	27.64		19.08	10.26	37.90		29.34	56.00	46.00	-18.10	-16.66	Р	
4	3.7219	26.43		9.74	10.47	36.90		20.21	56.00	46.00	-19.10	-25.79	Р	
5	5.6977	26.87		17.79	10.26	37.13		28.05	60.00	50.00	-22.87	-21.95	Р	
6	14.2538	26.51		15.60	10.12	36.63		25.72	60.00	50.00	-23.37	-24.28	Р	

Line Conducted Emission Test Line 2-N



No.	Freq.		ding_L (dBuV)		Correct Factor		easuren (dBuV)			mit uV)		rgin IB)	P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4218	34.83		24.52	10.35	45.18		34.87	57.41	47.41	-12.23	-12.54	Р	
2	0.8780	28.60		15.89	10.38	38.98		26.27	56.00	46.00	-17.02	-19.73	Р	
3	1.3020	28.76		16.29	10.38	39.14		26.67	56.00	46.00	-16.86	-19.33	Р	
4	1.7900	31.13		21.55	10.29	41.42		31.84	56.00	46.00	-14.58	-14.16	Р	
5	9.3696	28.30		19.20	10.34	38.64		29.54	60.00	50.00	-21.36	-20.46	Р	
6	14.3178	27.36		20.08	10.12	37.48		30.20	60.00	50.00	-22.52	-19.80	Р	


Page 37 of 38

APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



Report No.: AGC00374170401FE03 Page 38 of 38



----END OF REPORT----