FCC RF Test Report

APPLICANT : Planet Avvio EQUIPMENT : Mobile Phone

BRAND NAME : Mint MODEL NAME : M171

MARKETING NAME : Mint M171, M171 FCC ID : 2ALTAM171X

STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jun. 21, 2017 and testing was completed on Jul. 07, 2017. We, SPORTON International (ShenZhen) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON International (ShenZhen) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Frie Shih

Approved by: Jones Tsai / Manager

SPORTON International (ShenZhen) INC.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 1 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

TABLE OF CONTENTS

RE	VISIC	ON HISTORY	3
SU	ММА	RY OF TEST RESULT	4
1	GEN	IERAL DESCRIPTION	5
•	1.1	Applicant	
	1.2	Manufacturer	
	1.3	Product Feature of Equipment Under Test	
	1.4	Product Specification of Equipment Under Test	
	1.5	Modification of EUT	
	1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	
	1.7	Testing Location	
	1.8	Applicable Standards	7
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	8
	2.2	Connection Diagram of Test System	9
	2.3	Support Unit used in test configuration	10
	2.4	Measurement Results Explanation Example	10
3	CON	IDUCTED TEST RESULT	11
	3.1	Measuring Instruments	11
	3.2	Test Setup	11
	3.3	Test Result of Conducted Test	
	3.4	Conducted Output Power and ERP/EIRP	12
	3.5	Peak-to-Average Ratio	
	3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement	
	3.7	Conducted Band Edge	
	3.8	Conducted Spurious Emission	
	3.9	Frequency Stability	17
4	RAD	DIATED TEST ITEMS	
	4.1	Measuring Instruments	
	4.2	Test Setup	
	4.3	Test Result of Radiated Test	
	4.4	Field Strength of Spurious Radiation Measurement	19
5	LIST	OF MEASURING EQUIPMENT	20
6	UNC	ERTAINTY OF EVALUATION	21
ΑP	PEND	DIX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	DIX B. TEST RESULTS OF RADIATED TEST	
ΑP	PEND	DIX C. TEST SETUP PHOTOGRAPHS	

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 2 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE	
FG762108	Rev. 01	Initial issue of report	Jul. 12, 2017	

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 3 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	1
2.0	§2.1055 §22.355	Frequency Stability	< 2.5 ppm for Part 22H		
3.9	§2.1055 §24.235	for Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 14.47 dB at 11280 MHz

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 4 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

1 General Description

1.1 Applicant

Planet Avvio

Westside Plaza III – Office Suite 103,8200 NW 33 Street, Doral, Florida 33122

1.2 Manufacturer

Shenzhen Frog Technology Co.,Ltd

AB, 22F, Changhong Technology Building, High Tech South 12 Road, High Tech Park, Nanshan District, Shenzhen, China

1.3 Product Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Phone
Brand Name	Mint
Model Name	M171
FCC ID	2ALTAM171X
ELIT cupports Badios application	GSM/GPRS
EUT supports Radios application	Bluetooth V 2.1+EDR
IMEI Code	Conducted: 353175070000024/ 353175070000032
IMEI Code	Radiation: 353175070000883/353175070000891
HW Version	M128C
SW Version	MINT_M171_V02_20170613
EUT Stage Production Unit	

Remark:

- **1.** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose dual SIM1 card to perform all tests.

SPORTON International (ShenZhen) INC. TEL: 86-755-8637-9589

FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 5 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No. : FG762108

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification					
GSM/GPRS					
Tx Frequency	850:	824.2 MHz ~ 848.8 MHz			
	1900:	1850.2 MHz ~ 1909.8MHz			
	GSM/GF	PRS			
Rx Frequency	850:	869.2 MHz ~ 893.8 MHz			
	1900:	1930.2 MHz ~ 1989.8 MHz			
	GSM/GF	PRS			
Maximum Output Power to Antenna	850:	32.64 dBm			
	1900:	29.31 dBm			
Antenna Type	PIFA Antenna				
Antonno Coin	Cellular Band: -0.65 dBi				
Antenna Gain	PCS Band: 2.37 dBi				
Type of Modulation	GSM: GM	1SK			
i ype or inodulation	GPRS: GMSK				

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GSM	GMSK	0.9638	0.0150 ppm	243KGXW
Part 24E	GSM1900 GSM	GMSK	1.4723	0.0063 ppm	243KGXW

SPORTON International (ShenZhen) INC.TEL: 86-755-8637-9589
FAX: 86-755-8637-9595

FCC ID : 2ALTAM171X

Page Number : 6 of 21

Report Issued Date : Jul. 12, 2017

Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

1.7 Testing Location

Test Site	SPORTON International (ShenZhen) INC.				
	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District,				
	Shenzhen City, Guangdong Province, China				
Test Site Location	TEL: +86-755-8637-9589				
	FAX: +86-755-8637-9595				
Toot Site No	Sporton Site No.				
Test Site No.	TH01-SZ				

Report No. : FG762108

Test Site	SPORTON International (ShenZhen) INC.				
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China				
	TEL: +86-755- 3320-2398				
Toot Site No	Sporton Site No.	FCC Registration No.			
Test Site No.	03CH01-SZ	831040			

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 SPORTON International (ShenZhen) INC.
 Page Number
 : 7 of 21

 TEL: 86-755-8637-9589
 Report Issued Date
 : Jul. 12, 2017

 FAX: 86-755-8637-9595
 Report Version
 : Rev. 01

FCC ID : 2ALTAM171X Report Template No.: BU5-FG22/24/27 Version 1.2

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

- 1. 30 MHz to 10th harmonic for GSM850.
- 2. 30 MHz to 10th harmonic for GSM1900.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes							
Band	Radiated TCs	Conducted TCs					
GSM 850	■ GSM Link	■ GSM Link					
GSM 1900	■ GSM Link	■ GSM Link					


SPORTON International (ShenZhen) INC. TEL: 86-755-8637-9589

FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 8 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01


Report No. : FG762108

2.2 Connection Diagram of Test System

For 24E



For 22H



SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 9 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 4.0 + 10 = 14.0 (dB)

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 10 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No. : FG762108


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 11 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900.

According to KDB 412172 D01 Power Approach,

EIRP = P_T + G_T – L_C , ERP = EIRP -2.15, where

 P_T = transmitter output power in dBm

 G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure the maximum burst average power for GSM.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 12 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 3. Set EUT to transmit at maximum output power.
- 4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
- 5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 13 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
 The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- 4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- 5. Set the detection mode to peak, and the trace mode to max hold.
- Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
 (this is the reference value)
- 7. Determine the "-26 dB down amplitude" as equal to (Reference Value X).
- 8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- 9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. The band edges of low and high channels for the highest RF powers were measured.
- 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - =P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 15 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. The middle channel for the highest RF power within the transmitting frequency was measured.
- 5. The conducted spurious emission for the whole frequency range was taken.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
- = P(W) [43 + 10log(P)] (dB)
- = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
- = -13dBm.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 16 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was set up in the thermal chamber and connected with the system simulator.
- 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
- 3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 4. The variation in frequency was measured for the worst case.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 17 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 18 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

- The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
- 2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
- 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
- 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
- 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 9. Taking the record of output power at antenna port.
- 10. Repeat step 7 to step 8 for another polarization.
- 11.EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 12. ERP (dBm) = EIRP 2.15
- 13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

Page Number : 19 of 21
Report Issued Date : Jul. 12, 2017

Report No.: FG762108

Report Version : Rev. 01

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	Jul. 01, 2017	Apr.19, 2018	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 16, 2016	Jul. 01, 2017	Jul. 15, 2017	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 20, 2017	Jul. 07, 2017	Apr. 19, 2018	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5Ghz	Oct. 11, 2016	Jul. 07, 2017	Oct. 10, 2017	Radiation (03CH01-SZ
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz-2GHz	Apr. 25, 2017	Jul. 07, 2017	Apr. 24, 2018	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Nov. 19, 2016	Jul. 07, 2017	Nov. 18, 2017	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Aug.10, 2016	Jul. 07, 2017	Aug. 09, 2017	Radiation (03CH01-SZ)
Amplifier	HP	8447F	3113A04622	9kHz ~1300MHz / 30 dB	Jul. 16, 2016	Jul. 07, 2017	Jul. 15, 2017	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 16, 2016	Jul. 07, 2017	Jul. 15, 2017	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	NCR	Jul. 07, 2017	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 07, 2017	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 07, 2017	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 20 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.5 dB
Confidence of 95% (U = 2Uc(y))	2.5 UB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	3.5 dB
Confidence of 95% (U = 2Uc(y))	3.5 UB

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : 21 of 21
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850		GSM1900			
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.42	32.63	<mark>32.64</mark>	29.31	29.23	29.05
GPRS class 8	32.27	32.60	32.55	29.18	29.22	29.02
GPRS class 10	31.02	31.36	31.32	27.95	28.05	27.89
GPRS class 11	28.97	29.32	29.29	25.85	25.87	25.75
GPRS class 12	28.04	28.34	28.32	24.99	24.93	24.84

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A1 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2

ERP/EIRP

GSM850 (GT - LC= -0.65dBi)				
Channel	128	189	251	
	(Low)	(Mid)	(High)	
Frequency	004.0	836.4	0.40.0	
(MHz)	824.2		848.8	
Conducted Power (dBm)	32.42	32.63	32.64	
Conducted Power (Watts)	1.7458	1.8323	1.8365	
ERP(dBm)	29.62	29.83	29.84	
ERP(Watts)	0.9162	0.9616	0.9638	

GSM1900 (G _T - LC= 2.37dBi)				
	512	661	810	
Channel	(Low)	(Mid)	(High)	
Frequency	4050.0	1880	4000.0	
(MHz)	1850.2		1909.8	
Conducted Power (dBm)	29.31	29.23	29.05	
Conducted Power (Watts)	0.8531	0.8375	0.8035	
EIRP(dBm)	31.68	31.60	31.42	
EIRP(Watts)	1.4723	1.4454	1.3868	

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A2 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2


Peak-to-Average Ratio

Mode	GSM850(dB)	GSM1900(dB)	Limit: 13dB
Mod.	GSM		Result
Lowest CH	0.20	0.12	
Middle CH	0.20	0.20	PASS
Highest CH	0.12	0.12	1

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A3 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A4 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No.: FG762108


26dB Bandwidth

Mode	GSM850(MHz)	GSM1900(MHz)	
Mod.	GSM		
Lowest CH	0.315	0.311	
Middle CH	0.315	0.317	
Highest CH	0.316	0.315	

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A5 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2



TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A6 of A11
Report Issued Date : Jul. 12, 2017
Report Version : Rev. 01

Report No. : FG762108

Occupied Bandwidth

Mode	GSM850(MHz)	GSM1900(MHz)	
Mod.	GSM		
Lowest CH	0.243	0.242	
Middle CH	0.242	0.243	
Highest CH	0.243	0.243	

SPORTON International (ShenZhen) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: 2ALTAM171X Page Number : A7 of A11

Report Issued Date : Jul. 12, 2017

Report Version : Rev. 01

Report Template No.: BU5-FG22/24/27 Version 1.2