



FCC RF Test Report

APPLICANT : Planet Avvio LLC
EQUIPMENT : Mobile Phone
BRAND NAME : Mint
MODEL NAME : M345, Mint M345
MARKETING NAME : Mint M345
FCC ID : 2ALTAM345
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 22, 2017 and testing was completed on May 12, 2017. We, SPORTON International (ShenZhen) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON International (ShenZhen) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Approved by: Jones Tsai / Manager



SPORTON International (ShenZhen) INC.
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	10
2.4 Measurement Results Explanation Example	10
3 CONDUCTED TEST RESULT.....	11
3.1 Measuring Instruments.....	11
3.2 Test Setup	11
3.3 Test Result of Conducted Test.....	11
3.4 Conducted Output Power	12
3.5 Peak-to-Average Ratio	13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	14
3.7 Conducted Band Edge	15
3.8 Conducted Spurious Emission	16
3.9 Frequency Stability	17
4 RADIATED TEST ITEMS	18
4.1 Measuring Instruments.....	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test.....	18
4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	19
4.5 Field Strength of Spurious Radiation Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 UNCERTAINTY OF EVALUATION	23

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 27.20 dB at 3760.000 MHz



1 General Description

1.1 Applicant

Planet Avvio LLC

9725 NW 117th Ave., Medley, FL 33178, United States

1.2 Manufacturer

Shenzhen Crave Communication Co., Ltd.

Floor 3, Bldg8, Dongfangming Industrial City, No.83 Dabao Rd.,33 District, Shenzhen, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Mint
Model Name	M345, Mint M345
Marketing Name	Mint M345
FCC ID	2ALTAM345
EUT supports Radios application	GSM/GPRS/EGPRS (Downlink Only)/ WCDMA/HSPA/HSPA+(16QAM uplink is not supported) WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 352734080085135 Radiation: 352734080085093 ERP/EIRP: 352734080085150
HW Version	V13_MB_V1.3
SW Version	Mint_M345_V01_20170510
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM/GPRS: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM/GPRS: 850: 32.00 dBm 1900: 28.45 dBm WCDMA: Band V: 22.07 dBm Band II: 21.26 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK (Downlink Only) WCDMA: BPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Uplink is not supported)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GSM	GMSK	0.1067	0.0175 ppm	244KGXW
Part 22H	WCDMA Band V RMC 12.2Kbps	BPSK	0.0160	0.0179 ppm	4M16F9W
Part 24E	GSM1900 GSM	GMSK	1.7022	0.0180 ppm	244KGXW
Part 24E	WCDMA Band II RMC 12.2Kbps	BPSK	0.3170	0.0106 ppm	4M17F9W



1.7 Testing Location

Test Site	SPORTON International (ShenZhen) INC.
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595
Test Site No.	Sporton Site No. TH01-SZ

Test Site	SPORTON International (ShenZhen) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-3320-2398	
Test Site No.	Sporton Site No. 03CH03-SZ	FCC Registration No. 565805

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.0 + 10 = 14.0 \text{ (dB)} \end{aligned}$$

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.

Record the maximum PAPR level associated with a probability of 0.1%.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^\circ\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform (0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz) in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100



4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 07, 2016	May 05, 2017	May 06, 2017	Conducted (TH01-SZ)
Radio Communication Analyzer	Anritsu	MT8820C	6201563777	2G/3G/4G	Jan. 03, 2017	May 05, 2017	Jan. 02, 2018	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion	LP-150U	H2014081803	-40~+150°C	Jul. 16, 2016	May 05, 2017	Jul. 15, 2017	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 20, 2017	May 12, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	May 12, 2017	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Nov. 19, 2016	May 12, 2017	Nov. 18, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	May 12, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 11, 2016	May 12, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 06, 2017	May 12, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	NCR	May 12, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	May 12, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	May 12, 2017	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.8 dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.00	31.92	31.90	28.09	28.45	28.39
GPRS class 8	31.96	31.90	31.86	28.03	28.42	28.35
GPRS class 10	31.25	31.16	31.13	26.50	26.85	26.68
GPRS class 11	29.64	29.55	29.51	23.18	23.40	23.27
GPRS class 12	28.65	28.58	28.51	22.09	22.33	22.11

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
AMR 12.2K	22.06	22.00	22.02	21.24	21.17	21.15
RMC 12.2K	22.07	22.01	22.04	21.26	21.19	21.16
HSDPA Subtest-1	21.06	21.01	21.01	20.37	20.31	20.39
HSDPA Subtest-2	21.08	21.02	21.01	20.32	20.40	20.38
HSDPA Subtest-3	20.61	20.54	20.57	19.86	19.74	19.70
HSDPA Subtest-4	20.59	20.54	20.53	19.85	19.69	19.68
HSUPA Subtest-1	19.60	19.53	19.02	18.35	18.21	18.09
HSUPA Subtest-2	19.13	19.08	19.05	18.28	18.18	18.08
HSUPA Subtest-3	20.12	20.05	20.02	19.34	19.18	19.07
HSUPA Subtest-4	18.62	18.52	18.51	17.76	17.69	17.60
HSUPA Subtest-5	21.15	21.10	21.00	20.30	20.20	20.10

**ERP/EIRP**

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GSM	17.28	0.0535	6.96	0.0050
Middle		18.51	0.0710	8.71	0.0074
Highest		20.28	0.1067	11.14	0.0130
Lowest	WCDMA Band V RMC 12.2Kbps	9.88	0.0097	-1.10	0.0008
Middle		11.84	0.0153	1.31	0.0014
Highest		12.05	0.0160	2.01	0.0016
Limit	ERP < 7W	Result		PASS	


Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GSM	32.02	1.5922	32.11	1.6255
Middle		32.31	1.7022	32.31	1.7022
Highest		30.79	1.1995	31.15	1.3032
Lowest	WCDMA Band II RMC 12.2Kbps	24.79	0.3013	25.01	0.3170
Middle		24.64	0.2911	24.78	0.3006
Highest		23.63	0.2307	23.96	0.2489
Limit	EIRP < 2W	Result		PASS	




Peak-to-Average Ratio

Mode	GSM850(dB)	GSM1900(dB)	Limit: 13dB
Mod.	GSM	GSM	Result
Lowest CH	0.12	0.12	
Middle CH	0.14	0.20	
Highest CH	0.12	0.17	PASS

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.13	3.22	
Middle CH	3.28	3.33	
Highest CH	3.04	3.07	PASS







**26dB Bandwidth**

Mode	GSM850(MHz)	GSM1900(MHz)
Mod.	GSM	GSM
Lowest CH	0.317	0.316
Middle CH	0.317	0.317
Highest CH	0.315	0.316

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.68	4.67
Middle CH	4.67	4.69
Highest CH	4.68	4.69









Occupied Bandwidth

Mode	GSM850(MHz)	GSM1900(MHz)
Mod.	GSM	GSM
Lowest CH	0.244	0.244
Middle CH	0.244	0.242
Highest CH	0.242	0.244

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.14	4.15
Middle CH	4.16	4.17
Highest CH	4.15	4.16









Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Highest Band Edge



GSM1900 (GSM)

Lowest Band Edge

Highest Band Edge







WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge

Highest Band Edge



WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge


Highest Band Edge





Conducted Spurious Emission

GSM850 (GSM)		GSM1900 (GSM)																																																																													
Lowest Channel		Lowest Channel																																																																													
<p>Spectrum</p> <p>Ref Level 24.00 dBm Offset 14.00 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 28005 pts Stop 9.0 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>820.000 MHz</td><td>1.000 MHz</td><td>497.24889 MHz</td><td>-36.42 dBm</td><td>-25.42 dB</td></tr> <tr><td>855.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>954.96377 MHz</td><td>-27.33 dBm</td><td>-24.33 dB</td></tr> <tr><td>1.000 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.63992 GHz</td><td>-36.44 dBm</td><td>-23.44 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>4.12161 GHz</td><td>-31.91 dBm</td><td>-18.91 dB</td></tr> <tr><td>7.000 GHz</td><td>9.000 GHz</td><td>1.000 MHz</td><td>7.89601 GHz</td><td>-35.43 dBm</td><td>-22.43 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	820.000 MHz	1.000 MHz	497.24889 MHz	-36.42 dBm	-25.42 dB	855.000 MHz	1.000 GHz	1.000 MHz	954.96377 MHz	-27.33 dBm	-24.33 dB	1.000 GHz	3.000 GHz	1.000 MHz	2.63992 GHz	-36.44 dBm	-23.44 dB	3.000 GHz	7.000 GHz	1.000 MHz	4.12161 GHz	-31.91 dBm	-18.91 dB	7.000 GHz	9.000 GHz	1.000 MHz	7.89601 GHz	-35.43 dBm	-22.43 dB	<p>Spectrum</p> <p>Ref Level 24.50 dBm Offset 14.50 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 48006 pts Stop 19.1 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>373.93553 MHz</td><td>-37.49 dBm</td><td>-26.49 dB</td></tr> <tr><td>1.000 GHz</td><td>1.845 GHz</td><td>1.000 MHz</td><td>1.73119 GHz</td><td>-38.75 dBm</td><td>-25.75 dB</td></tr> <tr><td>1.915 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.62267 GHz</td><td>-35.61 dBm</td><td>-22.61 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>6.62930 GHz</td><td>-33.92 dBm</td><td>-20.92 dB</td></tr> <tr><td>7.000 GHz</td><td>13.600 GHz</td><td>1.000 MHz</td><td>10.78978 GHz</td><td>-35.54 dBm</td><td>-22.54 dB</td></tr> <tr><td>13.600 GHz</td><td>19.100 GHz</td><td>1.000 MHz</td><td>18.29539 GHz</td><td>-32.32 dBm</td><td>-19.32 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	1.000 GHz	1.000 MHz	373.93553 MHz	-37.49 dBm	-26.49 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.75 dBm	-25.75 dB	1.915 GHz	3.000 GHz	1.000 MHz	2.62267 GHz	-35.61 dBm	-22.61 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.62930 GHz	-33.92 dBm	-20.92 dB	7.000 GHz	13.600 GHz	1.000 MHz	10.78978 GHz	-35.54 dBm	-22.54 dB	13.600 GHz	19.100 GHz	1.000 MHz	18.29539 GHz	-32.32 dBm	-19.32 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	497.24889 MHz	-36.42 dBm	-25.42 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	954.96377 MHz	-27.33 dBm	-24.33 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	2.63992 GHz	-36.44 dBm	-23.44 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	4.12161 GHz	-31.91 dBm	-18.91 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	7.89601 GHz	-35.43 dBm	-22.43 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	373.93553 MHz	-37.49 dBm	-26.49 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.75 dBm	-25.75 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	2.62267 GHz	-35.61 dBm	-22.61 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.62930 GHz	-33.92 dBm	-20.92 dB																																																																										
7.000 GHz	13.600 GHz	1.000 MHz	10.78978 GHz	-35.54 dBm	-22.54 dB																																																																										
13.600 GHz	19.100 GHz	1.000 MHz	18.29539 GHz	-32.32 dBm	-19.32 dB																																																																										
<p>Date: 5 MAY 2017 10:45:47</p> <p>Middle Channel</p> <p>Spectrum</p> <p>Ref Level 24.00 dBm Offset 14.00 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 28005 pts Stop 9.0 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>820.000 MHz</td><td>1.000 MHz</td><td>597.16104 MHz</td><td>-36.42 dBm</td><td>-25.42 dB</td></tr> <tr><td>855.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>923.67691 MHz</td><td>-27.42 dBm</td><td>-24.42 dB</td></tr> <tr><td>1.000 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.74416 GHz</td><td>-37.88 dBm</td><td>-24.88 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>4.18210 GHz</td><td>-33.14 dBm</td><td>-20.14 dB</td></tr> <tr><td>7.000 GHz</td><td>9.000 GHz</td><td>1.000 MHz</td><td>7.07762 GHz</td><td>-35.73 dBm</td><td>-22.73 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	820.000 MHz	1.000 MHz	597.16104 MHz	-36.42 dBm	-25.42 dB	855.000 MHz	1.000 GHz	1.000 MHz	923.67691 MHz	-27.42 dBm	-24.42 dB	1.000 GHz	3.000 GHz	1.000 MHz	2.74416 GHz	-37.88 dBm	-24.88 dB	3.000 GHz	7.000 GHz	1.000 MHz	4.18210 GHz	-33.14 dBm	-20.14 dB	7.000 GHz	9.000 GHz	1.000 MHz	7.07762 GHz	-35.73 dBm	-22.73 dB	<p>Date: 5 MAY 2017 09:29:03</p> <p>Middle Channel</p> <p>Spectrum</p> <p>Ref Level 24.50 dBm Offset 14.50 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 48006 pts Stop 19.1 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>769.49775 MHz</td><td>-37.89 dBm</td><td>-24.89 dB</td></tr> <tr><td>1.000 GHz</td><td>1.845 GHz</td><td>1.000 MHz</td><td>1.73119 GHz</td><td>-38.24 dBm</td><td>-25.24 dB</td></tr> <tr><td>1.915 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.68661 GHz</td><td>-36.02 dBm</td><td>-23.02 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>6.95376 GHz</td><td>-34.11 dBm</td><td>-21.11 dB</td></tr> <tr><td>7.000 GHz</td><td>13.600 GHz</td><td>1.000 MHz</td><td>10.88709 GHz</td><td>-34.85 dBm</td><td>-21.85 dB</td></tr> <tr><td>13.600 GHz</td><td>19.100 GHz</td><td>1.000 MHz</td><td>17.60391 GHz</td><td>-32.67 dBm</td><td>-19.67 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	1.000 GHz	1.000 MHz	769.49775 MHz	-37.89 dBm	-24.89 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.24 dBm	-25.24 dB	1.915 GHz	3.000 GHz	1.000 MHz	2.68661 GHz	-36.02 dBm	-23.02 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.95376 GHz	-34.11 dBm	-21.11 dB	7.000 GHz	13.600 GHz	1.000 MHz	10.88709 GHz	-34.85 dBm	-21.85 dB	13.600 GHz	19.100 GHz	1.000 MHz	17.60391 GHz	-32.67 dBm	-19.67 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	597.16104 MHz	-36.42 dBm	-25.42 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	923.67691 MHz	-27.42 dBm	-24.42 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	2.74416 GHz	-37.88 dBm	-24.88 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	4.18210 GHz	-33.14 dBm	-20.14 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	7.07762 GHz	-35.73 dBm	-22.73 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	769.49775 MHz	-37.89 dBm	-24.89 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.24 dBm	-25.24 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	2.68661 GHz	-36.02 dBm	-23.02 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.95376 GHz	-34.11 dBm	-21.11 dB																																																																										
7.000 GHz	13.600 GHz	1.000 MHz	10.88709 GHz	-34.85 dBm	-21.85 dB																																																																										
13.600 GHz	19.100 GHz	1.000 MHz	17.60391 GHz	-32.67 dBm	-19.67 dB																																																																										
<p>Date: 5 MAY 2017 10:47:03</p> <p>Highest Channel</p> <p>Spectrum</p> <p>Ref Level 24.00 dBm Offset 14.00 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 28005 pts Stop 9.0 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>820.000 MHz</td><td>1.000 MHz</td><td>726.50910 MHz</td><td>-39.26 dBm</td><td>-25.26 dB</td></tr> <tr><td>855.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>986.51849 MHz</td><td>-27.42 dBm</td><td>-24.42 dB</td></tr> <tr><td>1.000 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.66892 GHz</td><td>-37.85 dBm</td><td>-24.85 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>5.09349 GHz</td><td>-31.97 dBm</td><td>-19.87 dB</td></tr> <tr><td>7.000 GHz</td><td>9.000 GHz</td><td>1.000 MHz</td><td>8.71141 GHz</td><td>-35.94 dBm</td><td>-22.94 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	820.000 MHz	1.000 MHz	726.50910 MHz	-39.26 dBm	-25.26 dB	855.000 MHz	1.000 GHz	1.000 MHz	986.51849 MHz	-27.42 dBm	-24.42 dB	1.000 GHz	3.000 GHz	1.000 MHz	2.66892 GHz	-37.85 dBm	-24.85 dB	3.000 GHz	7.000 GHz	1.000 MHz	5.09349 GHz	-31.97 dBm	-19.87 dB	7.000 GHz	9.000 GHz	1.000 MHz	8.71141 GHz	-35.94 dBm	-22.94 dB	<p>Date: 5 MAY 2017 09:30:19</p> <p>Highest Channel</p> <p>Spectrum</p> <p>Ref Level 24.50 dBm Offset 14.50 dB Mode Auto Sweep SQL Count 10/10</p> <p>1. Max</p> <p>20 dBm/100K Line SPURIOUS LINE_ABS_ PASS PASS</p> <p>10 dBm- 0 dBm- -10 dBm- -20 dBm- -30 dBm- -40 dBm- -50 dBm- -60 dBm- -70 dBm-</p> <p>Start 30.0 MHz 48006 pts Stop 19.1 GHz</p> <p>Spurious Emissions</p> <table border="1"> <thead> <tr> <th>Range Low</th><th>Range Up</th><th>RBW</th><th>Frequency</th><th>Power Abs</th><th>ΔLimit</th></tr> </thead> <tbody> <tr><td>30.000 MHz</td><td>1.000 GHz</td><td>1.000 MHz</td><td>972.12644 MHz</td><td>-36.33 dBm</td><td>-23.33 dB</td></tr> <tr><td>1.000 GHz</td><td>1.845 GHz</td><td>1.000 MHz</td><td>1.73119 GHz</td><td>-38.43 dBm</td><td>-25.43 dB</td></tr> <tr><td>1.915 GHz</td><td>3.000 GHz</td><td>1.000 MHz</td><td>2.61247 GHz</td><td>-36.41 dBm</td><td>-23.41 dB</td></tr> <tr><td>3.000 GHz</td><td>7.000 GHz</td><td>1.000 MHz</td><td>6.60530 GHz</td><td>-33.11 dBm</td><td>-20.11 dB</td></tr> <tr><td>7.000 GHz</td><td>13.600 GHz</td><td>1.000 MHz</td><td>10.03370 GHz</td><td>-35.76 dBm</td><td>-22.76 dB</td></tr> <tr><td>13.600 GHz</td><td>19.100 GHz</td><td>1.000 MHz</td><td>16.29736 GHz</td><td>-31.86 dBm</td><td>-18.86 dB</td></tr> </tbody> </table>	Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit	30.000 MHz	1.000 GHz	1.000 MHz	972.12644 MHz	-36.33 dBm	-23.33 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.43 dBm	-25.43 dB	1.915 GHz	3.000 GHz	1.000 MHz	2.61247 GHz	-36.41 dBm	-23.41 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.60530 GHz	-33.11 dBm	-20.11 dB	7.000 GHz	13.600 GHz	1.000 MHz	10.03370 GHz	-35.76 dBm	-22.76 dB	13.600 GHz	19.100 GHz	1.000 MHz	16.29736 GHz	-31.86 dBm	-18.86 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	726.50910 MHz	-39.26 dBm	-25.26 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	986.51849 MHz	-27.42 dBm	-24.42 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	2.66892 GHz	-37.85 dBm	-24.85 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	5.09349 GHz	-31.97 dBm	-19.87 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	8.71141 GHz	-35.94 dBm	-22.94 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	972.12644 MHz	-36.33 dBm	-23.33 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.73119 GHz	-38.43 dBm	-25.43 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	2.61247 GHz	-36.41 dBm	-23.41 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.60530 GHz	-33.11 dBm	-20.11 dB																																																																										
7.000 GHz	13.600 GHz	1.000 MHz	10.03370 GHz	-35.76 dBm	-22.76 dB																																																																										
13.600 GHz	19.100 GHz	1.000 MHz	16.29736 GHz	-31.86 dBm	-18.86 dB																																																																										
<p>Date: 5 MAY 2017 10:48:20</p>	<p>Date: 5 MAY 2017 09:31:36</p>																																																																														





Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0054	PASS
40	Normal Voltage	0.0069	
30	Normal Voltage	0.0018	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0155	
0	Normal Voltage	0.0158	
-10	Normal Voltage	0.0092	
-20	Normal Voltage	0.0175	
-30	Normal Voltage	0.0036	
20	Maximum Voltage	0.0036	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0012	

Note: Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V

Test Conditions	Middle Channel	GSM1900 (GSM)	Limit Note 2.
		Deviation (ppm)	
Temperature (°C)	Voltage (Volt)		
50	Normal Voltage	0.0078	PASS
40	Normal Voltage	0.0023	
30	Normal Voltage	0.0030	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0180	
0	Normal Voltage	0.0166	
-10	Normal Voltage	0.0112	
-20	Normal Voltage	0.0139	
-30	Normal Voltage	0.0079	
20	Maximum Voltage	0.0061	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0129	

Note:

1. Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0108	PASS
40	Normal Voltage	0.0007	
30	Normal Voltage	0.0152	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0060	
-10	Normal Voltage	0.0155	
-20	Normal Voltage	0.0048	
-30	Normal Voltage	0.0179	
20	Maximum Voltage	0.0137	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0036	

Note: Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0106	PASS
40	Normal Voltage	0.0066	
30	Normal Voltage	0.0071	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0019	
0	Normal Voltage	0.0023	
-10	Normal Voltage	0.0020	
-20	Normal Voltage	0.0015	
-30	Normal Voltage	0.0029	
20	Maximum Voltage	0.0032	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0005	

Note:

1. Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

GSM850 (GSM)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-55.71	-13	-42.71	-61.27	-60.12	2.84	9.40	H
	2509.2	-63.30	-13	-50.30	-73.72	-68.05	3.7	10.60	H
	3345.6	-61.70	-13	-48.70	-76.46	-67.78	4.37	12.60	H
	1672.8	-60.84	-13	-47.84	-65.55	-65.25	2.84	9.40	V
	2509.2	-64.87	-13	-51.87	-74.70	-69.62	3.70	10.60	V
	3345.6	-62.77	-13	-49.77	-76.34	-68.85	4.37	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-40.20	-13	-27.20	-60.54	-47.95	4.85	12.60	H
	5640	-49.56	-13	-36.56	-73.01	-57.08	5.58	13.10	H
	7520	-57.92	-13	-44.92	-81.44	-62.66	6.56	11.30	H
	3760	-46.47	-13	-33.47	-66.86	-54.22	4.85	12.6	V
	5640	-53.90	-13	-40.90	-77.95	-61.42	5.58	13.1	V
	7520	-57.66	-13	-44.66	-81.2	-62.40	6.56	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-65.60	-13	-52.60	-71.16	-70.01	2.84	9.40	H
	2509.2	-68.87	-13	-55.87	-79.29	-73.62	3.7	10.60	H
	3345.6	-65.92	-13	-52.92	-80.68	-72.00	4.37	12.60	H
	1672.8	-66.32	-13	-53.32	-71.03	-70.73	2.84	9.40	V
	2509.2	-69.30	-13	-56.30	-79.13	-74.05	3.70	10.60	V
	3345.6	-67.30	-13	-54.30	-80.87	-73.38	4.37	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-51.32	-13	-38.32	-70.93	-59.07	4.85	12.60	H
	5640	-57.86	-13	-44.86	-81.31	-65.38	5.58	13.10	H
	7520	-57.63	-13	-44.63	-81.15	-62.37	6.56	11.30	H
	3760	-51.87	-13	-38.87	-72.26	-59.62	4.85	12.6	V
	5640	-57.13	-13	-44.13	-81.18	-64.65	5.58	13.1	V
	7520	-57.67	-13	-44.67	-81.21	-62.41	6.56	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.