

FCC Part 15C Test Report

FCC ID: 2ALTDM9

Product Name:	M9 bluetooth headphones
Trademark:	N/A
Model Name :	M9
Serial Model:	M1, M2, M3, M4, M5, M6, M7, M8, M10, M11, M12
Prepared For :	SHENZHEN ZHENSHENG TECHNOLOGY CO.,LTD.
Address :	32th Buiding.Houting The Third Industrial Zone,Shajing Street,Bao'an District,Shenzhen City,P.R.China
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101,Yousong Road,Longhua New District, Shenzhen,China
Test Date:	Mar. 31 -Apr. 12, 2017
Date of Report :	Apr. 12, 2017
Report No.:	BCTC-FY170301692-2E

Report No.: BCTC-170301692-2E



VERIFICATION OF COMPLIANCE

Applicant's name : SHENZHEN ZHENSHENG TECHNOLOGY CO.,LTD.

Address : 32th Buiding.Houting The Third Industrial Zone,Shajing Street,Bao'an District,Shenzhen City,P.R.China

Manufacture's Name : SHENZHEN ZHENSHENG TECHNOLOGY CO.,LTD.

Address : 32th Buiding.Houting The Third Industrial Zone,Shajing

Street, Bao'an District, Shenzhen City, P.R. China

Product description

Product name...... M9 bluetooth headphones

Trademark: N/A

Model Name: M9, M1, M2, M3, M4, M5, M6, M7, M8, M10, M11, M12

Standards: ANSI C63.10-2013 FCC Part15.249

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Test Result Pass

Testing Engineer : tric lang

Reviewer (Supervisor) :

Approved & Authorized Signer(Manager) Conson . 2 May

Carson Zhang



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	7
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 8
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE 3.1.3 DEVIATION FROM TEST STANDARD	12 12
3.1.4 TEST SETUP	12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP 3.2.5 EUT OPERATING CONDITIONS	18 19
3.2.6 TEST RESULTS	20
4 . BANDWIDTH TEST	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD	25
4.1.3 TEST SETUP	25
4.1.4 EUT OPERATION CONDITIONS	25
4.1.5 TEST RESULTS	26
5 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 5.1 DEVIATION FROM STANDARD	28 29
5.2 TEST SETUP	29 29
5.3 EUT OPERATION CONDITIONS	29



8. PHOTOS OF THE EUT

	Shenzhen BCTC Technology Co., Ltd.	Report No.: BCTC-170301692-2E
Table of Contents		Page
5.4 TEST RI	ESULTS	29
6 . ANTENNA RE	QUIREMENT	32
6.1 STANDARD	REQUIREMENT	32
6.2 EUT ANTEN	INA	32
7 . EUT TEST PH	ото	33

35



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C					
Standard Section	Test Item	Judgment	Remark		
15.207	Conducted Emission	PASS			
15.249	Fundamental &Radiated Spurious Emission Measurement	PASS			
15.249	Bandwidth	PASS			
15.205	Band Edge Emission	PASS			
15.203	Antenna Requirement	PASS			

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add.: No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registration No.:187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	M9 bluetooth headphones			
Trade Name	N/A			
Model Name	M9			
Serial Model	M1, M2, M3, M4, M5, N	M6, M7, M8, M10, M11, M12		
Model Difference	All the model are the smodel names.	same circuit and RF module,except		
	Operation Frequency:	2402~2480 MHz		
	Modulation Type:	GFSK		
	Bit Rate of Transmitter	2M		
	Number Of Channel	40 CH		
Product Description	Antenna Designation:	Please see Note 3.		
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Channel List	Please refer to the Note 2	2.		
	Model: A8A-501000			
Battery	AC Power Input: 100-240V~ 50/60Hz 0.2A			
	Output: 5V 1000mA			
Connecting I/O Port(s)	Please refer to the User's Manual			
hardware version				
Software version				
Serial number				



Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2

	Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
01	2402	11	2422	21	2442	
02	2404	12	2424	22	2444	
03	2406	13	2426	23	2446	
~	~	~	~	~	~	
09	2418	19	2438	39	2478	
10	2420	20	2440	40	2480	

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	0.5dBi	N/A

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted & Radiated Emission				
Final Test Mode	Description			
Mode 1	CH01			
Mode 2	CH20			
Mode 3	CH40			
Mode 4	Link Mode			

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Frequency	2402 MHz	2440 MHz	2480 MHz
Channel	Low	Middle	High



2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Conducted Emission



Radiated Spurious Emission Test

E-1 EUT

RF test setup:



Note:

- 1. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.
- 2. Using the notebook and the transform board to control the fixed transmitting frequency and other test mode. After finishing the test setting, the notebook and the transform board will be removed during measurements.



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	M9 bluetooth headphones	N/A	M9	N/A	EUT
E-2	Adapter	N/A	A8A-501000	N/A	Lab Provide
E-3	Notebook	Lenovo	S2	N/A	Lab Provide
E-4	Transfrom board	N/A	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	USB cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

	Kind of	Kind of Manufactu Time No		0 1 N	Last	Calibrated	Calibratio
Item	Equipment	rer	Type No.	Serial No.	calibration	until	n period
1	Test Receiver	R&S	ESCI	1166.5950K 03-101165- ha	2016.06.06	2017.06.05	1 year
2	LISN	R&S	NSLK81 26	812646 6	2015.08.24	2016.08.23	1 year
3	LISN	R&S	NSLK81 26	812648 7	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2016.06.07	2017.06.06	1 year
5	RF cables	R&S	R204	R20X	2016.07.06	2017.07.05	1 year

Radiation test, Band-edge test and 20db bandwith test quipment

	Kind of	- cago tost and			Last	Calibrated	Calibratio
Item	Equipment	Manufacturer	Type No.	Serial No.	calibration	until	n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2016.07.06	2017.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2016.06.07	2017.06.06	1 year
3	Bilog Antenna	R&S	VULB 9168	VULB91 68-438	2016.07.06	2017.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2016.06.07	2017.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2016.06.07	2017.06.06	1 year
6	Horn Antenna	R&S	HF906	10027	2016.07.06	2017.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05	1 year
8	Amplifier	R&S	BBV9743	9743-01 9	2015.08.25	2016.08.24	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2016.06.08	2017.06.07	1 year
10	RF cables	R&S	R203	R20X	2016.07.06	2017.07.05	1 year
11	Antenna connector	Florida RFLa bs	Lab-Fle	RF 01#	2016.07.06	2017.07.05	1 year



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A	(dBuV)	Class B	Standard	
PREQUENCY (MHZ)	Quasi-peak	Average	Quas -peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.B oth of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



3.1.6 TEST RESULTS

Temperature :	25℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	L
Hest vollage .	Input: AC120V/60Hz Output: DC 3.7V	Test Mode:	Mode 4




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBu∀	dBu∀	dB	Detector	Comment
1		0.1780	8.82	9.66	18.48	64.57	-46.09	QP	
2		0.1780	-1.61	9.66	8.05	54.57	-46.52	AVG	
3		0.3460	11.39	9.66	21.05	59.06	-38.01	QP	
4		0.3460	3.51	9.66	13.17	49.06	-35.89	AVG	
5		0.6380	10.39	9.68	20.07	56.00	-35.93	QP	
6	*	0.6380	2.08	9.68	11.76	46.00	-34.24	AVG	
7		1.6260	7.48	9.70	17.18	56.00	-38.82	QP	
8		1.6260	-3.37	9.70	6.33	46.00	-39.67	AVG	
9		13.4780	8.52	9.84	18.36	60.00	-41.64	QP	
10		13.4780	-3.23	9.84	6.61	50.00	-43.39	AVG	
11		18.3620	9.05	9.87	18.92	60.00	-41.08	QP	
12		18.3620	-2.84	9.87	7.03	50.00	-42.97	AVG	



Shenzhen BCTC Technology Co., Ltd.

Temperature :	25 ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	N
Test vollage .	Input: AC120V/60Hz Output: DC 3.7V	Test Mode :	Mode 4



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.3620	8.86	9.67	18.53	58.68	-40.15	QP	
2		0.3620	-0.36	9.67	9.31	48.68	-39.37	AVG	
3	*	1.2260	8.98	9.69	18.67	56.00	-37.33	QP	
4		1.2260	-2.11	9.69	7.58	46.00	-38.42	AVG	
5		1.6460	8.93	9.70	18.63	56.00	-37.37	QP	
6		1.6460	-1.35	9.70	8.35	46.00	-37.65	AVG	
7		2.5900	7.25	9.72	16.97	56.00	-39.03	QP	
8		2.5900	-4.08	9.72	5.64	46.00	-40.36	AVG	
9		10.3260	8.02	9.83	17.85	60.00	-42.15	QP	
10		10.3260	-3.76	9.83	6.07	50.00	-43.93	AVG	
11		18.4660	7.42	9.87	17.29	60.00	-42.71	QP	
12		18.4660	-3.25	9.87	6.62	50.00	-43.38	AVG	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

	Class B (dBuV/m) (at 3M)			
FREQUENCY (MHz)	PEAK	AVERAGE		
Above 1000	74	54		

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting		
Attenuation	Auto		
Start Frequency	1000 MHz		
Stop Frequency	10th carrier harmonic		
RB / VB (emission in restricted	4 MHz / 4 MHz for Dook 4 MHz / 40Hz for Average		
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average		

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
 - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



Report No.: BCTC-170301692-2E




3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: BCTC-170301692-2E



3.2.6 TEST RESULTS

Radiated Spurious Emission (Below 30MHz)

Temperature :	20 ℃	Relative Humidity:	48%			
Pressure:	1010 hPa	Polarization :				
Test Voltage :	DC 3.7V From Battery					
Test Mode :	Link Mode					

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);


Limit line = specific limits(dBuv) + distance extrapolation factor.



Radiated Spurious Emission (Between 30MHz – 1GHz)

Temperature :	26 ℃	Relative Humidity:	54%				
Pressure:	1010 hPa	Polarization :	Horizontal				
Test Voltage :	DC 3.7V From Battery						
Test Mode : (Worst)	Link Mode						

Shenzhen BCTC Technology Co., Ltd.




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		41.5670	25.81	-15.25	10.56	40.00	-29.44	QP
2		54.8348	25.59	-15.09	10.50	40.00	-29.50	QP
3	•	104.9033	24.89	-16.17	8.72	43.50	-34.78	QP
4	2	256.5211	24.66	-13.52	11.14	46.00	-34.86	QP
5	3	360.4476	27.10	-10.40	16.70	46.00	-29.30	QP
6	* 6	33.9073	24.63	-4.09	20.54	46.00	-25.46	QP



Shenzhen	<u>BCTC</u>	<u>Technology</u>	Co.,	Ltd.

Temperature :	26 ℃	Relative Humidity:	54%				
Pressure :	1010 hPa	Polarization :	Vertical				
Test Voltage :	DC 3.7V From Battery						
Test Mode : (Worst)	Link Mode						



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∀	dB	dBuV/m	dB/m	dB	Detector
1		43.0505	24.75	-14.93	9.82	40.00	-30.18	QP
2		53.6932	26.58	-14.86	11.72	40.00	-28.28	QP
3	•	106.3850	25.52	-16.24	9.28	43.50	-34.22	QP
4	•	139.8508	29.58	-19.89	9.69	43.50	-33.81	QP
5	4	411.8240	29.93	-9.06	20.87	46.00	-25.13	QP
6	*	719.1995	25.49	-2.58	22.91	46.00	-23.09	QP



Radiated Spurious Emission (1GHz to 10th harmonics)

GFSK

OI OIC	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBµV)	(PK/QP/Ave)	(H/V)	(dB)	(dBµV/m)	(dBµV/m)	Rosun
	2402.00	93.68	PK	Н	13.85	107.53	114.00	Pass
	2402.00	71.76	Ave	Н	13.85	85.61	94.00	Pass
	4804.00	52.65	PK	Н	19.33	71.98	74.00	Pass
_	4804.00	39.42	Ave	Н	19.33	58.75	54.00	Pass
Lower Channel	12355.00	31.58	PK	Н	17.81	49.39	74.00	Pass
2402MHz	17850.00	20.74	PK	Н	25.39	46.13	74.00	Pass
	2402.00	92.36	PK	V	13.85	106.21	114.00	Pass
	2402.00	71.42	Ave	V	13.85	85.27	94.00	Pass
	4804.00	47.38	PK	V	19.33	66.71	74.00	Pass
	4804.00	35.58	Ave	V	19.33	54.91	54.00	Pass
	12355.00	31.74	PK	V	17.81	49.55	74.00	Pass
	17850.00	24.46	PK	V	25.39	49.85	74.00	Pass
	2440.00	93.55	PK	Н	13.94	107.49	114.00	Pass
	2440.00	72.08	Ave	Н	13.94	86.02	94.00	Pass
	4880.00	50.45	PK	Н	19.43	69.88	74.00	Pass
	4880.00	39.76	Ave	Н	19.43	59.19	54.00	Pass
	12355.00	30.24	PK	Н	17.81	48.05	74.00	Pass
Middle	17850.00	25.53	PK	Н	25.39	50.92	74.00	Pass
Channel 2440MHz	2440.00	92.71	PK	V	13.94	106.65	114.00	Pass
	2440.00	73.68	Ave	V	13.94	87.62	94.00	Pass
	4880.00	48.15	PK	V	19.43	67.58	74.00	Pass
	4880.00	31.24	Ave	V	19.43	50.67	54.00	Pass
	12355.00	24.40	PK	V	17.81	42.21	74.00	Pass
	17850.00	22.67	PK	V	25.39	48.06	74.00	Pass
Upper	2480.00	91.35	PK	Н	14.02	105.37	114.00	Pass
Channel	2480.00	70.57	Ave	Н	14.02	84.59	94.00	Pass
2480MHz	4960.00	48.83	PK	Н	19.51	68.34	74.00	Pass



Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-170301692-2E

4960.00	31.25	Ave	Н	19.51	50.76	54.00	Pass
12355.00	28.69	PK	Н	17.81	46.5	74.00	Pass
17850.00	23.42	PK	Н	25.39	48.81	74.00	Pass
2480.00	90.73	PK	V	14.02	104.75	114.00	Pass
2480.00	72.68	Ave	V	14.02	86.7	94.00	Pass
4960.00	46.15	PK	V	19.51	65.66	74.00	Pass
4960.00	29.36	Ave	V	19.51	48.87	54.00	Pass
12355.00	28.84	PK	V	17.81	46.65	74.00	Pass
17850.00	23.42	PK	V	25.39	48.81	74.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C							
Section	Test Item	Limit	Frequency Range (MHz)	Result			
15.249	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS			

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100KHz
VB	≥RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW≥ RBW, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




4.1.5 TEST RESULTS


Temperature :	5 °C Relative Humidity :		54%		
Pressure :	1012 hPa	Test Voltage :	DC 3.7V From Battery		
Test Mode :	CH01 / CH20 /CH40				

	Frequency	20dB Bandwidth (MHz)	Result
GFSK	2402 MHz	1.209	PASS
	2440 MHz	1.183	PASS
	2480 MHz	1.199	PASS

GFSK









5. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



5.1 DEVIATION FROM STANDARD

No deviation.

5.2 TEST SETUP

5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

Temperature :	25 ℃	Relative Humidity:	54%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V From Battery
Test Mode :	CH01/CH40		


	Frequency (MHz)	Antenna polarization (H/V)	Frequency (MHz)	Meter Reading (dBµV) Factor (dB)	Factor (dB)	Emission (dBuV/m) PK	Band edge Limit (dBuV/m) PK AV		Result
	<2400	<2400 H 2390.00	34.57	13.83		74.00	54.00	Pass	
GFSK	12400	11	2000.00	04.07	10.00	48.40	74.00	34.00	1 033
	<2400	V	2390.00	35.14	13.83	48.97	74.00	54.00	Pass
	<2400	Н	2400.00	34.25	13.85	48.10	74.00	54.00	Pass
	<2400	V	2400.00	35.09	13.85	48.94	74.00	54.00	Pass
	>2483.5	Н	2483.50	36.12	14.02	50.14	74.00	54.00	Pass
	>2483.5	V	2483.50	34.83	14.02	48.85	74.00	54.00	Pass
	>2483.5	Н	2485.50	35.72	14.04	49.76	74.00	54.00	Pass
	>2483.5	V	2485.50	36.38	14.04	50.42	74.00	54.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.


Report No.: BCTC-170301692-2E





2402 Horizontal




2402 Vertical











6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The EUT antenna is PCB antenna. It complies with the standard requirement.

Report No.: BCTC-170301692-2E




7. EUT TEST PHOTO















8. PHOTOS OF THE EUT



*** ** END OF REPORT *****