

# Global United Technology Services Co., Ltd.

Report No.: GTS201704000070F02

## RF EXPOSURE REPORT

Applicant: YFJ ELECTRONIC CO., LIMITED

**Address of Applicant:** Room 1620 of Jinhao building, Xintian community, Fuyong,

Shenzhen, China

**Equipment Under Test (EUT)** 

**Product Name:** Wireless charger

Model No.: YFJ-099

FCC ID: 2ALTO-YFJ099

FCC CFR Title 47 Part 15 Subpart C:2016 Applicable standards:

Date of sample receipt: April 17, 2017

**Date of Test:** April 17-20, 2017

Date of report issued: April 20, 2017

Test Result: PASS \*

In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo **Laboratory Manager** 

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



## 2 Version

Version No.	Date	Description		
00	April 20, 2017	Original		

Prepared By:	Tiger. Ohn	Date:	April 20, 2017
	Project Engineer		
Check By:	Andy wa	Date:	April 20, 2017
	Reviewer		



#### 2.1 Test Facility

#### • FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

#### • Industry Canada (IC) —Registration No.: 9079A-2

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

#### 2.2 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480 Fax: 0755-27798960

#### 2.3 Other Information Requested by the Customer

None.

#### 2.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC Approval	
N/A	Load	N/A	N/A	VOC	



#### 3 Test Instruments list

Rac	Radiated Emission:							
Item	Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	N/A	July 03 2015	July 02 2020		
2	Exposure Level Tester	Narda	ELT-400	N-0231	June 29 2016	June 28 2017		
3	Magnetic field probe 100cm <sup>2</sup>	Narda	ELT probe 100cm <sup>2</sup>	M0675	June 29 2016	June 28 2017		

#### 4 Method of measurement


#### 4.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

According KDB680106 D01v02: RF Exposure Wireless Charging Apps v02.

#### 5 Test Result





## 5.1 Equipment Approval Considerations:

Т	ne EUT does comply with item 5.2 of KDB 680106 D01v02
a)	Power transfer frequency is less than 1MHz.
	Yes; the device operate in the frequency range from 110 KHz to 205 KHz
b)	Output power from each primary coil is less than 5 watts
	Yes; the maximum output power of the primary coil is 4W<5W.
c)	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that able to detect and allow coupling only between individual pair of coils.
	Yes; the transfer system includes only single primary and secondary coils.
d)	Client device is inserted in or placed directly in contact with the transmitter.
	Yes; Client device is placed directly in contact with the transmitter.
e)	The maximum coupling surface area of the transmit (charging) device:
	Yes; The EUT coupling surface area was 65 cm2>60cm2
f)	Aggregate leakage fields at 10cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.
	Yes; The EUT field strength levels are 30% x MPE limit.

### 5.2 E and H field Strength

Test mode for wireless charger: Normal Operation (Charging mode)

Fraguency	E-Filed Strength at 10 cm from the edges surrounding the EUT (V/m)						Limita
Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	Limits (V/m)
0.1-0.205	1.06	1.98	0.62	0.76	1.26	1.77	614

Frequency Range (MHz)	H-Filed Strength at 10 cm from the edges surrounding the EUT (A/m)						Limita	
	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	Limits (A/m)	
	0.1-0.205	0.64	1.08	0.30	0.42	0.98	1.04	1.63

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



## 6 Test Setup Photo





----- End-----