

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Toy RC Gravity Rover operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V Rechargeable battery). Once use the USB cable charging to the EUT, the wireless function will be disabled. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -19.0 dBm (± 3 dB)

The nominal radiated output power (e.i.r.p) specified: -19.0 dBm (± 3 dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 78.1 dB μ V/m at 3m in the frequency 2412MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -17.13dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 74.7 dB μ V/m at 3m in the frequency 2471MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -20.53dBm
which is within the production variation.

The maximum conducted output power specified is -16dBm= 0.025mW

The source- based time-averaging conducted output power
=0.025* Duty cycle mW <0.025 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$P_{th}(\text{mW}) = \text{ERP}_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left(\frac{60}{\text{ERP}_{20\text{cm}} \sqrt{f}} \right))$$
$$= 3060 * (0.5/20)^{1.9} \text{ mW}$$
$$= 2.72 \text{ mW}$$

Since max. power of the source-based time-averaging conducted output power and effective radiated power (ERP) is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 16.1739ms

Effective period of the cycle = 0.5072ms x 3 = 1.5216ms

DC = 1.5216ms / 16.1739ms = 0.0941 or 9.41%