


RF TEST REPORT

Test Report No:	24-4791132400-3-1-1-RAD-A	
UL Project No:	4791132400	
Date of issue:	2025-01-24	
Total number of pages:	40	
Applicant:	SECO S.p.A. Via Achille Grandi, 20 52100 Arezzo (AR) – Italy	
Contact's person:	Giacomo Martini (giacomo.maritni@seco.com) Alessandro Savelli (alessandro.savelli@seco.com)	
Testing Laboratory:	UL International Italia S.r.l. Via delle Industrie, 6 (Sede A) 20061 Carugate (MI) – Italy	
Testing location:	UL International Italia S.r.l. Via delle Industrie, 6 20061 Carugate (MI) – Italy	
Test specification:		
Regulations:	FCC/ISED	
Standards:	FCC CFR 47 - Part 15 Subpart C RSS-247 Issue 3:2023 RSS-Gen Issue 5:2021	
Non-standard test method:	N/A	
Scope of testing:	Wireless - New testing	
TRF No.:	TRF_FCC 15C/RSS-247_Accredia_rev 0	
Test Report Form(s) Originator:	UL International Italia S.r.l.	
Master TRF	2023-03 .	
Compiled by: (name, function, signature)	Andrea Giovanni Galbiati Laboratory Engineer	
Approved by: (name, function, signature)	Francesco Casati Operations Leader	
General disclaimer: The test results presented in this test report relate only to the object tested, not selected by UL International Italia S.r.l.. This report shall not be reproduced, except in full, without the written approval of the issuing Testing Laboratory. This document contains data (of information) using color and if printed, should be printed in color to retain legibility and the information represented by the color.		
Declination of responsibility: Data provided by the customer are clearly identified with (*). UL International Italia S.r.l. cannot be considered responsible for this information, for any other document sent by the Applicant/Manufacturer and for any difference between the software version present in the tested sample and that present in the object intended for final sale. In some cases, the software in the tested sample is in a version dedicated exclusively to the test, and therefore does not represent the software installed in the final version of the product.		

Test Item Description:	Health station
Trade Mark: (*)	 TechnoGym
Manufacturer: (*)	Technogym S.p.A. Via Calcinaro, 2861 47521 Cesena (FC) – Italy
Model/Type reference: (*)	E030AR0
Ratings: (*)	100-240 Vac; 1.0-0.5 A; 50/60 Hz
Testing:	
Type of equipment considered in the present document:	☐ Non-radio product ☐ Non-radio product combined with one radio technology ☐ Non-radio product combined with more radio technologies, only capable of independent transmission ☒ Non-radio product combined with more radio technologies, capable of simultaneous transmission ☐ Radio product with one radio technology ☐ Radio product with more radio technologies, only capable of independent transmission ☐ Radio product with more radio technologies, capable of simultaneous transmission
Date of receipt of test item:	2024-02-19
UL Sample Tag No.:	6773319
Status of sample upon receipt:	☒ New and operational ☐ Reconditioned ☐ Damaged
Date(s) of performance of tests:	2024-03-14 to 2024-03-19
Name and address of factory(ies): (*)	Technogym S.p.A. Via Calcinaro, 2861 47521 Cesena (FC) – Italy
General remarks: A cross ☒ in a rectangular shape means that this option is applied. ☒ Indicates that the listed condition, standard or equipment is applicable for this report. ☐ Indicates that the listed condition, standard or equipment is not applicable for this report. Throughout this report a ☐ comma / ☒ point is used as decimal separator. Where not otherwise specified or communicated in writing, statements of conformity (e.g. Pass/Fail) are established according to the following decision rule: considering that the applied test standards take measurement uncertainty into account, acceptance limit equals the tolerance limit (simple acceptance). This leads to a maximum 50% of false accept or false reject when the measured value equals the tolerance limit. See ILAC-G8:09/2019 for further details.	

General product information: (*)

The Technogym Health represents an additional input point to further shape the Technogym personalized wellness journey.

It would allow to: collect additional users' health and fitness data needed to validate training program results, provide efficient and high-quality personalized training, increase Technogym's community, user motivation, health insights and retention. It would also represent a marketing tool to help the operator collecting new leads

Document history

Test Report No.	Reason for change	Date of issue
24-4791132400-3-1-0-RAD-A	Original release	2024-04-09
24-4791132400-3-1-1-RAD-A	Name of module (section 1.1) updated	2025-01-24

NOTE: New test report issue cancels and replaces the previous one.

Laboratory Accreditation

FCC Accredited Test Firm

Accreditation	MRA	Designation Number	Expiration Date
Ministero dello Sviluppo Economico- Direzione Generale Pianificazione e Gestione dello Spettro Radioelettrico <u>Scope:</u> - Unintentional Radiators - FCC Part 15 Subpart B - Industrial, Scientific, and Medical Equipment - FCC Part 18 - Intentional Radiators - FCC Part 15 Subpart C	US-EU	IT0010	2025-06-25

ISED Wireless Device Testing Laboratory

Company Number	CAB Identifier	Scope/Recognition Date	Expiration Date
UL INTERNATIONAL ITALIA S.R.L.	IT0008	RSS-GEN (2023-10-06) RSS-247 (2023-10-06)	RECOGNIZED UNTIL: 2025-06-16 ACCREDIA ISO/IEC 17025:2017 Expires: 2025-06-16

Table of Contents

Laboratory Accreditation.....	5
1 Test Item Description.....	7
1.1 Additional information of radio module (*)	10
2 Verdict summary section	12
3 Conformity decision rule	13
4 Formulas used	14
5 Tests	15
5.1 Radiated emissions & restricted bands emissions	15
5.2 Band edge	26
6 List of test equipment.....	31
7 Measurement instrumentation uncertainties.....	33
8 Photos of EUT	34
Attachment 1: Critical Component List (*)	37
Attachment 2: Product Identity Declaration / Model Variants (*).....	39
Attachment 3: Opinions and Interpretations	40

1 Test Item Description

Serial number: (*)	E30BR023080001					
Date of production: (*)	NIA					
Ports: (*)	Port name and description	Cable				
		Specified length(m)	Attached during test	Shielded		
	AC Mains	< 3	☒	☐		
	2 x USB type-A 2.0	< 3	☐	☐		
	Serial Port	< 3	☐	☐		
	Ethernet	> 3	☐	☐		
Supplementary information to the ports:	---					
Rated power supply: (*)		Voltage and frequency	Reference poles			
			N	L1	L2	L3
	☒	AC: 100-240V 50/60 Hz	☒	☒	☐	☐
	☐	DC:				
Working frequencies: (*)	32.768 kHz (RTC); 125 MHz (ETH Physical); 24MHz (USB); 74 MHz (LVDS spreaded) 2.4 GHz (Wi-Fi & BT) 5 GHz (Wi-Fi)					
Environment of intended use: (*)	☒	Household / Residential				
	☐	Professional / Commercial / Light-industrial				
	☐	Industrial				
	☐	Professional healthcare facility (only for ME)				
	☐	Home healthcare (only for ME)				
	☐	Special (only for ME)				
	☐	Road and Street				
	☐	Automotive				
Other parameters: (*)	NIA					
Firmware/Software version (original): (*)	40.15.2.5 + UnityTestApp_1.6					
Firmware/Software version (used for testing): (*)	40.15.2.5 + UnityTestApp_1.6					
Hardware version: (*)	NIA					
Mounting position: (*)	☐	Table top equipment				
	☐	Wall/Ceiling mounted equipment				
	☒	Floor standing equipment				
	☐	Hand-held equipment				
	☐	Other:				
Dimensions in cm (W x H x D): (*)	58 x 179 x 62					

Modules/parts: (*)	Module/parts of test item	Type	Manufacturer
	---	---	---
Operating modes:	No.	Operating mode of test item	
	1	Continuous transmission on BT technology at the low channel, rate 1 Mbit, max power	
	2	Continuous transmission on BT technology at the top channel, rate 1 Mbit, max power	
Supplemental information to the operating mode:	---		
Auxiliary equipment (AuxEq): <i>Peripheral equipment that is part of the system under test</i>	Description	Manufacturer	Type
	---	---	---
Associated equipment (AE): <i>Equipment that is not part of the system under test but needed to exercise and/or monitor the EUT</i>	Description	Manufacturer	Type
	---	---	---
Documents as provided by the applicant: (*)	Description	File name	Issue date
	---	---	---
Modifications to the test item during testing:	None		

Copy of marking plate: (*)

**Technogym S.p.A. Via Calcinaro 2861, 47521 Cesena (FC) - Italy****Made in Italy****TECHNOGYM CHECKUP****Model: E030AR0****Contains FCC IDs: 2ALZB-AS2DTGM, 2ARDN0615D, O6R3153****Contains ICs: 22688-AS2DTGM, 24364-0615D, 3797A-3153****100 - 240Vac 1.0 - 0.5A 50/60Hz****Maximum User's Weight: 300kg****Fuse: F 3.15A 250Vac****Information Technology Equipment: 59EA****Item Code: E030ARNR20****S/N E030AR024000001 03/24**

1.1 Additional information of radio module (*)


Producer :	SECO (contains Murata module)
Module name	AS2DTGM
Frequency range :	2400 – 2483.5 MHz ; 5000 MHz (Wi-Fi 2.4 GHz b/g/n) 5200 ; 5400 ; 5800 MHz (Wi-Fi 5GHz a) 5000 MHz (Wi-Fi 5 GHz ac) 2400 – 2483.5 MHz ; 5GHz (Wi-Fi 2.4 & 5 GHz ax) 2400 – 2483.5 (Bluetooth 5.3)
FCC ID :	2ALZB-AS2DTGM
IC ID :	22688-AS2DTGM
Antenna :	External antennas.



2 Key Features

- NXP 88W9098 inside
- Supports IEEE 802.11a/b/g/n/ac/ax specification: Dual band 2.4 GHz and 5 GHz
- MIMO with 20 MHz, 40 MHz, and 80 MHz channels
- Up to MCS11 data rates (1200 Mbps)
- Supports Bluetooth specification version 5.3
- For supported Bluetooth functions, refer to [Bluetooth SIG site](#) 
- WLAN interface: PCIe 2.0 and SDIO 3.0
- Bluetooth interface: HCI UART and PCM
- Dimensions: 19.1 x 16.5 x 2.1 mm
- Weight: 1355 mg
- MSL: 3
- Surface-mount type
- RoHS compliant
- B10 life: 13 years, B1 life: 10 years
(Wear-out failure with 20°C daily ambient room temperature change)
- Fit: 140.36 (Accidental failure)

Producer :	Electronica GF S.r.l. & Dynastream innovations Inc.
Module name :	061F & D52M
Frequency range :	13.56 MHz (RFID) & 2402 MHz ÷ 2480 MHz (BLE)
FCC ID :	2ARDN0615D & O6R3153
IC ID:	24364-0615D & 3797A-3153
Antenna :	Integrated antenna.



2 Verdict summary section

Standard clause		Description	Accreditation	Verdict	Note
FCC	ISED				
15.203	RSS-Gen 6.8	Antenna requirements	Accredia	N/P	1
15.207	RSS-Gen 8.8	AC power-line conducted emissions	Accredia	N/P	1
15.209 15.247(d)	RSS-Gen 6.13 RSS-Gen 8.9 RSS-Gen 8.10	Radiated emissions & restricted bands emissions	Accredia	P	
15.247(a)(1)	RSS-247 5.1	20 dB emission bandwidth	Accredia	N/P	1
15.247(a)(1)	RSS-247 5.1(b)	Carrier frequency separation	Accredia	N/P	1
15.247(a)(1)(iii)	RSS-247 5.1(d)	Quantity of hopping channels	Accredia	N/P	1
15.247(a)(1)(iii)	RSS-247 5.1(d)	Time of occupancy (dwell time)	Accredia	N/P	1
15.247(a)(2)	RSS-247 5.2(a)	6 dB emission bandwidth	Accredia	N/P	1
---	RSS-Gen 6.7	99% emission bandwidth	Accredia	N/P	1
15.247(b)(1) 15.247(b)(3) 15.247(b)(4)	RSS-247 5.4(b) RSS-247 5.4(d) RSS-247 5.4(f)	Maximum peak conducted output power	Accredia	N/P	1
15.247(d)	RSS-247 5.5	Band edge	Accredia	P	
15.247(e)	RSS-247 5.2(b)	Power spectral density	Accredia	N/P	1
Test method: ANSI C63.10-2013 / ANSI C63.10-2020 Test guide: FCC/KDB-558074 D01 15.247 Meas Guidance v05r02 Notes: 1. Not required by the Applicant.					

Possible test case verdicts:

Test case not performed: N/P


Test case does not apply to test object: N/A

Test object does meet requirement: Pass (P)

Test object does not meet requirement: Fail (F)

3 Conformity decision rule

Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.



4 Formulas used

☐ Disturbance voltage

$$V \text{ (dB}\mu\text{V)} = V \text{ receiver (dB}\mu\text{V)} + \text{Correction (dB)}$$

where:

$$\text{Correction (dB)} = \text{I.L. transducer (dB)} + \text{I.L. cable (dB)}$$

☐ Magnetic field

$$H \text{ (dB}\mu\text{A/m)} = V \text{ receiver (dB}\mu\text{V)} + \text{Correction (dB)}$$

where:

$$\text{Correction (dB)} = \text{Magnetic antenna factor (dB}/\Omega\text{m)} + \text{I.L. cables (dB)}$$

☒ Electric field

$$E \text{ (dB}\mu\text{V/m)} = V \text{ receiver (dB}\mu\text{V)} + \text{Correction (dB)}$$

where:

$$\text{Correction (dB)} = \text{Electric antenna factor (dB/m)} - \text{Gain external preamplifier (dB)} + \text{I.L. external filter (dB)} + \text{I.L. cables (dB)}$$

Note: external preamplifier and external filter are optional and, if used, are indicated in the list of test equipment

☒ Margin

$$\text{Margin (dB)} = \text{Measure} - \text{Limit}$$

☐ Radiated emission limit conversion for a different measuring distance

$$40 \text{ dB/decade (f<30 MHz); } 20 \text{ dB/decade (f}\geq\text{30 MHz)}$$

☐ Correction of radiated field from 5 m to 3 m

$$+8.87 \text{ dB (f<30 MHz); } +4.44 \text{ dB (f}\geq\text{30 MHz)}$$

☒ Linear to logarithmic conversion

$$\text{Log} = 20 \cdot \log(\text{Lin}) \text{ for voltage and current; } \text{Log} = 10 \cdot \log(\text{Lin}) \text{ for power}$$

☐ Conducted Radio Measurements

$$P_{\text{out_EUT}} = P_{\text{read_Amplifier}} \text{ (dBm)} + \text{Cable Losses (dB)} + \text{Attenuator (dB)}$$

☐ Duty Cycle

$$\text{Duty Cycle (\%)} = 100 \times [\text{On Time (TON)}] / [\text{Period(TON+ TOFF)}]$$

$$\text{Duty Cycle Correction Factor} = 10 \log 1 / [\text{On Time (TON)}] / [\text{Period(TON+ TOFF)}]$$

$$P_{\text{out_AVGcorr}} = P_{\text{out_AVG}} + \text{Duty Cycle Correction Factor}$$

☐ Average time of occupancy:

$$\text{Number of hops in the period specified in the requirements} =$$

$$(\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$$

$$\text{Average time of occupancy} = \text{transmit time per hop} \times \text{number of hops in the period specified in the requirements}$$


5 Tests

5.1 Radiated emissions & restricted bands emissions

Tested by:	Andrea Giovanni Galbiati	
Test date:	2024-03-14 to 2024-03-19	
Test location (stand):	Area 8: SAC 3-1.2 (RF emission)	
Ambient temperature:	22 °C to 24 °C	
Relative humidity:	45 % to 47 %	
Atmospheric pressure:	998 mbar to 1000 mbar	
FCC requirements (clauses):	15.209(a), 15.247(d)	
ISED requirements (clauses):	RSS-Gen 6.13, RSS-Gen 8.9, RSS-Gen 8.10	
ANSI C63.10 test method (clause):	6.3, 6.5, 6.6	
EUT Test set-up:	☐	<u>Table-top equipment</u> EUT on nonconducting support of 80 cm height above the floor for measurements at or below 1 GHz
	☐	<u>Table-top equipment</u> EUT on nonconducting support of 1.5 m height above the floor for measurements above 1 GHz
	☐	<u>Floor-standing equipment</u> EUT on nonconducting support of 10 cm height above the floor
	☒	<u>Floor-standing equipment</u> If possible, the antenna(s) of the EUT is located at a height of 1.5 m above the floor, and the intentional radiator circuitry is located within the system at a height of at least 0.8 m above the floor.
	☐	Use of LISN on the floor for measurements between 30 MHz and 1000 MHz (optional)
	☐	Other:
Supplementary test set-up description:	---	
Test facility:	☐	<u>Range: 9 kHz to 30 MHz</u> OATS or SAC using active loop antenna (distance: 3 m; height: 1 m from the loop center)
	☒	<u>Range: 30 MHz to 1 GHz</u> OATS or SAC using hybrid (bicon/log) antenna (distance: 3 m; height: 1 m to 4 m)
	☒	<u>Range: 1 GHz to 26 GHz</u> FSOATS using double-ridged guide horn antenna (distance: 3 m; height: 1 m to 4 m)
	☐	<u>Range: 26 GHz to 40 GHz</u> FSOATS using double-ridged guide horn antenna (distance: 1 m; height: 1 m to 4 m)
Used mains voltage/frequency:	120 V; 60 Hz	
Supplementary information:	---	

Block diagram of the test setup:

30 MHz to 1 GHz



1 GHz to 26 GHz






Photo of test setup:





18 GHz to 26 GHz



Results

Operating Mode:	1		
Test result:	Pass	Tested on:	2024-03-14

Start Frequency: 30 MHz; Stop Frequency: 1 GHz; Step: 30 kHz; Sweep Time: 20 ms/Step; RF Attenuation: Auto; RBW: 120 kHz; VBW: Auto; Preamplifier: ON; Preselector: ON





- ☐ The emissions are below the measurement system noise floor or 6 dB or more below the limit
- ☒ The measurement results of highest emissions relative to the limit for each detector type are shown below:

Final Measurement Table

Frequency	SR #	Measure Peak (dBμV/m)	Measure QPeak (dBμV/m)	Limit QPeak (dBμV/m)	Margin QPeak (dB)	Max height (m)	Max angle (°)	Polarization	RBW (Hz)	Meas.Time (s)	Comments	Correction (dB)
624.99 MHz	1	38.277	34.863	46.02	-11.157	1.389	135.5	Horizontal	120 k	5	Pass	27.845
874.98 MHz	1	41.362	38.211	46.02	-7.809	1.007	151.9	Horizontal	120 k	5	Pass	30.775
877.11 MHz	1	33.533	22.703	46.02	-23.317	2.392	284.4	Horizontal	120 k	5	Pass	30.789
890.31 MHz	1	33.623	22.838	46.02	-23.182	1.613	254	Horizontal	120 k	5	Pass	31.07
896.79 MHz	1	33.223	23.042	46.02	-22.978	3.878	275.1	Horizontal	120 k	5	Pass	31.28
905.01 MHz	1	33.582	23.245	46.02	-22.775	1.433	296.3	Horizontal	120 k	5	Pass	31.492
30.45 MHz	2	22.615	12.508	40	-27.492	3.741	256.4	Vertical	120 k	5	Pass	18.331
34.17 MHz	2	25.777	17.876	40	-22.124	2.875	301.9	Vertical	120 k	5	Pass	18.507
48.15 MHz	2	28.859	21.77	40	-18.23	1.156	302.2	Vertical	120 k	5	Pass	19.956
52.68 MHz	2	28.421	22.258	40	-17.742	1.005	346.1	Vertical	120 k	5	Pass	19.909
77.58 MHz	2	29.889	25.664	40	-14.336	1.168	349.6	Vertical	120 k	5	Pass	16.138
874.98 MHz	2	38.206	33.461	46.02	-12.559	1	352.5	Vertical	120 k	5	Pass	30.775

Operating Mode:	1	
Test result:	Pass	Tested on: 2024-03-15

Start Frequency: 1 GHz; Stop Frequency: 4 GHz; Step: 250 kHz; Sweep Time: 20 ms/Step; RF Attenuation: Auto; RBW: 1 MHz; VBW: Auto; Preamplifier: ON; Preselector: ON
Start Frequency: 4 GHz; Stop Frequency: 18 GHz; Step: 250 kHz; Sweep Time: 20 ms/Step; RF Attenuation: Auto; RBW: 1 MHz; VBW: Auto; Preamplifier: OFF; Preselector: ON





- ☐ The emissions are below the measurement system noise floor or 6 dB or more below the limit
- ☒ The measurement results of highest emissions relative to the limit for each detector type are shown below:

Final Measurement Table

Frequen cy	S R #	Measur e Peak (dBμV/ m)	Limit Peak (dBμV/ m)	Margi n Peak (dB)	Measur e CAvg (dBμV/ m)	Limit Avg (dBμV/ m)	Margi n Avg (dB)	Heig ht (m)	Angl e (°)	Polarizati on	RB W (Hz)	Meas.Ti me (s)	Commen ts	Correctio n (dB)
1.375 GHz	1	45.59	74	-28.41	35.209	54	-18.791	1	234.4	Horizontal	1 M	5	Pass	31.91
2.112 GHz	1	62.232	74	-11.768	41.659	54	-12.341	1.123	163.3	Horizontal	1 M	5	Pass	35.331
3.993 GHz	1	52.99	74	-21.01	37.527	54	-16.473	3.218	71.8	Horizontal	1 M	5	Pass	38.616
16.78 GHz	2	48.965	74	-25.035	35.586	54	-18.414	2.023	286.8	Horizontal	1 M	5	Pass	12.455
2.112 GHz	1	56.919	74	-17.081	36.489	54	-17.511	2.007	207.5	Vertical	1 M	5	Pass	35.331
3.981 GHz	1	53.485	74	-20.515	37.492	54	-16.508	2.975	227.7	Vertical	1 M	5	Pass	38.608
3.994 GHz	1	52.98	74	-21.02	37.505	54	-16.495	2.424	54	Vertical	1 M	5	Pass	38.617
16.781 GHz	2	49.478	74	-24.522	35.533	54	-18.467	2.246	340.3	Vertical	1 M	5	Pass	12.455

Operating Mode:	1		
Test result:	Pass	Tested on:	2024-03-19

Start Frequency: 18 GHz; Stop Frequency: 26 GHz; Step: 250 kHz; Sweep Time: 20 ms/Step; RF Attenuation: Auto; RBW: 1 MHz; VBW: Auto; Preamplifier: OFF; Preselector: ON





- ☐ The emissions are below the measurement system noise floor or 20 dB or more below the limit
- ☒ The measurement results of highest emissions relative to the limit for each detector type are shown below:

Final Measurement Table

Frequency	SR #	Measure Peak (dBμV/m)	Limit Peak (dBμV/m)	Margin Peak (dB)	Measure CAvg (dBμV/m)	Limit Avg (dBμV/m)	Margin Avg (dB)	Height (m)	Angle (°)	Polarization	RBW (Hz)	Meas. Time (s)	Comments	Correction (dB)
25.43 GHz	1	61.276	74	-12.724	47.969	54	-6.031	3.152	344.9	Horizontal	1 M	5	Pass	23.267
25.976 GHz	1	62.274	74	-11.726	48.91	54	-5.09	2.391	306.3	Horizontal	1 M	5	Pass	24.16
25.945 GHz	2	62.294	74	-11.706	48.612	54	-5.388	2.271	303	Vertical	1 M	5	Pass	23.837
25.97 GHz	2	62.045	74	-11.955	48.782	54	-5.218	1.941	343.7	Vertical	1 M	5	Pass	24.099

Operating Mode:	1		
Test result:	Pass	Tested on:	2024-03-18

Start Frequency: 2.31 GHz; Stop Frequency: 2.39 GHz; Step: 250 kHz; Sweep Time: 500 ms/Step; RF Attenuation: Auto; RBW: 1 MHz; VBW: Auto; Preamplifier: ON; Preselector: ON





- ☐ The emissions are below the measurement system noise floor or 20 dB or more below the limit
- ☒ The measurement results of highest emissions relative to the limit for each detector type are shown below:

Final Measurement Table

Frequency	SR #	Measure Peak (dBuV/m)	Limit Peak (dBuV/m)	Margin Peak (dB)	Measure CAvg (dBuV/m)	Limit Avg (dBuV/m)	Margin Avg (dB)	Height (m)	Angle (°)	Polarization	RBW (Hz)	Meas.Time (s)	Comments	Correction (dB)
2.374 GHz	1	48.532	74	-25.468	31.99	54	-22.01	1.955	268.1	Horizontal	1 M	5	Pass	35.991
2.375 GHz	1	49.401	74	-24.599	32.17	54	-21.83	2.558	152.2	Horizontal	1 M	5	Pass	35.997
2.341 GHz	2	48.019	74	-25.981	31.434	54	-22.566	3.558	57.9	Vertical	1 M	5	Pass	35.6
2.38 GHz	2	49.023	74	-24.977	31.874	54	-22.126	1.603	39.1	Vertical	1 M	5	Pass	36.031

Operating Mode:	2		
Test result:	Pass	Tested on:	2024-03-18

Start Frequency: 2.445 GHz; Stop Frequency: 2.5 GHz; Step: 1000 Pts; Sweep Time: 500 ms; RF Attenuation: 10 dB; RBW: 1 MHz; VBW: 3 MHz; Preamplifier: ON; Preselector: ON



- ☐ The emissions are below the measurement system noise floor or 20 dB or more below the limit
- ☒ The measurement results of highest emissions relative to the limit for each detector type are shown below:

Final Measurement Table

Frequency	SR #	Measure Peak (dBμV/m)	Measure Avg (dBμV/m)	Limit Peak (dBμV/m)	Margin Peak (dB)	Limit Avg (dBμV/m)	Margin Avg (dB)	Max height (m)	Max angle (°)	RBW (Hz)	Meas.Time (s)	Comments	Correction (dB)
2.492 GHz	1	58.285	42.703	74	-15.715	54	-11.297	1.001	300.1	1 M	0.5	Pass	36.294
2.499 GHz	1	60.732	42.794	74	-13.268	54	-11.206	1.998	329.9	1 M	0.5	Pass	36.334
2.494 GHz	2	58.743	42.746	74	-15.257	54	-11.254	3.501	240.2	1 M	0.5	Pass	36.302
2.497 GHz	2	60.432	42.752	74	-13.568	54	-11.248	3.998	329.8	1 M	0.5	Pass	36.323