

# WL8200-IT3 Outdoor Wireless AP



#### **Product Overview**

The WL8200-IT3 is a series of new-generation 802.11ac-based high-performance gigabit outdoor wireless access points (APs) launched by Yunke China Information Technology Limited (hereinafter referred to as DCN) for industrial users. The WL8200-IT3 uses GE ports as its uplink ports for access, which break through the limitations of FE ports and enable wireless multimedia applications to come true.

While completely taking into consideration important factors, such as wireless network security, radio frequency (RF) control, mobile access, quality of service (QoS) guarantee, and seamless roaming, the WL8200-IT3 may be used with DCN wireless ACs to perform data forwarding, security, and access control of wireless users.

The WL8200-IT3 operates in a 2.4 GHz or 5 GHz band and employs technologies such as multiple-input multiple-output (MIMO) and orthogonal frequency division multiplexing (OFDM), providing a data transmission rate of at most 400 Mbps in 2.4GHz band and 867Mbps in 5GHz band.

The WL8200-IT3 employs industrial standard components. Its shell of the IP67 class is solid, waterproof, and dustproof, enabling the device to suit an adverse indoor environment. Along with a high-gain outdoor antenna of DCN, the WL8200-IT3 provides customers with a choice for constructing a high-performance and high-coverage wireless network. The WL8200-IT3 is a series of high-rate wireless APs preferred in various outdoor application environments for purposes such as campus WLAN access, campus coverage, and operators' hot spot coverage.

# **Highlights**

### **High-Performance and High-Reliability Wireless Network**

#### High-speed wireless broadband access

The WL8200-IT3 supports the 802.11abgn/ac standard and may operate in a 2.4 GHz or 5 GHz band. It provides an access bandwidth up to 1.267Gbps.



### • GE ports for wired connections

GE ports are used as uplink ports for access, which break through the limitations of conventional FE ports, so that wired ports are no longer a bottleneck of wireless access rates, offering a platform for smooth upgrade to support higher rates and more RF portfolios in the future.

#### • High-performance RF characteristics

Professional optimized design is employed for the RF module of the WL8200-IT3, so that a single antenna port supports 27 dB transit power at all rate levels, thereby improving wireless coverage in high-rate access scenarios.

### • Automatic emergency mechanism of APs

In a centralized network architecture where fit APs and a wireless AC are deployed, the APs will be unable to operate normally when the wireless AC is down and then the entire wireless network will crash. DCN wireless APs support an automatic emergency mechanism. This mechanism enables an AP to intelligently detect links. When detecting that the wireless AC is down, the AP quickly switches its operating mode so that it may continue to forward data while enabling new users to access the network. This mechanism attains high availability in the entire wireless network and really helps wireless users to be always online.

### Broad operating temperature range

Thanks to deliberate hardware design and the selection of dedicated components operating in a broad temperature range, DCN smart APs may operate in an environment with its temperature ranging from -40°C to 65°C.

# **Wireless Network of Intelligent Control and Automatic Perception**

#### Only 11n access control mechanism

Since 802.11n is downward compatible with the 802.11a/b/g protocol, generally 802.11a/b/g users can also access an 802.11n wireless access device. When this compatibility is provided, however, users with 802.11n access capability will experience performance degradation to a certain extent. On DCN smart APs, a certain RF channel may be set to only 11n access mode so that 802.11n users have guaranteed bandwidths. For some 802.11n wireless access devices capable of simultaneously providing dual frequencies for user access, it is recommended that the 5 GHz RF channel be set to only 11n access mode to guarantee a high-speed bandwidth and access performance of 802.11n access users; while the 2.4 GHz RF channel be set to compatible access mode to guarantee normal access of original 802.11b/g users.

### • Intelligent RF management



RF detection and management algorithms to attain a better RF coverage effect. When the signals of an AP are interfered by strong external signals, the AP may automatically switch to an appropriate operating channel under the control of the AC to avoid such interference, thereby guaranteeing wireless network communications. The system also supports wireless network blackhole compensation. When an AP on the network accidentally stops operating, the RF management function of the AC compensates the resulting blind area of signals so that the wireless network can still operate normally.

#### • Intelligent control of terminals based on airtime fair

When some outdated 802.11b and 802.11g terminals are used on a wireless network or some terminals are far way from APs, negotiation rates will be low, causing a large number of users to experience a long WLAN access delay, low rates, or poor overall AP performance. The AP performance problem in a low-rate terminal access environment, however, cannot be resolved by simply employing rate control and traffic shaping. DCN smart APs have essentially resolved this problem by using intelligent control of terminals based on airtime fairness, ensuring that a user can always enjoy the same joyful WLAN experience in the same location, no matter what type of the terminal the user is holding.

The intelligent control of terminals based on airtime fairness greatly improves the performance of both the client and the entire network. It enables all clients with high data transmission rates to attain strikingly higher performance while low-rate clients are almost not affected at all. The performance will be even more obviously higher on an open wireless network. Once high-rate clients finish data transmission, fewer clients will be transmitting data on the wireless network. In this case, there will be less contention and retry on the network, thereby greatly improving overall AP performance.

### Intelligent load balancing mechanism

In general, a wireless client will select an AP according to the signal strength of APs. When this uncontrolled access mode is applied, however, a large number of clients could be connected to the same AP simply because the AP provides strong signals. As more clients are connected to an AP, the bandwidth available to each client will be smaller, thereby greatly affecting user experience of the clients. DCN wireless products support diversified intelligent load balancing means:

- AP load balancing based on traffic
- AP load balancing based on the number of users
- AP load balancing based on frequency bands
- Access control based on signal strength of terminals
- Mandatory roaming control of terminals to direct terminals to APs with stronger signals

### • Intelligent identification of terminals

DCN smart APs may be used with DCN wireless ACs and a unified authentication platform to intelligently identify the size, system type, and type of each terminal; and comprehensively support mainstream smart terminal operating systems, such as Apple iOS, Android, and Windows. They intelligently identify the size of a terminal and adaptively present a portal authentication page of the corresponding size and page pattern, freeing users from multiple times of dragging to adjust the screen



and enabling users to enjoy more intelligent wireless experience. They can also intelligently identify the system type of each terminal and present the system type of each terminal such as Windows, MAC OS, or Android on the unified authentication platform, exhibiting every detail of intelligence to users. In addition, they can intelligently identify the type of each terminal such as the mobile phone, tablet, or PC, and implement dynamic policy control of terminals according to different types of the terminals, making possible more intelligent user control at a finer granularity.

#### • Comprehensive support for IPv4/v6 dual-stack networks

Powered by DCN cutting-edge IPv6 technology, DCN smart APs may be deployed on an IPv6 network, with IPv6 tunnels established through auto negotiation between a wireless AC and an AP. When the wireless AC and the AP completely operate in IPv6 mode, the wireless AC can still correctly identify IPv4 terminals and process IPv4 packets from wireless clients. Featuring flexible adaptability to IPv4/6, DCN smart APs cater to complex applications involved in migration from an IPv4 network to an IPv6 network. They not only provide IPv4 service to customers on an IPv6 network, but also enable users on an IPv4 network to log in to the network through the IPv6 protocol at ease.

#### Network-wide seamless roaming

DCN wireless ACs support an advanced wireless AC cluster technology to support network-wide seamless roaming, the continuity of real-time mobile services is well guaranteed.

### **Secure and Controllable Wireless Network**

#### • User isolation policy

DCN wireless APs support the isolation of wireless users from one another. If this user isolation function is enabled, two wireless clients cannot directly communicate with each other but can only access an upstream wired network. This further guarantees the security of wireless network applications.

#### Wireless intrusion detection and intrusion defense

DCN wireless APs support wireless intrusion detection and intrusion defense features, such as detection of unauthorized wireless devices, intrusion detection, blacklist, and white list, thereby greatly improving security management of an entire wireless network.

### Wireless user management at a fine granularity

Each AP supports a maximum of 32 WLANs to implement multi-layer multi-service management of wireless users at a fine granularity. Each WLAN supports access control and uplink/downlink rate limit based on MAC or IP addresses. These WLANs may be bound to virtual local area networks (VLANs). In addition, different authentication and accounting policies can be implemented. This feature is practically significant in a multi-WLAN environment.



#### • Secure user admission

DCN smart APs may be used with wireless ACs to provide multiple secure access, authentication, and accounting mechanisms for various application environments. These mechanisms include:

- 802.1x authentication
- Captive portal authentication, including built-in portal, external portal, and custom portal authentication modes
- MAC address authentication
- LDAP authentication
- WAPI encryption and authentication
- Wired/wireless integrated authentication and accounting

#### Wireless SAVI

DCN wireless network products support a source address validation (SAVI) technology to deal with spoofed packet attacks that keep emerging on today's campus networks. As users' IP addresses are obtained through an address allocation protocol, users access the Internet using correct addresses in subsequent applications and cannot spoof others' IP addresses, thereby guaranteeing the reliability of source addresses. In addition, the SAVI technology is combined with a portal technology to further guarantee the authenticity and security of packets of all users accessing the Internet.

#### • PEAP user authentication

With the popularization and application of smart terminals, wireless terminal users require authentication mechanisms of higher usability and convenience. Using a mechanism that combines portal authentication and MAC address authentication, DCN wireless network products support Protected Extensible Authentication Protocol (PEAP) authentication to attain better user experience. Initially a user needs to manually perform portal authentication and later the user gets authenticated through PEAP in automatic mode. DCN wireless network products feature high terminal adaptation and provide good authentication compatibility. They adapt to the majority of WLAN terminals and do not need to adapt to clients. DCN wireless network products are compatible with existing portal authentication modes.

### • Secure access mechanism

An AP is usually deployed in a public area and therefore requires a strict security mechanism to guarantee the legality of access devices. The following secure access mechanisms may be applied between a DCN smart AP and a wireless AC:

- AP MAC address authentication
- AP password authentication
- Bidirectional digital certificate authentication



## **Easy-to-Manage Wireless Network**

### • Plug-and-play

DCN smart APs are able to automatically discover DCN wireless ACs. A wireless network function can be enabled on an AP without performing any configuration on the AP at all. The AP can be seamlessly integrated with existing switches, firewalls, authentication servers, and other network devices without changing existing network architecture.

When used with a DCN wireless AC, DCN smart APs support plug-and-play and zero configuration. The wireless AC undertakes all the management, control, and configuration of the APs. Network administrators do not need to separately manage or maintain a huge number of wireless APs. All actions, such as configuration, firmware upgrade, and security policy updating, are performed uniformly under the control of the wireless AC.

#### • Fit and Fat modes

DCN smart APs may work in fit or fat mode and can flexibly switch between the fit mode and the fat mode according to network planning requirements. Users may also flexibly choose an ex-factory device version according to specific application requirements. APs working in fit mode are managed by a wireless AC in a centralized manner. System administrators may easily manage the entire network as the states of all the APs are clear at a glance.

### • Remote probe analysis

DCN smart APs support a remote probe analysis function, which listens to and captures Wi-Fi packets in the coverage and mirrors them to a local analysis device in real time to help network administrators better perform troubleshooting or optimization analysis. The remote probe analysis function can perform non-convergence mirroring of a working channel and sampling of all channels in polling mode as well to flexibly meet various wireless network monitoring, operation, and maintenance requirements.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Use Restriction: This device is restricted to indoor use when operating in the 5150 to 5350 MHz frequency range in following countries:

BE	EL	LT	PT
BG	ES	LU	RO
CZ	FR	HU	SI
DK	HR	MT	SK
DE	IT	NL	FI
EE	CY	AT	SE
ΙE	LV	PL	UK

Belgium (BE), Greece (EL), Lithuania (LT), Portugal (PT), Bulgaria (BG), Spain (ES), Luxembourg (LU), Romania (RO), Czech Republic (CZ), France (FR), Hungary (HU), Slovenia (SI), Denmark (DK), Croatia (HR), Malta (MT), Slovakia (SK), Germany (DE), Italy (IT), Netherlands (NL), Finland (FI), Estonia (EE), Cyprus (CY), Austria (AT), Sweden (SE), Ireland (IE), Latvia (LV), Poland (PL) and United Kingdom (UK).



# **Product Specifications**

### **Hardware Specifications**

Item	WL8200-IT3
Dimensions (mm)	214mm×214mm×67.5mm
Working Frequency	2.4G: 802.11b/g/n 5G: 802.11a/n/ac wave2 2.4G: Bluetooth
Maximum Data Rate	2.4G: 400Mbps 5G: 867Mbps
Physical Port	1 * 10/100/1000Base-T PoE port for uplink 1 * 10/100/1000Base-T port for downlink, could connect external IoT module 1 * 1000M SFP fiber port One Bluetooth interface, could connect Bluetooth device which could be used for IoT
PoE	802.3at
Maximum power consumption	< 20W
Antenna	Internal antenna, 2.4G 7dBi, 5G 8dBi, H110
Working frequency band	802.11a/n: 5.150 GHz to 5.250GHz 5.725GHz to 5.850GHz 802.11b/g/n: 2.4 GHz to 2.483 GHz 802.11ac: 5.150GHz to 5.250GHz 5.725GHz to 5.850GHz
Modulation technology	OFDM: BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps DSSS:  DBPSK@1Mbps, DQPSK@2Mbps, CCK@5.5/11Mbps  MIMO-OFDM (11n): MCS 0-15  MIMO-OFDM (11ac): MCS 0-9  802.11b: BPSK, QPSK, CCK  802.11a/g/n:BPSK, QPSK, 16-QAM, 64-QAM  802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
Transmit power	Maximum 30 dBm for all rate levels and modulation modes
Power adjustment granularity	1 dBm



Working/Storage	-40°C to +65°C
temperature	-45°C to +80°C
Working/Storage RH	5% to 95% (non-condensing)
Protection level	IP67
FR standard	Radio Transmission Equipment Type Approval Certificate issued by the Ministry of Industry and
	Information Technology of P. R. China

# **Software Specifications**

Item	Feature	WL8200-IT3
	Product positioning	Outdoor dual-frequency
	Working frequency band	2.4 GHz and 5 GHz
	Maximum Concurrent Clients	256
	Virtual AP (BSSID)	32
	Number of spatial streams	2
	Dynamic channel adjustment (DCA)	Yes
	Transmit power control (TPC)	Yes
	Blind area detection and repair	Yes
WLAN	SSID hiding	Yes
	RTS/CTS	Yes
	RF environment scanning	Yes
	Hybrid access	Yes
	Restriction on the number of access users	Yes
	Link integrity check	Yes
	Intelligent control of terminals based on airtime	Yes
	fairness	105
	High-density application optimization	Yes
11n	40 MHz bundling	Yes



Item	Feature	WL8200-IT3
enhancements	400Mbps (PHY)	Yes
	Frame aggregation (A-MPDU)	Yes
	Maximum likelihood demodulation (MLD)	Yes
	Transmit beam forming (TxBF)	Yes
	Maximum ratio combining (MRC)	Yes
	Space-time block coding (STBC)	Yes
	Low-density parity-check code (LDPC)	Yes
	Encryption	64/128 WEP, dynamic WEP, TKIP, and CCMP encryption
	802.11i	Yes
	WAPI	Yes
	MAC address authentication	Yes
	LDAP authentication	Yes
	PEAP authentication	Yes
	WIDS/WIPS	Yes
	Protection against DoS attacks	Anti-DoS for wireless management packets
	Forwarding security	Frame filtering, white list, static blacklist, and dynamic
Security		blacklist
	User isolation	AP L2 forwarding suppression Isolation between virtual APs (multiple SSIDs)
	Periodic SSID enabling and disabling	Yes
	Access control of free resources	Yes
	Secure admission control of wireless terminals	Secure admission control of wireless terminals based on DCSM
	Wireless SAVI	Yes
	ACL	Access control of various data packets such as MAC, IPv4, and
		IPv6 packets
	Secure access control of APs	Secure access control of APs, such as MAC authentication,
		password authentication, or digital certificate authentication



Item	Feature	WL8200-IT3	
		between an AP and an AC	
Forwarding	IP address setting	Static IP address configuration or dynamic DHCP address	
		allocation	
	IPv6 forwarding	Yes	
	IPv6 portal	Yes	
	Local forwarding	Yes	
S	Multicast	IGMP Snooping	
	Roaming	Yes	
	AP switching reference	Signal strength, bit error rate, RSSI, S/N, whether neighboring APs are normally operating, etc.	
	WDS	Yes	
	WMM	Yes	
	Priority mapping	Ethernet port 802.1P identification and marking Mapping from wireless priorities to wired priorities	
	QoS policy mapping	Mapping of different SSIDs/VLANs to different QoS policies  Mapping of data streams that match with different packet fields to different QoS policies	
	L2-L4 packet filtering and flow classification	Yes: MAC, IPv4, and IPv6 packets	
QoS	Load balancing	Load balancing based on the number of users  Load balancing based on user traffic  Load balancing based on frequency bands	
	Bandwidth limit	Bandwidth limit based on APs Bandwidth limit based on SSIDs Bandwidth limit based on terminals Bandwidth limit based on specific data streams	
	Call admission control (CAC)	CAC based on the number of users	
	Power saving mode	Yes	
	Automatic emergency mechanism of APs	Yes	
	Intelligent identification of terminals	Yes	
	Wireless network VAS	Abundant wireless network VASs; applications based on smar	
		terminals; advertisement push based on site locations	



Item	Feature	WL8200-IT3	
		personalized push of the portal	
	Multicast enhancement	Multicast to unicast	
Management	Network management	Centralized management through an AC; both fit and fat modes	
	Maintenance mode	Both local and remote maintenance	
	Log function	Local logs, Syslog, and log file export	
	Alarm	Yes	
	Fault detection	Yes	
	Statistics	Yes	
	Switching between the fat and fit modes	An AP working in fit mode can switch to the fat mode through a wireless AC;  An AP working in fat mode can switch to the fit mode through a local control port or Telnet.	
	Remote probe analysis	Yes	
	Watchdog	Yes	

### **Product Purchase Information**

<b>Product Model</b>	Description	Remarks
WL8200-IT3	802.11a/b/g/n/ac wave2 outdoor high performance AP (2.4GHz & 5GHz	Mandatory
	dual band, 1.267Gbps, internal 10dBi directional antenna, 2 *	
	10/100/1000Base-T GE ports and 1 * SFP fiber port, 802.3at PoE)	
DCWL-PoEINJ-G+	10/100/1000 Mbps 1-port 802.3at PoE module	Optional

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- —Reorient or relocate the receiving antenna.
- —Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



### **Quick Installation Guide**

This quick installation guide describes the steps of installing the DCN Access Point, including the basic introduction the basic installation steps,lay out cables, etc.

#### Special attention

There is no CD of the Access Point manual which is in www.dcnglobal.com for obtaining.

#### **Technical Support**

Yunke China Information Technology Limited

Technology Plaza 3F, NO.9 Shangdi 9th Street, Haidian District, Beijing,

China


Zip code:100085

Website: www.dcnglobal.com


Service E-mail: dcn\_support@digitalchina.com

#### Wall Mount

1.Fix mounting bracket on the wall.



2. Fix device to the mounting bracket.



3. Fasten the screws.



### Pole Mount

1. Place the device on the pole.



2. Insert the straps in the slots on the device and wrap around pole.




Fasten the screws and check whether the device is fixed tightly on the pole.

#### Power up

1.Plug one end of the Ethernet cable into the PoE+ switch or injector and plug the other end into the LAN1 (PoE) on the device. Make sure the PoE+ source you are using is turned ON.

#### Connect to the network

As you are using PoE+, the device should already be connected to your network.






#### Check the LED status

Wait for a few minutes till the Power (PWR) LED and LAN1 (PoE) LED turn solid GREEN, which indicates that the device is online and operation.



### Waterproof Measure

Waterproof tape and PVC insulation tape must be wrapped around the interface of outside connecter. To prevent water from flowing into the device along the cable connected to service Port, a drip loop must be created on the cable.








Waterproof tape and PVC insulation tape

#### Lightning Surge Protection

Outdoor AP must be installed on a metal pole on top of which the lightning rod is welded. For outside antenna, an additional surge protective device can be installed and it is connected to a ground wire.



#### **Ground Protection**

Grounding is a key step in device installation. The ground wire of a device must be correctly connected to lightning proof earth grid to protect the device from lightning, electromagnetic interference, and electrostatic charges.