



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC Part 27C

Report Reference No..... : CTL211122071-W08

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Tested by:
(position+printed name+signature)

Gray Gao
(Test Engineer)

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)



Product Name..... : All Netcom Android module

Model/Type reference..... : M101C

List Model(s)..... : M101C-QVCT-1G8G, M101C-QVCX-1G8G, M101C-QVCT-2G16G,
M101C-QVCX-2G16G, M101C-QECT-1G8G, M101C-QECX-1G8G,
M101C-QECT-2G16G, M101C-QECX-2G16G

Trade Mark..... : Temolin

FCC ID..... : 2AM5I-M101C

Applicant's name..... : Temolin Technology, Inc

Address of applicant..... : Room 313c, Building South D, NO.33Guangshun Road,
Changning District, Shanghai, China

Test Firm..... : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm..... : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test specification..... :

Standard..... : FCC CFR Title 47 Part 2, Part 27
EIA/TIA 603-D: 2010
KDB 971168 D01

TRF Originator..... : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF..... : Dated 2011-01

Date of receipt of test item..... : Nov. 22, 2021

Date of sampling..... : Nov. 22, 2021

Date of Test Date..... : Nov. 22, 2021-Dec. 27, 2021

Data of Issue..... : Dec. 27, 2021

Result..... : Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. : CTL2111122071-W08	Dec. 27, 2021 Date of issue
--	--------------------------------

Equipment under Test : All Netcom Android module

Sample No : CTL211112207-1-S001

Model /Type : M101C

Listed Models : M101C-QVCT-1G8G, M101C-QVCX-1G8G,
M101C-QVCT-2G16G, M101C-QVCX-2G16G,
M101C-QECT-1G8G, M101C-QECX-1G8G,
M101C-QECT-2G16G, M101C-QECX-2G16G

Applicant : **Temolin Technology,Inc**

Address : Room 313c, Building South D, NO.33Guangshun
Road, Changning District, shanghai, China

Manufacturer : **Shenzhen Guoguan Electronics co., Ltd**

Address : 4 / F, building E, Xinxiong Industrial Zone, No. 157,
Gushu 1st Road, Xixiang street, Bao'an District,
Shenzhen

Test result	Pass *
--------------------	---------------

*In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

[illegible]

Table of Contents

Page

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY.....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2. GENERAL INFORMATION.....	7
2.1. ENVIRONMENTAL CONDITIONS.....	7
2.2. GENERAL DESCRIPTION OF EUT.....	7
2.3. DESCRIPTION OF TEST MODES.....	8
2.4. EQUIPMENTS USED DURING THE TEST.....	10
2.5. RELATED SUBMITTAL(S) / GRANT (S).....	10
2.6. MODIFICATIONS.....	10
3. TEST CONDITIONS AND RESULTS.....	11
3.1. OUTPUT POWER.....	11
3.2. PEAK-TO-AVERAGE RATIO (PAR).....	16
3.3. OCCUPIED BANDWIDTH AND EMISSION BANDWIDTH.....	17
3.4. BAND EDGE COMPLIANCE.....	18
3.5. SPURIOUS EMISSION.....	19
3.6. FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS.....	29
3.7. MODULATION CHARACTERISTICS.....	31
4. TEST SETUP PHOTOS OF THE EUT.....	32
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....	33

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 27](#) : MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[TIA/EIA 603 D June 2010](#):Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[FCC Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[KDB971168 D01: v03r01](#) MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

[ANSI C63.10: 2020](#): American National Standard for Testing Unlicensed Wireless Devices

[ANSI C63.4: 2014](#): –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz
Range of 9 kHz to 40GHz

1.2. Test Description

Test Item	Section in CFR 47	Result
Effective (Isotropic) Radiated Power Output Data	§2.1046 §27.50(b)(10)(c)(10)(h)(2)	Pass
Peak-to-Average Ratio	§2.1046 §27.50(d)(5)	Pass
Modulation Characteristics	§2.1047	Pass
Bandwidth	§2.1049	Pass
Band Edges Compliance	§ 2.1051 §27.53(c)(f)(g)(m)(4)	Pass
Conducted Spurious Emissions	§2.1051 §27.53(c)(f)(g)(m)(4)	Pass
Field Strength of Spurious Radiation	§2.1053 §27.53(c)(f)(g)(m)(4)	Pass
Frequency stability	§2.1055 §27.54	Pass

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahehexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	All Netcom Android module		
Model/Type reference:	M101C		
Power supply:	DC 5V from USB		
Hardware version:	V1.3		
Software version:	Alps-mp-p.mp1-v5.10-temolin-m100c-v1.34f		
LTE			
Mode:	LTE Band 4; LTE Band7; LTE Band41;		
Modulation Type:	(WCDMA)QPSK; (LTE)QPSK 16QAM		
Operating Frequency Range(S)	Band	Tx(MHz)	Rx(MHz)
	LTE Band 4	1710~1755	2110~2155
	LTE Band 7	2500~2570	2620~2690
	LTE Band 41	2496~2690	2496~2690
Release Version:	Release 9		
Category:	Cat 4		
Antenna type:	PIFA Antenna		
Antenna gain:	LTE Band 4: 3.0 dBi LTE Band 7:3.0 dBi LTE Band 41: 3.0 dBi		

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes

1. The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

2. Test Frequencies

Test Mode	Bandwidth	TX/RX	RF Channel		
			Low (L)	Middle (M)	High (H)
LTE Band 4	1.4MHz	TX	Channel 19957	Channel 20175	Channel 20393
			1710.7MHz	1732.5MHz	1754.3MHz
		RX	Channel 1975	Channel 2175	Channel 2375
			2112.5MHz	2132.5MHz	2152.5MHz
	3MHz	TX	Channel 19965	Channel 20175	Channel 20385
			1711.5MHz	1732.5MHz	1753.5MHz
		RX	Channel 2000	Channel 2175	Channel 2350
			2115MHz	2132.5MHz	2150MHz
	5MHz	TX	Channel 19975	Channel 20175	Channel 20375
			1712.5MHz	1732.5MHz	1752.5MHz
		RX	Channel 1975	Channel 2175	Channel 2375
			2112.5MHz	2132.5MHz	2152.5MHz
	10MHz	TX	Channel 20000	Channel 20175	Channel 20350
			1715MHz	1732.5MHz	1750MHz
		RX	Channel 2000	Channel 2175	Channel 2350
			2115MHz	2132.5MHz	2150MHz
	15MHz	TX	Channel 20025	Channel 20175	Channel 20325
			1717.5MHz	1732.5MHz	1747.5MHz
		RX	Channel 2025	Channel 2175	Channel 2325
			2117.5MHz	2132.5MHz	2147.5MHz
	20 MHz	TX	Channel 200.50	Channel 20175	Channel 20300
			1720MHz	1732.5MHz	1745MHz
		RX	Channel 2050	Channel 2175	Channel 2300
			2120MHz	2132.5MHz	2145MHz

Test Mode	Bandwidth	TX/RX	RF Channel		
			Low (L)	Middle (M)	High (H)
LTE Band 7	5MHz	TX	Channel 20775	Channel 21100	Channel 21425
			2502.5MHz	2535MHz	2567.5MHz
		RX	Channel 2775	Channel 3100	Channel 5825
			2622.5MHz	2655MHz	2687.5MHz
	10MHz	TX	Channel 20800	Channel 21100	Channel 21400
			2505MHz	2535MHz	2565MHz
		RX	Channel 2800	Channel 3100	Channel 3400
			2625MHz	2655MHz	2685MHz
	15MHz	TX	Channel 20825	Channel 21100	Channel 21375
			2507.5MHz	2535MHz	2562.5MHz
		RX	Channel 2825	Channel 3100	Channel 3375
			2627.5MHz	2655MHz	2682.5MHz
	20 MHz	TX	Channel 20850	Channel 21100	Channel 21350
			2510MHz	2535MHz	2560MHz
		RX	Channel 2850	Channel 3100	Channel 3350
			2630MHz	2655MHz	2680MHz

Test Mode	Bandwidth	TX/RX	RF Channel		
			Low (L)	Middle (M)	High (H)
LTE Band 41	5MHz	TX/ RX	Channel 39675	Channel 40620	Channel 41565
			2557.5MHz	2605.5MHz	2652.5MHz
	10MHz	TX/ RX	Channel 39700	Channel 40620	Channel 41540
			2560.0MHz	2605.0MHz	2650.0MHz
	15MHz	TX/ RX	Channel 39725	Channel 40620	Channel 41515
			2562.5MHz	2605.0MHz	2647.5MHz
	20 MHz	TX/ RX	Channel 39750	Channel 40620	Channel 41490
			2565.5MHz	2605.0MHz	2645.0MHz

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2020/04/08	2023/04/07
EMI Test Receiver	R&S	ESCI	101235	2021/08/20	2022/08/19
Spectrum Analyzer	Agilent	E4407B	MY41440676	2021/05/14	2022/05/13
Spectrum Analyzer	Agilent	N9020	US46220290	2021/05/14	2022/05/13
Spectrum Analyzer	Keysight	N9020A	MY53420874	2021/05/14	2022/05/13
Controller	EM Electronics	Controller EM 1000	N/A	2021/05/22	2022/05/21
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2020/09/22	2023/09/21
Active Loop Antenna	SCHWARZBEC K	ZN30900A	N/A	2021/05/13	2024/05/12
Amplifier	Agilent	8349B	3008A02306	2021/05/10	2022/05/09
Amplifier	Agilent	8447D	2944A10176	2021/05/10	2022/05/09
Temperature/Humidity Meter	Gangxing	CTH-608	02	2021/05/11	2022/05/10
Wideband Radio Communication Tester	R&S	CMW500	101814	2021/05/14	2022/05/13
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2021/05/22	2022/05/21
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2021/05/22	2022/05/21
RF Cable	HUBER+SUHNER	RG214	N/A	2021/05/22	2022/05/21
Climate Chamber	ESPEC	EL-10KA	A20120523	2021/05/22	2022/05/21
SIGNAL GENERATOR	Agilent	E4421B	US40051744	2021/05/14	2022/05/13
Directional Coupler	Agilent	87300B	3116A03638	2021/05/14	2022/05/13
Power Sensor	Agilent	U2021XA	MY5365004	2021/05/14	2022/05/13
Power Meter	Agilent	U2531A	TW53323507	2021/05/14	2022/05/13

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with of the Part 27 Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS


3.1. Output Power

LIMIT


According to §27.50 (d) (4): Fixed, mobile, and portable (hand- held) stations operating in are limited to 1 watt EIRP.

TEST CONFIGURATION

Conducted Power Measurement



Radiated Power Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- The output of the test antenna shall be connected to the measuring receiver.

- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) Test site anechoic chamber refer to ANSI C63.10.

TEST RESULTS**Conducted Measurement :**

1. Please refer to Appendix B: Section 1
2. Please refer to Appendix E: Section 1
3. Please refer to Appendix G: Section 1

Radiated Measurement:**Limits**

Rule Part 27.50(b)(10) specifies that " Portable stations (hand-held devices) transmitting in the 746~757 MHz , 776MHz~788MHz, and 805~806MHz bands are limited to 3 watts ERP "

Rule Part 27.50(c)(10) specifies that " Portable stations (hand-held devices) in the 600MHz uplink band and the 698-746MHz band, and mobile stations in the 600MHz uplink band are limited to 3 watts ERP "

Rule Part 27.50(d)(4) specifies that " mobile stations (hand-held) stations operating in the 1710~1755 MHz , band and mobile and portable stations operating in the 1695MHz~1710MHz and 1755~1780MHz bands are limited to 1 watts ERP "

Rule Part 27.50 (h) (2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP.

All user stations are limited to 2.0 watts transmitter output power.

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of WCDMA Band IV, TE Band 4, LTE Band 7, LTE Band 12, Band 13, Band 17, Band 41, Band 66, Band 71. recorded worst case for each Channel Bandwidth of WCDMA Band IV, TE Band 4, LTE Band 7, LTE Band 12, Band 13, Band 17, Band 41, Band 66, Band 71.

LTE FDD Band 4

Bandwidth	Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Polarization	Conclusion
1.4MHz QPSK	Low	1710.7	25.62	30.00	H	Pass
	Mid	1732.5	25.59	30.00	H	Pass
	High	1754.3	25.15	30.00	H	Pass
3MHz QPSK	Low	1711.5	25.66	30.00	H	Pass
	Mid	1732.5	25.18	30.00	H	Pass
	High	1753.5	25.25	30.00	H	Pass
5MHz QPSK	Low	1712.5	25.84	30.00	H	Pass
	Mid	1732.5	25.15	30.00	H	Pass
	High	1752.5	25.62	30.00	H	Pass
10MHz QPSK	Low	1715.0	25.15	30.00	H	Pass
	Mid	1732.5	25.88	30.00	H	Pass
	High	1750.0	25.44	30.00	H	Pass
15MHz QPSK	Low	1717.5	25.83	30.00	H	Pass
	Mid	1732.5	25.84	30.00	H	Pass
	High	1747.5	25.13	30.00	H	Pass
20MHz QPSK	Low	1720.0	25.32	30.00	H	Pass
	Mid	1732.5	25.27	30.00	H	Pass
	High	1745.0	25.91	30.00	H	Pass
1.4MHz 16QAM	Low	1710.7	25.16	30.00	H	Pass
	Mid	1732.5	25.52	30.00	H	Pass

3MHz 16QAM	High	1754.3	25.66	30.00	H	Pass
	Low	1711.5	25.48	30.00	H	Pass
	Mid	1732.5	25.47	30.00	H	Pass
	High	1753.5	25.11	30.00	H	Pass
5MHz 16QAM	Low	1712.5	25.62	30.00	H	Pass
	Mid	1732.5	25.29	30.00	H	Pass
	High	1752.5	25.21	30.00	H	Pass
10MHz 16QAM	Low	1715.0	25.22	30.00	H	Pass
	Mid	1732.5	25.94	30.00	H	Pass
	High	1750.0	25.28	30.00	H	Pass
15MHz 16QAM	Low	1717.5	25.29	30.00	H	Pass
	Mid	1732.5	25.92	30.00	H	Pass
	High	1747.5	25.48	30.00	H	Pass
20MHz 16QAM	Low	1720.0	25.22	30.00	H	Pass
	Mid	1732.5	25.18	30.00	H	Pass
	High	1745.0	25.34	30.00	H	Pass

LTE FDD Band 7

Bandwidth	Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Polarization	Conclusion
5MHz QPSK	Low	2502.5	26.65	33.01	H	Pass
	Mid	2535	26.38	33.01	H	Pass
	High	2567.5	26.94	33.01	H	Pass
10MHz QPSK	Low	2505	26.15	33.01	H	Pass
	Mid	2535	26.18	33.01	H	Pass
	High	2565	26.37	33.01	H	Pass
5MHz 16QAM	Low	2507.5	26.77	33.01	H	Pass
	Mid	2535	26.28	33.01	H	Pass
	High	2562.5	26.19	33.01	H	Pass
10MHz 16QAM	Low	2510	26.75	33.01	H	Pass
	Mid	2535	26.48	33.01	H	Pass
	High	2560	26.95	33.01	H	Pass

LTE FDD Band 41


Bandwidth	Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Polarization	Conclusion
5MHz QPSK	Low	2557.5	26.26	33.00	H	Pass
	Mid	2605.0	26.48	33.00	H	Pass
	High	2652.5	26.32	33.00	H	Pass
10MHz QPSK	Low	2560.0	26.11	33.00	H	Pass
	Mid	2605.0	26.32	33.00	H	Pass
	High	2650.0	26.48	33.00	H	Pass
15MHz QPSK	Low	2562.5	26.49	33.00	H	Pass
	Mid	2605.0	26.15	33.00	H	Pass
	High	2647.5	26.76	33.00	H	Pass
20MHz QPSK	Low	2565.0	26.29	33.00	H	Pass
	Mid	2605.0	26.23	33.00	H	Pass
	High	2645.0	26.14	33.00	H	Pass
5MHz 16QAM	Low	2557.5	26.75	33.00	H	Pass
	Mid	2605.0	26.38	33.00	H	Pass
	High	2652.5	26.49	33.00	H	Pass
10MHz 16QAM	Low	2560.0	26.47	33.00	H	Pass
	Mid	2605.0	26.38	33.00	H	Pass
	High	2650.0	26.22	33.00	H	Pass
15MHz 16QAM	Low	2562.5	26.18	33.00	H	Pass
	Mid	2605.0	26.75	33.00	H	Pass
	High	2647.5	26.95	33.00	H	Pass
20MHz 16QAM	Low	2565.0	26.55	33.00	H	Pass
	Mid	2605.0	26.09	33.00	H	Pass
	High	2645.0	26.07	33.00	H	Pass

3.2. Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,
 - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS


1. Please refer to Appendix B: Section 5
2. Please refer to Appendix E: Section 5
3. Please refer to Appendix G: Section 5

3.3. Occupied Bandwidth and Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded.

Set RBW was set to about 1% of emission BW, VBW $\geq$ 3 times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS


1. Please refer to Appendix B: Section 4
2. Please refer to Appendix E: Section 4
3. Please refer to Appendix G: Section 4

3.4. Band Edge compliance

LIMIT

According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

1. Please refer to Appendix B: Section 6
2. Please refer to Appendix E: Section 6
3. Please refer to Appendix G: Section 6


3.5. Spurious Emission

LIMIT


According to §27.53 (h): For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Spurious Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.
- The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.

Radiated Spurious Measurement:

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- l. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
- r. Test site anechoic chamber refer to ANSI C63.

TEST RESULTS**Conducted Measurement :**

1. Please refer to Appendix B: Section 6
2. Please refer to Appendix E: Section 6
3. Please refer to Appendix G: Section 6

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of *LTE Band 4*, *LTE Band 7*, *Band 41*; recorded worst case for each Channel Bandwidth of *LTE Band 4*, *LTE Band 7*, *Band 41*, @ QPSK
2. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
3. We were not recorded other points as values lower than limits.
4. Margin = EIRP- Limit

LTE Band 4 Channel Bandwidth 1.4MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.4	-41.51	5.26	3.00	9.88	-36.89	-13.00	-23.89	H
5132.1	-51.27	6.11	3.00	11.36	-46.02	-13.00	-33.02	H
3421.4	-42.34	5.26	3.00	9.88	-37.72	-13.00	-24.72	V
5132.1	-47.62	6.11	3.00	11.36	-42.37	-13.00	-29.37	V

LTE Band 4 Channel Bandwidth 1.4MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-43.18	5.32	3.00	10.03	-38.47	-13.00	-25.47	H
5197.5	-51.99	6.19	3.00	11.41	-46.77	-13.00	-33.77	H
3465.0	-40.94	5.32	3.00	10.03	-36.23	-13.00	-23.23	V
5197.5	-47.36	6.19	3.00	11.41	-42.14	-13.00	-29.14	V

LTE Band 4 Channel Bandwidth 1.4MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.6	-41.57	5.36	3.00	9.62	-37.31	-13.00	-24.31	H
5262.9	-53.75	6.24	3.00	11.46	-48.53	-13.00	-35.53	H
3508.6	-41.48	5.36	3.00	9.62	-37.22	-13.00	-24.22	V
5262.9	-54.62	6.24	3.00	11.46	-49.40	-13.00	-36.40	V

LTE Band 4 Channel Bandwidth 3MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3423.0	-43.66	5.36	3.00	9.62	-39.40	-13.00	-26.40	H
5134.5	-48.97	6.24	3.00	11.46	-43.75	-13.00	-30.75	H
3423.0	-41.19	5.36	3.00	9.62	-36.93	-13.00	-23.93	V
5134.5	-54.14	6.24	3.00	11.46	-48.92	-13.00	-35.92	V

LTE Band 4 Channel Bandwidth 3MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-45.62	5.26	3.00	9.88	-41.00	-13.00	-28.00	H
5197.5	-47.18	6.11	3.00	11.36	-41.93	-13.00	-28.93	H
3465.0	-41.67	5.26	3.00	9.88	-37.05	-13.00	-24.05	V
5197.5	-50.64	6.11	3.00	11.36	-45.39	-13.00	-32.39	V

LTE Band 4 Channel Bandwidth 3MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3507.0	-41.11	5.32	3.00	10.03	-36.40	-13.00	-23.40	H
5260.5	-54.38	6.19	3.00	11.41	-49.16	-13.00	-36.16	H
3507.0	-43.23	5.32	3.00	10.03	-38.52	-13.00	-25.52	V
5260.5	-49.61	6.19	3.00	11.41	-44.39	-13.00	-31.39	V

LTE Band 4 Channel Bandwidth 5MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3425.0	-40.97	5.36	3.00	9.62	-36.71	-13.00	-23.71	H
5137.5	-51.19	6.24	3.00	11.46	-45.97	-13.00	-32.97	H
3425.0	-40.91	5.36	3.00	9.62	-36.65	-13.00	-23.65	V
5137.5	-55.76	6.24	3.00	11.46	-50.54	-13.00	-37.54	V

LTE Band 4 Channel Bandwidth 5MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-43.65	5.26	3.00	9.88	-39.03	-13.00	-26.03	H
5197.5	-48.57	6.11	3.00	11.36	-43.32	-13.00	-30.32	H
3465.0	-42.87	5.26	3.00	9.88	-38.25	-13.00	-25.25	V
5197.5	-50.46	6.11	3.00	11.36	-45.21	-13.00	-32.21	V

LTE Band 4 Channel Bandwidth 5MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3505.0	-48.27	4.62	3.00	9.81	-43.08	-13.00	-30.08	H
5257.5	-51.90	5.94	3.00	10.86	-46.98	-13.00	-33.98	H
3505.0	-52.59	4.62	3.00	9.81	-47.40	-13.00	-34.40	V
5257.5	-54.98	5.94	3.00	10.86	-50.06	-13.00	-37.06	V

LTE Band 4 Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3430.0	-45.97	5.32	3.00	10.03	-41.26	-13.00	-28.26	H
5145.0	-49.82	6.19	3.00	11.41	-44.60	-13.00	-31.60	H
3430.0	-41.52	5.32	3.00	10.03	-36.81	-13.00	-23.81	V
5145.0	-50.93	6.19	3.00	11.41	-45.71	-13.00	-32.71	V

LTE Band 4 Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-42.90	5.36	3.00	9.62	-38.64	-13.00	-25.64	H
5197.5	-46.33	6.24	3.00	11.46	-41.11	-13.00	-28.11	H
3465.0	-44.11	5.36	3.00	9.62	-39.85	-13.00	-26.85	V
5197.5	-50.90	6.24	3.00	11.46	-45.68	-13.00	-32.68	V

LTE Band 4 Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3500.0	-42.75	5.26	3.00	9.88	-38.13	-13.00	-25.13	H
5250.0	-47.15	6.11	3.00	11.36	-41.90	-13.00	-28.90	H
3500.0	-40.61	5.26	3.00	9.88	-35.99	-13.00	-22.99	V
5250.0	-47.53	6.11	3.00	11.36	-42.28	-13.00	-29.28	V

LTE Band 4 Channel Bandwidth 15MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3435.0	-45.45	5.32	3.00	10.03	-40.74	-13.00	-27.74	H
5152.5	-48.00	6.19	3.00	11.41	-42.78	-13.00	-29.78	H
3435.0	-45.82	5.32	3.00	10.03	-41.11	-13.00	-28.11	V
5152.5	-52.74	6.19	3.00	11.41	-47.52	-13.00	-34.52	V

LTE Band 4 Channel Bandwidth 15MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-42.91	5.26	3.00	9.88	-38.29	-13.00	-25.29	H
5197.5	-55.20	6.11	3.00	11.36	-49.95	-13.00	-36.95	H
3465.0	-42.85	5.26	3.00	9.88	-38.23	-13.00	-25.23	V
5197.5	-55.38	6.11	3.00	11.36	-50.13	-13.00	-37.13	V

LTE Band 4 Channel Bandwidth 15MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3495.0	-40.03	4.62	3.00	9.81	-34.84	-13.00	-21.84	H
5242.5	-53.57	5.94	3.00	10.86	-48.65	-13.00	-35.65	H
3495.0	-40.07	4.62	3.00	9.81	-34.88	-13.00	-21.88	V
5242.5	-52.35	5.94	3.00	10.86	-47.43	-13.00	-34.43	V

LTE Band 4 Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-45.90	4.63	3.00	9.84	-40.69	-13.00	-27.69	H
5160.0	-49.61	5.94	3.00	10.86	-44.69	-13.00	-31.69	H
3440.0	-42.82	4.63	3.00	9.84	-37.61	-13.00	-24.61	V
5160.0	-51.76	5.94	3.00	10.86	-46.84	-13.00	-33.84	V

LTE Band 4 Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-41.37	4.65	3.00	9.9	-36.12	-13.00	-23.12	H
5197.5	-55.22	5.95	3.00	10.91	-50.26	-13.00	-37.26	H
3465.0	-42.73	4.65	3.00	9.9	-37.48	-13.00	-24.48	V
5197.5	-48.96	5.95	3.00	10.91	-44.00	-13.00	-31.00	V

LTE Band 4 Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-45.54	4.62	3.00	9.81	-40.35	-13.00	-27.35	H
5235.0	-52.74	5.94	3.00	10.86	-47.82	-13.00	-34.82	H
3490.0	-42.78	4.62	3.00	9.81	-37.59	-13.00	-24.59	V
5235.0	-48.80	5.94	3.00	10.86	-43.88	-13.00	-30.88	V

LTE Band 7 Channel Bandwidth 5MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5005	-43.01	4.63	3.00	9.84	-37.80	-13.00	-24.80	H
7507.5	-51.87	5.94	3.00	10.86	-46.95	-13.00	-33.95	H
5005	-41.17	4.63	3.00	9.84	-35.96	-13.00	-22.96	V
7507.5	-52.73	5.94	3.00	10.86	-47.81	-13.00	-34.81	V

LTE Band 7 Channel Bandwidth 5MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070	-45.68	4.65	3.00	9.9	-40.43	-13.00	-27.43	H
7605	-47.45	5.95	3.00	10.91	-42.49	-13.00	-29.49	H
5070	-44.57	4.65	3.00	9.9	-39.32	-13.00	-26.32	V
7605	-50.63	5.95	3.00	10.91	-45.67	-13.00	-32.67	V

LTE Band 7 Channel Bandwidth 5MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5135	-44.79	4.62	3.00	9.81	-39.60	-13.00	-26.60	H
7702.5	-52.81	5.94	3.00	10.86	-47.89	-13.00	-34.89	H
5135	-44.26	4.62	3.00	9.81	-39.07	-13.00	-26.07	V
7702.5	-52.40	5.94	3.00	10.86	-47.48	-13.00	-34.48	V

LTE Band 7 Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5010	-41.16	4.63	3.00	9.84	-35.95	-13.00	-22.95	H
7515	-55.39	5.94	3.00	10.86	-50.47	-13.00	-37.47	H
5010	-43.73	4.63	3.00	9.84	-38.52	-13.00	-25.52	V
7515	-55.32	5.94	3.00	10.86	-50.40	-13.00	-37.40	V

LTE Band 7 Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070	-44.46	4.65	3.00	9.9	-39.21	-13.00	-26.21	H
7605	-51.69	5.95	3.00	10.91	-46.73	-13.00	-33.73	H
5070	-44.39	4.65	3.00	9.9	-39.14	-13.00	-26.14	V
7605	-47.32	5.95	3.00	10.91	-42.36	-13.00	-29.36	V

LTE Band 7 Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5730	-44.04	4.62	3.00	9.81	-38.85	-13.00	-25.85	H
7695	-46.20	5.94	3.00	10.86	-41.28	-13.00	-28.28	H
5730	-43.06	4.62	3.00	9.81	-37.87	-13.00	-24.87	V
7695	-48.83	5.94	3.00	10.86	-43.91	-13.00	-30.91	V

LTE Band 7 Channel Bandwidth 15MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5015	-40.59	4.63	3.00	9.84	-35.38	-13.00	-22.38	H
7522.5	-48.43	5.94	3.00	10.86	-43.51	-13.00	-30.51	H
5015	-41.87	4.63	3.00	9.84	-36.66	-13.00	-23.66	V
7522.5	-53.69	5.94	3.00	10.86	-48.77	-13.00	-35.77	V

LTE Band 7 Channel Bandwidth 15MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070	-45.88	4.65	3.00	9.9	-40.63	-13.00	-27.63	H
7605	-52.03	5.95	3.00	10.91	-47.07	-13.00	-34.07	H
5070	-44.09	4.65	3.00	9.9	-38.84	-13.00	-25.84	V
7605	-55.45	5.95	3.00	10.91	-50.49	-13.00	-37.49	V

LTE Band 7 Channel Bandwidth 15MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5125	-41.48	4.62	3.00	9.81	-36.29	-13.00	-23.29	H
7687.5	-47.48	5.94	3.00	10.86	-42.56	-13.00	-29.56	H
5125	-40.32	4.62	3.00	9.81	-35.13	-13.00	-22.13	V
7687.5	-55.77	5.94	3.00	10.86	-50.85	-13.00	-37.85	V

LTE Band 7 Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5020	-45.01	4.63	3.00	9.84	-39.80	-13.00	-26.80	H
7530	-54.00	5.94	3.00	10.86	-49.08	-13.00	-36.08	H
5020	-45.26	4.63	3.00	9.84	-40.05	-13.00	-27.05	V
7530	-46.48	5.94	3.00	10.86	-41.56	-13.00	-28.56	V

LTE Band 7 Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070	-41.21	4.65	3.00	9.9	-35.96	-13.00	-22.96	H
5705	-49.05	5.95	3.00	10.91	-44.09	-13.00	-31.09	H
5070	-42.68	4.65	3.00	9.9	-37.43	-13.00	-24.43	V
5705	-52.94	5.95	3.00	10.91	-47.98	-13.00	-34.98	V

LTE Band 7 Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5120	-42.22	4.62	3.00	9.81	-37.03	-13.00	-24.03	H
7680	-50.98	5.94	3.00	10.86	-46.06	-13.00	-33.06	H
5120	-43.08	4.62	3.00	9.81	-37.89	-13.00	-24.89	V
7680	-51.19	5.94	3.00	10.86	-46.27	-13.00	-33.27	V

LTE Band 41 Channel Bandwidth 5MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4997	-43.19	4.63	3.00	9.84	-37.98	-13.00	-24.98	H
7495.5	-54.15	5.94	3.00	10.86	-49.23	-13.00	-36.23	H
4997	-40.34	4.63	3.00	9.84	-35.13	-13.00	-22.13	V
7495.5	-46.88	5.94	3.00	10.86	-41.96	-13.00	-28.96	V

LTE Band 41 Channel Bandwidth 5MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5186	-43.19	4.65	3.00	9.9	-37.94	-13.00	-24.94	H
7779	-46.23	5.95	3.00	10.91	-41.27	-13.00	-28.27	H
5186	-42.98	4.65	3.00	9.9	-37.73	-13.00	-24.73	V
7779	-49.25	5.95	3.00	10.91	-44.29	-13.00	-31.29	V

LTE Band 41_Channel Bandwidth 5MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5375	-45.09	4.62	3.00	9.81	-39.90	-13.00	-26.90	H
8062.5	-51.82	5.94	3.00	10.86	-46.90	-13.00	-33.90	H
5375	-40.78	4.62	3.00	9.81	-35.59	-13.00	-22.59	V
8062.5	-47.09	5.94	3.00	10.86	-42.17	-13.00	-29.17	V

LTE Band 41_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5007	-45.19	4.63	3.00	9.84	-39.98	-13.00	-26.98	H
7510.5	-48.56	5.94	3.00	10.86	-43.64	-13.00	-30.64	H
5007	-40.81	4.63	3.00	9.84	-35.60	-13.00	-22.60	V
7510.5	-46.51	5.94	3.00	10.86	-41.59	-13.00	-28.59	V

LTE Band 41_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5186	-40.88	4.65	3.00	9.9	-35.63	-13.00	-22.63	H
7779	-54.36	5.95	3.00	10.91	-49.40	-13.00	-36.40	H
5186	-43.16	4.65	3.00	9.9	-37.91	-13.00	-24.91	V
7779	-48.96	5.95	3.00	10.91	-44.00	-13.00	-31.00	V

LTE Band 41_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5365	-45.55	4.62	3.00	9.81	-40.36	-13.00	-27.36	H
8047.5	-51.64	5.94	3.00	10.86	-46.72	-13.00	-33.72	H
5365	-44.07	4.62	3.00	9.81	-38.88	-13.00	-25.88	V
8047.5	-53.44	5.94	3.00	10.86	-48.52	-13.00	-35.52	V

LTE Band 41_Channel Bandwidth 15MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5007	-45.81	4.63	3.00	9.84	-40.60	-13.00	-27.60	H
7510.5	-46.36	5.94	3.00	10.86	-41.44	-13.00	-28.44	H
5007	-43.89	4.63	3.00	9.84	-38.68	-13.00	-25.68	V
7510.5	-52.19	5.94	3.00	10.86	-47.27	-13.00	-34.27	V

LTE Band 41_Channel Bandwidth 15MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5180	-44.89	4.62	3.00	9.81	-39.70	-13.00	-26.70	H
7779	-46.51	5.94	3.00	10.86	-41.59	-13.00	-28.59	H
5180	-42.11	4.62	3.00	9.81	-36.92	-13.00	-23.92	V
7779	-55.21	5.94	3.00	10.86	-50.29	-13.00	-37.29	V

LTE Band 41_Channel Bandwidth 15MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5365	-40.17	4.63	3.00	9.84	-34.96	-13.00	-21.96	H
8047.5	-52.39	5.94	3.00	10.86	-47.47	-13.00	-34.47	H
5365	-41.62	4.63	3.00	9.84	-36.41	-13.00	-23.41	V
8047.5	-52.28	5.94	3.00	10.86	-47.36	-13.00	-34.36	V

LTE Band 41_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5012	-43.04	4.65	3.00	9.9	-37.79	-13.00	-24.79	H
7518	-54.26	5.95	3.00	10.91	-49.30	-13.00	-36.30	H
5012	-42.45	4.65	3.00	9.9	-37.20	-13.00	-24.20	V
7518	-54.48	5.95	3.00	10.91	-49.52	-13.00	-36.52	V

LTE Band 41_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5180	-41.17	4.62	3.00	9.81	-35.98	-13.00	-22.98	H
7779	-54.13	5.94	3.00	10.86	-49.21	-13.00	-36.21	H
5180	-40.40	4.62	3.00	9.81	-35.21	-13.00	-22.21	V
7779	-52.98	5.94	3.00	10.86	-48.06	-13.00	-35.06	V

LTE Band 41_Channel Bandwidth 20MHz_QPSK_High Channel


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5360	-44.38	4.63	3.00	9.84	-39.17	-13.00	-26.17	H
8040	-48.19	5.94	3.00	10.86	-43.27	-13.00	-30.27	H
5360	-41.16	4.63	3.00	9.84	-35.95	-13.00	-22.95	V
8040	-48.80	5.94	3.00	10.86	-43.88	-13.00	-30.88	V

3.6. Frequency Stability under Temperature & Voltage Variations

LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Frequency Stability under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

1. Please refer to Appendix B: Section 2
2. Please refer to Appendix E: Section 2
3. Please refer to Appendix G: Section 2

3.7. Modulation Characteristics

Standard Applicable

According to FCC Part 2 §2.1047:

(a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

(b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.

(c) Single sideband and independent sideband radiotelephone transmitters which employ a device or circuit to limit peak envelope power. A curve showing the peak envelope power output versus the modulation input voltage shall be supplied. The modulating signals shall be the same in frequency as specified in paragraph (c) of §2.1049 for the occupied bandwidth tests.

(d) Other types of equipment. A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

TEST RESULTS

1. Please refer to Appendix B: Section 3
2. Please refer to Appendix E: Section 3
3. Please refer to Appendix G: Section 3

4. Test Setup Photos of the EUT



5. External and Internal Photos of the EUT

Reference to the test report No. CTL2111122071-W01

***** End of Report *****