



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC Part 22 Subpart H / Part 24 Subpart E

Report Reference No. : **CTL1706302041-WF02**

Compiled by: (position+printed name+signature)	Allen Wang (File administrators)	
Tested by: (position+printed name+signature)	Nice Nong (Test Engineer)	
Approved by: (position+printed name+signature)	Ivan Xie (Manager)	

Product Name : Android All Mode Wireless Module

Model/Type reference : M100-QVCX-2G16G

List Model(s) : See next page

Trade Mark : Temolin

FCC ID : 2AM5I-TML-M100

Applicant's name : **Temolin Technology Co., Ltd**

Address of applicant : Room 311, Building B, No.125 TianShan Road West, ChangNing District, Shanghai City, China

Test Firm : **Shenzhen CTL Testing Technology Co., Ltd.**

Address of Test Firm : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

Test specification :

Standard : **FCC CFR Title 47 Part 2, Part 22H and Part 24E**
EIA/TIA 603-D: 2010
KDB 971168 D01

TRF Originator : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF : Dated 2011-01

Date of Receipt : Jun. 23, 2017

Date of Test Date : Jun. 24, 2017–Jul. 11, 2017

Date of Issue : Jul. 12, 2017

Result : Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL1706302041-WF02	Jul. 12, 2017
		Date of issue

Equipment under Test : Android All Mode Wireless Module

Model /Type : M100-QVCX-2G16G

Listed Models : M100-OVCX-1G8G, M100-OVCX-2G16G, M100-OVWX-1G8G, M100-OVWX-2G16G, M100-OVTX-1G8G, M100-OVTX-2G16G, M100-QVCX-1G8G, M100-QVCX-2G16G, M100-QVWX-1G8G, M100-QVWX-2G16G, M100-QVTX-1G8G, M100-QVTX-2G16G, M100-OWNX-1G8G, M100-OWNX-2G16G, M100-QWNX-1G8G, M100-QWNX-2G16G

Applicant : Temolin Technology Co., Ltd

Address : Room 311, Building B, No.125 TianShan Road West, ChangNing District, Shanghai City, China

Manufacturer : Temolin Technology Co., Ltd

Address : Room 311, Building B, No.125 TianShan Road West, ChangNing District, Shanghai City, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.


It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

** Modified History **



Contents

1	SUMMARY.....	5
1.1	TEST STANDARDS	5
1.2	TEST DESCRIPTION.....	5
1.3	TEST FACILITY	6
1.4	STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2	GENERAL INFORMATION	7
2.1	ENVIRONMENTAL CONDITIONS.....	7
2.2	GENERAL DESCRIPTION OF EUT	7
2.3	DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	7
2.4	EQUIPMENTS USED DURING THE TEST	8
2.5	RELATED SUBMITTAL(s) / GRANT (s)	8
2.6	MODIFICATIONS.....	8
3	TEST CONDITIONS AND RESULTS	9
3.1	OUTPUT POWER	9
3.2	OCCUPIED BANDWIDTH	13
3.3	BAND EDGE COMPLIANCE	16
3.4	SPURIOUS EMISSION	19
3.5	FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS	29
4	TEST SETUP PHOTOS OF THE EUT	31



1 SUMMARY

1.1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22: PRIVATE LAND MOBILE RADIO SERVICES.](#)

[FCC Part 24: PUBLIC MOBILE SERVICES](#)

[TIA/EIA 603 D June 2010: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.](#)

[FCC Part 2: FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS](#)

[KDB971168 D01:v02r02 MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS](#)

[ANSI C63.26-2015 American National Standard for Compliance Testing of Transmitters Used in Licensed Radio](#)

1.2 Test Description

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 ©	Pass
Peak-to-Average Ratio	Part 24.232 (d)	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability	Part 2.1055 Part 22.355 Part 24.235	Pass

1.3 Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. Quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 GENERAL INFORMATION

2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2 General Description of EUT

Product Name:	Android All Mode Wireless Module
Model/Type reference:	M100-QVCX-2G16G
Power supply:	DC 3.3V from host device
CDMA	
Operation Band:	BC0 TX: 824.70 MHz ~ 848.31 MHz BC1 TX: 1851.25 MHz ~ 1908.75 MHz BC0 RX: 869.70 MHz ~ 893.31 MHz BC1 RX: 1931.25 MHz ~ 1988.75 MHz
Supported Type:	CDMA200 1x RTT/CDMA2000 1xEv-DO - Revision A
Modulation Type:	QPSK
Antenna type:	FPC antenna

Note: For more details, refer to the user's manual of the EUT.

2.3 Description of Test Modes and Test Frequency

The EUT has been tested under typical operating condition. The CUM200 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

Test Frequency:

Cellular Band		PCS Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1013	824.70	25	1851.25
384	836.52	600	1880.00
777	848.31	1175	1908.75

2.4 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2017/06/02	2018/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061714	2017/06/02	2018/06/01
EMI Test Receiver	R&S	ESCI	103710	2017/06/02	2018/06/01
Spectrum Analyzer	Agilent	E4407B	MY45108355	2017/06/02	2018/06/01
Controller	EM Electronics	Controller EM 1000	N/A	2017/05/21	2018/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2017/05/19	2018/05/18
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062014	2017/05/19	2018/05/18
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2017/05/19	2018/05/18
Amplifier	Agilent	8349B	3008A02306	2017/05/19	2018/05/18
Amplifier	Agilent	8447D	2944A10176	2017/05/19	2018/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2017/05/20	2018/05/19
Radio Communication Tester	R&S	CMU200	115419	2017/05/22	2018/05/21
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2017/05/20	2018/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2017/05/20	2018/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2017/05/20	2018/05/19
Climate Chamber	ESPEC	EL-10KA	A20120523	2017/05/20	2018/05/19
SIGNAL GENERATOR	Agilent	E4421B	US40051744	2017/05/20	2018/05/19
Directional Coupler	Agilent	87300B	3116A03638	2017/05/20	2018/05/19

2.5 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID:2AM5I-TML-M100 filing to comply with of the FCC Part 22 and Part 24 Rules.

2.6 Modifications

No modifications were implemented to meet testing criteria.

3 TEST CONDITIONS AND RESULTS

3.1 Output Power

LIMIT


BC0: 7W

BC1: 2W


The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION

Conducted Power Measurement



Radiated Power Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Coupler.
- EUT Communicate with CMU200 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter

- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.

TEST RESULTS**Conducted Measurement:**

EUT Mode	Channel	Frequency (MHz)	Avg.Burst Power (dBm)	Peak-to-Average Ratio (dB)	Limit (dBm)	Result
CDMA 1xRTT, BC0, CELL BAND	1013	824.7	23.11	/	38.45	Pass
	384	836.52	23.21	/		
	777	848.31	23.13	/		
CDMA2000 EVDO REV A 850MHz BAND	1013	824.7	23.29	/	38.45	Pass
	384	836.52	23.14	/		
	777	848.31	23.23	/		
CDMA2000 1xRTT, BC1, PCS BAND	25	1851.25	23.25	3.26	33.01	Pass
	600	1880.00	22.98	3.45		
	1175	1908.75	23.06	3.85		
CDMA2000 EVDO REV A 1900MHz BAND	25	1851.25	23.12	3.66	33.01	Pass
	600	1880.00	23.05	3.89		
	1175	1908.75	23.17	3.54		

Note:

1. maximum PK burst power=maximum Avg. burst power+Peak-to-Average Ratio.
2. The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.
3. This device was tested under all R.C.s and S.O.s. The worst case is reported with RC1/SO55 for 1xRTT and FTAP Rate 2Slot 307.2 kbps/RETAP Rate 2048 bits for EVDO Rev.A with 'All Up' power control bits.

Radiated Measurement:

Note: 1. The field strength of radiation emission was measured in the following position: EUT stand-up position (Zaxis), lie-down position (X, Y axis). The data show in this report only with the worst case setup. After exploratory measurement the worst case of Z axis was reported.

Note: 2 We test the H direction and V direction and V direction is worse.

CDMA 1xRTT, BC0, CELL BAND

Channel	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1013	-14.55	2.42	8.45	2.15	36.82	26.15	38.45	12.30	V
384	-13.77	2.46	8.45	2.15	36.82	26.89	38.45	11.56	V
777	-14.08	2.53	8.36	2.15	36.82	26.42	38.45	12.03	V

CDMA2000 EVDO REV A 850MHz BAND

Channel	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1013	-14.49	2.42	8.45	2.15	36.82	26.21	38.45	12.24	V
384	-14.11	2.46	8.45	2.15	36.82	26.55	38.45	11.90	V
777	-14.18	2.53	8.36	2.15	36.82	26.32	38.45	12.13	V

CDMA2000 1xRTT, BC1, PCS BAND

Channel	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
25	-15.28	3.41	10.24	33.6	25.15	33.01	7.86	V
600	-14.10	3.49	10.24	33.6	26.25	33.01	6.76	V
1175	-14.30	3.55	10.23	33.6	25.98	33.01	7.03	V

CDMA2000 EVDO REV A 1900MHz BAND

Channel	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
25	-14.99	3.41	10.24	33.6	25.44	33.01	7.57	V
600	-14.21	3.49	10.24	33.6	26.14	33.01	6.87	V
1175	-14.04	3.55	10.23	33.6	26.24	33.01	6.77	V

Remark:


1. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + P_{Ag}(dB) + G_a(dB)$
2. $ERP = EIRP - 2.15dB$ as EIRP by subtracting the gain of the dipole.

3.2 Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION





TEST PROCEDURE

1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer
2. RBW was set to about 1% of emission BW, $VBW \geq 3$ times RBW.
3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
CDMA 1xRTT, BC0, CELL BAND	1013	824.70	1.274	1.432
	384	836.52	1.278	1.434
	777	848.31	1.274	1.442
CDMA2000 EVDO REV A 850MHz BAND	1013	824.70	1.278	1.421
	384	836.52	1.269	1.421
	777	848.31	1.282	1.435
CDMA2000 1xRTT, BC1, PCS BAND	25	1851.25	1.288	1.468
	600	1880.00	1.307	1.468
	1175	1908.75	1.290	1.492
CDMA2000 EVDO REV A 1900MHz BAND	25	1851.25	1.296	1.494
	600	1880.00	1.304	1.484
	1175	1908.75	1.296	1.424






3.3 Band Edge compliance

LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

TEST CONFIGURATION





TEST PROCEDURE

In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

TEST RESULTS

CDMA 1xRTT, BC0, CELL BAND					
Channel Number	Frequency (MHz)	Max Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
1013	824.70	824.0000	-14.80	-13.00	Pass
777	848.31	849.0050	-13.24	-13.00	Pass



CDMA2000 EVDO REV A 1900MHz BAND					
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Verdict
		Frequency (MHz)	Values (dBm)		
25	1851.25	1849.9975	-20.84	-13.00	Pass
1175	1909.75	1910.0175	-20.73	-13.00	Pass

Agilent

Ref 30 dBm #Atten 30 dB Mkr1 1.8499975 GHz 20.84 dBm

#Avg Log 10 dB/Offst 10 dB DI -13.0 dBm PAvg 100 W1 S2 S3 FS AA

Start 1.849 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 8 ms (401 pts)

Agilent

Ref 30 dBm #Atten 30 dB Mkr1 1.9100175 GHz 20.73 dBm

#Avg Log 10 dB/Offst 10 dB DI -13.0 dBm PAvg 100 W1 S2 S3 FS AA

Start 1.91 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 8 ms (401 pts)

Trace/View

1 2 3

Clear Write

Max Hold

Min Hold

View

Blank

More 1 of 2

Trace/View

1 2 3

Clear Write

Max Hold

Min Hold

View

Blank

More 1 of 2




3.4 Spurious Emission

LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

TEST CONFIGURATION

Conducted Spurious Measurement:



Radiated Spurious Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Conducted Spurious Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- EUT Communicate with CMU200 then selects a channel for testing.




- d) Add a correction factor to the display of spectrum, and then test.
- e) The resolution bandwidth of the spectrum analyzer was set at 1MHz for Part 22 and 1MHz for Part 24, sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.

Radiated Spurious Measurement:




- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- l) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.

TEST RESULTS**Conducted Measurement:**


CDMA 1xRTT, BC0, CELL BAND





CDMA2000 EVDO REV A 850MHz BAND








CDMA2000 1xRTT, BC1, PCS BAND





CDMA2000 EVDO REV A 1900MHz BAND





Radiated Measurement:**CDMA 1xRTT, BC0, CELL BAND**

Channel	Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Distance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1013	1649.40	-31.14	3.00	3.00	9.58	-24.56	-13.00	11.56	H
	2474.10	-36.13	3.47	3.00	10.72	-28.88	-13.00	15.88	H
	1649.40	-30.24	3.00	3.00	9.68	-23.56	-13.00	10.56	V
	2474.10	-35.04	3.47	3.00	10.72	-27.79	-13.00	14.79	V
384	1673.00	-31.32	3.14	3.00	9.61	-24.85	-13.00	11.85	H
	2509.50	-35.14	3.59	3.00	10.77	-27.96	-13.00	14.96	H
	1673.00	-29.69	3.14	3.00	9.61	-23.22	-13.00	10.22	V
	2509.50	-33.92	3.59	3.00	10.77	-26.74	-13.00	13.74	V
777	1696.60	-31.03	3.26	3.00	9.77	-24.52	-13.00	11.52	H
	2544.90	-35.83	3.69	3.00	10.89	-28.63	-13.00	15.63	H
	1696.60	-29.76	3.26	3.00	9.77	-23.25	-13.00	10.25	V
	2544.90	-35.07	3.69	3.00	10.89	-27.87	-13.00	14.87	V

CDMA2000 EVDO REV A 850MHz BAND

Channel	Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Distance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1013	1649.40	-31.57	3.00	3.00	9.58	-24.99	-13.00	11.99	H
	2474.10	-35.77	3.47	3.00	10.72	-28.52	-13.00	15.52	H
	1649.40	-29.91	3.00	3.00	9.68	-23.23	-13.00	10.23	V
	2474.10	-35.03	3.47	3.00	10.72	-27.78	-13.00	14.78	V
384	1673.00	-30.99	3.14	3.00	9.61	-24.52	-13.00	11.52	H
	2509.50	-34.78	3.59	3.00	10.77	-27.60	-13.00	14.60	H
	1673.00	-29.70	3.14	3.00	9.61	-23.23	-13.00	10.23	V
	2509.50	-33.70	3.59	3.00	10.77	-26.52	-13.00	13.52	V
777	1696.60	-31.29	3.26	3.00	9.77	-24.78	-13.00	11.78	H
	2544.90	-35.42	3.69	3.00	10.89	-28.22	-13.00	15.22	H
	1696.60	-30.14	3.26	3.00	9.77	-23.63	-13.00	10.63	V
	2544.90	-34.48	3.69	3.00	10.89	-27.28	-13.00	14.28	V

CDMA 1xRTT, BC1, PCS BAND

Channel	Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Distance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
25	3702.50	-33.50	4.25	3.00	12.34	-25.41	-13.00	12.41	H
	5553.75	-38.07	4.97	3.00	13.52	-29.52	-13.00	16.52	H
	3702.50	-32.72	4.25	3.00	12.34	-24.63	-13.00	11.63	V
	5553.75	-36.43	4.97	3.00	13.52	-27.88	-13.00	14.88	V
600	3760.00	-33.59	4.38	3.00	12.34	-25.63	-13.00	12.63	H
	5640.00	-38.31	5.01	3.00	13.58	-29.74	-13.00	16.74	H
	3760.00	-32.46	4.38	3.00	12.34	-24.50	-13.00	11.50	V
	5640.00	-35.90	5.01	3.00	13.58	-27.33	-13.00	14.33	V
1175	3817.50	-33.46	4.49	3.00	12.45	-25.50	-13.00	12.50	H
	5726.25	-37.87	5.26	3.00	13.66	-29.47	-13.00	16.47	H
	3817.50	-32.81	4.49	3.00	12.45	-24.85	-13.00	11.85	V
	5726.25	-35.65	5.26	3.00	13.66	-27.25	-13.00	14.25	V

CDMA2000 EVDO REV A 1900MHz BAND

Channel	Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Distance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
25	3702.50	-33.34	4.25	3.00	12.34	-25.25	-13.00	12.25	H
	5553.75	-38.44	4.97	3.00	13.52	-29.89	-13.00	16.89	H
	3702.50	-32.31	4.25	3.00	12.34	-24.22	-13.00	11.22	V
	5553.75	-36.00	4.97	3.00	13.52	-27.45	-13.00	14.45	V
600	3760.00	-33.48	4.38	3.00	12.34	-25.52	-13.00	12.52	H
	5640.00	-37.93	5.01	3.00	13.58	-29.36	-13.00	16.36	H
	3760.00	-32.51	4.38	3.00	12.34	-24.55	-13.00	11.55	V
	5640.00	-36.42	5.01	3.00	13.58	-27.85	-13.00	14.85	V
1175	3817.50	-33.59	4.49	3.00	12.45	-25.63	-13.00	12.63	H
	5726.25	-38.28	5.26	3.00	13.66	-29.88	-13.00	16.88	H
	3817.50	-32.46	4.49	3.00	12.45	-24.50	-13.00	11.50	V
	5726.25	-35.64	5.26	3.00	13.66	-27.24	-13.00	14.24	V

Remark:

1. $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + G_a(dBi)$
2. We were not recorded other points as values lower than limits.
3. Margin = Limit - EIRP




3.5 Frequency Stability under Temperature & Voltage Variations

LIMIT

Cellular Band: $\pm 2.5\text{ppm}$ PCS Band: Within the authorized frequency block

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603C

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Reference Frequency: Cell Band Middle channel=384 frequency=836.52MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	56.58	0.068	2.5	Pass
	-20	70.79	0.085		
	-10	70.44	0.084		
	0	79.00	0.094		
	10	68.25	0.082		
	20	44.48	0.053		
	30	65.19	0.078		
	40	51.05	0.061		
	50	42.82	0.051		
4.26	25	40.71	0.049		
End point 3.15	25	49.26	0.059		

Reference Frequency: PCS Band Middle channel=600 frequency=1880MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	92.88	0.049	Within the authorized frequency block	Pass
	-20	84.62	0.045		
	-10	44.36	0.024		
	0	36.40	0.019		
	10	52.79	0.028		
	20	42.84	0.023		
	30	92.36	0.049		
	40	83.57	0.044		
	50	50.31	0.027		
4.26	25	68.08	0.036		
End point 3.15	25	36.39	0.019		

4 Test Setup Photos of the EUT



5 Photos of the EUT

Reference to the test report No. CTL1706302041-WF01

***** End of Report *****

