

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W178R-D002

AGR No. : A176A-401

Applicant : Huintech Co., Ltd.

Address : BI Center 218, 85, Daehak-ro, Gwangyang-eup, Gwangyang-si, Jeollanam-do, Korea

Manufacturer : Huintech Co., Ltd.

Address : BI Center 218, 85, Daehak-ro, Gwangyang-eup, Gwangyang-si, Jeollanam-do, Korea

Type of Equipment: Cording Robot

FCC ID. : 2AM64HU-COCONUT01

Model Name : Coconut

Serial number : N/A

Total page of Report : 6 pages (including this page)

Date of Incoming : July 03, 2017

Date of issue : August 02, 2017

SUMMARY

The equipment complies with the regulation; FCC PART 15 SUBPART C Section 15.247

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Jae-Ho Lee / Chief Engineer ONETECH Corp. Approved by:

Keun-Young, Choi / Vice President

Report No.: W178R-D002

ONETECH Corp.





CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	5
3. EUT MODIFICATIONS	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION	6
4.3 CALCULATED MPE SAFE DISTANCE	6





Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W178R-D002	August 02, 2017	Initial Issue	All





1. VERIFICATION OF COMPLIANCE

Applicant : Huintech Co., Ltd.

Address : BI Center 218, 85, Daehak-ro, Gwangyang-eup, Gwangyang-si, Jeollanam-do, Korea

Contact Person: Jongsil, Kim / CEO Telephone No.: +82-70-8031-3113

FCC ID : 2AM64HU-COCONUT01

Model Name : Coconut

Brand Name : Serial Number : N/A

Date : August 02, 2017

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM		
E.U.T. DESCRIPTION	Cording Robot		
KIND OD EQUIPMENT	Modular Transmitter		
THIS REPORT CONCERNS	Original Grant		
MEASUREMENT PROCEDURES	ANSI C63.10: 2013		
TYPE OF EQUIPMENT TESTED	Pre-Production		
KIND OF EQUIPMENT	Certification		
AUTHORIZATION REQUESTED			
EQUIPMENT WILL BE OPERATED	FCC PART 15 SUBPART C Section 15.247		
UNDER FCC RULES PART(S)	1 CC TART 13 SOBTART C Section 13.247		
Modifications on the Equipment to Achieve Compliance	None		
Final Test was Conducted On	3 m, Semi Anechoic Chamber		

^{-.} The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



2. GENERAL INFORMATION

2.1 Product Description

The Huintech Co., Ltd., Model Coconut (referred to as the EUT in this report) is a Cording Robot. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Cording Robot
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-1.71 dBm
Number of Channel	40 Channel
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	-5.38 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	12 MHz, 16 MHz, 32 MHz
Rated Supply Voltage	DC 3.7 V

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None





4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310, the limit for General Population/Uncontrolled exposure is 1 mW/cm^2 for the device operating $1.500 \sim 100\,000 \text{ MHz}$.

4.2 EUT Description

4.2 EUT Description	2.2 EUT Description				
Kind of EUT	Cording Robot				
Operating Frequency Band	 □ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz □ WLAN: 2 412 MHz ~ 2 462 MHz □ WLAN: 5 180 MHz ~ 5 240 MHz □ WLAN: 5 745 MHz ~ 5 825 MHz □ Bluetooth: 2 402 MHz ~ 2 480 MHz ■ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz 				
MAX. RF OUTPUT POWER	-1.71 dBm				
Antenna Gain	-5.38 dBi				
Exposure Evaluation Applied	■ MPE □ SAR □ N/A				

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

1	Operating Freq. Band	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm²) @ 20 cm	Limit (mW/c
	(MHz)	(dBm)	(dBm)	(mW)	Log	Linear		Separation	m²)
	2 402	-2.21 ± 0.5	-1.71	0.67	-5.38	0.290	0.12	0.00 004	1.00