



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# FCC Test Report

**Applicant:** Shenzhen TAT Electronics Co., Ltd

**Address of Applicant:** F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China

**Manufacturer:** Shenzhen TAT Electronics Co., Ltd

**Address of Manufacturer:** F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China

**Factory:** Shenzhen TAT Electronics Co., Ltd

**Address of Factory:** F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China

**Equipment Under Test (EUT):**

**Product:** Remote Control

**Model No.:** T14, T12

**Test Model No.:** T14

**Brand Name:** N/A

**FCC ID:** 2AM69T14

**Standards:** 47 CFR Part 15, Subpart C

**Date of Test:** 2017-07-04 to 2017-07-11

**Date of Issue:** 2017-07-11

**Report No. :** CQASZ170701413EW-01

**Test Result :** PASS\*

**Tested By:**

  
(Aaron Ma)

**Reviewed By:**

  
(Owen Zhou)

**Approved By:**

  
( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

## 2 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ170701413EW-01	Rev.01	Initial report	2017-07-11

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2013)	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	N/A
<b>Field Strength of the Fundamental Signal</b>	47 CFR Part 15, Subpart C Section 15.249 (a)	ANSI C63.10 (2013)	PASS
<b>Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.249 (a)/15.209	ANSI C63.10 (2013)	PASS
<b>Restricted bands around fundamental frequency (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.249(a)/15.205	ANSI C63.10 (2013)	PASS
<b>20dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.215 (c)	ANSI C63.10 (2013)	PASS

N/A: Not Applicable, the EUT power supply by battery.

## 4 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 TEST SUMMARY .....</b>	<b>3</b>
<b>4 CONTENTS.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 TEST ENVIRONMENT AND MODE .....	7
5.4 DESCRIPTION OF SUPPORT UNITS.....	7
5.5 TEST LOCATION.....	7
5.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	7
5.7 TEST FACILITY.....	8
5.8 DEVIATION FROM STANDARDS.....	8
5.9 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
5.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
5.11 EQUIPMENT LIST.....	9
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>10</b>
6.1 ANTENNA REQUIREMENT .....	10
6.2 RADIATED EMISSION.....	11
6.3 20DB BANDWIDTH.....	21
<b>7 PHOTOGRAPHS .....</b>	<b>24</b>
7.1 RADIATED EMISSION TEST SETUP .....	24
7.2 EUT CONSTRUCTIONAL DETAILS .....	26
<b>END OF THE REPORT .....</b>	<b>30</b>

## 5 General Information

### 5.1 Client Information

Applicant:	Shenzhen TAT Electronics Co., Ltd
Address of Applicant:	F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China
Manufacturer:	Shenzhen TAT Electronics Co., Ltd
Address of Manufacturer:	F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China
Factory:	Shenzhen TAT Electronics Co., Ltd
Address of Factory:	F5-6, Building B, Hedong Industrial Park, Xixiang, Shenzhen, China

### 5.2 General Description of EUT

Name:	Remote Control
Model No.:	T14, T12
Trade Mark :	N/A
Hardware Version:	V1.0
Software Version:	V10
Frequency Range:	2405 MHz ~ 2475MHz
Modulation Type:	GFSK
Number of Channels:	3 (declared by the client)
Sample Type:	Portable production
Test Software of EUT:	N/A
Antenna Type:	PCB antenna
Antenna Gain:	1.5dBi
Power Supply:	Lithium battery: CR2032, DC3V

Note: Only the model T14 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405MHz	2	2433MHz	3	2475MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel(CH1)	2405MHz
The Middle channel(CH2)	2433MHz
The Highest channel(CH3)	2475MHz

### 5.3 Test Environment and Mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1008 mbar
Test Mode:	Set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

### 5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

### 5.5 Test Location

All tests were performed at:

**Shenzhen Tongce Testing Lab,**

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

### 5.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Tongce Testing Lab** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for **TCT** laboratory is reported:

Test	Range	Uncertainty	Notes
Radiated Emission	Below 1GHz	±3.92dB	(1)
Radiated Emission	Above 1GHz	±4.28dB	(1)
Conducted Disturbance	0.15~30MHz	±2.56dB	(1)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 5.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC – Registration No.: 572331**

**Shenzhen Tongce Testing Lab** has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 572331

## 5.8 Deviation from Standards

None.

## 5.9 Abnormalities from Standard Conditions

None.

## 5.10 Other Information Requested by the Customer

None.

## 5.11 Equipment List

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
1	EMI Test Receiver	R&S	ESVD	100008	2017/08/11
2	Spectrum Analyzer	R&S	FSEM	848597/001	2017/08/11
3	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017/08/12
4	Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	2017/08/11
5	Pre-amplifier	HP	8447D	2727A05017	2017/08/11
6	Loop antenna	ZHINAN	ZN30900A	12024	2017/08/13
7	Broadband Antenna	R&S	VULB9163	340	2017/08/13
8	Horn Antenna	R&S	BBHA 9120D	631	2017/08/13
9	Horn Antenna	R&S	BBHA 9170	373	2017/08/13
10	Antenna Mast	CCS	CC-A-4M	N/A	N/A
11	Coax cable (9KHz~40GHz)	TCT	RE-low-01	N/A	2017/08/11
12	Coax cable (9KHz~40GHz)	TCT	RE-high-02	N/A	2017/08/11
13	Coax cable (9KHz~40GHz)	TCT	RE-low-02	N/A	2017/08/11
14	Coax cable (9KHz~40GHz)	TCT	RE-high-04	N/A	2017/08/11
15	Spectrum Analyzer	R&S	FSU	200054	2017/08/11
16	Antenna Connector	TCT	RFC-01	N/A	2017/08/12
17	RF cable(9KHz~40GHz)	TCT	RE-06	N/A	2017/08/12

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



## 6 Test results and Measurement Data

### 6.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
<b>EUT Antenna:</b>	
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.5dBi.	

## 6.2 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.249 and 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For fundamental frequency, RBW=5MHz, VBW=5MHz, Peak detector is for PK value, RMS detector is for Average value.					
Limit: (Spurious Emissions and band edge)	Frequency	Field strength (microvolt/meter )	Limit (dBuV/m )	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				
2) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.					
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)	Remark		
	2400MHz-2483.5MHz	94.0	Average Value		
		114.0	Peak Value		

Test Setup:	
	
	<p>Figure 1. Below 30MHz</p>
	
	<p>Figure 2. 30MHz to 1GHz</p>
	<p>Figure 3. Above 1 GHz</p>
Test Procedure:	<p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz:  Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p>

	e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case Pretest the EUT at Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the highest channel. Only the worst case is recorded in the report.
Test Voltage:	DC3.0V
Test Results:	Pass

### Measurement Data

#### 1) Field strength of the fundamental signal


Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
2405.00	85.82	-9.4	76.42	114	-37.58	Peak	H
2405.00	82.64	-9.4	73.24	94	-20.76	Average	H
2405.00	97.63	-9.4	88.23	114	-25.77	Peak	V
2405.00	94.79	-9.4	85.39	94	-8.61	Average	V
2433.00	84.73	-9.34	75.39	114	-38.61	Peak	H
2433.00	81.17	-9.34	71.83	94	-22.17	Average	H
2433.00	98.5	-9.34	89.16	114	-24.84	Peak	V
2433.00	96.26	-9.34	86.92	94	-7.08	Average	V
2475.00	86.6	-9.32	77.28	114	-36.72	Peak	H
2475.00	84.62	-9.32	75.3	94	-18.7	Average	H
<b>2475.00</b>	<b>100.71</b>	<b>-9.4</b>	<b>91.31</b>	<b>114</b>	<b>-22.69</b>	<b>Peak</b>	<b>V</b>
2475.00	97.24	-9.4	87.84	94	-6.16	Average	V

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

## 2) Spurious Emissions


30MHz~1GHz		
Test mode:	Transmitting (highest channel)	Horizontal



Freq	Read			Limit		Over		Pol/Phase
	Level	Factor	Level	Line	Limit	Remark		
	MHz	dB <sub>UV</sub>	dB/m	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		
1 pp	32.29	10.08	18.73	28.81	40.00	-11.19	Peak	HORIZONTAL
2	87.42	17.82	10.06	27.88	40.00	-12.12	Peak	HORIZONTAL
3	171.39	19.19	7.73	26.92	43.50	-16.58	Peak	HORIZONTAL
4	213.76	17.63	10.02	27.65	43.50	-15.85	Peak	HORIZONTAL
5	370.70	18.36	13.79	32.15	46.00	-13.85	Peak	HORIZONTAL
6	651.94	10.14	19.44	29.58	46.00	-16.42	Peak	HORIZONTAL

**30MHz~1GHz**

Test mode:	Transmitting (highest channel)	Vertical
------------	--------------------------------	----------



Freq	Read		Limit	Over	Remark	Pol/Phase
	Level	Factor				
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	36.64	12.88	17.35	30.23	40.00	-9.77 Peak VERTICAL
2	60.70	18.85	5.32	24.17	40.00	-15.83 Peak VERTICAL
3 pp	87.42	21.66	10.06	31.72	40.00	-8.28 Peak VERTICAL
4	142.82	14.31	8.35	22.66	43.50	-20.84 Peak VERTICAL
5	216.02	12.32	9.98	22.30	46.00	-23.70 Peak VERTICAL
6	982.62	10.12	22.40	32.52	54.00	-21.48 Peak VERTICAL

Above 1GHz							
Test mode:	Transmitting		Test channel:	Lowest			

Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
1276	51.87	-13.77	38.1	74	-35.9	Peak	H
1696	49.96	-8.66	41.3	74	-32.7	Peak	H
1864	48.75	-7.09	41.66	74	-32.34	Peak	H
3178	49.83	-7.2	42.63	74	-31.37	Peak	H
4810	51.54	-4.32	47.22	74	-26.78	Peak	H
6874	47.84	-0.03	47.81	74	-26.19	Peak	H
1276	51.3	-13.77	37.53	74	-36.47	Peak	V
1810	48.7	-6.93	41.77	74	-32.23	Peak	V
3442	49.55	-6.66	42.89	74	-31.11	Peak	V
3910	50.23	-4.97	45.26	74	-28.74	Peak	V
4810	56.08	-4.32	51.76	74	-22.24	Peak	V
6040	47.79	-2.00	45.79	74	-28.21	Peak	V

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 7GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Above 1GHz							
Test mode:		Transmitting		Test channel:		Middle	
Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
1264	53.71	-13.86	39.85	74	-34.15	Peak	H
1732	48.9	-7.68	41.22	74	-32.78	Peak	H
1828	49.26	-6.97	42.29	74	-31.71	Peak	H
3346	49.74	-6.97	42.77	74	-31.23	Peak	H
4864	51.52	-4.13	47.39	74	-26.61	Peak	H
6874	47.45	-0.03	47.42	74	-26.58	Peak	H
1264	58.41	-13.86	44.55	74	-29.45	Peak	V
1732	48.97	-7.68	41.29	74	-32.71	Peak	V
3730	49.68	-5.16	44.52	74	-29.48	Peak	V
4210	49.27	-5.01	44.26	74	-29.74	Peak	V
4864	52.34	-4.13	48.21	74	-25.79	Peak	V
6868	48.15	-0.06	48.09	74	-25.91	Peak	V

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 7GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Above 1GHz							
Test mode:		Transmitting		Test channel:		Highest	


Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
1264	56.31	-13.86	42.45	74	-31.55	Peak	H
1690	52.43	-8.93	43.5	74	-30.5	Peak	H
3808	49	-4.93	44.07	74	-29.93	Peak	H
4954	50.41	-4.03	46.38	74	-27.62	Peak	H
5878	48.08	-2.21	45.87	74	-28.13	Peak	H
6880	47.54	-0.01	47.53	74	-26.47	Peak	H
1264	54.2	-13.86	40.34	74	-33.66	Peak	V
1696	50.21	-8.66	41.55	74	-32.45	Peak	V
1828	48.59	-6.97	41.62	74	-32.38	Peak	V
4072	49.52	-5.09	44.43	74	-29.57	Peak	V
4948	52.65	-4.03	48.62	74	-25.38	Peak	V
6880	47.52	-0.01	47.51	74	-26.49	Peak	V

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 7GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

### 3) Band edge

Above 1GHz			
Test mode:	Transmitting	Test channel:	Lowest




Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
2390	47.76	-4.36	43.4	74	-30.6	Peak	H
2400	60.07	-4.36	55.71	74	-18.29	Peak	H
2400	38.22	-4.36	33.86	54	-20.14	Average	H




Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
2390	52.90	-4.36	48.54	74	-25.46	Peak	V
2400	71.93	-4.36	67.57	74	-6.43	Peak	V
2400	43.17	-4.36	38.81	54	-15.19	Average	V

Test mode:	Transmitting	Test channel:	Highest
------------	--------------	---------------	---------



Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
2483.5	51.01	-4.22	46.79	74	-27.21	Peak	H




Freq (MHz)	Read_Level (dB $\mu$ V)	Factor (dB)	Level (dB $\mu$ V/m)	Limit_Line (dB $\mu$ V/m)	Over_Limit (dB)	Remark	Pol.
2483.5	55.53	-4.22	51.31	74	-22.69	Peak	V

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 6.3 20dB Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2013
Test Setup:	
Test Mode:	Transmitting with GFSK modulation.
Limit:	N/A
Test Results:	Pass

#### Measurement Data


Test channel	20dB bandwidth (MHz)	Results
Lowest	0.657	Pass
Middle	0.617	Pass
Highest	0.657	Pass

**Test plot as follows:**


Test channel:	Lowest
---------------	--------



Test channel:	Middle
---------------	--------



Test channel: Highest




## 7 Photographs

### 7.1 Radiated Emission Test Setup


9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:






## 7.2 EUT Constructional Details











**END OF THE REPORT**