

RF Exposure Evaluation Report

Product : Camera
Trade mark : STREAMAX
Model/Type reference : AD Plus2.0, C6 Lite
Serial Number : N/A
Report Number : EED32R80870903
FCC ID : 2AM6L-ADP211R1
Date of Issue : Jun. 26, 2025
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1091
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF Exposure
Guidance v01
Test result : PASS

Prepared for:

Streamax Technology Co.,Ltd
21-23/F, Building B1, Zhiyuan, No.1001, Xueyuan Avenue, Nanshan
District, Shenzhen City, Guangdong Province, P.R.China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Keven Tan

Keven Tan

Reviewed by:

Frazer Li

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Date:

Jun. 26, 2025



Check No.: 9614290525

1 Version

Version No.	Date	Description
00	Jun. 26, 2025	Original

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
3.4 TEST LOCATION	6
3.5 DEVIATION FROM STANDARDS	6
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4 RF EXPOSURE EVALUATION	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 EUT RF Exposure Evaluation	8

3 General Information

3.1 Client Information

Applicant:	Streamax Technology Co.,Ltd
Address of Applicant:	21-23/F, Building B1, Zhiyuan, No.1001, Xueyuan Avenue, Nanshan District, Shenzhen City, Guangdong Province, P.R.China
Manufacturer:	Streamax Technology Co.,Ltd
Address of Manufacturer:	21-23/F, Building B1, Zhiyuan, No.1001, Xueyuan Avenue, Nanshan District, Shenzhen City, Guangdong Province, P.R.China

3.2 General Description of EUT

Product Name:	Camera
Model No.(EUT):	AD Plus2.0, C6 Lite
Test Model No.:	AD Plus2.0
Trade mark:	STREAMAX

3.3 Product Specification subjective to this standard

Frequency Range:	2.4GHz Wi-Fi: IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz LTE: B2: 1850-1910MHz, B4: 1710-1755MHz, B5: 824-849MHz, B12: 699-716MHz, B13: 777-787MHz, B14: 788 -798 MHz, B66: 1710-1780MHz, B71: 663-698MHz
Modulation Type:	2.4GHz Wi-Fi: IEEE for 802.11b:DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g:OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20): OFDM (64QAM, 16QAM,QPSK,BPSK) LTE: QPSK,16QAM
Test Power Grade:	Default
Test Software of EUT:	CMD
Antenna Type:	Internal antenna
Antenna Gain:	2.4GHz Wi-Fi: -0.37dBi LTE B2: -0.35dBi, LTE B4: -0.59dBi, LTE B5: -0.84dBi, LTE B12: -1.94dBi, LTE B13: -1.94dBi, LTE B14: -0.84dBi, LTE B66: -0.59dBi, LTE B71: -1.94dBi
Power Supply:	9-36V  2A
Sample Received Date:	Sep. 30, 2024

Sample tested Date:	Sep. 30, 2024 to Jun. 16, 2025
Remark: Model No.: AD Plus2.0, C6 Lite All model was tested, only the worst data was recorded(AD Plus2.0) in report. Their have similar electrical,PCB and layout,only the model name and colour are different, AD Plus2.0 and C6 Lite are different for marketing requirements.	

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

1)Maximum tune-up Power

	Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
2.4G Wi-Fi	1	1.71	1.00±1	2.00	1.585
LTE	Band 14	23.88	23.5±1	24.50	281.838

Remark: The Max Conducted Peak Output Power data refer to the report EED32R80870901, No.: R2203A0238-R1, R2203A0238-R2, R2203A0238-R3, R2203A0238-R4. Only the worst case was recorded in the report. (LTE module's FCC ID: XMR202008EC25AFXD.)

2)For Stand alone:

①2.4G Wi-Fi:

Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
@2.4GHz	20	1.71	-0.37	-0.81	0.830	3060	0.00027	Pass

②LTE:

Calculated data:

Band	Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
Band 14	793	20	23.88	-0.84	20.89	122.744	1254.974	0.0978	Pass

Note:

- ①EIRP=conducted power+antenna gain;
- ②ERP=EIRP-2.15;
- ③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;
- ④ERP(mW) = $10^{(ERP \text{ (dBm)}/10)}$;
- ⑤The estimation distance is 20cm;

Report No. : EED32R80870903

Page 9 of 10

⑥The test data please refer to the report of EED32R80870901, EED32R80870902 and only the worst case data was recorded in the report.

For Simultaneous Transmission:

As MPE ratio (2.4G Wi-Fi +LTE)= $0.00027^2 + 0.0978^2 = 0.00956 < 1$, it' s deemed to fulfil the RF exposure requirement.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***