

Shenzhen Huatongwei International Inspection Co., Ltd.

1/F,Bldg 3,Hongfa Hi-tech Industrial Park,Genyu Road,Tianliao,Gongming,Shenzhen,China Phone:86-755-26748019 Fax:86-755-26748089 http://www.szhtw.com.cn



FCC REPORT

Report Reference No.....: TRE1708017601 R/C......: 29420

FCC ID.....: 2AM6Q-W1450

Applicant's name: GRUPO SOLONE SA DE CV

Address...... AV. LOMAS DE SOTELO NO. 1112 PB,COL. LOMA HERMOSA,

DEL. MIGUEL HIDALGO, CIUDAD DE MEXICO.

Manufacturer...... GUANGDONG ENOK COMMUNICATION CO, LTD

Dongguan, Guangdong China

Test item description: Smart Phone

Trade Mark SOLONE

Model/Type reference...... W1450

Listed Model(s) -

Standard: FCC Part 22: PUBLIC MOBILE SERVICES

FCC Part 24: PERSONAL COMMUNICATIONS SERVICES

Candy Liu, Cron Con

FCC Part 27: MISCELLANEOUS WIRELESS

COMMUNICATIONS SERVICES

Date of receipt of test sample........... Aug.25, 2017

Date of testing...... Aug.26, 2017 - Sep.07, 2017

Date of issue...... Sep.08, 2017

Result...... Pass

Compiled by

(position+printedname+signature)...: File administrators Candy Liu

Supervised by

(position+printedname+signature)....: Project Engineer Lion Cai

Approved by

(position+printedname+signature)....: Manager Hans Hu

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd.

Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Report No.: TRE1708017601 Page: 2 of 62 Issued: 2017-09-08

Contents

<u>1.</u>	TEST STANDARDS AND REPORT VERSION	3
1.1.	Applicable Standards	3
1.2.	Report version	3
<u>2.</u>	TEST DESCRIPTION	4
<u>3.</u>	SUMMARY	5
		_
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	TEST ENVIRONMENT	7
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Equipments Used during the Test	8
4.4.	Environmental conditions	9
4.5.	Statement of the measurement uncertainty	9
<u>5.</u>	TEST CONDITIONS AND RESULTS	10
5.1.	Conducted Output Bower	40
5.1. 5.2.	Conducted Output Power 99% & -26 dB Occupied Bandwidth	10 12
5.2. 5.3.	Conducted Spurious Emissions	23
5.3. 5.4.	Band Edge	29
5.4. 5.5.	ERP and EIRP	40
5.6.	Radiated Spurious Emission	43
5.6. 5.7.	Frequency stability V.S. Temperature measurement	50 50
		53
5.8.	Frequency stability V.S. Voltage measurement	55 55
5.9.	Peak-Average Ratio	55
<u>6.</u>	TEST SETUP PHOTOS OF THE EUT	5 6
7	EYTERNAL AND INTERNAL PHOTOS OF THE FILT	5.7

Report No.: TRE1708017601 Page: 3 of 62 Issued: 2017-09-08

1. Test standards and Report version

1.1. Applicable Standards

The tests were performed according to following standards:

FCC Part 22: PRIVATE LAND MOBILE RADIO SERVICES.

FCC Part 24: PUBLIC MOBILE SERVICES

FCC Part 27:MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

TIA/EIA 603 D June 2010:Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

FCC Part 2: FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REGULATIONS

<u>971168 D01 Power Meas License Digital Systems v02r02:</u>provides a methodology for fully characterizing the fundamental power of wideband (> 1 MHz) digitally modulated RF signals acceptable to the FCC for demonstrating compliance for licensed transmitters.

1.2. Report version

Version No.	Date of issue	Description
00	Sep.08, 2017	Original

Report No.: TRE1708017601 Page: 4 of 62 Issued: 2017-09-08

2. Test Description

Test Item	Section in CFR 47	Result	Test Engineer
RF Output Power	Part 2.1046 Part 22.913(a) Part 24.232(c) Part 27.50	Pass	William Wang
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917(b) Part 24.238(b)	Pass	William Wang
Conducted Spurious Emissions	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass	William Wang
Band Edge	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass	William Wang
ERP and EIRP	Part 22.913(a) Part 24.232(b)	Pass	William Wang
Radiated Spurious Emissions	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	William Wang
Frequency stability vs. temperature	Part 2.1055(a)(1)(b) Part 22.355 Part 24.235 Part 27.54	Pass	William Wang
Frequency stability vs. voltage	Part 2.1055(d)(1)(2) Part 22.355 Part 24.235 Part 27.54	Pass	William Wang
Peak-Average Ratio	Part 24.232 Part 27.50	Pass	William Wang

Note: The measurement uncertainty is not included in the test result.

Report No.: TRE1708017601 Page: 5 of 62 Issued: 2017-09-08

3. **SUMMARY**

3.1. Client Information

Applicant:	GRUPO SOLONE SA DE CV
Address:	AV. LOMAS DE SOTELO NO. 1112 PB,COL. LOMA HERMOSA, DEL. MIGUEL HIDALGO,CIUDAD DE MEXICO.
Manufacturer:	GUANGDONG ENOK COMMUNICATION CO,.LTD
Address:	139&137Lixiang road ,Songmushan Dalang town,Dongguan, Guangdong China

3.2. Product Description

Name of EUT:	Smart Phone
Trade Mark:	SOLONE
Model No.:	W1450
Listed Model(s):	-
IMEI:	911524550220641
Power supply:	DC 3.8V From exchange battery
Adapter information:	Input: 100-240Va.c., 50/60Hz, 0.2A Output: 5Vd.c., 1A
Hardware version:	Ver.A
Software version:	M1701W1450V001
2G:	
Support Network:	GSM, GPRS, EGPRS
Support Band:	GSM850, PCS1900
Modulation:	GSM/GPRS/EGPRS: GMSK EGPRS: 8PSK
Transmit Frequency:	GSM850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz
Receive Frequency:	GSM850: 869.20MHz-893.80MHz PCS1900: 1930.20MHz-1989.80MHz
GPRS Class:	12
EGPRS Class:	12
Antenna type:	LOOP Antenna
Antenna gain:	GSM850: 1.6dBi PCS1900: 3.9dBi
3G:	
Operation Band:	FDD Band II and FDD Band IV, FDD Band V
Power Class:	Power Class 3
Modilation Type:	QPSK/16QAM/64QAM/HSUPA/HSDPA
DC-HSUPA Release Version:	Not Supported
Antenna type:	LOOP Antenna
Antenna gain:	Band II: 3.8 dBi, Band IV: 3.7dBi ,Band V: 1.7dBi

Report No.: TRE1708017601 Page: 6 of 62 Issued: 2017-09-08

3.3. Operation state

> Test frequency list

GSI	1850	PCS1900		
Channel	Frequency (MHz) Channel		Frequency (MHz)	
128	824.20	512	1850.20	
190	836.60	661	1880.00	
251	848.80	810	1909.80	

FDD Band II		FDD Band IV		FDD Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
9262	1852.4	1313	1712.6	4132	826.40
9400	1880.0	1450	1740.0	4183	836.60
9538	1907.6	1512	1752.4	4233	846.60

Test mode

For RF test items

The EUT has been tested under typical operating condition. Testing was performed by configuring EUT to maimum output power status.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

Length (m): /	I
Shield: /	1
Detachable: /	1
Manufacturer: /	I
Model No.: /	l

3.5. Modifications

No modifications were implemented to meet testing criteria.

Report No.: TRE1708017601 Page: 7 of 62 Issued: 2017-09-08

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd. Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

Report No.: TRE1708017601 Page: 8 of 62 Issued: 2017-09-08

4.3. Equipments Used during the Test

RF Co	onducted				
No.	Equipment	Manufacturer	Model No.	SerialNo.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	2016/11/13
2	WIDEB.RADIO COMM.TESRER	Rohde&Schwarz	CMW500	1201.0002K50	2016/11/13
3	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	2016/11/13
4	MXA Signal Analyzer	Agilent Technologies	N9020A	MY5050187	2016/11/13
5	Splitter	Mini-Circuit	ZAPD-4	400059	2016/11/13
6	Climate Chamber	ESPEC	EL-10KA	05107008	2016/11/13

RF Ra	adiated				
No.	Equipment	Manufacturer	Model No.	SerialNo.	Last Cal.
1	UNIVERSAL RADIO COMMUNICATION	Rohde&Schwarz	CMU200	112012	2016/11/13
2	WIDEB.RADIO COMM.TESRER	Rohde&Schwarz	CMW500	1201.0002K50	2016/11/13
3	Spectrum Analyzer	Rohde&Schwarz	FSU26	201141	2016/11/13
4	HORNANTENNA	ShwarzBeck	9120D	1012	2016/11/13
5	HORNANTENNA	ShwarzBeck	9120D	1011	2016/11/13
6	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2016/11/13
7	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	539	2016/11/13
8	TURNTABLE	MATURO	TT2.0		N/A
9	ANTENNA MAST	MATURO	TAM-4.0-P		N/A
10	EMI Test Software	Audix	E3	N/A	N/A
11	EMI Test Receiver	Rohde&Schwarz	ESIB 26	100009	2016/11/13
12	RF Test Panel	Rohde&Schwarz	TS / RSP	335015/ 0017	2016/11/13
13	High pass filter	Compliance Direction systems	BSU-6	34202	2016/11/13
14	Splitter	Mini-Circuit	ZAPD-4	400059	2016/11/13
15	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2016/11/13
16	Horn Antenna	SCHWARZBECK	BBHA9170	25842	2016/11/13
17	Preamplifier	ShwarzBeck	BBV 9718	BBV 9718	2016/11/13
18	Broadband Preamplifier	ShwarzBeck	BBV743	9743-0079	2016/11/13
19	Signal Generator	Rohde&Schwarz	SMF100A	101932	2016/11/13
20	Amplifer	Compliance Direction systems	PAP1-4060	120	2016/11/13
21	TURNTABLE	ETS	2088	2149	2016/11/13
22	ANTENNA MAST	ETS	2075	2346	2016/11/13
23	HORNANTENNA	Rohde&Schwarz	HF906	100068	2016/11/13
24	HORNANTENNA	Rohde&Schwarz	HF906	100039	2016/11/13

The calibration interval was one year.

Report No.: TRE1708017601 Page: 9 of 62 Issued: 2017-09-08

4.4. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature/Tnor:	15~35°C
lative Humidity	30~60 %
Air Pressure	950-1050 hPa

4.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01"Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1"and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Test Items MeasurementUncertainty	
Frequency stability	25 Hz	(1)
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-12.75 GHz	1.60 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth		(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Report No.: TRE1708017601 Page: 10 of 62 Issued: 2017-09-08


5. TEST CONDITIONS AND RESULTS

5.1. Conducted Output Power

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output port was connected to base station.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator, the path loss was compensated to the results for each measurement.
- 3. Set EUT at maximum power through base station.
- 4. Select lowest, middle, and highest channels for each band and different modulation.
- 5. Measure the maximum burst average power.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

 Report No.: TRE1708017601 Page: 11 of 62 Issued: 2017-09-08


EUT Mode	Channel	Frequency (MHz)	Power (dBm)
	128	824.20	32.58
GSM 850 (GMSK)	190	836.60	32.55
(GMON)	251	848.80	32.51
	128	824.20	32.60
GPRS850 (GMSK,1Slot)	190	836.60	32.56
(GWGIX, TOIOL)	251	848.80	32.50
E000000	128	824.20	27.25
EGPRS850 (8PSK,1Slot)	190	836.60	27.10
(653K, 13101)	251	848.80	26.88
	512	1850.20	28.35
PCS1900 (GMSK)	661	1880.00	28.30
(OMOR)	810	1909.80	28.50
	512	1850.20	28.33
GPRS1900 (GMSK,1Slot)	661	1880.00	28.30
(GWOR, FOICE)	810	1909.80	28.51
	512	1850.20	25.83
EGPRS1900 (8PSK,1Slot)	661	1880.00	25.92
(0F3K, 1310t)	810	1909.80	26.50
	9262	1852.40	22.69
WCDMA Band II	9400	1880.00	22.76
	9538	1907.60	22.71
	1313	1712.6	22.70
WCDMA Band IV	1450	1740.0	22.55
	1512	1752.4	22.63
	4132	826.40	23.20
WCDMA Band V	4183	836.60	23.24
	4233	846.60	23.19

Report No.: TRE1708017601 Page: 12 of 62 Issued: 2017-09-08

5.2. 99% & -26 dB Occupied Bandwidth

LIMIT N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer
- 2. RBWwas set to about 1% of emission BW, VBW= 3 times RBW.
- 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth isthe delta frequency between the two points where the display line intersects the signal trace.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


 Report No.: TRE1708017601 Page: 13 of 62 Issued: 2017-09-08

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
	128	824.20	244.75	324.20
GSM 850 (GMSK)	190	836.60	244.75	325.60
(Gillort)	251	128 824.20 190 836.60 251 848.80 128 824.20 190 836.60 251 848.80 128 824.20 190 836.60 251 848.80 128 824.20 190 836.60 251 848.80 512 1850.20 661 1880.00 810 1909.80 512 1850.20 661 1880.00 810 1909.80 512 1850.20 661 1880.00 810 1909.80	244.75	325.60
	128	824.20	244.75	319.20
GPRS850 (GMSK,1Slot)	190	836.60	245.75	323.00
(Ginera, relet)	251	848.80	244.75	323.30
FORDOOS	128	824.20	237.76	312.90
EGPRS850 (8PSK,1Slot)	190	836.60	239.76	312.10
(01 314, 13101)	251	848.80	236.76	314.70
	512	1850.20	243.75	320.20
PCS1900 (GMSK)	661	1880.00	244.75	318.60
(Givert)	810	1909.80	245.75	323.30
	512	1850.20	242.75	322.90
GPRS1900 (GMSK,1Slot)	661	1880.00	243.75	328.50
(GIVISK, 15101)	810	1909.80	244.75	322.40
	512	1850.20	237.76	322.00
EGPRS1900 (8PSK,1Slot)	661	1880.00	239.76	323.50
(orsk, 1310t)	810	1909.80	241.75	315.80
	9262	1852.40	4205.79	4874.00
WCDMA Band II	9400	1880.00	4205.79	4875.00
	9538	1907.60	4215.78	4887.00
	1313	1712.60	4215.78	4871.00
WCDMA Band IV	1450	1740.00	4205.79	4871.00
	1512	1752.40	4195.80	4877.00
	4132	826.40	4195.80	4871.00
WCDMA Band V	4183	836.60	4205.79	4885.00
	4233	846.60	4215.78	4891.00


Report No.: TRE1708017601 Page: 14 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 15 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 16 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 17 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 18 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 19 of 62 Issued: 2017-09-08




Report No.: TRE1708017601 Page: 20 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 21 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 22 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 23 of 62 Issued: 2017-09-08


5.3. Conducted Spurious Emissions

LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
- 2. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficientscans were taken to show the out of band Emissions if any up to 10th harmonic.
- 3. For the out of band: Set the RBW= 1MHz, VBW = 3MHz, Start=30MHz, Stop= 10th harmonic.


TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Note:Worst case at GSM850/PCS1900


Report No.: TRE1708017601 Page: 24 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 25 of 62 Issued: 2017-09-08

PCS1900

| MultiView | Spectrum | Spec




Report No.: TRE1708017601 Page: 26 of 62 Issued: 2017-09-08 WCDMA Band II MultiView Spectrum
Ref Level 25.00 dBm Offset
att 18 dB SWT
1 Frequency Sweep 30.0 MHz Dete: 31.AUG.2017 10:07:01 Channel 9262 MultiView Spectrum


Ref Level 26.00 dBm Offset 8.00

att 18 d8 SWT 100


I Frequency Sweep Detec 31.AUG:2017 10:06:14 Channel 9400 Ref Level 26.00 dBm Offset



Report No.: TRE1708017601 Page: 27 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 28 of 62 Issued: 2017-09-08



Report No.: TRE1708017601 Page: 29 of 62 Issued: 2017-09-08


5.4. Band Edge

LIMIT

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
- 2. For the bandedge: 2G:Set the RBW=3KHz, VBW = 10KHz, Sweep time= Auto

3G: Set the RBW=100KHz, VBW = 300KHz, Sweep time= Auto

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

 Report No.: TRE1708017601 Page: 30 of 62 Issued: 2017-09-08

GSM850						
Channel	Frequency	Measureme	nt Results	Limit	Verdict	
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	Verdict	
128	824.2	824	-16.60	-13.00	Pass	
251	848.8	849	-16.28	-13.00	Pass	

GPRS850						
Channel Frequency Measurement Results Limit					Verdict	
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	verdict	
128	824.2	824	-13.28	-13.00	Pass	
251	848.8	849	-14.17	-13.00	Pass	

EGPRS850						
Channel	el Frequency Measurement Results Limit				Verdict	
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	Verdict	
128	824.2	824	-14.31	-13.00	Pass	
251	848.8	849	-15.86	-13.00	Pass	

PCS1900						
Channel	Frequency	Measurement Results		Limit Verdict		
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	verdict	
512	1850.2	1850	-14.15	-13.00	Pass	
810	1909.8	1910	-13.75	-13.00	Pass	

GPRS1900						
Channel	Frequency	Measurement Results Limit				
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	Verdict	
512	1850.2	1850	-16.23	-13.00	Pass	
810	1909.8	1910	-15.55	-13.00	Pass	

	EGPRS1900						
Channel	Frequency	Measurement Results Limit			Verdict		
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	verdict		
512	1850.2	1850	-19.57	-13.00	Pass		
810	1909.8	1910	19.93	-13.00	Pass		

WCDMA Band II							
Channel Frequency Measurement Results Limit					Verdict		
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	Verdict		
9262	1852.4	1850	-15.04	-13.00	Pass		
9538	1907.6	1910	-15.34	-13.00	Pass		

WCDMA Band IV							
Channel	Frequency	Measureme	nt Results	Limit	Verdict		
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	verdict		
1313	1712.6	1710	-29.82	-13.00	Pass		
1512	1752.4	1755	-28.54	-13.00	Pass		

WCDMA Band V						
Channel	Frequency	Measurement Results Limit			Verdict	
Number	(MHz)	Frequency(MHz)	Values(dBm)	(dBm)	verdict	
4132	826.4	824	-13.61	-13.00	Pass	
4233	846.6	849	-14.47	-13.00	Pass	

Report No.: TRE1708017601 Page: 31 of 62 Issued: 2017-09-08

