



- Please check the items when you receive the product and if there is anything defective or missing, please contact your terminal provider.
 For any other AC Type Plug requirement, please contact your terminal provider.

- This is a new multi-functional POS seeminal M950.
 It has different optional configurations and accessories.
 Please select by yourself according to this document, or supplier.

-- 74.25 mm ---



Installation

Recommendation
The terminal should be kept away from very hot zone and precented from vibrations, dust, damp or electioning-sets radiation is computer screen, while is intercome set.

 Environment condition.



Installation steps
Step 1: Turn the terminal upside down and push the
bottomy cover in the direction of the arrows
open the battery cover(fig. 1)
Step 2: Insert the battery plug into the socket and pus
the battery into the battery compartment(fig. 2)

Step 3: After the battery is installed, press the battery cable to make the cable height lower than the batterytifg.3)

Step 4: Cover the battery cover/fg.41

Disassembly steps
 Reverse the above steps.

Paper Roll Installation

Installing Battery





Step 1: Open the paper real cover (fig.4)
 Step 2: Insert the paper real in the compartment following the directions believe on the performance following the directions believe on the performance from the top of the terminal. Light 5:
 Step 3: Indextrast the paper and dose the following step of the control of the following the first owner of the first owner owner

- 371.25 mm

Installing SAM/SIM/MicroSD card



Westing

Westing

Westing

A set of this file terminal is power of and the the set of this file terminal is power of and the the AMASAMANS SC conf.

Set 1: Thum the setternal quade decisions and egan the setternal power of the AMASAMANS SC conf.

Set 2: A considery on the SMASAMANS SC Cond.

Set 3: A considery on the SMASAMANS SC Cond.

Set 4: A considery on the SMASAMANS SC Cond.

The SMASAMANS SC COND.

Set 4: A considery on the SMASAMANS SC COND.

The SMASAMANS SC COND.

Set 4: A considery on the SMASAMANS SC COND.

Set 5: A set 5: A condition of the register of and it is set to product configuration.

Set 5: A se

Charging the Battery

Place the terminal on the charging base (if available) or connected to the adapter to charge the battery.

Switching On/Off the Terminal

- Power on Press power button for about 2 seconds of the LCD is it to switch on.

 Power offileboot Press and hold power button to see a pop-ty prinders stout the screen to select. "Power off" to power off the terminal, (Or to select. "Reboot" and then "ON" to seboot the terminal.

 Nate of there is a coash, please press power button.

Reading Card



Reading Card

Sint and

You the City ope in the City op in the City op







External Connections





- 1. Censect PC and POS terrifinal (fig. 11) for maliforance and download.
 2. Censect the power adapter and POS terminal (Fig. 12) for charging.
 3. If you need to connect other paripherals, please consect terminal provides.

- Safety

- 1. Prises be sure to side to comply with the specification in this decorates to the document of the specification in this document.

 1. Do not discountly farmable option of submitted option of submitted options of submitted options.

 1. Do not discountle the terminal operat degler of the submitted options of the submit

Security of Your Terminal

Security of Your Terminal
You T

CE Marking
The CE marking indicates NR50 complies the requirements of European Directive 2014/SSEQU of 16 April, 2014 on Rodio and Telecommunications Telemon Supprincer for:
1. The protection of the health and the safety of the user and any other person.

Standards

Troubleshooting

- I. The terminal does not turn on
 Check that the battery is installed correctly
 Please charge the battery to check if it is fully discharged.

- 2. Battery life septems, please replaces the battery.

 III. Card treat differ supports card or suffer seed self-please has been success rate.

 C. Deck that the suspers card is susped correctly (seth mangaret badd on immerial side).

 The support badd on immerial side.

 The support badd on immerial side.

 The support badd in support badd on the support badd from such side into the suspers.

 The SLC cards card bar suspers.

 The SLC cards card bar incomed correctly the Chip card into the Chip card readed half the Chip facing (sp.).

 2. One-SLT the card Side is blocked or if the cord is in control profition.
- contect position.

 V. Ticket cannot be printed or printed incompletely.

 1. Check the presence and proper positioning of the paper ool.

 2. Check the type of paper used is correct.

 3. Check the type of paper used is correct.

 4. Check the type of paper used paper in the printed clean.

- Fujian Newland Payment Technology Co., Ltd.
 No. 8602, Building #1, Habda Jingmon Plaza Pushou Bonded Area 350015, Fujian, China