

FCC ID: 2AM7LTURTLE-SP-ATA

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances ≤ 50 mm, the SAR test exclusion threshold is determined according to the following

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$$

1. SAR test exclusion threshold

Frequency: 2 480 MHz (min. separation distances = 5 mm)

SAR test exclusion thresholds (5 mm) = $3 \times 5 / (\sqrt{2.480}) = 9.525$ mW

| Max. Tune-up Tolerance (mW) | SAR Test Exclusion Thresholds (5mm) (mW) |
|-----------------------------|--|
| 0.4 | 9.525 |

Calculation value : 0.4 (mW) / 5 (mm) $\times \sqrt{2.480} = 0.126$

So, Calculation value ≤ 3.0

Remark:

-Max. conducted power 0.37 (mW) is closest 0.4 (mW), so 0.4 (mW) was calculated.

-When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. Conclusion: No SAR is required.