



RF Test Report

Applicant : NoNap.Play Inc.
Product Type : Totokan baby monitor
Trade Name : Totokan
Model Number : TTK0088001
Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013
Receive Date : Jul. 20, 2017
Test Period : Jul. 27 ~ Aug. 21, 2017
Issue Date : Aug. 24, 2017

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Test Firm MRA designation number: TW0010

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Revised By
00	Aug. 24, 2017	Initial Issue	Janet Chao

Verification of Compliance

Issued Date: Aug. 24, 2017

Applicant : NoNap.Play Inc.
Product Type : Totokan baby monitor
Trade Name : Totokan
Model Number : TTK0088001
FCC ID : 2AM8W-TTK001
EUT Rated Voltage : DC 5V, 2A
Test Voltage : 120 Vac / 60 Hz
Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013

Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By	: <u>Fly Lu</u>	Reviewed By	: <u>Eric Ou Yang</u>
(Manager)	(Fly Lu)	(Testing Engineer)	(Eric Ou Yang)

TABLE OF CONTENTS

1	General Information	6
2	EUT Description	7
3	Test Methodology	8
	3.1. Mode of Operation.....	8
	3.2. EUT Exercise Software.....	12
	3.3. Configuration of Test System Details	13
	3.4. Test Site Environment.....	13
4	AC Power Line Conducted Emission Measurement	14
	4.1. Limit	14
	4.2. Test Instruments	14
	4.3. Test Setup	14
	4.4. Test Procedure	15
	4.5. Test Result.....	16
5	Radiated Emission Measurement	18
	5.1. Limit	18
	5.2. Test Instruments	18
	5.3. Setup.....	19
	5.4. Test Procedure	21
	5.5. Test Result.....	23
6	Maximum Conducted Output Power Measurement	64
	6.1. Limit	64
	6.2. Test Setup	64
	6.3. Test Instruments	64
	6.4. Test Procedure	64
	6.5. Test Result.....	65
7	6dB RF Bandwidth Measurement.....	70
	7.1. Limit	70
	7.2. Test Setup	70
	7.3. Test Instruments	70
	7.4. Test Procedure	70
	7.5. Test Result.....	71
	7.6. Test Graphs.....	72



8	Maximum Power Density Measurement	78
8.1.	Limit	78
8.2.	Test Setup	78
8.3.	Test Instruments	78
8.4.	Test Procedure	78
8.5.	Test Result.....	79
8.6.	Test Graphs	80
9	Out of Band Conducted Emissions Measurement.....	86
9.1.	Limit	86
9.2.	Test Setup	86
9.3.	Test Instruments	86
9.4.	Test Procedure	86
9.5.	Test Graphs	87
10	Antenna Measurement.....	105
10.1.	Limit	105
10.2.	Antenna Description	105
10.3.	Directional Gain Calculated	105

1 General Information

1.1 Summary of Test Result

Standard	Item	Result	Remark
15.247			
15.207	AC Power Conducted Emission	PASS	-----
Standard	Item	Result	Remark
15.247			
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6dB RF Bandwidth	PASS	-----
15.247(e)	Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conducted Emission	9kHz ~ 150KHz	2.7
	150kHz ~ 30MHz	2.7
Radiated Emission	9kHz ~ 30MHz	1.7
	30MHz ~ 1000MHz	5.7
	1000MHz ~ 18000MHz	5.5
	18000MHz ~ 26500MHz	4.8
	26500MHz ~ 40000MHz	4.8
Conducted Output Power	+0.27 dB / -0.28 dB	
RF Bandwidth	4.96%	
Power Spectral Density	+0.71 dB / -0.77 dB	



2 EUT Description

Applicant	NoNap.Play Inc. #10 Keelung Road Section 2, 15th Floor Taipei, Taiwan 110			
Manufacturer	NoNap.Play Inc. #10 Keelung Road Section 2, 15th Floor Taipei, Taiwan 110			
Product Type	Totokan baby monitor			
Trade Name	Totokan			
Model Number	TTK0088001			
FCC ID	2AM8W-TTK001			
Operate Freq. Band	Frequency Range (MHz)	Modulation	Channel Bandwidth	Data Rate 800 GI (ns)
IEEE 802.11b	2412 ~ 2462	DSSS	20MHz	Up to 11Mbps
IEEE 802.11g	2412 ~ 2462	OFDM	20MHz	Up to 54Mbps
IEEE 802.11n 2.4GHz 20MHz	2412 ~ 2462	OFDM	20MHz	Up to130Mbps
IEEE 802.11n 2.4GHz 40MHz	2422 ~ 2452	OFDM	40MHz	Up to 270Mbps
Antenna information	Type		Max. Gain (dBi)	
	PIFA Antenna		1.5	
Antenna Delivery	See section 3.1			
Operate Temp. Range	0 ~ 40 ℃			

Frequency Band	Max. RF Output Power (W)
IEEE 802.11b	0.023
IEEE 802.11g	0.150
IEEE 802.11n 2.4GHz 20MHz	0.213
IEEE 802.11n 2.4GHz 40MHz	0.244

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit mode
Mode 2: IEEE 802.11b Continuous TX mode
Mode 3: IEEE 802.11g Continuous TX mode
Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode
Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in TX mode only.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.


Note: Power worst case is ANT-0

Test Mode	ANT-0	ANT-1	ANT-0+1
Mode 2	V	V	---
Mode 3	V	V	---
Mode 4	V	V	V
Mode 5	V	V	V


Test Mode	Antenna Delivery	Data Rate	Test Channel
Mode 2	1TX / 1RX (Diversity)	1M	1, 6, 11
Mode 3	1TX / 1RX (Diversity)	6M	1, 6, 11
Mode 4	2TX / 2RX (MIMO)	13M	1, 6, 11
Mode 5	2TX / 2RX (MIMO)	27M	3, 6, 9

Duty cycle

Test Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
Mode 2	2412	8.490	8.520	0.996	0.015	0.010
Mode 3	2412	1.405	1.530	0.918	0.370	0.712
Mode 4	2412	0.688	0.828	0.831	0.804	1.453
Mode 5	2422	0.354	0.446	0.794	1.003	2.825




Mode 2: IEEE 802.11b Continuous TX mode






Mode 3: IEEE 802.11g Continuous TX mode

On time




On+off time



Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode



On time



On+off time



Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode

On time	
On+off time	


3.2. EUT Exercise Software

1. Setup the EUT shown on 3.3.
2. Turn on the power of all equipment.
3. Turn on TX function
4. EUT run test program.


Measurement Software	
1	EZ-EMC Ver. ATL-03A1-1
2	EZ-EMC Ver ATL-ITC-3A1-1

3.3. Configuration of Test System Details

Conducted Emissions



Radiated Emission



3.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

4 AC Power Line Conducted Emission Measurement

4.1. Limit


Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Test Receiver	R&S	ESCI	100367	05/18/2017	1 year
LISN	R&S	ENV216	101040	04/01/2017	1 year
LISN	R&S	ENV216	101041	03/15/2017	1 year
RF Cable	Woken	00100D1380194M	TE-02-02	05/19/2017	1 year
Test Site	ATL	TE02	TE02	N.C.R.	-----

Note: N.C.R. = No Calibration Request.

4.3. Test Setup



4.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\Omega // 50\mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega // 50\mu\text{H}$ coupling impedance with 50Ω termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12mm insulating material.


Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150kHz to 30MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0,8 m from the AMN. If the mains power cable is longer than 1m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4m. All of interconnecting cables that hang closer than 40cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1m. All 50Ω ports of the LISN shall be resistively terminated into 50Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.5. Test Result

Standard:	FCC Part 15.247	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
		Date:	07/27/2017
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.2060	43.13	27.48	9.53	52.66	37.01	63.37	53.37	-10.71	-16.36	Pass
2	0.2740	34.29	17.50	9.53	43.82	27.03	61.00	51.00	-17.18	-23.97	Pass
3	0.4540	32.68	20.50	9.54	42.22	30.04	56.80	46.80	-14.58	-16.76	Pass
4	0.5900	31.56	18.05	9.54	41.10	27.59	56.00	46.00	-14.90	-18.41	Pass
5	0.8260	30.61	17.74	9.56	40.17	27.30	56.00	46.00	-15.83	-18.70	Pass
6	1.5060	30.65	19.88	9.60	40.25	29.48	56.00	46.00	-15.75	-16.52	Pass
7	3.9060	27.22	13.70	9.67	36.89	23.37	56.00	46.00	-19.11	-22.63	Pass

Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.247	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
		Date:	01/24/2015
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1820	38.50	17.00	9.63	48.13	26.63	64.39	54.39	-16.26	-27.76	Pass
2	0.2500	34.95	14.90	9.63	44.58	24.53	61.76	51.76	-17.18	-27.23	Pass
3	0.4820	30.87	15.65	9.64	40.51	25.29	56.30	46.30	-15.79	-21.01	Pass
4	0.5580	30.24	15.90	9.64	39.88	25.54	56.00	46.00	-16.12	-20.46	Pass
5	1.8100	26.53	17.78	9.70	36.23	27.48	56.00	46.00	-19.77	-18.52	Pass
6	4.8900	25.78	11.51	9.80	35.58	21.31	56.00	46.00	-20.42	-24.69	Pass

Note: 1. Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).



5 Radiated Emission Measurement

5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


5.2. Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
RF Pre-selector	Agilent	N9039A	MY46520256	04/24/2017	1 year
Spectrum Analyzer	Agilent	E4446A	MY46180578	04/24/2017	1 year
Pre Amplifier	Agilent	8449B	3008A02237	10/11/2016	1 year
Pre Amplifier	Agilent	8447D	2944A11119	01/12/2017	1 year
Broadband Antenna	Schwarzbeck	VULB9168	416	10/13/2016	1 year
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/20/2017	1 year
Horn Antenna (18~40GHz)	ETS	3116	86467	09/05/2016	1 year
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	01/26/2017	1 year
Microwave Cable	EMCI	EMC102-KM-KM-14000	151001	02/20/2017	1 year
Microwave Cable	EMCI	EMC-104-SM-SM-14000	140202	02/20/2017	1 year
Microwave Cable	EMCI	EMC104-SM-SM-600	140301	02/20/2017	1 year
Test Site	ATL	TE01	888001	08/29/2016	1 year


Note: N.C.R. = No Calibration Request.

5.3. Setup


9kHz ~ 30MHz



Below 1GHz



Above 1GHz



5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height (below 1GHz use 0.8m turntable / above 1GHz use 1.5m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >0.98 / $1/T$ for average measurements when Duty cycle <0.98 . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts per meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1) $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2) $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



5.5. Test Result

Below 1GHz

Standard:		FCC Part 15.247		Test Distance:		3m	
Test item:		Harmonic		Power:		AC 120V/60Hz	
Mode:		Mode 1		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
				Date:		08/19/2017	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
417.0300	38.54	-0.99	37.55	46.00	-8.45	QP	H
491.7200	30.66	0.43	31.09	46.00	-14.91	QP	H
586.7800	30.07	2.42	32.49	46.00	-13.51	QP	H
702.2100	29.71	4.48	34.19	46.00	-11.81	QP	H
862.2600	28.51	7.61	36.12	46.00	-9.88	QP	H
967.0200	31.01	9.44	40.45	54.00	-13.55	QP	H
365.6200	38.12	-2.12	36.00	46.00	-10.00	QP	V
418.0000	35.55	-0.97	34.58	46.00	-11.42	QP	V
523.7300	32.33	1.10	33.43	46.00	-12.57	QP	V
579.9900	33.36	2.29	35.65	46.00	-10.35	QP	V
923.3700	28.91	8.76	37.67	46.00	-8.33	QP	V
967.0200	33.15	9.44	42.59	54.00	-11.41	QP	V


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3.No emission found between lowest internal used/generated frequencies to 30MHz (9 kHz~30MHz).

Above 1GHz

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	58.62	-6.34	52.28	74.00	-21.72	peak
2	4824.000	59.63	-6.34	53.29	54.00	-0.71	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	58.22	-6.34	51.88	74.00	-22.12	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	59.68	-6.16	53.52	74.00	-20.48	peak
2	4874.000	59.00	-6.16	52.84	54.00	-1.16	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	58.95	-6.16	52.79	74.00	-21.21	peak
2	4874.000	57.96	-6.16	51.80	54.00	-2.20	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	60.83	-5.98	54.85	74.00	-19.15	peak
2	4924.000	58.91	-5.98	52.93	54.00	-1.07	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/19/2017
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	58.42	-5.98	52.44	74.00	-21.56	peak
2	4924.000	57.84	-5.98	51.86	54.00	-2.14	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	75.63	-9.39	66.24	74.00	-7.76	peak
2	4824.000	62.25	-9.39	52.86	54.00	-1.14	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	72.96	-9.39	63.57	74.00	-10.43	peak
2	4824.000	60.56	-9.39	51.17	54.00	-2.83	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	70.43	-9.26	61.17	74.00	-12.83	peak
2	4874.000	62.34	-9.26	53.08	54.00	-0.92	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	67.44	-9.26	58.18	74.00	-15.82	peak
2	4874.000	61.30	-9.26	52.04	54.00	-1.96	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	66.31	-9.15	57.16	74.00	-16.84	peak
2	4924.000	62.10	-9.15	52.95	54.00	-1.05	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/19/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	67.38	-9.15	58.23	74.00	-15.77	peak
2	4924.000	60.58	-9.15	51.43	54.00	-2.57	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	72.51	-9.39	63.12	74.00	-10.88	peak
2	4824.000	62.51	-9.39	53.12	54.00	-0.88	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	69.30	-9.39	59.91	74.00	-14.09	peak
2	4824.000	59.82	-9.39	50.43	54.00	-3.57	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	70.77	-9.26	61.51	74.00	-12.49	peak
2	4874.000	62.56	-9.26	53.30	54.00	-0.70	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	68.89	-9.26	59.63	74.00	-14.37	peak
2	4874.000	60.43	-9.26	51.17	54.00	-2.83	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	70.53	-9.15	61.38	74.00	-12.62	peak
2	4924.000	62.62	-9.15	53.47	54.00	-0.53	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	70.15	-9.15	61.00	74.00	-13.00	peak
2	4924.000	60.85	-9.15	51.70	54.00	-2.30	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2422MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	69.93	-9.39	60.54	74.00	-13.46	peak
2	4824.000	62.32	-9.39	52.93	54.00	-1.07	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2422MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4844.000	69.70	-9.33	60.37	74.00	-13.63	peak
2	4844.000	60.46	-9.33	51.13	54.00	-2.87	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	70.98	-9.26	61.72	74.00	-12.28	peak
2	4874.000	62.54	-9.26	53.28	54.00	-0.72	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2437MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	65.78	-9.26	56.52	74.00	-17.48	peak
2	4874.000	60.74	-9.26	51.48	54.00	-2.52	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4904.000	72.34	-9.19	63.15	74.00	-10.85	peak
2	4904.000	62.60	-9.19	53.41	54.00	-0.59	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Harmonic	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4904.000	70.10	-9.19	60.91	74.00	-13.09	peak
2	4904.000	61.52	-9.19	52.33	54.00	-1.67	AVG


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Band Edge

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2358.400	53.57	-1.73	51.84	74.00	-22.16	peak
2	2390.000	51.70	-1.61	50.09	74.00	-23.91	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/20/2017
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2383.480	52.63	-1.64	50.99	74.00	-23.01	peak
2	2390.000	50.53	-1.61	48.92	74.00	-25.08	peak


Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.



Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	49.31	-1.28	48.03	74.00	-25.97	peak
2	2487.480	52.07	-1.26	50.81	74.00	-23.19	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	50.56	-1.28	49.28	74.00	-24.72	peak
2	2488.840	51.75	-1.25	50.50	74.00	-23.50	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.430	55.89	-1.70	54.19	74.00	-19.81	peak
2	2366.430	43.30	-1.70	41.60	54.00	-12.40	AVG
3	2390.000	55.71	-1.61	54.10	74.00	-19.90	peak
4	2390.000	44.10	-1.61	42.49	54.00	-11.51	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2374.240	53.61	-1.67	51.94	74.00	-22.06	peak
2	2390.000	52.66	-1.61	51.05	74.00	-22.95	peak

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	59.30	-1.28	58.02	74.00	-15.98	peak
2	2483.500	45.13	-1.28	43.85	54.00	-10.15	AVG
3	2484.320	60.53	-1.26	59.27	74.00	-14.73	peak
4	2484.320	43.86	-1.26	42.60	54.00	-11.40	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	53.88	-1.28	52.60	74.00	-21.40	peak
2	2483.500	42.58	-1.28	41.30	54.00	-12.70	AVG
3	2484.600	56.53	-1.26	55.27	74.00	-18.73	peak
4	2484.600	41.70	-1.26	40.44	54.00	-13.56	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.650	60.09	-1.61	58.48	74.00	-15.52	peak
2	2388.650	43.89	-1.61	42.28	54.00	-11.72	AVG
3	2390.000	58.34	-1.61	56.73	74.00	-17.27	peak
4	2390.000	44.78	-1.61	43.17	54.00	-10.83	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2412MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	55.17	-1.61	53.56	74.00	-20.44	peak
2	2389.200	42.64	-1.61	41.03	54.00	-12.97	AVG
3	2390.000	54.01	-1.61	52.40	74.00	-21.60	peak
4	2390.000	42.69	-1.61	41.08	54.00	-12.92	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	61.29	-1.28	60.01	74.00	-13.99	peak
2	2483.500	50.22	-1.28	48.94	54.00	-5.06	AVG
3	2483.920	62.48	-1.28	61.20	74.00	-12.80	peak
4	2483.920	49.26	-1.28	47.98	54.00	-6.02	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2462MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 4	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	60.02	-1.28	58.74	74.00	-15.26	peak
2	2483.500	46.61	-1.28	45.33	54.00	-8.67	AVG
3	2484.240	60.19	-1.26	58.93	74.00	-15.07	peak
4	2484.240	45.03	-1.26	43.77	54.00	-10.23	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2422MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.000	73.03	-1.62	71.41	74.00	-2.59	peak
2	2388.000	51.78	-1.62	50.16	54.00	-3.84	AVG
3	2390.000	66.28	-1.61	64.67	74.00	-9.33	peak
4	2390.000	53.13	-1.61	51.52	54.00	-2.48	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2422MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.520	70.81	-1.62	69.19	74.00	-4.81	peak
2	2387.520	49.75	-1.62	48.13	54.00	-5.87	AVG
3	2390.000	62.04	-1.61	60.43	74.00	-13.57	peak
4	2390.000	50.98	-1.61	49.37	54.00	-4.63	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2452MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	65.34	-1.28	64.06	74.00	-9.94	peak
2	2483.500	54.18	-1.28	52.90	54.00	-1.10	AVG
3	2484.150	67.54	-1.26	66.28	74.00	-7.72	peak
4	2484.150	54.47	-1.26	53.21	54.00	-0.79	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

Standard:	FCC Part 15.247	Test Distance:	3m
Test item:	Band edge	Power:	AC 120V/60Hz
Frequency:	2452MHz	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 5	Date:	08/20/2017
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	67.22	-1.28	65.94	74.00	-8.06	peak
2	2483.500	52.70	-1.28	51.42	54.00	-2.58	AVG
3	2484.550	70.04	-1.26	68.78	74.00	-5.22	peak
4	2484.550	50.68	-1.26	49.42	54.00	-4.58	AVG

Note:1.Result (dBuV/m) = Correct Factor (dB/m) + Reading(dBuV).

2.Correction factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) – Pre-Amplifier gain (dB).

3. When the peak results are less than average limit, so not need to evaluate the average.

6 Maximum Conducted Output Power Measurement

6.1. Limit


For systems using digital modulation in the 2400-2483.5MHz, the limit for maximum output power is 30dBm.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

* SISO mode : Directional Gain = Max. Gain = 1.5 dBi < 6 dBi.

* MIMO mode : Directional Gain = $10 \cdot \log \left[\left(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20} \right)^2 / N_{ANT} \right] = 4.51 \text{ dBi} < 6 \text{ dBi}$

6.2. Test Setup



6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Power Sensor	Anritsu	MA2411B	1126022	08/29/2016	1 year
Power Meter	Anritsu	ML2495A	1135009	08/29/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	02/22/2017	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

Note: N.C.R. = No Calibration Request.

6.4. Test Procedure

The testing follows the Measurement Procedure of ANSI C63.10-2013 section 11.9.2.3 Method AVGPM.

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor.

6.5. Test Result

Test Item	Maximum Conducted Output Power						
ANT-0							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 2	2412	1M	11.65	0.015	13.68	0.023	< 30
	2437		9.12	0.008	11.15	0.013	< 30
	2462		8.92	0.008	10.96	0.012	< 30
	2437	2M	9.10	0.008	11.13	0.013	< 30
	2437	5.5M	9.09	0.008	11.10	0.013	< 30
	2437	11M	9.05	0.008	11.08	0.013	< 30
Mode 3	2412	6M	10.77	0.012	19.83	0.096	< 30
	2437		12.01	0.016	20.77	0.119	< 30
	2462		13.47	0.022	21.77	0.150	< 30
	2437	9M	12.00	0.016	20.75	0.119	< 30
	2437	12M	11.98	0.016	20.74	0.119	< 30
	2437	18M	11.95	0.016	20.72	0.118	< 30
	2437	24M	11.94	0.016	20.70	0.117	< 30
	2437	36M	11.91	0.016	20.69	0.117	< 30
	2437	48M	11.90	0.015	20.67	0.117	< 30
	2437	54M	11.88	0.015	20.66	0.116	< 30

Note: The relevant measured result has the offset with cable loss already.

Test Item	Maximum Conducted Output Power						
ANT-0							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 4	2412	13M	12.50	0.018	20.07	0.102	< 30
	2437		11.91	0.016	19.58	0.091	< 30
	2462		12.91	0.020	20.56	0.114	< 30
	2437	26M	11.90	0.015	19.55	0.090	< 30
	2437	39M	11.88	0.015	19.53	0.090	< 30
	2437	52M	11.86	0.015	19.52	0.090	< 30
	2437	78M	11.85	0.015	19.50	0.089	< 30
	2437	104M	11.83	0.015	19.48	0.089	< 30
	2437	117M	11.81	0.015	19.47	0.089	< 30
	2437	130M	11.80	0.015	19.45	0.088	< 30
Mode 5	2422	27M	12.12	0.016	20.36	0.109	< 30
	2437		13.05	0.020	20.97	0.125	< 30
	2452		13.15	0.021	21.04	0.127	< 30
	2437	54M	13.03	0.020	20.95	0.124	< 30
	2437	81M	13.00	0.020	20.93	0.124	< 30
	2437	108M	12.98	0.020	20.90	0.123	< 30
	2437	162M	12.95	0.020	20.87	0.122	< 30
	2437	216M	12.93	0.020	20.85	0.122	< 30
	2437	243M	12.90	0.019	20.84	0.121	< 30
	2437	270M	12.88	0.019	21.00	0.126	< 30

Note: The relevant measured result has the offset with cable loss already.

Test Item	Maximum Conducted Output Power						
ANT-1							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 2	2412	1M	11.09	0.013	13.18	0.021	< 30
	2437		9.04	0.008	11.07	0.013	< 30
	2462		8.05	0.006	10.05	0.010	< 30
	2437	2M	9.02	0.008	11.05	0.013	< 30
	2437	5.5M	8.98	0.008	11.02	0.013	< 30
	2437	11M	8.95	0.008	10.99	0.013	< 30
Mode 3	2412	6M	10.74	0.012	19.72	0.094	< 30
	2437		11.37	0.014	20.06	0.101	< 30
	2462		12.81	0.019	20.92	0.124	< 30
	2437	9M	11.35	0.014	20.05	0.101	< 30
	2437	12M	11.33	0.014	20.03	0.101	< 30
	2437	18M	11.32	0.014	20.01	0.100	< 30
	2437	24M	11.30	0.013	19.98	0.100	< 30
	2437	36M	11.29	0.013	19.96	0.099	< 30
	2437	48M	11.27	0.013	19.94	0.099	< 30
	2437	54M	11.26	0.013	19.93	0.098	< 30

Note: The relevant measured result has the offset with cable loss already.

Test Item	Maximum Conducted Output Power						
ANT-1							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 4	2412	13M	12.30	0.017	19.62	0.092	< 30
	2437		11.16	0.013	19.39	0.087	< 30
	2462		12.36	0.017	19.96	0.099	< 30
	2437	26M	11.15	0.013	19.35	0.086	< 30
	2437	39M	11.13	0.013	19.33	0.086	< 30
	2437	52M	11.12	0.013	19.30	0.085	< 30
	2437	78M	11.10	0.013	19.28	0.085	< 30
	2437	104M	11.08	0.013	19.27	0.085	< 30
	2437	117M	11.07	0.013	19.25	0.084	< 30
	2437	130M	11.05	0.013	19.23	0.084	< 30
Mode 5	2422	27M	12.11	0.016	20.28	0.107	< 30
	2437		12.55	0.018	20.71	0.118	< 30
	2452		12.54	0.018	20.68	0.117	< 30
	2437	54M	12.53	0.018	20.67	0.117	< 30
	2437	81M	12.52	0.018	20.65	0.116	< 30
	2437	108M	12.50	0.018	20.62	0.115	< 30
	2437	162M	12.48	0.018	20.60	0.115	< 30
	2437	216M	12.45	0.018	20.58	0.114	< 30
	2437	243M	12.43	0.017	20.55	0.114	< 30
	2437	270M	12.40	0.017	20.53	0.113	< 30

Note: The relevant measured result has the offset with cable loss already.

Test Item	Maximum Conducted Output Power						
ANT-0+1							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 4	2412	13M	15.41	0.035	22.86	0.193	< 30
	2437		14.56	0.029	22.50	0.178	< 30
	2462		15.65	0.037	23.28	0.213	< 30
	2437	26M	14.55	0.029	22.46	0.176	< 30
	2437	39M	14.53	0.028	22.44	0.175	< 30
	2437	52M	14.52	0.028	22.42	0.175	< 30
	2437	78M	14.50	0.028	22.40	0.174	< 30
	2437	104M	14.48	0.028	22.39	0.173	< 30
	2437	117M	14.47	0.028	22.37	0.173	< 30
	2437	130M	14.45	0.028	22.35	0.172	< 30
Mode 5	2422	27M	15.13	0.033	23.33	0.215	< 30
	2437		15.82	0.038	23.85	0.243	< 30
	2452		15.87	0.039	23.87	0.244	< 30
	2437	54M	15.80	0.038	23.82	0.241	< 30
	2437	81M	15.78	0.038	23.80	0.240	< 30
	2437	108M	15.76	0.038	23.77	0.238	< 30
	2437	162M	15.73	0.037	23.75	0.237	< 30
	2437	216M	15.71	0.037	23.73	0.236	< 30
	2437	243M	15.68	0.037	23.71	0.235	< 30
	2437	270M	15.66	0.037	23.78	0.239	< 30


Note: The relevant measured result has the offset with cable loss already.

7 6dB RF Bandwidth Measurement

7.1. Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

7.2. Test Setup



7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer	Agilent	N9030A	MY53120541	12/22/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	02/22/2017	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

Note: N.C.R. = No Calibration Request.

7.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

7.5. Test Result

Test Item	6dB RF Bandwidth			
Test Mode	Frequency (MHz)	Measurement (kHz)		Limit (kHz)
		ANT-0	ANT-1	
Mode 2	2412	9114	---	> 500
	2437	10080	---	> 500
	2462	10070	---	> 500
Mode 3	2412	15130	---	> 500
	2437	15140	---	> 500
	2462	15140	---	> 500
Mode 4	2412	15130	15120	> 500
	2437	15140	15130	> 500
	2462	15140	15130	> 500
Mode 5	2422	35110	35080	> 500
	2437	35090	35080	> 500
	2452	35110	35080	> 500



7.6. Test Graphs

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz



2437 MHz




2462 MHz






Mode 3: IEEE 802.11g Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-0


2412 MHz



2437 MHz



2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-0


2422 MHz



2437 MHz



2452 MHz





Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-1

2412 MHz



2437 MHz



2462 MHz





Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-1

2422 MHz



2437 MHz



2452 MHz



8 Maximum Power Density Measurement


8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

* SISO mode : Directional Gain = Max. Gain = 1.5 dBi ><6 dBi.

* MIMO mode : Directional Gain = $10 \cdot \log [(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / N_{ANT}] = 4.51 \text{ dBi}$

8.2. Test Setup



8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer	Agilent	N9030A	MY53120541	12/22/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	02/22/2017	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

Note: N.C.R. = No Calibration Request.

8.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 section 10.2 Method PKPSD for compliance to FCC 47CFR 15.247 requirements.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.5. Test Result

Test Item	Maximum Power Density				
Test Mode	Frequency (MHz)	Measurement (dBm/3KHz)			Limit (dBm/3KHz)
		ANT-0	ANT-1	ANT-0+1	
Mode 2	2412	-9.311	---	---	< 8
	2437	-8.551	---	---	< 8
	2462	-8.951	---	---	< 8
Mode 3	2412	-11.162	---	---	< 8
	2437	-9.868	---	---	< 8
	2462	-10.399	---	---	< 8
Mode 4	2412	-10.618	-10.944	-7.768	< 8
	2437	-11.513	-10.198	-7.796	< 8
	2462	-10.647	-12.897	-8.618	< 8
Mode 5	2422	-13.315	-16.772	-11.698	< 8
	2437	-16.687	-14.921	-12.705	< 8
	2452	-16.767	-16.200	-13.464	< 8



8.6. Test Graphs

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz






Mode 3: IEEE 802.11g Continuous TX mode_ANT-0


2412 MHz



2437 MHz



2462 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-0


2422 MHz



2437 MHz



2452 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-1


2412 MHz



2437 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-1


2422 MHz



2437 MHz



2452 MHz




9 Out of Band Conducted Emissions Measurement

9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

9.2. Test Setup



9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
Spectrum Analyzer	Agilent	N9030A	MY53120541	12/22/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	02/22/2017	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

Note: N.C.R. = No Calibration Request.

9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.



9.5. Test Graphs

Reference level

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz





Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz





Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz





Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-0


2422 MHz



2437 MHz



2452 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-1


2412 MHz



2437 MHz



2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-1

2422 MHz



2437 MHz



2452 MHz







Out of Band Conducted Emissions

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz






Mode 3: IEEE 802.11g Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-0


2422 MHz



2437 MHz




2452 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-1


2412 MHz



2437 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-1


2422 MHz



2437 MHz




2452 MHz




**Conducted Band Edge**

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz




2462 MHz






Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2412 MHz




2462 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-0

2412 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-0

2422 MHz




2452 MHz






Mode 4: IEEE 802.11n 2.4GHz 20MHz Continuous TX mode_ANT-1

2412 MHz




2462 MHz






Mode 5: IEEE 802.11n 2.4GHz 40MHz Continuous TX mode_ANT-1

2422 MHz



2452 MHz





10 Antenna Measurement

10.1. Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Description

See section 2 – antenna information.

10.3. Directional Gain Calculated

$$\text{Directional Gain} = 10 \cdot \log \left[\left(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20} \right)^2 / N_{\text{ANT}} \right] = 4.51 \text{ dBi} < 6 \text{ dBi}$$

Operate Freq. Band	Directional Gain (dBi)
IEEE 802.11n 2.4GHz 20MHz Continuous TX Mode	4.51
IEEE 802.11n 2.4GHz 40MHz Continuous TX Mode	4.51