



REPORT No.: SZ17080057W01

# FCC RF TEST REPORT

**APPLICANT** : VECTRIX CORPORATION

**PRODUCT NAME** : Radio module

**MODEL NAME** : TXG

**TRADE NAME** : N/A

**BRAND NAME** : Telemeasure II

**FCC ID** : 2AM9DGC667894

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**ISSUE DATE** : 2017-09-25

**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, Shenzhen , GuangDong Province, P. R. China

Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.com      E-mail: service@morlab.cn



## DIRECTORY

<b>TEST REPORT DECLARATION</b>	4
<b>1. TECHNICAL INFORMATION</b>	5
<b>1.1 APPLICANT INFORMATION</b>	5
<b>1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION</b>	5
<b>1.2.1 IDENTIFICATION OF ALL USED EUTS</b>	6
<b>1.3 TEST STANDARDS AND RESULTS</b>	6
<b>1.3.1 TEST ENVIRONMENT CONDITIONS</b>	7
<b>2. 47 CFR PART 15C REQUIREMENTS</b>	8
<b>2.1 ANTENNA REQUIREMENT</b>	8
<b>2.1.1 APPLICABLE STANDARD</b>	8
<b>2.1.2 RESULT: COMPLIANT</b>	8
<b>2.2 NUMBER OF HOPPING FREQUENCY</b>	8
<b>2.2.1 REQUIREMENT</b>	8
<b>2.2.2 TEST DESCRIPTION</b>	8
<b>2.2.3 TEST PROCEDURE</b>	8
<b>2.2.4 TEST RESULT</b>	9
<b>2.3 PEAK OUTPUT POWER</b>	11
<b>2.3.1 REQUIREMENT</b>	11
<b>2.3.2 TEST DESCRIPTION</b>	11
<b>2.3.3 TEST RESULT</b>	11
<b>2.4 20dB BANDWIDTH</b>	12
<b>2.4.1 DEFINITION</b>	12
<b>2.4.2 TEST DESCRIPTION</b>	12
<b>2.4.3 TEST PROCEDURE</b>	12
<b>2.4.4 TEST RESULT</b>	12
<b>2.5 CARRIED FREQUENCY SEPARATION</b>	16
<b>2.5.1 DEFINITION</b>	16
<b>2.5.2 TEST DESCRIPTION</b>	16
<b>2.5.3 TEST PROCEDURE</b>	16
<b>2.5.4 TEST RESULT</b>	17
<b>2.6 TIME OF OCCUPANCY (DWELL TIME)</b>	18



2.6.1	REQUIREMENT	18
2.6.2	TEST DESCRIPTION	18
2.6.3	TEST PROCEDURE	18
2.6.4	TEST RESULT	19
<b>2.7</b>	<b>CONDUCTED SPURIOUS EMISSIONS</b>	<b>21</b>
2.7.1	REQUIREMENT	21
2.7.2	TEST DESCRIPTION	21
2.7.3	TEST PROCEDURE	21
2.7.4	TEST RESULT	22
<b>2.8</b>	<b>RESTRICTED FREQUENCY BANDS</b>	<b>26</b>
2.8.1	REQUIREMENT	26
2.8.2	TEST DESCRIPTION	26
2.8.3	TEST PROCEDURE	27
2.8.4	TEST RESULT	27
<b>2.9</b>	<b>CONDUCTED EMISSION</b>	<b>30</b>
2.9.1	REQUIREMENT	30
2.9.2	TEST DESCRIPTION	30
2.9.3	TEST RESULT	31
<b>2.10</b>	<b>RADIATED EMISSION</b>	<b>32</b>
2.10.1	REQUIREMENT	32
2.10.2	TEST DESCRIPTION	33
2.10.3	TEST PROCEDURE	35
2.10.4	TEST RESULT	35
<b><u>ANNEX A GENERAL INFORMATION</u></b>		<b><u>39</u></b>

Change History		
Issue	Date	Reason for change
1.0	2017-09-25	First edition



## TEST REPORT DECLARATION

Applicant	VECTRIX CORPORATION
Applicant Address	1-4-11 sadashin-kanamecho-building ,kanamecho, toshimaku, tokyo, 171-0043, japan
Manufacturer	VECTRIX Co.,LTD
Manufacturer Address	1-4-11 sadashin-kanamecho-building ,kanamecho, toshimaku, tokyo, 171-0043, japan
Product Name	Radio module
Model Name	TXG
Brand Name	Telemeasure II
HW Version	VR24TX-P5
SW Version	VR24TX-V3
Test Standards	47 CFR Part 15 Subpart C
Test Date	2017-09-06 to 2017-09-21
Test Result	PASS

Tested by : Su Hang  
Su Hang (Test Engineer)

Approved by : Andy Yeh  
Andy Yeh (Supervisor)



## 1. TECHNICAL INFORMATION

Note: Provide by applicant.

### 1.1 Applicant Information

Company:	VECTRIX CORPORATION
Address:	1-4-11 sadashin-kanamecho-building ,kanamecho, toshimaku, tokyo, 171-0043, japan

### 1.2 Equipment under Test (EUT) Description

Brand Name:	Telemeasure II
Trade Name:	N/A
Model Name:	TXG
Frequency Range:	The frequency range used is 2402MHz – 2482MHz
Channel:	Refer to Note 1
Modulation Type:	GFSK
Antenna Type:	Ceramic Antenna
Antenna Gain:	2.14dBi

**NOTE 1:** The EUT is a Radio module. It's operating at 2.4GHz ISM band. The frequency and channel as Table1. The Lowest Channel 1, Middle 9 and Highest 16 were selected for test in the report.

**Table 1:**

Channel	Frequency	Channel	Frequency
1	<b>2402</b>	9	<b>2441</b>
2	2406	10	2446
3	2411	11	2452
4	2416	12	2459
5	2421	13	2465
6	2426	14	2471
7	2431	15	2477
8	2436	16	<b>2482</b>

**NOTE 2:** The EUT connected to the serial port of the computer with a serial communication cable, we use the dedicated software to control the EUT into the test mode, and then use MT8852B base station to control the EUT continuous transmission.

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
01	1.0r	1.0

### 1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Test Date	Result
1	15.203	Antenna Requirement	N/A	<u>PASS</u>
2	15.247(a)	Number of Hopping Frequency	Sep 21, 2017	<u>PASS</u>
3	15.247(b)	Peak Output Power	Sep 21, 2017	<u>PASS</u>
4	15.247(a)	20dB Bandwidth	Sep 21, 2017	<u>PASS</u>
5	15.247(a)	Carrier Frequency Separation	Sep 21, 2017	<u>PASS</u>
6	15.247(a)	Time of Occupancy (Dwell time)	Sep 21, 2017	<u>PASS</u>
7	15.247(d)	Conducted Spurious Emission	Sep 21, 2017	<u>PASS</u>
8	15.247(d)	Restricted Frequency Bands	Sep 07, 2017	<u>PASS</u>
9	15.209 15.247(d)	Radiated Emission	Sep 07, 2017	<u>PASS</u>
10	15.207	Conducted Emission	N/A	<u>N/A</u>

**Note:** Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

**NOTE:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013.



### 1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

## 2. 47 CFR PART 15C REQUIREMENTS

### 2.1 Antenna requirement

#### 2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.


### 2.2 Number of Hopping Frequency

#### 2.2.1 Requirement

According to FCC §15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

#### 2.2.2 Test Description

##### A. Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

##### B. Equipments List:

Please reference ANNEX A(1.5).

#### 2.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:



Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize


## 2.2.4 Test Result


The EUT operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

### A. Test Verdict:

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
GFSK	2400 - 2483.5	16	15	Plot A	PASS

### B. Test Plots:





(Plot A: GFSK)




## 2.3 Peak Output Power

### 2.3.1 Requirement

According to FCC §15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

### 2.3.2 Test Description

#### A. Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

#### B. Equipments List:

Please reference ANNEX A(1.5).

### 2.3.3 Test Result

The EUT operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the module.

#### 2.3.3.1 GFSK Mode

#### A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2402	-0.73	0.00085	30	1	PASS
9	2441	-1.10	0.00078			PASS
16	2482	-2.38	0.00058			PASS




## 2.4 20dB Bandwidth

### 2.4.1 Definition

According to FCC §15.247(a)(1), the 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ( $10 \times \log 1\% = 20\text{dB}$ ) taking the total RF output power.

### 2.4.2 Test Description

#### A. Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

#### B. Equipments List:

Please reference ANNEX A(1.5).

### 2.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 2.4.4 Test Result

The EUT operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.




#### 2.4.4.1 GFSK Mode

##### A. Test Verdict:

The maximum 20dB bandwidth measured is 1.683 MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
1	2402	1.034	Plot A
9	2441	1.683	Plot B
16	2482	1.597	Plot C

##### B. Test Plots:



(Plot A: Channel = 1 @ GFSK)



REPORT No.: SZ17080057W01



(Plot B: Channel = 9 @ GFSK)



(Plot C: Channel = 16 @ GFSK)




## 2.5 Carried Frequency Separation

### 2.5.1 Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 2.5.2 Test Description

#### A. Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

#### B. Equipments List:

Please reference ANNEX A(1.5).

### 2.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 2.5.4 Test Result

The EUT operates at hopping-on test mode. For any adjacent channels (e.g. the channel 9 and 10 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (refer to section 2.4.4), whichever is greater. So, the verdict is PASSING

Test Mode	Measured Channel Numbers	Carried Frequency Separation	Refer to Plot	20dB bandwidth (MHz)	Min. Limit	Verdict
GFSK	9 and 10	5.010	Plot A	1.683	20dB bandwidth	PASS



(Plot A: GFSK)


## 2.6 Time of Occupancy (Dwell time)

### 2.6.1 Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 2.6.2 Test Description

#### A. Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

#### B. Equipments List:

Please reference ANNEX A(1.5).

### 2.6.3 Test Procedure

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (16 channel \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$ .




## 2.6.4 Test Result

### 2.6.4.1 GFSK Mode

#### A. Test Verdict:


Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
1.05	27	0.02835	0.2835	0.4	PASS

#### B. Test Plots:





REPORT No.: SZ17080057W01



(Plot A: GFSK)


## 2.7 Conducted Spurious Emissions

### 2.7.1 Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.7.2 Test Description

#### A. Test Setup:



The EUT which is powered by the adapter, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

#### B. Equipments List:

Please reference ANNEX A(1.5).

### 2.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.



## 2.7.4 Test Result

The EUT operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


### 2.7.4.1 GFSK Mode

#### A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
1	2402	-52.33	Plot A	-0.96	-20.96	PASS
9	2441	-52.99	Plot B	-1.37	-21.37	PASS
16	2482	-53.16	Plot C	-2.74	-22.74	PASS

#### B. Test Plots:

**Note:** the power of the Module transmitting frequency should be ignored.



(Plot A: Channel = 1, 30MHz to 25GHz @ GFSK Mode)



REPORT No.: SZ17080057W01




(Channel = 1, Band edge @ GFSK Mode)




(Channel = 1, Band edge with hopping on @ GFSK Mode)



REPORT No.: SZ17080057W01



(Plot B: Channel = 9, 30MHz to 25GHz @ GFSK Mode)



(Plot C: Channel = 16, 30MHz to 25GHz @ GFSK Mode)



REPORT No.: SZ17080057W01



(Channel = 16, Band edge @ GFSK Mode)



(Channel = 16, Band edge with hopping on @ GFSK Mode)


## 2.8 Restricted Frequency Bands

### 2.8.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.8.2 Test Description

#### A. Test Setup:



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

#### B. Equipments List:

Please reference ANNEX A(1.5).



### 2.8.3 Test Procedure

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 KHz for  $f < 1\text{GHz}$

VBW = 3 MHz for peak and 10Hz for average

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

### 2.8.4 Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}/\text{m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

#### 2.8.4.1 GFSK Mode


##### A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dB $\mu$ V)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission $E$ (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
1	2382.99	PK	47.83	-33.63	32.56	46.76	74	Pass
1	2387.36	AV	35.33	-33.63	32.56	34.26	54	Pass
16	2487.53	PK	48.44	-33.18	32.50	47.76	74	Pass
16	2483.50	AV	37.04	-33.18	32.50	36.36	54	Pass


##### B. Test Plots:



REPORT No.: SZ17080057W01




(Plot A1:Channel = 1 PEAK @ GFSK)




(Plot A2:Channel = 1 AVERAGE @ GFSK)



REPORT No.: SZ17080057W01



(Plot B1: Channel = 16 PEAK @ GFSK)



(Plot B2: Channel = 16 AVERAGE @ GFSK)

## 2.9 Conducted Emission

### 2.9.1 Requirement

According to RSS-GEN section 8.8, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

**NOTE:**

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.9.2 Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



REPORT No.: SZ17080057W01

**B. Equipments List:**

Please reference ANNEX A(1.5).

**2.9.3 Test Result**

**A. Test setup:**

N/A

**B. Test Plots:**

N/A



## 2.10 Radiated Emission

### 2.10.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:**


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


## 2.10.2 Test Description

### A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



## 3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, the EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant



emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

## B. Equipments List:

Please reference ANNEX A(1.5).

### 2.10.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 2.10.4 Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}/\text{m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor AT and  $A_{\text{Factor}}$  were built in test software.

**Note:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



#### 2.10.4.1 GFSK Mode


##### A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 1



Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
49.424	16.76	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
2325.970	44.61	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
4653.028	45.86	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
5761.011	46.21	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
9361.957	48.39	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
16042.444	49.45	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 1)




Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
48.210	14.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
2799.600	45.10	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
4449.354	45.34	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
5679.542	47.11	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
10347.736	48.13	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
16400.909	49.47	N/A	N/A	74.0	N/A	54.00	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 1)




Plot for Channel = 9



Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
48.210	14.86	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
104.055	13.93	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2442.497	46.43	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
3357.665	45.40	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
9313.075	47.20	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
16417.203	49.64	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 9)




Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
49.424	15.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
2409.844	50.24	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
4767.085	45.72	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
8620.586	47.39	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
11736.789	48.08	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
16018.003	49.55	N/A	N/A	74.0	N/A	54.00	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 9)




Plot for Channel = 16



Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
44.568	14.34	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
104.055	17.19	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2410.484	50.42	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
4701.909	46.11	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
5724.350	46.87	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS
15688.052	48.96	N/A	N/A	74.0	N/A	54.00	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 16)



Fre. (MHz)	Pk (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
49.424	16.76	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
104.055	14.55	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2409.204	49.65	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
5044.081	46.27	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
10364.030	47.22	N/A	N/A	74.0	N/A	54.00	Vertical	PASS
16034.297	49.44	N/A	N/A	74.0	N/A	54.00	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 16)



## ANNEX A GENERAL INFORMATION

### 1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192.

### 1.4 Maximum measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Number of Hopping Frequency	±5%
Peak Output Power	±2.22dB
20dB Bandwidth	±5%
Carrier Frequency Separation	±5%
Time of Occupancy (Dwell time)	±5%
Conducted Spurious Emission	±2.77 dB
Restricted Frequency Bands	±5%



Radiated Emission	±2.95dB
Conducted Emission	±2.44dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

### 1.5 Test Equipments Utilized

#### 1.5.1 Conducted Test Equipments

##### Conducted Test Equipment

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2017.05.24	2018.05.23
2	Power Splitter	NW521	1506A	Weinschel	2017.05.24	2018.05.23
3	Attenuator 1	(N/A.)	10dB	Resnet	2017.05.24	2018.05.23
4	Attenuator 2	(N/A.)	3dB	Resnet	2017.05.24	2018.05.23
5	EXA Signal Analyzer	MY53470836	N9010A	Agilent	2016.12.07	2017.12.06
6	USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2017.05.24	2018.05.23
7	RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
8	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
9	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

#### 1.5.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2017.05.24	2018.05.23
2	LISN	812744	NSLK 8127	Schwarzbeck	2017.05.24	2018.05.23
3	Service Supplier	100448	CMU200	R&S	2017.05.24	2018.05.23
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2017.05.24	2018.05.23
5	Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

#### 1.5.3 Auxiliary Test Equipment

Auxiliary Test Equipment						
No.	Equipment Name	Model No.	Brand Name	Manufacturer	Cal.Date	Cal.Due Date
1	Computer	T430i	Think Pad	Lenovo	N/A	N/A

#### 1.5.4 Radiated Test Equipments

Radiated Test Equipments
--------------------------



REPORT No.: SZ17080057W01

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	GB45360846	8960-E5515C	Agilent	2017.05.17	2018.05.16
2	Receiver	MY54130016	N9038A	Agilent	2017.05.17	2018.05.16
3	Test Antenna - Bi-Log	N/A	VULB9163	Schwarzbeck	2016.12.09	2017.12.08
4	Test Antenna - Horn	9120C-384	BBHA 9120C	Schwarzbeck	2017.03.30	2018.03.29
5	Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2017.03.30	2018.03.29
6	Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
7	Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
8	Coaxial cable(N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
9	1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2017.05.17	2018.05.16
10	18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2017.05.17	2018.05.16

#### 1.5.5 Climate Chamber

Climate Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2017.01.11	2018.01.10

#### 1.5.6 Vibration Table

Vibration Table						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2017.01.11	2018.01.10

#### 1.5.7 Anechoic Chamber

Anechoic Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Changning	2017.01.11	2018.01.10

\*\*\*\*\* END OF REPORT \*\*\*\*\*