

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W17DR-D025
AGR No. : A17NA-358
Applicant : CHAHOO Limited
Address : B-4F, 25 Pangyo-ro 256beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do 13487
South Korea
Manufacturer : CHAHOO Limited
Address : B-4F, 25 Pangyo-ro 256beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do 13487
South Korea
Type of Equipment : Digital Door Lock
FCC ID. : 2AM9GIG302
Model Name : IG302
Multiple Model Name : Entrava NEXT, 929SS-DMF1
Serial number : N/A
Total page of Report : 8 pages (including this page)
Date of Incoming : November 23, 2017
Date of issue : December 13, 2017

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:


Jae-Ho Lee / Chief Engineer
ONETECH Corp.

Approved by:


Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION.....	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	7
4.3 CALCULATED MPE SAFE DISTANCE.....	8

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W17DR-D025	December 13, 2017	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : CHAHOO Limited
Address : B-4F, 25 Pangyo-ro 256beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do 13487 South Korea
Contact Person : YoungJae Im / HW Team Leader
Telephone No. : +82-31-696-0499
FCC ID : 2AM9GIG302
Model Name : IG302
Serial Number : N/A
Date : December 13, 2017

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Digital Door Lock
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The CHAHOO Limited, Model IG302 (referred to as the EUT in this report) is a Digital Door Lock. Product specification information described herein was obtained from product data sheet or user's manual.

Device Type	Digital Door Lock	
Operating Frequency	BLE	2 402 MHz ~ 2 480 MHz
	NFC	13.563 9 MHz
RF Output Power	BLE	-30.25 dBm
Number of Channel	BLE	40 Channels
	NFC	1 Channel
Modulation Type	BLE	GFSK
	NFC	ASK
Antenna Type	BLE	PCB Pattern antenna
	NFC	PCB Loop antenna
Antenna Gain	BLE	-1.28 dBi
List of each Osc. or crystal Freq.(Freq. \geq 1 MHz)	16 MHz, 27.12 MHz	
Rated Supply Voltage	DC 6.0 V	

2.2 Alternative type(s)/model(s); also covered by this test report.

- The following lists consist of the added models and their differences.

Model Name	Differences	Tested
IG302	Basic Model.	<input checked="" type="checkbox"/>
Entrava NEXT, 929SS-DMF1	The models are identical to basic model except for the OEM Brand.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

3. EUT MODIFICATIONS

- None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m , G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm , using $P (\text{mW}) = P (\text{W}) / 1000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm , P = Power in mW , G = Numeric antenna gain, and S = Power density in mW/cm^2

4.2 EUT Description

Kind of EUT	Digital Door Lock
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz <input type="checkbox"/> and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 240 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Bluetooth BLE: 2 402 MHz ~ 2 480 MHz
MAX. RF OUTPUT POWER	-30.25 dBm
Antenna Gain	-1.28 dBi
Exposure	<input checked="" type="checkbox"/> MPE
Evaluation Applied	<input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(dBm)	(mW)	Log		
2 402 ~ 2 480	BLE (GFSK)	-30.25 ± 0.5	-29.75	0.001 1	-1.28	0.745	0.000 000 16	1.00



Tested by: Ha-Ram, Lee / Assistant Manager