



# FCC Test Report

## FCC ID: 2AMA8-H8

**Product:** Internet TV BOX

**Trade Mark:** Zoomtak

**Model Number:** H8

**Serial Model:** H8plus

**Report No.:** NTEK-2017NT05273588F2

**Prepared for**

Shen Zhen Zoomtak Electronics Co., Ltd  
F6, A2 Building, HuaFeng Industrial Park, HangCheng Avenue, Gushu,  
Bao'an District, Shenzhen, China

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel.: +86-755-6115 9388  
Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Shen Zhen Zoomtak Electronics Co., Ltd  
Address ..... : F6, A2 Building, HuaFeng Industrial Park, HangCheng Avenue, Gushu, Bao'an District, Shenzhen, China

**Manufacturer's Name** ..... : Shen Zhen Zoomtak Electronics Co., Ltd  
Address ..... : F6, A2 Building, HuaFeng Industrial Park, HangCheng Avenue, Gushu, Bao'an District, Shenzhen, China

### Product description

Product name ..... : Internet TV BOX  
Model and/or type reference : H8  
Standards ..... : FCC Part15B:Apr 11.2017  
ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

### Date of Test

Date (s) of performance of tests ..... : 27 May. 2017 ~ 13 Jun. 2017  
Date of Issue ..... : 13 Jun. 2017  
Test Result ..... : **Pass**

Testing Engineer : Lake Xie  
(Lake Xie)

Technical Manager : Jason Chen  
(Jason Chen)

Authorized Signatory : Sam Chen  
(Sam Chen)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 TEST RESULTS	19
3.2.5 TEST RESULTS(1000~6000MHz)	21
4 . EUT TEST PHOTO	22

**1. TEST SUMMARY**

Test procedures according to the technical standards:

<b>EMC Emission</b>				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B:2014 ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number:238937; IC Registration Number:9270A-1

CNAS Registration Number:L5516

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~12.4GHz	5.0	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Internet TV BOX						
Trade Mark	Zoomtak						
Model Name	H8						
Serial Model	H8plus						
Model Difference	All the model are the same circuit and RF module, except the model No.						
Product Description	<p>The EUT is a Internet TV BOX.</p> <table border="1"><tr><td>Connecting I/O port:</td><td>USB, DC in, HDMI, RJ45, OPTICAL, AV</td></tr><tr><td>Operation Frequency:</td><td>WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz</td></tr><tr><td>Modulation Type:</td><td>IEEE 802.11b : DSSS (CCK, QPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)</td></tr></table>	Connecting I/O port:	USB, DC in, HDMI, RJ45, OPTICAL, AV	Operation Frequency:	WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz	Modulation Type:	IEEE 802.11b : DSSS (CCK, QPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Connecting I/O port:	USB, DC in, HDMI, RJ45, OPTICAL, AV						
Operation Frequency:	WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz						
Modulation Type:	IEEE 802.11b : DSSS (CCK, QPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)						
Power Source	DC 5V/2A from Adapter.						
Adapter	Model: HJ-AD18-050200 Input:100~240V 50~60Hz 0.7Amax Output:5V, 2000mA						
Battery	N/A						
HW Version	RL-SM020-8189ETV-V1.3						
SW Version	ZoomtakH8.20170518.V8.1.4						

### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	SD card Play+HDMI
Mode 2	USB Playing+HDMI
Mode 3	LAN
Mode 4	WIFI


For Conducted Test	
Final Test Mode	Description
Mode 1	SD card Play+HDMI
Mode 2	USB Playing+HDMI
Mode 3	LAN
Mode 4	WIFI

For Radiated Test	
Final Test Mode	Description
Mode 1	SD card Play+HDMI
Mode 2	USB Playing+HDMI
Mode 3	LAN
Mode 4	WIFI

Note: Final Test Mode: Through Pre-scan, find the mode 2 is the worst case.

Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Internet TV BOX	Zoomtak	H8	N/A	EUT
E-2	Adapter	/	HJ-0501000E1-US	N/A	Peripherals
E-3	Monitor	SONY	KDL-24EX520	N/A	Peripherals
E-4	Earphone	N/A	2688	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	NO	1.5m	
C-2	HDMI Cable	NO	NO	1.0m	
C-3	Earphone Cable	NO	NO	1.2m	

**Note:**

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

## Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2017.06.06	2018.06.05	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2017.06.06	2018.06.05	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2017.04.09	2018.04.08	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05	1 year
8	Amplifier	EMC	EMC051835SE	980246	2016.08.09	2017.08.08	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
10	Power Meter	DARE	RPR3006W	15I00041S NO84	2016.08.09	2017.08.08	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2016.07.06	2017.07.05	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
13	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
14	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year

## Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.06.06	2018.06.05	1 year
2	LISN	R&S	ENV216	101313	2017.04.19	2018.04.18	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2017.06.06	2018.06.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2017.06.06	2018.06.05	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of **2.3** Unless otherwise a special operating condition is specified in the follows during the testing.


## 3.1.5 TEST RESULTS

EUT:	Internet TV BOX	Model Name. :	H8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2017-6-13
Test Mode:	Mode 2	Phase :	L
Test Voltage:	DC 5V from Adapter AC120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
						QP
0.1820	45.56	9.70	55.26	64.39	-9.13	QP
0.1820	28.99	9.70	38.69	54.39	-15.70	AVG
0.5460	36.64	9.71	46.35	56.00	-9.65	QP
0.5460	27.06	9.71	36.77	46.00	-9.23	AVG
3.6860	35.08	9.96	45.04	56.00	-10.96	QP
3.6860	19.67	9.96	29.63	46.00	-16.37	AVG
6.2859	46.50	9.92	56.42	60.00	-3.58	QP
6.2859	32.31	9.92	42.23	50.00	-7.77	AVG
10.1219	42.17	9.91	52.08	60.00	-7.92	QP
10.1219	28.95	9.91	38.86	50.00	-11.14	AVG
25.9940	37.85	10.24	48.09	60.00	-11.91	QP
25.9940	24.52	10.24	34.76	50.00	-15.24	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Internet TV BOX	Model Name. :	H8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2017-6-13
Test Mode:	Mode 2	Phase :	N
Test Voltage:	DC 5V from Adapter AC120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1900	39.44	9.80	49.24	64.03	-14.79	QP
0.1900	22.86	9.80	32.66	54.03	-21.37	AVG
0.5380	39.83	9.81	49.64	56.00	-6.36	QP
0.5380	18.16	9.81	27.97	46.00	-18.03	AVG
1.4020	39.82	9.82	49.64	56.00	-6.36	QP
1.4020	21.21	9.82	31.03	46.00	-14.97	AVG
3.2180	38.40	9.85	48.25	56.00	-7.75	QP
3.2180	19.99	9.85	29.84	46.00	-16.16	AVG
5.7979	45.59	9.91	55.50	60.00	-4.50	QP
5.7979	32.88	9.91	42.79	50.00	-7.21	AVG
7.3099	44.91	9.98	54.89	60.00	-5.11	QP
7.3099	29.01	9.98	38.99	50.00	-11.01	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Internet TV BOX	Model Name. :	H8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2017-6-13
Test Mode:	Mode 2	Phase :	L
Test Voltage:	DC 5V from Adapter AC240V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.5420	36.91	9.71	46.62	56.00	-9.38	QP
0.5420	31.69	9.71	41.40	46.00	-4.60	AVG
1.2660	36.91	9.79	46.70	56.00	-9.30	QP
1.2660	16.10	9.79	25.89	46.00	-20.11	AVG
2.4900	39.04	9.84	48.88	56.00	-7.12	QP
2.4900	23.06	9.84	32.90	46.00	-13.10	AVG
4.5739	42.83	9.97	52.80	56.00	-3.20	QP
4.5739	26.89	9.97	36.86	46.00	-9.14	AVG
6.2059	46.38	9.92	56.30	60.00	-3.70	QP
6.2059	30.43	9.92	40.35	50.00	-9.65	AVG
7.6779	46.42	9.88	56.30	60.00	-3.70	QP
7.6779	31.72	9.88	41.60	50.00	-8.40	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Internet TV BOX	Model Name. :	H8
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Date:	2017-6-13
Test Mode:	Mode 2	Phase :	N
Test Voltage:	DC 5V from Adapter AC240V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1786	42.60	9.80	52.40	64.55	-12.15	QP
0.1786	25.50	9.80	35.30	54.55	-19.25	AVG
0.4661	39.03	9.81	48.84	56.58	-7.74	QP
0.4661	11.77	9.81	21.58	46.58	-25.00	AVG
0.5460	38.99	9.81	48.80	56.00	-7.20	QP
0.5460	27.07	9.81	36.88	46.00	-9.12	AVG
6.1819	44.94	9.94	54.88	60.00	-5.12	QP
6.1819	31.09	9.94	41.03	50.00	-8.97	AVG
10.9619	41.56	10.03	51.59	60.00	-8.41	QP
10.9619	26.47	10.03	36.50	50.00	-13.50	AVG
26.0740	36.55	10.32	46.87	60.00	-13.13	QP
26.0740	21.90	10.32	32.22	50.00	-17.78	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



## 3.2.4 TEST RESULTS


## TEST RESULTS (30~1000 MHz)

EUT:	Internet TV BOX	Model Name:	H8
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2017-6-13
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from Adapter AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	197.2000	26.25	13.75	40.00	43.50	-3.50	QP
H	299.3158	27.15	14.71	41.86	46.00	-4.14	QP
H	339.5887	28.34	14.23	42.57	46.00	-3.43	QP
H	526.3967	25.40	17.52	42.92	46.00	-3.08	QP
H	661.1504	20.77	20.93	41.70	46.00	-4.30	QP
H	912.8619	17.96	25.04	43.00	46.00	-3.00	QP

## Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	Internet TV BOX	Model Name :	H8
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2017-6-13
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from Adapter AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	147.4036	28.80	11.32	40.12	43.50	-3.38	QP
V	299.3158	28.26	14.71	42.97	46.00	-3.03	QP
V	339.5887	28.72	14.23	42.95	46.00	-3.05	QP
V	519.0648	25.81	17.08	42.89	46.00	-3.11	QP
V	668.1422	22.00	20.98	42.98	46.00	-3.02	QP
V	975.7528	16.89	27.41	44.30	54.00	-9.70	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



## 3.2.5 TEST RESULTS(1000~6000MHz)

EUT:	Internet TV BOX	Model Name :	H8
Temperature:	24 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Test Date :	2017-6-13
Test Mode :	Mode 1		
Test Power :	DC 5V from Adapter AC120V/60Hz		



All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequenc y	Reading	Correc t	Result	Limit	Over Limit	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	1038.34	65.87	-15.3	50.61	74	-23.39	Pk
V	1038.34	48.85	-15.3	33.59	54	-20.41	AV
V	1187.69	70.58	-13.3	57.31	74	-16.69	Pk
V	1187.69	47.43	-13.3	34.16	54	-19.84	AV
V	1485.84	65.77	-11.6	54.15	74	-19.85	Pk
V	1485.84	45.84	-11.6	34.22	54	-19.78	AV
H	1038.34	70.88	-15.3	55.62	74	-18.38	Pk
H	1038.34	50.92	-15.3	35.66	54	-18.34	AV
H	1187.69	72.53	-13.3	59.26	74	-14.74	Pk
H	1187.69	51.25	-13.3	37.98	54	-16.02	AV
H	1485.84	66.22	-11.6	54.6	74	-19.4	Pk
H	1485.84	45.19	-11.6	33.57	54	-20.43	AV

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Only the worst results data points are reported in the report.

**4. EUT TEST PHOTO****Radiated Measurement Photos**

**Conducted Measurement Photos**