

FCC RF Exposure

EUT Description: Bluetooth Headphone

Model No.: Arc-1-ANC, Arc-1-ANC-A, Arc-1-ANC-B, Arc-1-ANC-C, Arc-1-ANC-D, Arc-1-ANC-E, Arc-1-ANC-F, Arc-1-ANC-G, Arc-1-ANC-H, Arc-1-ANC-I, Arc-1-ANC-J

FCC ID: 2AMC6-ARC1ANC

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max power of channel, including tune - up tolerance, mW)/(min. test separation distance, mm)] \cdot $\sqrt{f(\text{GHz})}$ ≤ 3.0 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

$$\text{Result} = P/D \cdot \sqrt{F}$$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit	SAR Test Exclusion
BT	4.204	4±1	5/3.1623	5	0.98019	3.0	Pass

Note:
PK Output power= conducted power.
Conducted power see the test report **HK2008262424-E**, antenna gain=0dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.98019 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] \cdot [$\sqrt{f(\text{GHz})}$]

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm