

FCC TEST REPORT

Product Name: Personal Emergency Response System
Trade Mark: IdentiFind
Model No.: IF-4G
Report Number: 180621015RFM-3
Test Standards: FCC 47 CFR Part 27
FCC 47 CFR Part 2
FCC ID: 2AMCHIF4G
Test Result: PASS
Date of Issue: August 7, 2018


Prepared for:

Identifind LLC
1504 Penny Ln, Keller, Texas, United States


Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Tested by:


Henry Lu
Project Engineer

Reviewed by:


Kevin Liang
Assistant Manager

Approved by:


Billy Li
Technical Director

Date:

August 7, 2018



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Version

Version No.	Date	Description
V1.0	August 7, 2018	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 DESCRIPTION OF SUPPORT UNITS	5
1.5 TEST LOCATION	5
1.6 TEST FACILITY	5
1.7 DEVIATION FROM STANDARDS	6
1.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.10 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.2 TEST SETUP	10
4.2.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.2.2 FOR CONDUCTED RF TEST SETUP	12
4.3 TEST CHANNELS	13
4.4 SYSTEM TEST CONFIGURATION	13
4.5 PRE-SCAN	14
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	16
5.1 REFERENCE DOCUMENTS FOR TESTING	16
5.2 ERP OR EIRP	16
5.3 CONDUCTED OUTPUT POWER	19
5.4 PEAK-TO-AVERAGE RATIO	20
5.5 99%&26dB BANDWIDTH	26
5.6 BAND EDGE AT ANTENNA TERMINALS	39
5.7 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	54
5.8 FIELD STRENGTH OF SPURIOUS RADIATION	65
5.9 FREQUENCY STABILITY	126
APPENDIX 1 PHOTOS OF TEST SETUP	129
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	129

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Identifind LLC
Address of Applicant:	1504 Penny Ln, Keller, Texas, United States
Manufacturer:	Identifind LLC
Address of Manufacturer:	1504 Penny Ln, Keller, Texas, United States

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Personal Emergency Response System	
Model No.:	IF-4G	
Add. Model No.:	N/A	
Trade Mark:	IdentiFind	
DUT Stage:	Identical Prototype	
EUT Supports Function:	UTRA Bands:	Band II/ Band V
	E-UTRA Bands:	FDD Band 2/ Band 4/ Band 12
Sample Received Date:	June 22, 2018	
Sample Tested Date:	June 22, 2018 to July 28, 2018	

1.2.2 Description of Accessories

Adapter	
Model No.:	S005BNU0500100
Input:	100-240 V~50/60 Hz 0.15 A
Output:	5.0 V $\pm$ 1000 mA
AC Cable:	N/A
DC Cable:	N/A

Battery	
Battery Type:	Ni-Mh Battery
Rated Voltage:	3.6 Vdc
Rated Capacity:	2500 mAh

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Support Networks:	LTE	
Type of Modulation:	LTE Band 4/12:	QPSK, 16QAM
Antenna Type:	PCB Antenna	
Antenna Gain:	LTE Band 4:	1.59 dBi
	LTE Band 12:	1.72 dBi
Normal Test Voltage:	3.6 Vdc or/and 120V~60Hz	
Extreme Test Voltage:	3.3 to 4.1Vdc or 102V~60Hz to 138V~60Hz	
Extreme Test Temperature:	-30 °C to +50 °C	

Summary of Results:							
Band	BW (MHz)	Frequency Range (MHz)	Max RF Output Power (dBm)		Type of Emission		
			Conducted (Average)	ERP/EIRP (Average)	QPSK	16QAM	64QAM
LTE Band 4	1.4	1710.7-1754.3	20.70	23.17	1M19G7D	1M19W7D	N/A
	3	1711.5-1753.5	19.98	23.05	2M71G7D	2M71W7D	N/A
	5	1712.5-1752.5	20.70	23.19	4M52G7D	4M52W7D	N/A
	10	1715-1750	20.71	23.14	8M98G7D	8M98W7D	N/A
	15	1717.5-1747.5	20.66	23.18	13M5G7D	13M5W7D	N/A
	20	1720-1745	20.72	23.14	18M0G7D	18M0W7D	N/A
LTE Band 12	1.4	699.7-715.3	22.93	22.09	1M15G7D	1M14W7D	N/A
	3	700.5-714.5	22.93	22.13	2M71G7D	2M71W7D	N/A
	5	701.5-713.5	22.93	22.12	4M53G7D	4M53W7D	N/A
	10	704-711	22.95	22.05	9M01G7D	9M00W7D	N/A

1.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
---	---	---	---	---

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust

1.5 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.6 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

IC-Registration No.: 21600-1

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.7 DEVIATION FROM STANDARDS

None.

1.8 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.10 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

FCC 47 CFR Part 27 Test Cases (LTE Band 4)			
Test Item	Test Requirement	Test Method	Result
Equivalent Isotropic Radiated Power (EIRP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Peak-to-average ratio	FCC 47 CFR Part 27.50(d)(5)	KDB 971168 D01v03	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 27.53(h)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 27.53(h)(1)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 27.53(h)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 27.53(h)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 27.54	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS

FCC 47 CFR Part 27 Test Cases (LTE Band 12)			
Test Item	Test Requirement	Test Method	Result
Effective Radiated Power (ERP)	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(c)(10)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Conducted Output Power	FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(c)(10)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Peak-to-average ratio	FCC 47 CFR Part 27.50(d)(5)	KDB 971168 D01v03	PASS
99%&26dB Bandwidth	FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 27.53(g)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Band Edge at antenna terminals	FCC 47 CFR Part 27.53(g)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Spurious emissions at antenna terminals	FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 27.53(g)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Field strength of spurious radiation	FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 27.53(g)	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS
Frequency stability	FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 27.54	ANSI/TIA-603-E-2016 & KDB 971168 D01v03	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 20, 2015	Dec. 19, 2018
☒	Receiver	R&S	ESIB26	100114	Dec. 10, 2017	Dec. 10, 2018
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec.10, 2017	Dec. 10, 2018
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	Dec. 22, 2017	Dec. 22, 2018
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Dec. 17, 2017	Dec. 17, 2018
☒	Preamplifier	HP	8447F	2805A02960	Dec. 10, 2017	Dec. 10, 2018
☒	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	May 19, 2018	May 19, 2019
☒	Horn Antenna	ETS-LINDGREN	3117	00164202	Dec. 17, 2017	Dec. 17, 2018
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May 22, 2018	May 22, 2019
☒	Horn Antenna	ETS-LINDGREN	3116C	00200180	May 20, 2018	May 20, 2019
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Dec. 17, 2017	Dec. 17, 2018
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☐	Highpass Filter (1.2GHz~18GHz)	Micro-Tronics	HPM50108	G552	Dec. 13, 2017	Dec. 13, 2018
☐	Highpass Filter (3GHz~18GHz)	Micro-Tronics	HPM50117	G005	Dec. 13, 2017	Dec. 13, 2018
☒	Test Software	Audix	e3	Software Version: 9.160323		

2/3/4G RF Test System Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☐	Spectrum Analyzer	R&S	FSP 13	1164.4391.13	June 06, 2018	June 06, 2019
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Dec. 10, 2017	Dec. 10, 2018
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec.10, 2017	Dec. 10, 2018
☒	Wideband Radio Communication Tester	R&S	CMW500	116254	June 07, 2018	June 07, 2019
☒	Universal Radio Communication Tester	R&S	CMU200	114713	Dec. 10, 2017	Dec. 10, 2018
☒	DC Source	KIKUSUI	PWR400L	LK003024	Sep. 14, 2017	Sep. 13, 2018
☐	Temp & Humidity chamber	Espec	GL(U)04KA(W)	16921H201P3	Sep. 14, 2017	Sep. 13, 2018
☒	Temp & Humidity chamber	Votisch	VT4002	58566133290020	June 05, 2018	June 05, 2019
☒	Test Software	ECIT	AutomationTestSystem	Software Version: 2.170530		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions


Test Environment	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
TN/VN	+15 to +35	3.6	20 to 75
TL/VL	-30	3.3	20 to 75
TH/VL	+50	3.3	20 to 75
TL/VH	-30	4.1	20 to 75
TH/VH	+50	4.1	20 to 75


Remark:

- 1) The EUT just work in such extreme temperature of -30 °C to +50 °C and the extreme voltage of 3.3 V to 4.1 V, so here the EUT is tested in the temperature of -30 °C to +50 °C and the voltage of 3.3 V to 4.1 V.
- 2) VN: Normal Voltage; TN: Normal Temperature;
TL: Low Extreme Test Temperature; TH: High Extreme Test Temperature;
VL: Low Extreme Test Voltage; VH: High Extreme Test Voltage.


4.2 TEST SETUP

4.2.1 For Radiated Emissions test setup





4.2.2 For Conducted RF test setup



4.3 TEST CHANNELS

Band	Test Frequency ID	Bandwidth (MHz)	Number [UL]	Frequency of Uplink (MHz)
LTE Band 4 TX:1710-1755MHz	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Middle Range	1.4/3/5/10/ 15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE Band 12 TX:699-716MHz	Low Range	1.4	23017	699.7
		3	23025	700.5
		5	23035	701.5
		10	23060	704
	Middle Range	1.4/3/5/10	23095	707.5
	High Range	1.4	23173	715.3
		3	23165	714.5
		5	23155	713.5
		10	23130	711

4.4 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 120V~60Hz and/or 3.6V battery. Only the worst case data were recorded in this test report.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, X/Y/Z axis, and antenna ports.

The worst case was found when positioned as the table below.

Band	Mode	Antenna Port	Worst-case axis positioning
LTE Band 4	1TX	Chain 0	Y axis
LTE Band 12	1TX	Chain 0	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.5 PRE-SCAN

Pre-scan under all rate at lowest middle and highest channel, find the transmitter power as below.

LTE Band 4 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	19.84	20.25	20.53	1	0	19.86	20.27	20.52
	1	2	20.21	20.43	20.70	1	7	20.17	20.44	20.70
	1	5	19.97	20.33	20.58	1	14	19.93	20.33	20.58
	3	0	20.01	20.20	20.39	8	0	19.00	19.23	19.39
	3	1	20.16	20.36	20.27	8	3	19.09	19.36	19.29
	3	3	20.03	20.32	20.24	8	7	19.00	19.39	19.28
	6	0	19.22	19.23	19.22	15	0	19.19	19.24	19.16
16QAM	1	0	19.60	19.87	19.52	1	0	19.57	19.93	19.55
	1	2	19.68	19.95	19.33	1	7	19.65	19.98	19.31
	1	5	19.90	19.46	18.99	1	14	19.93	19.46	18.99
	3	0	19.18	19.22	19.11	8	0	18.14	18.23	18.11
	3	1	19.50	19.85	19.46	8	3	18.55	18.80	18.49
	3	3	19.64	19.97	19.30	8	7	18.66	18.95	18.26
	6	0	18.87	18.44	17.94	15	0	18.87	18.38	17.97
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	19.87	20.22	20.53	1	0	19.84	20.25	20.53
	1	12	20.22	20.41	20.70	1	24	20.22	20.41	20.71
	1	24	19.94	20.32	20.62	1	49	19.91	20.36	20.58
	12	0	19.03	19.23	19.36	25	0	19.04	19.22	19.39
	12	6	19.09	19.37	19.30	25	12	19.15	19.31	19.30
	12	13	19.04	19.35	19.29	25	25	19.02	19.32	19.28
	25	0	19.17	19.27	19.19	50	0	19.22	19.27	19.16
16QAM	1	0	19.58	19.89	19.55	1	0	19.58	19.86	19.51
	1	12	19.62	20.01	19.30	1	24	19.67	19.97	19.33
	1	24	19.93	19.46	18.98	1	49	19.93	19.47	18.95
	12	0	18.14	18.21	18.08	25	0	18.16	18.19	18.14
	12	6	18.52	18.84	18.45	25	12	18.56	18.78	18.50
	12	13	18.61	18.97	18.29	25	25	18.60	18.98	18.26
	25	0	18.87	18.39	17.94	50	0	18.91	18.38	17.98
Channel Bandwidth: 15 MHz						Channel Bandwidth: 20 MHz				
QPSK	1	0	19.91	20.25	20.50	1	0	19.92	20.29	20.58
	1	37	20.20	20.46	20.66	1	50	20.24	20.49	20.72
	1	74	19.97	20.39	20.59	1	99	19.99	20.40	20.63
	37	0	19.01	19.23	19.40	50	0	19.07	19.28	19.41
	37	19	19.16	19.36	19.30	50	25	19.17	19.38	19.35
	37	39	19.00	19.33	19.28	50	50	19.08	19.40	19.30
	75	0	19.22	19.25	19.21	100	0	19.23	19.29	19.24
16QAM	1	0	19.62	19.93	19.51	1	0	19.65	19.94	19.57
	1	37	19.66	19.98	19.33	1	50	19.70	20.03	19.35
	1	74	19.89	19.52	18.97	1	99	19.95	19.54	19.00
	37	0	18.20	18.19	18.15	50	0	18.22	18.27	18.16
	37	19	18.50	18.82	18.46	50	25	18.58	18.86	18.51
	37	39	18.65	18.96	18.29	50	50	18.68	19.02	18.31
	75	0	18.92	18.41	17.91	100	0	18.93	18.46	17.99

LTE Band 12 Maximum Average Power (dBm)										
Modulation	RB		Test Channel			RB		Test Channel		
	Size	Offset	Low	Mid	High	Size	Offset	Low	Mid	High
Channel Bandwidth: 1.4 MHz						Channel Bandwidth: 3 MHz				
QPSK	1	0	22.37	22.50	22.70	1	0	22.39	22.52	22.69
	1	2	22.38	22.85	22.93	1	7	22.34	22.86	22.93
	1	5	22.61	22.36	22.56	1	14	22.57	22.36	22.56
	3	0	22.62	22.62	22.83	8	0	21.61	21.65	21.83
	3	1	22.62	22.70	22.70	8	3	21.55	21.70	21.72
	3	3	22.62	22.66	22.67	8	7	21.59	21.73	21.71
16QAM	6	0	21.77	21.79	21.80	15	0	21.74	21.80	21.74
	1	0	21.49	21.36	22.19	1	0	21.46	21.42	22.22
	1	2	21.93	22.20	22.42	1	7	21.90	22.23	22.40
	1	5	21.89	21.00	22.06	1	14	21.92	21.00	22.06
	3	0	21.72	21.72	21.76	8	0	20.68	20.73	20.76
	3	1	21.38	21.38	22.14	8	3	20.43	20.33	21.17
QPSK	3	3	21.88	22.17	22.41	8	7	20.90	21.15	21.37
	6	0	20.86	19.99	20.97	15	0	20.86	19.93	21.00
Channel Bandwidth: 5 MHz						Channel Bandwidth: 10 MHz				
QPSK	1	0	22.40	22.47	22.70	1	0	22.45	22.54	22.75
	1	12	22.39	22.83	22.93	1	24	22.41	22.91	22.95
	1	24	22.58	22.35	22.60	1	49	22.63	22.43	22.61
	12	0	21.64	21.65	21.80	25	0	21.68	21.70	21.85
	12	6	21.55	21.71	21.73	25	12	21.63	21.72	21.78
	12	13	21.63	21.69	21.72	25	25	21.67	21.74	21.73
16QAM	25	0	21.72	21.83	21.77	50	0	21.78	21.85	21.82
	1	0	21.47	21.38	22.22	1	0	21.54	21.43	22.24
	1	12	21.87	22.26	22.39	1	24	21.95	22.28	22.44
	1	24	21.92	21.00	22.05	1	49	21.94	21.08	22.07
	12	0	20.68	20.71	20.73	25	0	20.76	20.77	20.81
	12	6	20.40	20.37	21.13	25	12	20.46	20.39	21.19
16QAM	12	13	20.85	21.17	21.40	25	25	20.92	21.22	21.42
	25	0	20.86	19.94	20.97	50	0	20.92	20.01	21.02

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2 Subpart J	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 27	Miscellaneous Wireless Communications Services
3	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
4	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03

5.2 ERP OR EIRP

Test Requirement: FCC 47 CFR Part 2.1046(a)
LTE Band 4: FCC 47 CFR Part 27.50(d)(4)
LTE Band 12: FCC 47 CFR Part 27.50(c)(10)
Test Method: KDB 971168 D01v03 & ANSI/TIA-603-E-2016

Limit:

FCC 47 CFR Part 27.50(c)(10): Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

FCC 47 CFR Part 27.50(d)(4): Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Test Procedure:

Test procedure as below:

- The EUT was powered ON and placed on a 0.8/1.5m high table at a 3 meter semi/fully Anechoic Chamber. The antenna of the transmitter was extended to its maximum length. Modulation mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- Steps 1) to 3) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 3) is obtained for this set of conditions.
- The output power into the substitution antenna was then measured.
- Steps 6) and 7) were repeated with both antennas polarized.
- Calculate power in dBm by the following formula:

$$\text{ERP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP} = \text{ERP} + 2.15\text{dB}$$

where:

Pg is the generator output power into the substitution antenna.

- Test the EUT in the lowest channel, the middle channel the Highest channel
- The radiation measurements are performed in X, Y, Z axis positioning for EUT operation mode, and found the Y axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
30MHz-1GHz	Peak	100kHz	300kHz	Peak
Above 1GHz	Peak	1MHz	3MHz	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230888

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Test Setup: Refer to section 4.2.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: See table below

LTE Band 4 Maximum EIRP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	21.99	21.36	N/A	30.00	Pass
Middle	22.13	21.63	N/A	30.00	Pass
Highest	23.17	21.77	N/A	30.00	Pass
Channel Bandwidth: 3MHz					
Lowest	21.81	21.36	N/A	30.00	Pass
Middle	22.09	21.57	N/A	30.00	Pass
Highest	23.05	21.64	N/A	30.00	Pass
Channel Bandwidth: 5MHz					
Lowest	21.91	21.32	N/A	30.00	Pass
Middle	22.15	21.64	N/A	30.00	Pass
Highest	23.19	21.80	N/A	30.00	Pass
Channel Bandwidth: 10MHz					
Lowest	21.98	21.49	N/A	30.00	Pass
Middle	22.05	21.65	N/A	30.00	Pass
Highest	23.14	21.65	N/A	30.00	Pass
Channel Bandwidth: 15MHz					
Lowest	21.89	21.33	N/A	30.00	Pass
Middle	22.08	21.64	N/A	30.00	Pass
Highest	23.18	21.72	N/A	30.00	Pass
Channel Bandwidth: 20MHz					
Lowest	21.93	21.41	N/A	30.00	Pass
Middle	22.15	21.63	N/A	30.00	Pass
Highest	23.14	21.69	N/A	30.00	Pass

LTE Band 12 Maximum ERP (dBm)					
Channel	QPSK; RB:1	16QAM; RB:1	64QAM; RB:1	Limit (dBm)	Result
Channel Bandwidth: 1.4MHz					
Lowest	18.83	19.37	N/A	34.77	Pass
Middle	20.46	20.42	N/A	34.77	Pass
Highest	22.09	21.53	N/A	34.77	Pass
Channel Bandwidth: 3MHz					
Lowest	19.66	19.35	N/A	34.77	Pass
Middle	21.11	20.32	N/A	34.77	Pass
Highest	22.13	21.55	N/A	34.77	Pass
Channel Bandwidth: 5MHz					
Lowest	19.75	19.18	N/A	34.77	Pass
Middle	20.99	20.50	N/A	34.77	Pass
Highest	22.12	21.44	N/A	34.77	Pass
Channel Bandwidth: 10MHz					
Lowest	19.91	19.36	N/A	34.77	Pass
Middle	21.09	20.47	N/A	34.77	Pass
Highest	22.05	21.55	N/A	34.77	Pass

5.3 CONDUCTED OUTPUT POWER

FCC 47 CFR Part 2.1046(a)

Test Requirement: **LTE Band 4:** FCC 47 CFR Part 27.50(d)(4)
LTE Band 12: FCC 47 CFR Part 27.50(c)(10)

Test Method: KDB 971168 D01v03 & ANSI/TIA-603-E-2016

Limit:

FCC 47 CFR Part 27.50(c)(10): Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

FCC 47 CFR Part 27.50(d)(4): Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Test Procedure:

The EUT was set up for the maximum power with WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: [The full result refer to section 4.5 for details.](#)

5.4 PEAK-TO-AVERAGE RATIO

Test Requirement: FCC 47 CFR Part 24.232(d)

Test Method: KDB 971168 D01v03

Limit: In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

Test Procedure:

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer.

- Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth
- Set the number of counts to a value that stabilizes the measured CCDF curve
- Record the maximum PAPR level associated with a probability of 0.1 %

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.


Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: See table below

LTE Band 4 Peak-to-average ratio (dB)						
Channel	RB Configuration	Channel Bandwidth: 20 MHz			Limit (dB)	Result
		QPSK	16QAM	64QAM		
Lowest	1 RB	4.52	4.64	N/A	13	Pass
	Full RB	5.01	4.96	N/A	13	Pass
Middle	1 RB	4.55	4.61	N/A	13	Pass
	Full RB	5.07	4.99	N/A	13	Pass
Highest	1 RB	4.32	4.46	N/A	13	Pass
	Full RB	4.90	4.90	N/A	13	Pass





LTE Band 12 Peak-to-average ratio (dB)						
Channel	RB Configuration	Channel Bandwidth: 10 MHz			Limit (dB)	Result
		QPSK	16QAM	64QAM		
Lowest	1 RB	4.29	4.29	N/A	13	Pass
	Full RB	4.81	4.78	N/A	13	Pass
Middle	1 RB	4.29	4.20	N/A	13	Pass
	Full RB	4.72	4.70	N/A	13	Pass
Highest	1 RB	4.17	4.12	N/A	13	Pass
	Full RB	4.55	4.55	N/A	13	Pass





5.5 99%&26DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 24.238(b)

Test Method: ANSI/TIA-603-E-2016 & KDB 971168 D01v03

Limit: No Limit

Test Procedure:

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The 99% and -26dB bandwidths was also measured and recorded.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: See table below

LTE Band 4								
Channel	RB Configuration		26 dB BW (MHz)			99% BW (MHz)		
	Size	Offset	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
Channel Bandwidth: 1.4 MHz								
Lowest	6	0	1.427	1.423	N/A	1.1906	1.1907	N/A
Middle	6	0	1.434	1.450	N/A	1.1876	1.1919	N/A
Highest	6	0	1.452	1.420	N/A	1.1943	1.1782	N/A
Channel Bandwidth: 3 MHz								
Lowest	15	0	2.996	3.006	N/A	2.7073	2.7092	N/A
Middle	15	0	3.003	2.999	N/A	2.7114	2.7135	N/A
Highest	15	0	3.003	3.003	N/A	2.7091	2.7096	N/A
Channel Bandwidth: 5 MHz								
Lowest	25	0	5.017	5.017	N/A	4.5179	4.5028	N/A
Middle	25	0	5.007	5.016	N/A	4.5065	4.5207	N/A
Highest	25	0	5.007	5.011	N/A	4.5011	4.5015	N/A
Channel Bandwidth: 10 MHz								
Lowest	50	0	9.972	9.962	N/A	8.9780	8.9780	N/A
Middle	50	0	9.929	9.941	N/A	8.9716	8.9702	N/A
Highest	50	0	9.808	9.779	N/A	8.9773	8.9614	N/A
Channel Bandwidth: 15 MHz								
Lowest	75	0	14.76	14.76	N/A	13.461	13.459	N/A
Middle	75	0	14.74	14.74	N/A	13.409	13.410	N/A
Highest	75	0	14.74	14.73	N/A	13.421	13.414	N/A
Channel Bandwidth: 20 MHz								
Lowest	100	0	19.37	19.36	N/A	17.950	17.987	N/A
Middle	100	0	19.44	19.38	N/A	17.919	17.926	N/A
Highest	100	0	19.50	19.42	N/A	17.833	17.829	N/A

