

7. RADIO FREQUENCY EXPOSURE

7.1. Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm ²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

F = frequency in MHz

* = Plane-wave equivalent power density

Maximum Permissible Exposure

The MPE was calculated at 20cm to show compliance with the power density limit.

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna.

Note:

1. Manufacturer declared that the maximum antenna gain is 5.0 dBi(Max.).
2. Manufacturer declared that the nearest distance between human and the EUT is 20cm.

3. Only record worst case data.

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)	Tolerance $\pm$ (dB)
GFSK	00	2402	3.454	3.0 ± 1.0
	39	2441	3.630	3.0 ± 1.0
	78	2480	3.644	3.0 ± 1.0
$\pi/4$ DQPSK	00	2402	2.474	2.0 ± 1.0
	39	2441	2.575	2.0 ± 1.0
	78	2480	2.513	2.0 ± 1.0
8-DPSK	00	2402	2.571	2.0 ± 1.0
	39	2441	2.647	2.0 ± 1.0
	78	2480	2.594	2.0 ± 1.0
GFSK	0	2402	-2.520	-2.0 ± 1.0
	19	2440	-3.172	-3.0 ± 1.0
	39	2480	-3.476	-3.0 ± 1.0

Test Mode	Channel	Frequency (MHz)	Power (dBm, Peak)	Power Tune Up (dBm)
802.11b	Low	2412	15.20	15.0 ± 1.0
	Middle	2437	15.36	15.0 ± 1.0
	High	2462	15.37	15.0 ± 1.0
802.11g	Low	2412	13.08	13.0 ± 1.0
	Middle	2437	13.18	13.0 ± 1.0
	High	2462	12.84	12.0 ± 1.0
802.11n HT20	Low	2412	12.83	12.0 ± 1.0
	Middle	2437	13.38	13.0 ± 1.0
	High	2462	13.34	13.0 ± 1.0
802.11n HT40	Low	2422	12.63	12.0 ± 1.0
	Middle	2437	12.95	12.0 ± 1.0
	High	2452	12.96	12.0 ± 1.0

Test Mode	Channel	Max. Tune Up Power (dBm, Peak)	Max. Tune Up Power (mW)	MPE (mW/cm ²)	Limit (mW/cm ²)
GFSK	00	4.0	2.51	0.0008	1.0
	39	4.0	2.51	0.0008	1.0
	78	4.0	2.51	0.0008	1.0
π/4DQPSK	00	3.0	2.00	0.0006	1.0
	39	3.0	2.00	0.0006	1.0
	78	3.0	2.00	0.0006	1.0
8-DPSK	00	3.0	2.00	0.0006	1.0
	39	3.0	2.00	0.0006	1.0
	78	3.0	2.00	0.0006	1.0
GFSK	0	-1.0	0.79	0.0002	1.0
	19	-2.0	0.63	0.0002	1.0
	39	-2.0	0.63	0.0002	1.0

Test Mode	Channel	Max. Tune Up Power (dBm, Peak)	Max. Tune Up Power (mW)	MPE (mW/cm ²)	Limit (mW/cm ²)
802.11b	Low	16.0	39.81	0.0125	1.0
	Middle	16.0	39.81	0.0125	1.0
	High	16.0	39.81	0.0125	1.0
802.11g	Low	14.0	25.12	0.0079	1.0
	Middle	14.0	25.12	0.0079	1.0
	High	13.0	19.95	0.0063	1.0
802.11n HT20	Low	13.0	19.95	0.0063	1.0
	Middle	14.0	25.12	0.0079	1.0
	High	14.0	25.12	0.0079	1.0
802.11n HT40	Low	13.0	19.95	0.0063	1.0
	Middle	13.0	19.95	0.0063	1.0
	High	13.0	19.95	0.0063	1.0

Antenna Gain (typical): 5dBi, 3.16(numeric)

Prediction distance: >=20cm

The power density level worst case at 20 cm is below the uncontrolled exposure limit.