

## RF Exposure Report

**Report No.:** SA181206D08

**FCC ID:** 2AMD3-BT021

**Test Model:** BM021

**Received Date:** Dec. 14, 2018

**Test Date:** Dec. 17 ~ 22, 2018

**Issued Date:** Jan. 4, 2019

**Applicant:** BEAUTIFUL LIGHT TECHNOLOGY CORPORATION

**Address:** No.16-2,Dingshanmen,Neighbor 12,Jinlan Village,Jhongpu  
Township,Chiayi,Taiwan 60665

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
(R.O.C.)

**FCC Registration /  
Designation Number:** 198487 / TW2021



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                         |          |
|---------------------------------------------------------|----------|
| <b>Release Control Record</b> .....                     | <b>3</b> |
| <b>1 Certificate of Conformity</b> .....                | <b>4</b> |
| <b>2 RF Exposure</b> .....                              | <b>5</b> |
| 2.1 Limits For Maximum Permissible Exposure (MPE).....  | 5        |
| 2.2 MPE Calculation Formula .....                       | 5        |
| 2.3 Classification .....                                | 5        |
| 2.4 Calculation Result Of Maximum Conducted Power ..... | 6        |

### Release Control Record

| Issue No.   | Description       | Date Issued  |
|-------------|-------------------|--------------|
| SA181206D08 | Original release. | Jan. 4, 2019 |

## 1 Certificate of Conformity

**Product:** Module

**Brand:** BLTC

**Test Model:** BM021

**Sample Status:** Engineering sample

**Applicant:** BEAUTIFUL LIGHT TECHNOLOGY CORPORATION

**Test Date:** Dec. 17 ~ 22, 2018

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**



**Date:** Jan. 4, 2019

Jessica Cheng / Senior Specialist

**Approved by :**



**Date:** Jan. 4, 2019

Rex Lai / Associate Technical Manager

## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

| Frequency Range (MHz)                                 | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (minutes) |
|-------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure |                               |                               |                                     |                        |
| 300-1500                                              | ...                           | ...                           | F/1500                              | 30                     |
| 1500-100,000                                          | ...                           | ...                           | 1.0                                 | 30                     |

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

## 2.4 Calculation Result Of Maximum Conducted Power

| Frequency<br>(MHz) | Max Power<br>(dBm) | Antenna Gain<br>(dBi) | Distance<br>(cm) | Power Density<br>(mW/cm <sup>2</sup> ) | Limit<br>(mW/cm <sup>2</sup> ) |
|--------------------|--------------------|-----------------------|------------------|----------------------------------------|--------------------------------|
| 2402-2480          | 6.37               | 2.11                  | 20               | 0.0014                                 | 1                              |

--- END ---